



SLOVENSKI STANDARD

SIST-TP CEN/TR 17603-60-10:2022

01-marec-2022

Vesoljska tehnika - Smernice za nadzor delovanja

Space engineering - Control performance guidelines

Raumfahrttechnik - Richtlinien für Leistung von Regelung/Steuerung

Ingénierie spatiale - Lignes directrices des performances du contrôle

Ta slovenski standard je istoveten z: CEN/TR 17603-60-10:2022

SIST-TP CEN/TR 17603-60-10:2022

ICS:

49.140

Vesoljski sistemi in operacije Space systems and operations

SIST-TP CEN/TR 17603-60-10:2022

en,fr,de

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

SIST-TP CEN/TR 17603-60-10:2022

<https://standards.iteh.ai/catalog/standards/sist/fa2f8eb8-589c-4032-a27c-63b0283b679a/sist-tp-cen-tr-17603-60-10-2022>

TECHNICAL REPORT

CEN/TR 17603-60-10

RAPPORT TECHNIQUE

TECHNISCHER BERICHT

January 2022

ICS 49.140

English version

Space engineering - Control performance guidelines

Ingénierie spatiale - Lignes directrices des
performances du contrôleRaumfahrttechnik - Richtlinien für Leistung von
Regelung/Steuerung

This Technical Report was approved by CEN on 29 November 2021. It has been drawn up by the Technical Committee CEN/CLC/JTC 5.

CEN and CENELEC members are the national standards bodies and national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

iTeh STANDARD
PREVIEW
(standards.iteh.ai)

SIST-TP CEN/TR 17603-60-10:2022

<https://standards.iteh.ai/catalog/standards/sist/fa2f8eb8-589c-4032-a27c-63b0283b679a/sist-tp-cen-tr-17603-60-10-2022>



CEN-CENELEC Management Centre:
Rue de la Science 23, B-1040 Brussels

Table of contents

European Foreword	7
Introduction	8
1 Scope	10
2 References	11
3 Terms, definitions and abbreviated terms	12
3.1 Terms from other documents	12
3.2 Terms specific to the present handbook	12
3.3 Abbreviated terms	16
4 General outline for control performance process	18
4.1 The general control structure	18
4.1.1 Description of the general control structure – Extension to system level	18
4.1.2 General performance definitions	19
4.1.3 Example – Earth observation satellite	20
4.2 Review of generic performance specification elements	21
4.2.1 General	21
4.2.2 Preliminary remark on intrinsic and extrinsic performance properties	21
4.2.3 Examples of high-level performance requirements	23
4.2.4 Formalising requirements through performance indicators	25
4.3 Overview on performance specification and verification process	27
4.3.1 Introduction	27
4.3.2 Requirements capture & dissemination	28
4.3.3 Performance verification	29
4.3.4 Control performance engineering tasks during development phases	31
5 Extrinsic performance – error indices and analysis methods	38
5.1 Introduction	38
5.2 Performance and measurement error indices	38

5.2.1	Definition of error function	38
5.2.2	Definition of error indices.....	39
5.2.3	Common performance error indices	39
5.2.4	Common knowledge error indices	41
5.3	Formulation of performance requirements using error indices.....	42
5.3.1	Structure of a requirement.....	42
5.3.2	Choice of error function	42
5.3.3	Use of error indices	43
5.3.4	Statistical interpretation of a requirement	43
5.3.5	Formulation of Knowledge Requirements.....	46
5.4	Assessing compliance with a performance requirement	46
5.4.1	Overview	46
5.4.2	Experimental approach	47
5.4.3	Numerical simulations	47
5.4.4	Use of an error budget	49
5.5	Performance error budgeting	50
5.5.1	Overview	50
5.5.2	Identifying errors	50
5.5.3	Statistics of contributing terms	51
5.5.4	Combination of error terms.....	52
5.5.5	Comparison with requirements.....	53
5.5.6	Practical use of a budget (Synthesis)	53
6	Intrinsic performance indicators for closed-loop controlled systems.....	56
6.1	Overview	56
6.2	Closed-loop controlled systems	57
6.2.1	General closed-loop structure	57
6.2.2	General definitions for closed-loop controlled systems.....	57
6.3	Stability of a closed-loop controlled system.....	59
6.4	Stability margins	60
6.4.2	Stability margins for SISO LTI systems	60
6.4.3	Stability margins for MIMO LTI system – S and T criteria	62
6.4.4	Why specifying stability margins?.....	64
6.5	Level of robustness of a closed-loop controlled system	65
6.6	Time & Frequency domain behaviour of a closed-loop controlled system	65
6.6.1	Overview	65
6.6.2	Time domain indicators (transient)	65
6.6.3	Frequency domain performance indicators	67

CEN/TR 17603-60-10:2022 (E)

6.7	Formulation of performance requirements for closed-loop controlled systems	70
6.7.1	General	70
6.7.2	Structure of a requirement.....	70
6.7.3	Specification for general systems (possibly MIMO, coupled or nested loops).....	71
6.7.4	Example of stability margins requirement.....	71
6.8	Assessing compliance with performance requirements.....	72
6.8.1	Guidelines for stability and stability margins verification	72
6.8.2	Methods for (systematic) robustness assessment.....	73
7	Hierarchy of control performance requirements	74
7.1	Overview	74
7.2	From top level requirements down to design rules	74
7.2.1	General	74
7.2.2	Top level requirements.....	74
7.2.3	Intermediate level requirements	75
7.2.4	Lower level requirements – Design rules.....	75
7.3	The risks of counterproductive requirements	76
7.3.1	An example of counterproductive requirement	76
7.3.2	How to avoid counterproductive control performance requirements?	76
Annex A	LTI systems	77
A.1	Overview	77
A.2	General properties of LTI systems.....	77
A.2.1	Simplified structure of a closed-loop controlled system	77
A.2.2	Representation of LTI systems.....	78
A.3	On stability margins of SISO and MIMO LTI systems	80
A.3.1	Interpretation of stability margins.....	80
A.3.2	Analysis of stability margins – some illustrations	82
Annex B	Appendices to clause 5: Guidelines and mathematical elements	84
B.1	Error Indices with domains other than time	84
B.2	Considerations regarding time intervals	85
B.3	Relationship between error indices and physical quantities	85
B.4	Statistics for Monte Carlo Minimum Number of Runs	87
B.5	Determining the error PDFs	88
B.5.1	Overview	88
B.5.2	White noise	88
B.5.3	Biases	89

B.5.4	Uniform random errors	90
B.5.5	Harmonic errors	90
B.5.6	Drift Errors	91
B.5.7	Transient Errors	92
B.5.8	Others (General Analysis Methods)	93
B.5.9	Distributions of Ensemble Parameters	94
B.6	Mathematics of an Error Budget	95
B.6.1	Probability distributions and the statistical interpretation	95
B.6.2	Exact error combination methods.....	96
B.6.3	Alternative approximation formulae	97
Annex C	Satellite AOCS case study	98
C.1	Introduction.....	98
C.2	Satellite AOCS architecture	98
C.3	From Image quality to AOCS requirements.....	98
C.4	Formulation of the requirements C.3a1 to C.3a4 using error indices.....	101
C.4.1	General	101
C.4.2	Choice of signal error function	102
C.4.3	Choice of error indices and maximum values	102
C.4.4	Assigning a probability density function (PDF)	102
C.4.5	Choice of statistical interpretation (temporal, ensemble, mixed...)	103
C.4.6	Requirements formulation	103
C.5	Formulation of requirements C.3b1 and C.3b2	104
C.6	Control Performance verification principles	104
C.6.1	Choice of verification method	104
C.6.2	Compiling the error budget (requirements C.3a1 to C.3a4)	105
C.6.3	Assessing compliance to control loop requirements C.3b1 and C.3b2	110
C.7	Performance budget examples	111
C.7.1	Overview	111
C.7.2	Pointing Knowledge Budget	111
C.7.3	Pointing budget	114
C.7.4	Pointing stability Budget (Requirements C.3a3 and C.3a4).....	116

Figures

Figure 4-1	General control structure, ECSS-E-HB-60A	18
Figure 4-2	General control structure extended up to system level	19
Figure 4-3	Example of requirements capture and dissemination for a typical AOCS case	30

CEN/TR 17603-60-10:2022 (E)

Figure 4-4	Example of pointing performance verification, for a typical mission profile.....	30
Figure 5-1	Illustration of the different ways of meeting a requirement.....	44
Figure 5-2	Statistics for the different statistical interpretations. L-R: temporal interpretation, ensemble interpretation, mixed interpretation	44
Figure 6-1	Simplified scheme for a closed-loop controlled system.....	57
Figure 6-2	Example of gain and phase margins identification.....	62
Figure 6-3	Illustration of the transient response indicators.....	66
Figure 6-4	Bandwidth, cut-off frequency and rejection of resonances.....	69

Tables

Table 3-1:	Relationships of the definitions of the different kinds of performance, performance knowledge and their corresponding errors.....	16
Table 4-1	Example of a control structure breakdown for an Earth observation satellite	21
Table 4-2	Example of AOCS extrinsic and intrinsic specifiable performances	22
Table 4-3	General template for building extrinsic performance indicators.....	26
Table 4-4	Summary of control performance engineering tasks.....	28
Table 4-5	Summary of the control performance management activities during the phases of mission development (guidelines only).....	31
Table 4-6	Control performance engineering inputs, tasks and outputs, Phase 0/A.....	32
Table 4-7	Control performance engineering inputs, tasks and outputs, Phase B.....	34
Table 4-8	Control performance engineering inputs, tasks and outputs, Phase C/D	36
Table 4-9	Control performance engineering inputs, tasks and outputs, Phase E/F.....	37
Table 5-1	Minimum number of simulation runs required to verify a requirement at confidence level P_c to a verification confidence of 95 %.....	49
Table 5-2	Example of a table used for a performance budget (APE for Euler angles)	55
Table 6-1	Formulas for the usual SISO stability margins.....	61

European Foreword

This document (CEN/TR 17603-60-10:2022) has been prepared by Technical Committee CEN/CLC/JTC 5 "Space", the secretariat of which is held by DIN.

It is highlighted that this technical report does not contain any requirement but only collection of data or descriptions and guidelines about how to organize and perform the work in support of EN 16603-60.

This Technical report (CEN/TR 17603-60-10:2022) originates from ECSS-E-HB-60-10A.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

This document has been developed to cover specifically space systems and has therefore precedence over any TR covering the same scope but with a wider domain of applicability (e.g.: aerospace).

SIST-TP CEN/TR 17603-60-10:2022

<https://standards.iteh.ai/catalog/standards/sist/fa2f8eb8-589c-4032-a27c-63b0283b679a/sist-tp-cen-tr-17603-60-10-2022>

Introduction

This document focuses on the specific issues raised by managing all performance aspects of control systems in the frame of space projects. It provides a set of practical definitions, engineering rules, recommendations and guidelines to be used when specifying or verifying the performance of a general control system; attention was paid by the authors to keep the application field as open as possible, and not to restrict to a specific domain – such as spacecraft attitude control for example.

It is not intended to substitute to textbook material on automatic control theory. The readers and the users are assumed to possess general knowledge of control system engineering and its applications to space missions. Nevertheless when required – to avoid any risks of ambiguity for example, or for the clearness of the presentation – some basic definitions and rules are provided in dedicated annexes.

This document was originally intended to focus on the specific case of pointing systems and AOCS, starting from an existing ESA handbook [Pointing Error Handbook, ESA-NCR-502], to be updated, completed, and extended to be built up as an applicable ECSS document. But after reviewing the scope, this approach appeared somewhat restrictive:

- restricting performance concepts to “pointing” does not allow to deal with problems such as thermal control, position control (robotics), or more generally any other type of control systems, even though these problems share the same theoretical framework;
- AOCS is one major contributor to the overall system pointing performance, yet not the only one: misalignments, thermoelastic effects, payload behaviour, etc. all contribute to the final performance. This remark can be extended to general systems, considering that the controlled part is but one of the contributors.

Accounting for these remarks led to extending the initial scope of this document. The upgraded objective is to set up a generalised framework introducing performance definitions, performance indices and budget calculations. “Generalised” is understood here in two directions:

- transversally, so as to be applicable independently on the physical nature of the control system (not only pointing),
- and vertically, in the sense that in many practical situations the proposed definitions and techniques can also apply to any part of the system (basically to the controlled part, but not restrictively). This should assure consistency between the performances indices (error budgets) of the complete system and of the controlled system part. Motivation is also that dedicated but generic methods for budget breakdown can be applied on different levels i.e. on system level and on controlled system level.

NOTE 1 The idea of defining a general framework applying from equipment level to system level is driven by a concern for technical and conceptual consistency. In a later phase, relevant system aspects can be transferred or copied to the appropriate System Engineering standard – if found more convenient.

NOTE 2 The general control structure from the Control Engineering handbook [ECSS-E-HB-60A, Figure 4-1] has been extended in support, showing also the system performance in the output (Figure 4-2 of this handbook)

NOTE 3 The objective of this document is not to cover the high level system or mission performance aspects, which clearly belong to a different category.

In addition to this will for general and generic concepts, a clause of this document covers the performance issues which are more specific for the controlled systems themselves (mainly involving feedback loops in practice) or which are based on well-known control methods. The need for this clause arises as such systems call for particular technical know-how and feature specific performance indicators that require additional insight. For example: stability and robustness properties, transient responses (settling time, response time etc.) and frequency domain indicators.

Although this document is designed to be as general as possible, clearly in practice pointing and AOCS issues are the most demanding space engineering disciplines in terms of control systems. They are covered by an informative annex of the document which declines the general concepts and illustrates how pointing issues can be managed as a special case of vector-type data on a high resolution Earth observation mission.

Driven by a similar concern for illustration on space engineering applications of practical interest, another annex of the document shows how to decline the general concepts to deal with the control performance issue arisen by robotics applications.

iteh STANDARD
PREVIEW
(standards.iteh.ai)

SIST-TP CEN/TR 17603-60-10:2022

<https://standards.iteh.ai/catalog/standards/sist/fa2f8eb8-589c-4032-a27c-63b0283b679a/sist-tp-cen-tr-17603-60-10-2022>

1

Scope

This Handbook deals with control systems developed as part of a space project. It is applicable to all the elements of a space system, including the space segment, the ground segment and the launch service segment.

It addresses the issue of control performance, in terms of definition, specification, verification and validation methods and processes.

The handbook establishes a general framework for handling performance indicators, which applies to all disciplines involving control engineering, and which can be declined as well at different levels ranging from equipment to system level. It also focuses on the specific performance indicators applicable to the case of closed-loop control systems.

Rules and guidelines are provided allowing to combine different error sources in order to build up a performance budget and to assess the compliance with a requirement.

This version of the handbook does not cover control performance issues in the frame of launch systems.

SIST-TP CEN/TR 17603-60-10:2022

<https://standards.iteh.ai/catalog/standards/sist/fa2f8eb8-589c-4032-a27c-63b0283b679a/sist-tp-cen-tr-17603-60-10-2022>

2 References

EN Reference	Reference in text	Title
EN 16601-00-01	ECSS-S-ST-00-01	ECSS System - Glossary of terms
EN 16603-10	ECSS-E-ST-10	Space engineering – System engineering general requirements
EN 16603-60-10	ECSS-E-ST-60-10	Space engineering – Control performance
EN 16603-60-20	ECSS-E-ST-60-20	Space engineering – Stars sensors terminology and performance specifications
TR 16703-60	ECSS-E-HB-60	Space engineering – Control engineering handbook
EN 16601-40	ECSS-M-ST-40	Space project management – Configuration and information management

(standards.iteh.ai)

SIST-TP CEN/TR 17603-60-10:2022

<https://standards.iteh.ai/catalog/standards/sist/fa2f8eb8-589c-4032-a27c-63b0283b679a/sist-tp-cen-tr-17603-60-10-2022>

Terms, definitions and abbreviated terms

3.1 Terms from other documents

For the purpose of this document, the terms and definitions from ECSS-S-ST-00-01 apply.

3.2 Terms specific to the present handbook

3.2.1 control performance (state)

quantified output of a **controlled system**

NOTE 1 Depending on the context, the control performance is realised either as **signal performance** or as **control loop performance**.

NOTE 2 Can also be applied to a **control system**.

3.2.2 control (performance) knowledge (state)

estimated **control performance** after measurement and processing, if any

NOTE The control performance knowledge is not necessarily the best available knowledge of the **control performance**. The achieved accuracy and the allowed deviation (control performance knowledge error) depends on the application.

3.2.3 control reference (state)

ideal reference input, desired state or reference state of controlled part of the plant

3.2.4 domain variable

independent variable which can be used to put some dependent quantity into a certain order

NOTE This comprises continuous time, discrete time, N-dimensional space, etc.

3.2.5 ergodicity

property of a stochastic process such that its ensemble and time statistical properties are identical. Ergodicity allows to transfer the statistical results of a single realisation of a stochastic process to the whole ensemble

NOTE (Weak) **stationarity** is prerequisite for (weak) ergodicity.

3.2.6 error index

parameter isolating a particular aspect of the time variation of a performance error or knowledge error

3.2.7 extrinsic performance

element of performance related to the response of the system to its interaction with the outer world (control reference signal, error sources and other disturbances)

NOTE 1 for example the pointing error of a satellite is relevant to this category of extrinsic performance (it depends on the disturbing torques and on the measurement noises)

NOTE 2 can also be defined in opposition to **intrinsic performance**

3.2.8 intrinsic performance

element of performance related to the intrinsic properties of the system, independently on its interaction with the outer world (control reference, the nature and the amplitude of the error sources and other disturbances)

NOTE 1 for example the **stability** of a closed-loop controlled system is relevant to this category of **intrinsic performances**

NOTE 2 can also be defined in opposition to **extrinsic performance**

NOTE 3 "I have some of my properties purely in virtue of the way I am. (My mass is an example.) I have other properties in virtue of the way I interact with the world. (My weight is an example.) The former are the intrinsic properties, the latter are the extrinsic properties" [Weatherson, Brian, "Intrinsic vs. Extrinsic Properties", The Stanford Encyclopedia of Philosophy (Fall 2004 Edition), Edward N. Zalta (ed.)]

3.2.9 individual error source

elementary physical characteristic or process originating from a well-defined source which contributes to a **performance error** or a **performance knowledge error**

NOTE For example sensor noise, sensor bias, actuator noise, actuator bias, disturbance forces/torques (e.g. micro-vibrations, manoeuvres, external or internal subsystem motions), friction force/torque, misalignments, thermal distortions, assembly distortions, digital quantization, control law performance (steady state error), jitter, etc.

3.2.10 performance error (state difference)

deviation of a performance from its reference; realised as **control (signal or control loop) performance error** or **system performance error**, depending on the context

3.2.11 performance error indicator (state difference)

any quantity suitable to define the **performance error** or **performance knowledge error** of a **controlled system** or one of its parts. Examples are signal error functions, signal error indices or control loop performance indicators