



FINAL DRAFT International Standard

ISO/FDIS 10218-1.2

Robotics — Safety requirements — Part 1: Industrial robots

*Robotique — Exigences de sécurité —
Partie 1: Robots industriels*

ISO/TC 299

Secretariat: **SIS**

Voting begins on:
2024-10-07

Voting terminates on:
2024-12-02

<https://standards.iteh.ai/catalog/standards/iso/a5dbc528-9b3d-4fa1-84cf-c1c9e667a373/iso-fdis-10218-1-2>

ISO/CEN PARALLEL PROCESSING

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/FDIS 10218-1.2](https://standards.iteh.ai/catalog/standards/iso/a5dbc528-9b3d-4fa1-84cf-c1c9e667a373/iso-fdis-10218-1-2)

<https://standards.iteh.ai/catalog/standards/iso/a5dbc528-9b3d-4fa1-84cf-c1c9e667a373/iso-fdis-10218-1-2>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	2
3 Terms, definitions and abbreviated terms	3
3.1 Terms and definitions.....	3
3.1.1 Robot, robot system, robot application, application.....	3
3.1.2 Sub-assemblies and components.....	4
3.1.3 Controls-related.....	6
3.1.4 Program-related.....	7
3.1.5 Power-, energy-related.....	8
3.1.6 Hazard-related.....	8
3.1.7 Role-related.....	8
3.1.8 Functional safety-related.....	9
3.1.9 Spaces, zones and distances.....	10
3.1.10 Risk reduction measures.....	11
3.1.11 Verification and validation.....	12
3.2 Abbreviated terms and symbols.....	12
4 Risk assessment	13
5 Design and risk reduction measures	13
5.1 Robot design.....	13
5.1.1 General.....	13
5.1.2 Materials, mechanical strength and mechanical design.....	13
5.1.3 Handling, lifting and transportation.....	14
5.1.4 Packaging.....	15
5.1.5 Stability.....	15
5.1.6 Temperature and fire risks.....	15
5.1.7 Special equipment.....	15
5.1.8 Position holding.....	15
5.1.9 Auxiliary axis (axes).....	15
5.1.10 Power loss or change.....	16
5.1.11 Component malfunction.....	16
5.1.12 Hazardous energy.....	16
5.1.13 Electrical, pneumatic and hydraulic parts.....	17
5.1.14 Tool centre point (TCP) setting.....	17
5.1.15 Payload setting.....	18
5.1.16 Cybersecurity.....	18
5.1.17 Robot class.....	18
5.2 Controls.....	19
5.2.1 General.....	19
5.2.2 Protection from unexpected start-up.....	19
5.2.3 Singularity.....	20
5.2.4 Interlocking devices.....	20
5.2.5 Status indication and warning devices.....	20
5.2.6 Labelling.....	20
5.2.7 Modes.....	20
5.2.8 Means of controlling the robot.....	23
5.2.9 Means of initiating automatic operation.....	25
5.3 Safety functions.....	25
5.3.1 General.....	25
5.3.2 Functional safety standards.....	25
5.3.3 Performance.....	25
5.3.4 Failure or fault detection.....	26

ISO/FDIS 10218-1.2:2024(en)

5.3.5	Parameterization of safety functions	26
5.3.6	Communications	26
5.3.7	Electromagnetic compatibility (EMC)	27
5.4	Stopping functions	28
5.4.1	General	28
5.4.2	Emergency stop	28
5.4.3	Protective stop	29
5.4.4	Normal stop	29
5.5	Other safety functions	30
5.5.1	Single-point-of-control	30
5.5.2	Start/restart interlock and reset	30
5.5.3	Speed limit(s) monitoring	31
5.5.4	Enabling function	32
5.5.5	Monitored-standstill	33
5.5.6	Stopping time limiting	33
5.5.7	Stopping distance limiting	34
5.6	Simultaneous motion	34
5.7	Limiting robot motion	34
5.7.1	General	34
5.7.2	Mechanical limiting	35
5.7.3	Electro-mechanical limiting	35
5.7.4	Software-based limiting	35
5.7.5	Dynamic limiting	36
5.8	Movement without drive power	36
5.9	Lasers and laser equipment	36
5.10	Capabilities for collaborative applications	36
5.10.1	General	36
5.10.2	Hand-guided control (HGC)	36
5.10.3	Speed and separation monitoring (SSM)	37
5.10.4	Power and force limiting (PFL)	38
6	Verification and validation	38
6.1	General	38
6.2	Verification and validation	38
7	Information for use	39
7.1	General	39
7.2	Signals and warning devices	39
7.3	Marking	39
7.4	Signs (pictograms) and written warnings	40
7.5	Instruction handbook	40
7.5.1	General	40
7.5.2	Identification	40
7.5.3	Intended use	40
7.5.4	Installation	41
7.5.5	Stopping	41
7.5.6	Commissioning and programming	42
7.5.7	Operation and setting	42
7.5.8	Singularity	42
7.5.9	Hazardous energy	42
7.5.10	Movement without drive power	42
7.5.11	Cybersecurity	43
7.5.12	Functional safety	43
7.5.13	Teach pendants	46
7.5.14	Change or addition of component parts	46
7.5.15	Standards	46
7.5.16	Maintenance	46
7.5.17	Abnormal and emergency situations	47
7.5.18	Handling, lifting and transportation	47

ISO/FDIS 10218-1.2:2024(en)

Annex A (informative) List of significant hazards	48
Annex B (informative) Illustrations of spaces	53
Annex C (normative) Safety functions	56
Annex D (informative) Safety function information	62
Annex E (normative) Test methodology for Class I robots - Maximum force per manipulator (F_{MPM})	64
Annex F (informative) Symbols	72
Annex G (informative) Means of verification and validation of the design and risk reduction measures	74
Annex H (normative) Stopping time and distance measurement	93
Annex I (informative) Implementation of start/restart interlock and reset functions	94
Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2006/42/EC aimed to be covered	96
Bibliography	99

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO/FDIS 10218-1.2](https://standards.iteh.ai/catalog/standards/iso/a5dbc528-9b3d-4fa1-84cf-c1c9e667a373/iso-fdis-10218-1-2)

<https://standards.iteh.ai/catalog/standards/iso/a5dbc528-9b3d-4fa1-84cf-c1c9e667a373/iso-fdis-10218-1-2>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 299, *Robotics*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 310, *Advanced automation technologies and their applications*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 10218-1:2011), which has been technically revised.

The main changes are as follows:

- additional requirements for design;
- mode requirements;
- clarifying requirements for functional safety;
- robot classification (Class I and Class II) for functional safety requirements;
- test methodology to determine the maximum force per manipulator for Class I robots;
- adding requirements for cybersecurity to the extent that it applies to industrial robot safety;
- incorporating safety requirements for industrial robots intended for use in collaborative applications (formerly, the content of ISO/TS 15066).

A list of all parts in the ISO 10218 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The ISO 10218 series has been created in recognition of the hazards that are presented by robotics in an industrial environment. This document addresses robots as partly completed machinery, while ISO 10218-2¹⁾ addresses robots integrated into machinery (robot applications and cells).

This document is a type-C standard according to ISO 12100.

This document is of relevance for the following stakeholder groups representing the market players regarding robot safety:

- robot manufacturers (small, medium and large enterprises);
- robot application integrators (small, medium and large enterprises);
- health and safety bodies (regulators, accident prevention organisations, market surveillance, etc.).

Others can be affected by the level of safety achieved with the means of the document by the above mentioned stakeholder groups:

- robot application users/employers (small, medium and large enterprises);
- robot application users/employees (e.g. trade unions);
- service providers, e.g. for maintenance (small, medium and large enterprises);

The above-mentioned stakeholder groups have been given the possibility to participate in the drafting process of this document.

Robots and the extent to which hazards, hazardous situations or hazardous events are covered are indicated in the Scope of this document.

When provisions of a type-C standard are different from those that are stated in type-A or type-B standards, the provisions of the type-C standard take precedence over the provisions of the other standards for machines that have been designed and built in accordance with the provisions of the type-C standard.

In recognition of the variable nature of hazards with different uses of industrial robots, the ISO 10218 series is divided into two parts. This document provides requirements for safety of the robot. For safety of the integration and commissioning of industrial robot applications, ISO/FDIS 10218-2:2024 provides requirements for the safeguarding of operators during integration, commissioning, functional testing, programming, operation, maintenance and repair.

The ISO 10218 series deals with robotics in an industrial environment, which is comprised of workplaces where the public is excluded and the allowed people (operators) are working adults. Other standards cover topics such as general characteristics, coordinate systems and axis motions, mechanical interfaces performance criteria and related testing methods, and end-effectors.

For ease of reading this document, the words “robot” and “robot application” refer to “industrial robot” and “industrial robot application” as defined in this document.

This document has been updated based on experience gained since the release of the ISO 10218 series in 2011. This document remains aligned with the minimum requirements of a harmonized type-C standard for robots in an industrial environment.

Where appropriate, ISO/TS 15066:2016 on the safety of collaborative robot applications was added to the ISO 10218 series. Because human-robot collaboration relates to the application and not to the robot alone, most of the requirements of ISO/TS 15066 have been incorporated into ISO/FDIS 10218-2:2024. Safety functions that enable a collaborative task can be part of the robot or can be provided by a protective device, or a combination.

1) Under preparation, current stage: ISO/FDIS 10218-2:2024, it will be published in conjunction with this document.

ISO/FDIS 10218-1.2:2024(en)

It is important to emphasize that the terms “collaborative operation” and “collaborative robot” are not used in this document. Only the application can be developed, verified and validated as a collaborative application.

iTeh Standards (<https://standards.itih.ai>) Document Preview

[ISO/FDIS 10218-1.2](https://standards.itih.ai/catalog/standards/iso/a5dbc528-9b3d-4fa1-84cf-c1c9e667a373/iso-fdis-10218-1-2)

<https://standards.itih.ai/catalog/standards/iso/a5dbc528-9b3d-4fa1-84cf-c1c9e667a373/iso-fdis-10218-1-2>

Robotics — Safety requirements —

Part 1: Industrial robots

1 Scope

This document specifies requirements for the inherently safe design, risk reduction measures and information for use of robots for an industrial environment.

This document addresses the robot as an incomplete machine.

This document is not applicable to the following uses and products:

- underwater;
- law enforcement;
- military (defence);
- airborne and space robots, including outer space;
- medical robots;
- healthcare robots;
- prosthetics and other aids for the physically impaired;
- service robots, which provide a service to a person and as such where the public can have access;
- consumer products, as this is household use to which the public can have access;
- lifting or transporting people..

NOTE 1 Requirements for robot integration and robot applications are covered in ISO/FDIS 10218-2:2024.

NOTE 2 Additional hazards can be created by robot applications (e.g. welding, laser cutting, machining). These hazards are addressed during robot application design. See ISO/FDIS 10218-2:2024.

This document deals with the significant hazards, hazardous situations or hazardous events when used as intended and under specified conditions of misuse which are reasonably foreseeable by the manufacturer.

This document does not cover the hazards related to:

- severe conditions (e.g. extreme climates, freezer use, strong magnetic fields) outside of manufacturer's specifications;
- underground use;
- use that has hygienic requirements;
- use in nuclear environments;
- use in potentially explosive environments;
- mobility when robots or manipulators are fixed to or part of driverless industrial trucks;

- mobility when robots or manipulators are fixed to or part of mobile platforms;
- use in environments with ionizing and non-ionizing radiation levels;
- hazardous ionizing and non-ionizing radiation;
- handling loads the nature of which can lead to dangerous situations (e.g. molten metals, acids/bases, radiating materials);
- handling or lifting or transporting people;
- when the public, all ages or non-working adults have access (e.g. service robots, consumer products).

Noise emission is generally not considered a significant hazard of the robot alone, and consequently noise is excluded from the scope of this document.

This document is not applicable to robots that are manufactured before the date of its publication.

2 Normative references

The following documents are referred to in the text in such a way that some or all their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3864-1:2011, *Graphical symbols — Safety colours and safety signs — Part 1: Design principles for safety signs and safety markings*

ISO 3864-2:2016, *Graphical symbols — Safety colours and safety signs — Part 2: Design principles for product safety labels*

ISO 3864-3:2024, *Graphical symbols — Safety colours and safety signs — Part 3: Design principles for graphical symbols for use in safety signs*

ISO 3864-4:2011, *Graphical symbols — Safety colours and safety signs — Part 4: Colorimetric and photometric properties of safety sign materials*

ISO 4413:2010, *Hydraulic fluid power — General rules and safety requirements for systems and their components*

ISO 4414:2010, *Pneumatic fluid power — General rules and safety requirements for systems and their components*

ISO 7010:2019, *Graphical symbols — Safety colours and safety signs — Registered safety signs*

ISO 9283:1998, *Manipulating industrial robots — Performance criteria and related test methods*

ISO 12100:2010, *Safety of machinery — General principles for design — Risk assessment and risk reduction*

ISO 13732-1:2006, *Ergonomics of the thermal environment — Methods for the assessment of human responses to contact with surfaces — Part 1: Hot surfaces*

ISO 13732-3:2005, *Ergonomics of the thermal environment — Methods for the assessment of human responses to contact with surfaces — Part 3: Cold surfaces*

ISO 13849-1:2023, *Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design*

ISO 13850:2015, *Safety of machinery — Emergency stop function — Principles for design*

ISO 14118:2017, *Safety of machinery — Prevention of unexpected start-up*

ISO 14119:2024, *Safety of machinery — Interlocking devices associated with guards — Principles for design and selection*

ISO 14120:2015, *Safety of machinery — Guards — General requirements for the design and construction of fixed and movable guards*

ISO 19353:2019, *Safety of machinery — Fire prevention and fire protection*

ISO 20607:2019, *Safety of machinery — Instruction handbook — General drafting principles*

ISO 20643:2005/Amd 1:2012, *Mechanical vibration — Hand-held and hand-guided machinery — Principles for evaluation of vibration emission*

IEC 60073:2002, *Basic and safety principles for man-machine interface, marking and identification — Coding principles for indication devices and actuators*

IEC 60204-1:2016+AMD1:2021, *Safety of machinery — Electrical equipment of machines — Part 1: General requirements*

IEC 60947-5-8:2020, *Low-voltage switchgear and controlgear — Part 5-8: Control circuit devices and switching elements — Three-position enabling switches*

IEC 61310-1:2007, *Safety of machinery — Indication, marking and actuation — Part 1: Requirements for visual, acoustic and tactile signals*

IEC 61310-2:2007, *Safety of machinery — Indication, marking and actuation — Part 2: Requirements for marking*

IEC 61310-3:2007, *Safety of machinery — Indication, marking and actuation — Part 3: Requirements for the location and operation of actuators*

IEC 61508-2:2010, *Functional safety of electrical/electronic/ programmable electronic safety-related systems — Part 2: Requirements for electrical/ electronic/ programmable electronic safety-related systems*

IEC 62061:2021, *Safety of machinery — Functional safety of safety-related electrical, electronic and programmable electronic control systems*

IEC 62745:2017, *Safety of machinery — Requirements for cableless control systems of machinery*

3 Terms, definitions and abbreviated terms

For the purposes of this document, the terms and definitions given in ISO 12100:2010 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>;
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1 Terms and definitions

3.1.1 Robot, robot system, robot application, application

3.1.1.1

industrial environment

workplace where the public is restricted from access or not reasonably expected to be present for the intended tasks and *robot application(s)* (3.1.1.4)

Note 1 to entry: This includes manufacturing, laboratory, pharmaceutical, warehousing, logistics, and more.

**3.1.1.2
industrial robot
robot**

automatically controlled, reprogrammable multipurpose *manipulator(s)* (3.1.2.5), programmable in three or more *axes* (3.1.2.1), which can be either fixed in place or fixed to a *mobile platform* (3.1.2.8) for use in automation *applications* (3.1.1.5) in an *industrial environment* (3.1.1.1)

Note 1 to entry: The industrial robot includes:

- the *manipulator(s)* (3.1.2.5), including *robot actuators* (3.1.2.10) controlled by the robot control;
- the robot control; and
- the means to teach or program the robot, including any communications interface (hardware and software).

Note 2 to entry: This includes any axes that are *integrated* (3.1.7.1) into the kinematic solution.

Note 3 to entry: A mobile robot consists of a *mobile platform* (3.1.2.9) with an integrated *manipulator* (3.1.2.7) or robot.

**3.1.1.3
robot system
industrial robot system**

industrial robot (3.1.1.2), *end-effector(s)* (3.1.2.3), and any end-effector sensors and equipment needed to support the *end-effector(s)* (3.1.2.3)

Note 1 to entry: Examples of equipment are vision systems, adhesive dispensing, weld control.

**3.1.1.4
robot application
industrial robot application**

machine comprising an industrial *robot system* (3.1.1.3), workpieces, *task program* (3.1.4.2), and machinery and equipment to support the *application* (3.1.1.5) and intended tasks

**3.1.1.5
application**

intended use and purpose of the *robot* (3.1.1.2) or *robot application* (3.1.1.4), i.e. the process, the task(s)

EXAMPLE Manipulating, processing, machining, inspection, spot welding, painting, assembly, palletizing.

**3.1.1.6
collaborative application**

applications (3.1.1.5) that contains one or more *collaborative task(s)* (3.1.1.7)

Note 1 to entry: *Collaborative applications* can include non-collaborative.

**3.1.1.7
collaborative task**

portion of the robot sequence where both the *robot application* (3.1.1.4) and *operator(s)* (3.1.7.2) are within the same *safeguarded space* (3.1.9.5)

**3.1.1.8
robot cell
industrial robot cell**

one or more *robot applications* (3.1.1.4) including any obstacle or object that has influence on the risk assessment of the intended use, associated *safeguarded space(s)* (3.1.9.5) and *safeguards* (3.1.10.4)

3.1.2 Sub-assemblies and components

**3.1.2.1
axis**

actuated (e.g. rotating about a pivot, moving linearly) mechanical joint that provides at least one degree of freedom

3.1.2.2

auxiliary axis

axis (3.1.2.1) that is not physically part of the *manipulator* (3.1.2.5) and is controlled by the *robot* (3.1.1.2)

Note 1 to entry: Controlled means that there is a feedback signal(s) to enable closed loop control by the *robot* (3.1.1.2).

3.1.2.3

end-effector

device specifically designed for attachment to the *mechanical interface* (3.1.2.7) to enable the *robot application* (3.1.1.4) to perform its task

EXAMPLE Gripper, welding gun, spray gun.

Note 1 to entry: End-effectors are sometimes known as end-of-arm tooling (EOAT).

3.1.2.4

gripper

end-effector (3.1.2.3) designed for seizing and holding workpieces

Note 1 to entry: Various types of grippers and the terms grip, grasp, grasping and releasing are defined in ISO 14539:2000.

[SOURCE: ISO 14539:2000, 4.1.2, modified — Note 1 to entry has been added.]

3.1.2.5

manipulator

mechanism consisting of an arrangement of segments, jointed or sliding relative to one another

Note 1 to entry: *Robot actuators* (3.1.2.10) can constitute parts of a *manipulator*.

3.1.2.6

mass per manipulator

M

mass of all moving parts of the *manipulator* (3.1.2.5)

3.1.2.7

mechanical interface

mounting surface at the end of the *manipulator* (3.1.2.5) to which the *end-effector* (3.1.2.3) is attached

3.1.2.8

mobile platform

assembly of the components which enables locomotion and provides the structure to affix or integrate a *manipulator* (3.1.2.5) or *robot* (3.1.1.2)

3.1.2.9

payload

mass of all that is attached to the *manipulator* (3.1.2.5), including the *end-effector* (3.1.2.3) and workpiece

Note 1 to entry: The payload can be, but is not limited to, the payload attached to the *mechanical interface* (3.1.2.7) of the *robot* (3.1.1.2).

3.1.2.10

robot actuator

powered mechanism that converts energy to effect motion

Note 1 to entry: Energy can be electrical, hydraulic, pneumatic or more.

3.1.2.11

tool centre point

TCP

point defined for a given *application* (3.1.1.5) relative to the *mechanical interface* (3.1.2.7) coordinate system.

Note 1 to entry: The TCP setting defines the location of the TCP relative to the *mechanical interface* (3.1.2.7).

3.1.3 Controls-related

3.1.3.1

control station

enclosure which contains one or more control devices intended to activate or deactivate functions

Note 1 to entry: The *control station* can be fixed in place (e.g. control panel) or can be movable (*teach pendant* (3.1.3.3) or *pendant* (3.1.3.2) which can be referred to as a portable control station).

3.1.3.2

pendant

hand-held *control station* (3.1.3.1)

3.1.3.3

teach pendant

pendant (3.1.3.2) with which a *robot* (3.1.1.2) can be programmed, moved or actuated

Note 1 to entry: Hand-held units or devices which only have the capability of displaying parameters (e.g. no motion and no actuation capabilities), are not considered to be *control stations* (3.1.3.1) or *teach pendants* (3.1.3.3).

Note 2 to entry: The *teach pendant* can be linked to the *end-effector* (3.1.2.3) and other parts of the *robot application* (3.1.1.4).

3.1.3.4

direct control

movement or operation effected by the *control station* (3.1.3.1) that is part of the *robot* (3.1.1.2)

Note 1 to entry: Previously direct control was known as local control of the *robot* (3.1.1.2).

3.1.3.5

external control

movement or operation effected by the *control station* (3.1.3.1) not a part of the *robot* (3.1.1.2)

Note 1 to entry: Previously external control was known as remote control of the *robot* (3.1.1.2).

Note 2 to entry: See ISO/FDIS 10218-2:2024 for requirements of remote control.

3.1.3.6

singularity

occurrence whenever the rank of the Jacobian matrix becomes less than full rank

Note 1 to entry: Mathematically, in a singular configuration, the joint velocity in joint space can become infinite to maintain Cartesian velocity. In actual operation, motions defined in Cartesian space that pass near singularities can produce high axis speeds. These high axis speeds can be unexpected to an *operator* (3.1.7.2).

3.1.3.7

span-of-control

predetermined portion of a *robot* (3.1.1.2), *robot application* (3.1.1.4), *robot cell* (3.1.1.8) or machinery that is under control of a specific device for a *safety function* (3.1.8.1)

Note 1 to entry: *Protective devices* (3.1.10.5) and emergency stop devices could initiate a stop of a machine, a portion of a machine, or partly completed machinery, i.e. a *robot* (3.1.1.2).

3.1.3.8

simultaneous motion

motion of two or more *robots* (3.1.1.2) at the same time under the control of a single robot, which can be coordinated or can be synchronous