

DRAFT INTERNATIONAL STANDARD

ISO/DIS 27919-2

ISO/TC 265

Secretariat: SCC

Voting begins on:
2020-08-27

Voting terminates on:
2020-11-19

Carbon dioxide capture —

Part 2:

Evaluation procedure to assure and maintain stable performance of post-combustion CO₂ capture plant integrated with a power plant

ICS: 13.020.40

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/DIS 27919-2](https://standards.iteh.ai/catalog/standards/sist/a26d09da-bc6c-41ed-8b1c-70cd92077667/iso-dis-27919-2)

<https://standards.iteh.ai/catalog/standards/sist/a26d09da-bc6c-41ed-8b1c-70cd92077667/iso-dis-27919-2>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.



Reference number
ISO/DIS 27919-2:2020(E)

© ISO 2020

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/DIS 27919-2

<https://standards.iteh.ai/catalog/standards/sist/a26d09da-bc6c-41ed-8b1c-70cd92077667/iso-dis-27919-2>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 Terms and definitions	1
3.2 Abbreviations	6
4 Principles	7
4.1 Introduction	7
4.2 General	7
4.3 Reliable performance	7
4.4 Ensuring and maintaining reliable performance	7
4.5 Procedure outline	7
4.5.1 Outline of procedure flow	7
4.5.2 Process step 1 to 3 outline — Main part	8
4.5.3 Process step 4 to 6 outline — Evaluations of items peculiar to a PCC plant with some uncertainty	9
4.6 Governing principles	9
5 Availability, reliability and maintainability - basic concepts for a PCC plant	10
5.1 General	10
5.2 Spatial and temporal evaluation boundary	11
5.3 Evaluation and quantification of availability	11
5.4 Evaluation and quantification of reliability	12
5.5 Evaluation and quantification of maintainability	14
5.6 Combined aspect of availability, reliability and maintainability	15
5.7 Unavailability (three categories)	15
6 Defining reliability, availability and maintainability in the design stage	16
6.1 Procedure of design evaluation	16
6.2 PCC plant definition	16
6.3 Basic design phase	16
7 Determining reliability and availability in the operational stage	17
7.1 Introduction	17
7.2 Review of operation result	17
7.3 Basic operation pattern for evaluation and reporting of operation	17
7.4 Normal operation (transient and steady)	19
7.5 Start-up and shut-down	20
7.6 Emergency operations	21
7.7 Downtime	21
7.8 Plant operator organization and training	21
8 Implications for maintenance	21
8.1 Maintainability and mean downtime	21
8.2 Maintenance strategies	22
9 Reporting availability	23
9.1 General	23
9.2 PCC plant capacity availability and product CO ₂ producibility	24
9.3 Schedule compliance	26
9.4 Time availability	27
9.5 On-stream factor	28
Annex A (informative) Detailed evaluation procedure to ensure and maintain stable performance of a post-combustion CO₂ capture plant	30

Annex B (informative) The reference plant and its component experience	38
Annex C (informative) Technology Qualification.....	44
Annex D (informative) Classification of influence factors for PCC plant capacity availability and Product CO₂ producibility in Clause 9	45
Annex E (informative) PCC plant achievability	46
Annex F (informative) Calculation example of each KPI.....	48
Annex G (Informative) Map of key issues and items to be checked relating the performance requirement	52
Bibliography	56

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/DIS 27919-2

<https://standards.iteh.ai/catalog/standards/sist/a26d09da-bc6c-41ed-8b1c-70cd92077667/iso-dis-27919-2>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC265.

A list of all parts in the ISO 27919 series can be found on the ISO website:
<http://www.iso.org/iso/27919>

Introduction

It is very important to reduce atmospheric carbon dioxide (CO₂) emission in order to meet climate change mitigation targets. Inclusion of carbon dioxide capture and storage (CCS) among the variety of available emission reduction approaches enhances the probability of meeting these targets at the lowest cost to the global economy. CO₂ capture from gases produced by combustion of carbonaceous fuels is the only technology capable of dealing directly with emissions from power plants and other industrial sectors, such as cement manufacture and fertilizer production.

This document is the second in a series of standards for post-combustion CO₂ capture (PCC) from a power plant using a liquid-based chemical absorption process. Building on the first standard on evaluation of key performance parameters (KPIs), this document provides an evaluation procedure to assure and maintain reliable performance of a PCC plant integrated with a power plant. New or revised standards focusing on other CO₂ capture technologies and approaches will be developed later.

PCC is applicable to all combustion-based thermal power plants. A simplified block diagram illustrating the PCC is shown in [Figure 1](#).




Figure 1 — Simplified block diagram for PCC

In a typical power generation facility, carbonaceous fuel (e.g. coal, oil, gas, biomass) is combusted with air in a boiler to raise steam that drives a turbine/generator to produce power. In a gas turbine combined cycle system, the combustion occurs in the gas turbine to drive power generation, and steam generated through a heat recovery steam generator (HRSG) contributes to additional power generation. Flue gas from the boiler or gas turbine consists mostly of N₂, CO₂, H₂O and O₂ with smaller amounts of other compounds depending on the fuel used. The CO₂ capture process is located downstream of conventional pollutant controls. Chemical absorption-based PCC usually requires the extraction of steam from the power plant's steam cycle or, depending on the absorption liquid/process employed, the use of lower grade heat sources for absorption liquid regeneration.

The economic and environmental value of a PCC plant is not only determined by its technical performance, but also by its ability to achieve and maintain stable operation as required by its owners/stakeholders. The owner of the flue gas source has an interest in sustained CO₂-emission reductions; the owner of the CO₂-product has an interest being able to supply CO₂ at the desired rate regardless of external conditions; The CO₂ receiver has an interest in CO₂-product availability for its own operations.

The provision of a framework for quantifying and assessing the stability of a PCC plant operation according to this standard will clarify PCC plant availability at the design and operational stage. It will also underpin the quantification of plant reliability and maintainability.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/DIS 27919-2](https://standards.iteh.ai/catalog/standards/sist/a26d09da-bc6c-41ed-8b1c-70cd92077667/iso-dis-27919-2)

<https://standards.iteh.ai/catalog/standards/sist/a26d09da-bc6c-41ed-8b1c-70cd92077667/iso-dis-27919-2>

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

ISO/DIS 27919-2

<https://standards.iteh.ai/catalog/standards/sist/a26d09da-bc6c-41ed-8b1c-70cd92077667/iso-dis-27919-2>

Carbon dioxide capture —

Part 2:

Evaluation procedure to assure and maintain stable performance of post-combustion CO₂ capture plant integrated with a power plant

1 Scope

This document provides definitions, guidelines and supporting information for evaluating and reporting (in respect of the basic design items ongoing and the operational results of a reference plant or unit as feedback to ensure) the (designed) performance of a PCC plant integrated with the host power plant which separates CO₂ from the power plant flue gas in preparation for subsequent transportation and geological storage. The physical system being addressed is a single power plant, optionally with an auxiliary unit to provide thermal energy required for the PCC plant, and a single PCC plant as described in ISO 27919-1.

The formulas and methods presented in this document describe issues that are addressed during the design and construction phases (to assure reliable performance) and to practices that can document reliability and availability during routine operation. These practices would also guide ongoing maintenance programs.

This document does not provide guidelines for benchmark, comparison or assessment studies for PCC plant operations using different capture technologies (i.e. absorbents), nor does it specify appropriate operating conditions such as temperature, etc.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 27919-1:2018, *Carbon dioxide capture — Part 1: Performance evaluation methods for post-combustion CO₂ capture integrated with a power plant*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 Terms and definitions

3.1.1

administrative delay

delay to maintenance incurred for administrative reasons

[SOURCE: IEC 60050-192 (192-7-12), modified]

3.1.2

availability

ability of a PCC plant integrated with the power plant to be in a state to perform as required under given conditions at a given instant of time or over a given time interval, assuming that the required external resources are provided

3.1.3

corrective maintenance

maintenance carried out after fault detection to effect restoration

Note 1 to entry: Corrective maintenance of critical items disrupts the plant availability.

3.1.4

critical item

item that needs to be available and operating in order for the PCC plant to be available

3.1.5

downtime

time interval for which the item is in a state of being unable to perform as required due to internal faults, or preventive maintenance

[SOURCE: IEC 60050-192 (192-02-21), modified]

3.1.6

emergency operation

type of sudden shut-down operation to protect hardware from damage. If the cause of the emergency trip shut-down is solved without corrective maintenance repair, such as adjustment of operating conditions or control parameter, it is linked by sudden restoration or resumption

3.1.7

external influence

critical items occurring outside of the PCC plant evaluation boundary

3.1.8

failure mechanism

process that leads to failure

Note 1 to entry: The process may be physical, chemical, logical, or a combination thereof.

[SOURCE: IEC 60050-192 (192-03-12), modified]

3.1.9

item

subject being considered

Note 1 to entry: An item may be an individual part, component, device, functional unit, equipment, subsystem, or system.

Note 2 to entry: An item may consist of hardware, software, people or any combination thereof.

Note 3 to entry: An item is often comprised of elements that may each be individually considered.

[SOURCE: IEC 60050-192 (192-01-01), modified]

3.1.10

logistic delay

delay, excluding administrative delay, incurred for the provision of resources needed for a maintenance action to proceed or continue

[SOURCE: ISO 20815:2018, definition 3.1.24]

3.1.11**maintainability**

ability to be retained in, or restored to, a state in which the required function can be performed under given conditions

3.1.12**maintenance**

combination of all technical and management actions intended to retain an item in, or restore it to, a state in which it can perform as required

Note 1 to entry: Management is assumed to include supervision activities.

[SOURCE: IEC 60050-192:2015, 192-06-01]

3.1.13**mean downtime****MDT**

expectation of the downtime

[SOURCE: IEC 60050-192 (192-08-10)]

3.1.14**mean time between failures****MTBF**

average time between failures which initiate a forced outage, i.e. the ratio of attempted operating hours to the number of forced outages

3.1.15**mission time**

duration of the mission

[SOURCE: ISO 10438-1:2007(en), 3.1.19]

3.1.16**net dependable capacity****NDC**

gross dependable capacity minus the unit capacity using for that unit's station services or auxiliaries

[SOURCE: ISO 3977-9]

3.1.17**nominal product CO₂ capacity**

highest continuous flow rate of delivering captured CO₂ under typical representative conditions defined by the plant operator

3.1.18**normal operation**

operation where the product CO₂ is exported to the transporting system maintaining the required performance based on ISO 27919-1

3.1.19**on-stream factor**

ratio of the summation of all on-stream time to the reference period, with both expressed as hours

3.1.20**outage**

time interval for which the item is in a state of being unable to perform as required, for any reason

[SOURCE: IEC 60050-192 (192-02-19), modified]

3.1.21

PCC plant

process and associated equipment that produces a CO₂ stream from combustion gases

[SOURCE: ISO 27919-1:2018(en), [3.1.26](#)]

3.1.22

PCC plant capacity availability

availability of PCC plant from a perspective of product CO₂ amount during a reference period

Note 1 to entry: It is mathematically defined by [Formula \(3\)](#)

[SOURCE: ISO 3977-9:1999(E), modified]

3.1.23

PCC plant load

ratio of 'the product CO₂ capacity (in operation) to the 'nominal product CO₂ capacity (flow rate)', expressed as a percentage

3.1.24

planned (scheduled) maintenance

maintenance carried out in accordance with a specified time schedule

Note 1 to entry: Scheduled maintenance may identify the need for some corrective maintenance action.

[SOURCE: IEC 60050-192 (192-06-12), modified]

3.1.25

preventive maintenance

maintenance carried out in accordance with an established time schedule and performing according to a prescribed criteria

Note 1 to entry: See also condition-based maintenance (192-06-07), and scheduled maintenance (192-06-12).

[SOURCE: ISO 23815-1]

3.1.26

project cycle

series of phases of which a project consists, e.g. basic design, engineering, manufacturing, commissioning and operation

3.1.27

product CO₂ amount

volume, moles or mass of CO₂ resulting from the PCC process

3.1.28

product CO₂ capacity

total flow rate of the captured CO₂ exported

Note 1 to entry: It is generally expressed as product CO₂ amount per hour.

3.1.29

product CO₂ producibility

ratio of the product CO₂ produced to the total amount of produced nominal product CO₂

3.1.30

proven technology element

element with low or acceptable uncertainty levels

3.1.31 redundancy

item where an equivalent unit can be put online to provide the same function should the principal item fail to provide the service

Note 1 to entry: Redundancy is related to a strategy of design, where a spare system or component is provided so that, even if one critical item fails, the spare system or component will operate in place of the deficient item such that plant performance is not affected.

3.1.32 reference period

period of time between an initial time and an end time over which all historical or projected performance metrics are measured or projected

Note 1 to entry: Reference period is equivalent to period hours (PH).

3.1.33 reliability

measure of the probability of success for an operation to perform its intended function and the ability of each item to perform its intended function in an assembled PCC plant during a given interval.

3.1.34 reliable performance

ability of a PCC plant to function as intended

3.1.35 schedule compliance

ratio of the product CO₂ amount to the scheduled CO₂ product amount requirement met (historical) or to be met (projected) by the PCC plant within a given time period

3.1.36 service hours

accumulated period of time from main flame ignition through to flame extinction

[SOURCE: ISO 3977-9:1999(en), 3.98]

3.1.37 shut-down

event during which all required function of a PCC plant, and its equipment, is brought from an operating state to a stoppage state under the control of a programmed sequence

3.1.38 stand-by state

non-operating state during the required period

3.1.39 starting reliability

probability of successful start-up when the PCC plant is on stream within a specified period

3.1.40 start-up

act of getting a PCC plant and its equipment from a stoppage state ready to activate its items to an operation state

3.1.41 technical delay

accumulated time necessary to perform auxiliary technical actions associated with the maintenance action itself

3.1.42

time availability

ratio of PCC plant unavailable time (excluding external influences) subtracted from the reference period to the reference period

Note 1 to entry: an available time is calculated by subtraction of the unavailable time from reference period.

3.1.43

time reliability

ability of a system to perform

3.1.44

unavailability

PCC plant is not in a state to perform as required due to the internal reason or preventive maintenance

3.1.45

uptime

time interval during which a PCC plant is in a state of being able to perform as required

Note 1 to entry: Absence of necessary external resources may prevent operation, but do not affect the up state.

[SOURCE: IEC 60050-192 (192-02-02), modified]

3.2 Abbreviations

CCS carbon dioxide capture and storage

DSS daily start and stop

EHS environment, health and safety

EOR enhanced oil recovery

EPC engineering, procurement and construction

ESD emergency shut-down

KPIs key performance indicators

MDT mean downtime

MR mission reliability

MTBF mean time between failure

MTPM mean time for preventive maintenance

MTTR mean time to repair

PCA PCC plant capacity availability

PCC post-combustion CO₂ capture

RAM reliability, availability and maintainability

SR starting reliability

TA time availability

iteh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/DIS 27919-2](https://standards.iteh.ai/catalog/standards/sist/a26d09da-bc6c-41ed-8b1c-70cd92077667/iso-dis-27919-2)

<https://standards.iteh.ai/catalog/standards/sist/a26d09da-bc6c-41ed-8b1c-70cd92077667/iso-dis-27919-2>

TQ	technology qualification
TR	time reliability
TRL	technology readiness level

4 Principles

4.1 Introduction

The evaluation procedure described in this document assumes the following:

- A PCC plant shall be designed, manufactured and constructed in line with proven and established engineering practices during the whole project life cycle.
- A PCC plant design may be a combination of proven technology items with some novel ones which can contribute to improve performance and/or economy in construction or operation. The level of novelty is closely related with the technological readiness of the applied technology items.
- A shut-down of the PCC plant will not cause immediate stoppage of the upstream power plant or the downstream side CO₂ transportation.
- A PCC plant is a maintainable system and availability may be improved if maintainability as well as reliability of each technology item is improved through feedback of operational results.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This document describes a procedure that combines technology-item evaluation methods with reliability, availability, and (in some cases) maintainability evaluation methods.

<https://standards.iteh.ai/catalog/standards/sist/a26d09da-bc6c-41ed-8b1c-70cd92077667/iso-dis-27919-2>

4.3 Reliable performance

Reliable performance depends on having a PCC plant that functions as intended.

Reliable performance has two aspects:

- that the required performance is satisfied at the initial conditions and
- that it is maintained during a defined period.

4.4 Ensuring and maintaining reliable performance

To perform as required, this document provides the following as part of the PCC's plant's project life cycle:

- basic concepts of reliability, availability and maintainability – refer to [Clause 5](#)
- guidelines for ensuring reliable performance at delivery in terms of design – refer to [Clause 6](#).
- guidelines for adequate monitoring and for evaluating reliable performance in terms of operation and maintenance – refer to [Clause 7](#) and [Clause 8](#)
- guidelines for reporting availability – refer to [Clause 9](#) based on [Clause 6](#), [Clause 7](#) and [Clause 8](#)

4.5 Procedure outline

4.5.1 Outline of procedure flow

The evaluation procedure consists of process step 1 to 6 crossing through actions in the related project life cycle phases and its block flow should be referred to [Figure 2](#). Process step 1, 2 (Summary) and 3 are