

ETSI TS 136 101 V14.27.0 (2025-02)



LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 14.27.0 Release 14)

[ETSI TS 136 101 V14.27.0 \(2025-02\)](https://standards.iteh.ai/catalog/standards/etsi/b9a4ff7-59ec-4c84-82db-b1782c49715e/etsi-ts-136-101-v14-27-0-2025-02)

<https://standards.iteh.ai/catalog/standards/etsi/b9a4ff7-59ec-4c84-82db-b1782c49715e/etsi-ts-136-101-v14-27-0-2025-02>



Reference

RTS/TSGR-0436101ver0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2025-02)

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	30
1 Scope	31
2 References	31
3 Definitions, symbols and abbreviations	31
3.1 Definitions	31
3.2 Symbols.....	33
3.3 Abbreviations	36
4 General	37
4.1 Relationship between minimum requirements and test requirements	37
4.2 Applicability of minimum requirements	37
4.3 Void.....	38
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1, UE category M2, UE category 1bis, UE category NB1 and NB2, V2X Communication, MBMS UE)	38
4.4 RF requirements in later releases	39
5 Operating bands and channel arrangement.....	40
5.1 General	40
5.2 Void.....	40
5.3 Void.....	40
5.4 Void.....	40
5.5 Operating bands.....	40
5.5A Operating bands for CA	42
5.5B Operating bands for UL-MIMO	50
5.5C Operating bands for Dual Connectivity	50
5.5D Operating bands for ProSe.....	51
5.5E Operating bands for UE category 0, UE category M1 and M2 and UE category 1bis	52
5.5F Operating bands for category NB1 and NB2.....	52
5.5G Operating bands for V2X Communication.....	52
5.6 Channel bandwidth.....	53
5.6.1 Channel bandwidths per operating band.....	54
5.6A Channel bandwidth for CA.....	55
5.6A.1 Channel bandwidths per operating band for CA.....	58
5.6B Channel bandwidth for UL-MIMO	104
5.6B.1 Void	104
5.6C Channel bandwidth for Dual Connectivity.....	104
5.6C.1 Void	104
5.6D Channel bandwidth for ProSe.....	104
5.6D.1 Channel bandwidths per operating band for ProSe.....	104
5.6F Channel bandwidth for category NB1 and NB2.....	105
5.6G Channel bandwidth for V2X Communication.....	106
5.6G.1 Channel bandwidths per operating band for V2X Communication	106
5.7 Channel arrangement.....	107
5.7.1 Channel spacing.....	107
5.7.1A Channel spacing for CA.....	107
5.7.1F Channel spacing for category NB1 and NB2.....	108
5.7.2 Channel raster	108
5.7.2A Channel raster for CA.....	108
5.7.2F Channel raster for category NB1 and NB2.....	108
5.7.3 Carrier frequency and EARFCN.....	108
5.7.3F Carrier frequency and EARFCN for category NB1 and NB2.....	110

5.7.4	TX–RX frequency separation	110
5.7.4A	TX–RX frequency separation for CA	111
5.7.4E	TX–RX frequency separation for category M1 and M2	111
5.7.4F	TX–RX frequency separation for category NB1 and NB2	111
6	Transmitter characteristics	111
6.1	General	111
6.2	Transmit power	111
6.2.1	Void	111
6.2.2	UE maximum output power	111
6.2.2A	UE maximum output power for CA	113
6.2.2B	UE maximum output power for UL-MIMO	115
6.2.2C	Void	116
6.2.2D	UE maximum output power for ProSe	117
6.2.2E	UE maximum output power for Category M1 and M2 UE	117
6.2.2F	UE maximum output power for category NB1 and NB2	118
6.2.2G	UE maximum output power for V2X Communication	118
6.2.3	UE maximum output power for modulation / channel bandwidth	119
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	120
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	123
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe	123
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1 and M2	124
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1 and NB2	125
6.2.3G	UE maximum output power for modulation / channel bandwidth for V2X Communication	126
6.2.3G.1	MPR for Power class 3 V2X UE	126
6.2.3G.2	MPR for Power class 2 V2X UE	127
6.2.4	UE maximum output power with additional requirements	127
6.2.4A	UE maximum output power with additional requirements for CA	139
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	140
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	141
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	142
6.2.4A.4	A-MPR for CA_NS_04	142
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	143
6.2.4A.6	A-MPR for CA_NS_06	144
6.2.4A.7	A-MPR for CA_NS_07	145
6.2.4A.8	A-MPR for CA_NS_08	145
6.2.4B	UE maximum output power with additional requirements for UL-MIMO	146
6.2.4D	UE maximum output power with additional requirements for ProSe	146
6.2.4E	UE maximum output power with additional requirements for category M1 and M2 UE	147
6.2.4F	UE maximum output power with additional requirements for category NB1 and NB2 UE	149
6.2.4G	UE maximum output power with additional requirements for V2X Communication	149
6.2.5	Configured transmitted power	151
6.2.5A	Configured transmitted power for CA	181
6.2.5B	Configured transmitted power for UL-MIMO	183
6.2.5C	Configured transmitted power for Dual Connectivity	183
6.2.5D	Configured transmitted power for ProSe	185
6.2.5F	Configured transmitted Power for category NB1 and NB2	186
6.2.5G	Configured transmitted power for V2X Communication	187
6.3	Output power dynamics	191
6.3.1	(Void)	191
6.3.2	Minimum output power	191
6.3.2.1	Minimum requirement	191
6.3.2A	UE Minimum output power for CA	191
6.3.2A.1	Minimum requirement for CA	191
6.3.2B	UE Minimum output power for UL-MIMO	192
6.3.2B.1	Minimum requirement	192
6.3.2C	Void	192
6.3.2D	UE Minimum output power for ProSe	192
6.3.2F	UE Minimum output power for category NB1 and NB2	192
6.3.2G	UE Minimum output power for V2X Communication	192
6.3.3	Transmit OFF power	193
6.3.3.1	Minimum requirement	193

6.3.3A	UE Transmit OFF power for CA	193
6.3.3A.1	Minimum requirement for CA	193
6.3.3B	UE Transmit OFF power for UL-MIMO	194
6.3.3B.1	Minimum requirement	194
6.3.3D	Transmit OFF power for ProSe.....	194
6.3.3F	Transmit OFF power for category NB1 and NB2.....	194
6.3.3G	Transmit OFF power for V2X Communication.....	195
6.3.4	ON/OFF time mask.....	195
6.3.4.1	General ON/OFF time mask	195
6.3.4.2	PRACH and SRS time mask	196
6.3.4.2.1	PRACH time mask	196
6.3.4.2.2	SRS time mask	196
6.3.4.3	Slot / Sub frame boundary time mask	197
6.3.4.4	PUCCH / PUSCH / SRS time mask.....	198
6.3.4A	ON/OFF time mask for CA	200
6.3.4B	ON/OFF time mask for UL-MIMO	201
6.3.4D	ON/OFF time mask for ProSe.....	201
6.3.4D.1	General time mask for ProSe	201
6.3.4D.2	PSSS/SSSS time mask	201
6.3.4D.3	PSSS / SSSS / PSBCH time mask.....	202
6.3.4D.4	PSSCH / SRS time mask.....	203
6.3.4F	ON/OFF time mask for category NB1 and NB2.....	203
6.3.4F.1	General ON/OFF time mask	203
6.3.4F.2	NPRACH time mask	204
6.3.4G	ON/OFF time mask for V2X Communication.....	204
6.3.4G.1	PSSS / SSSS / PSBCH time mask.....	204
6.3.5	Power Control.....	205
6.3.5.1	Absolute power tolerance.....	205
6.3.5.1.1	Minimum requirements	205
6.3.5.2	Relative Power tolerance.....	206
6.3.5.2.1	Minimum requirements	206
6.3.5.3	Aggregate power control tolerance	207
6.3.5.3.1	Minimum requirement.....	207
6.3.5A	Power control for CA.....	207
6.3.5A.1	Absolute power tolerance	207
6.3.5A.1.1	Minimum requirements	207
6.3.5A.2	Relative power tolerance	208
6.3.5A.2.1	Minimum requirements	208
6.3.5A.3	Aggregate power control tolerance	208
6.3.5A.3.1	Minimum requirements	208
6.3.5B	Power control for UL-MIMO	209
6.3.5D	Power Control for ProSe.....	209
6.3.5D.1	Absolute power tolerance.....	209
6.3.5E	Power control for category M1 and M2.....	209
6.3.5E.1	Absolute power tolerance.....	209
6.3.5E.2	Relative Power tolerance.....	209
6.3.5E.3	Aggregate power control tolerance	209
6.3.5E.3.1	Minimum requirement.....	210
6.3.5F	Power Control for category NB1 and NB2.....	210
6.3.5F.1	Absolute power tolerance.....	210
6.3.5F.2	Relative power tolerance.....	211
6.3.5F.3	Aggregate power control tolerance for category NB1 and NB2	211
6.3.5F.3.1	Minimum requirement.....	212
6.3.5G	Power Control for V2X Communication	212
6.3.5G.1	Absolute power tolerance.....	212
6.4	Void.....	212
6.5	Transmit signal quality	212
6.5.1	Frequency error.....	212
6.5.1A	Frequency error for CA.....	213
6.5.1B	Frequency error for UL-MIMO	213
6.5.1D	Frequency error for ProSe.....	213
6.5.1E	Frequency error for UE category M1 and M2	213

6.5.1F	Frequency error for UE category NB1 and NB2	213
6.5.1G	Frequency error for V2X Communication.....	214
6.5.2	Transmit modulation quality.....	214
6.5.2.1	Error Vector Magnitude	214
6.5.2.1.1	Minimum requirement.....	214
6.5.2.2	Carrier leakage	215
6.5.2.2.1	Minimum requirements	215
6.5.2.3	In-band emissions	215
6.5.2.3.1	Minimum requirements	215
6.5.2.4	EVM equalizer spectrum flatness	216
6.5.2.4.1	Minimum requirements	217
6.5.2A	Transmit modulation quality for CA.....	218
6.5.2A.1	Error Vector Magnitude	218
6.5.2A.2	Carrier leakage for CA.....	218
6.5.2A.2.1	Minimum requirements.....	218
6.5.2A.3	In-band emissions	218
6.5.2A.3.1	Minimum requirement for CA.....	218
6.5.2B	Transmit modulation quality for UL-MIMO	220
6.5.2B.1	Error Vector Magnitude	221
6.5.2B.2	Carrier leakage	221
6.5.2B.3	In-band emissions	221
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	221
6.5.2D	Transmit modulation quality for ProSe.....	221
6.5.2D.1	Error Vector Magnitude	221
6.5.2D.2	Carrier leakage	221
6.5.2D.3	In-band emissions	221
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	221
6.5.2E	Transmit modulation quality for category M1 and M2.....	222
6.5.2E.1	Error Vector Magnitude	222
6.5.2E.2	Carrier leakage	222
6.5.2E.2.1	Minimum requirements	222
6.5.2E.3	In-band emissions	222
6.5.2E.3.1	Minimum requirements	222
6.5.2F	Transmit modulation quality for Category NB1 and NB2.....	223
6.5.2F.1	Error Vector Magnitude	223
6.5.2F.2	Carrier leakage	223
6.5.2F.3	In-band emissions	223
6.5.2G	Transmit modulation quality for V2X Communication.....	224
6.5.2G.1	Error Vector Magnitude	224
6.5.2G.2	Carrier leakage	224
6.5.2G.3	In-band emissions	224
6.5.2G.4	EVM equalizer spectrum flatness	225
6.6	Output RF spectrum emissions.....	225
6.6.1	Occupied bandwidth	225
6.6.1.1	Additional minimum requirement for E-UTRA (network signalled value "NS_29").....	225
6.6.1A	Occupied bandwidth for CA	225
6.6.1B	Occupied bandwidth for UL-MIMO.....	226
6.6.1F	Occupied bandwidth for category NB1 and NB2	226
6.6.1G	Occupied bandwidth for V2X Communication	226
6.6.2	Out of band emission	227
6.6.2.1	Spectrum emission mask	227
6.6.2.1.1	Minimum requirement.....	227
6.6.2.1A	Spectrum emission mask for CA.....	227
6.6.2.2	Additional spectrum emission mask	229
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21").....	229
6.6.2.2.2	Minimum requirement (network signalled value "NS_04")	229
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	230
6.6.2.2.4	Minimum requirement (network signalled value "NS_33" or "NS_34")	230
6.6.2.2.5	Minimum requirement (network signalled value "NS_27").....	231
6.6.2.2.6	Minimum requirement (network signalled value "NS_28").....	231
6.6.2.2A	Additional Spectrum Emission Mask for CA.....	232
6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04").....	232

6.6.2.3	Adjacent Channel Leakage Ratio.....	232
6.6.2.3.1	Minimum requirement E-UTRA	233
6.6.2.3.1a	Additional minimum requirement for E-UTRA (network signalled value "NS_29")	234
6.6.2.3.1A	Void.....	234
6.6.2.3.1Aa	Void.....	234
6.6.2.3.2	Minimum requirements UTRA	234
6.6.2.3.2A	Minimum requirement UTRA for CA.....	235
6.6.2.3.3A	Minimum requirements for CA E-UTRA.....	236
6.6.2.4	Void.....	237
6.6.2.4.1	Void.....	237
6.6.2A	Void.....	237
6.6.2B	Out of band emission for UL-MIMO.....	237
6.6.2C	Void	238
6.6.2D	Out of band emission for ProSe.....	238
6.6.2F	Out of band emission for category NB1 and NB2	238
6.6.2F.1	Spectrum emission mask.....	238
6.6.2F.2	Additional Spectrum Emission Mask for Category NB1 and NB2This requirement is specified in terms of an "additional spectrum emission" requirement	239
6.6.2F.2.1	Minimum requirement (network signalled value "NS_02")	239
6.6.2F.2.2	Minimum requirement (network signalled value "NS_03")	239
6.6.2F.3	Adjacent Channel Leakage Ratio for category NB1 and NB2.....	239
6.6.2G	Out of band emission for V2X Communication	240
6.6.3	Spurious emissions	240
6.6.3.1	Minimum requirements.....	240
6.6.3.1A	Minimum requirements for CA.....	241
6.6.3.2	Spurious emission band UE co-existence	242
6.6.3.2A	Spurious emission band UE co-existence for CA	247
6.6.3.3	Additional spurious emissions	256
6.6.3.3.1	Minimum requirement (network signalled value "NS_05")	256
6.6.3.3.2	Minimum requirement (network signalled value "NS_07").....	256
6.6.3.3.3	Minimum requirement (network signalled value "NS_08").....	256
6.6.3.3.4	Minimum requirement (network signalled value "NS_09").....	257
6.6.3.3.5	Minimum requirement (network signalled value "NS_12").....	257
6.6.3.3.6	Minimum requirement (network signalled value "NS_13").....	257
6.6.3.3.7	Minimum requirement (network signalled value "NS_14").....	258
6.6.3.3.8	Minimum requirement (network signalled value "NS_15").....	258
6.6.3.3.9	Minimum requirement (network signalled value "NS_16").....	258
6.6.3.3.10	Minimum requirement (network signalled value "NS_17").....	258
6.6.3.3.11	Minimum requirement (network signalled value "NS_18").....	259
6.6.3.3.12	Minimum requirement (network signalled value "NS_19").....	259
6.6.3.3.13	Minimum requirement (network signalled value "NS_11").....	259
6.6.3.3.14	Minimum requirement (network signalled value "NS_20").....	259
6.6.3.3.15	Minimum requirement (network signalled value "NS_21").....	260
6.6.3.3.16	Minimum requirement (network signalled value "NS_22").....	260
6.6.3.3.17	Minimum requirement (network signalled value "NS_23").....	260
6.6.3.3.18	Void.....	261
6.6.3.3.19	Minimum requirement (network signalled value "NS_04").....	261
6.6.3.3.20	Minimum requirement (network signalled value "NS_24").....	261
6.6.3.3.21	Minimum requirement (network signalled value "NS_25").....	262
6.6.3.3.22	Minimum requirement (network signalled value "NS_26").....	262
6.6.3.3.23	Minimum requirement (network signalled value "NS_27").....	262
6.6.3.3.24	Minimum requirement (network signalled value "NS_28").....	262
6.6.3.3.25	Minimum requirement (network signalled value "NS_29").....	263
6.6.3.3.26	Minimum requirement (network signalled value "NS_30").....	263
6.6.3.3.27	Minimum requirement (network signalled value "NS_31").....	264
6.6.3.3.28	Minimum requirement (network signalled value "NS_36").....	265
6.6.3.3.29	Void.....	265
6.6.3.3.30	Void.....	265
6.6.3.3.31	Void.....	265
6.6.3.3.32	Void.....	265
6.6.3.3.33	Void.....	265
6.6.3.3.34	Void.....	265

6.6.3.3.35	Minimum requirement (network signalled value "NS_56").....	265
6.6.3.3A	Additional spurious emissions for CA	266
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01").....	266
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02").....	266
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03").....	267
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05").....	267
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06").....	267
6.6.3.3A.6	Minimum requirement for CA_39C and CA_39C-41A (network signalled value "CA_NS_07").....	268
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08").....	268
6.6.3.3A.8	Minimum requirement for CA_41C (network signalled value "CA_NS_04").....	268
6.6.3A	Void	269
6.6.3B	Spurious emission for UL-MIMO	269
6.6.3C	Void	269
6.6.3D	Spurious emission for ProSe.....	269
6.6.3F	Spurious emission for category NB1 and NB2.....	269
6.6.3G	Spurious emission for V2X Communication	269
6.6A	Void.....	271
6.6B	Void.....	271
6.7	Transmit intermodulation	271
6.7.1	Minimum requirement	271
6.7.1A	Minimum requirement for CA	271
6.7.1B	Minimum requirement for UL-MIMO.....	272
6.7.1F	Minimum requirement for category NB1 and NB2	272
6.7.1G	Minimum requirement for V2X Communication	272
6.8	Void.....	273
6.8A	Void.....	273
6.8B	Time alignment error for UL-MIMO	273
6.8B.1	Minimum Requirements	273
7	Receiver characteristics	273
7.1	General	273
7.2	Diversity characteristics	274
7.3	Reference sensitivity power level.....	274
7.3.1	Minimum requirements (QPSK).....	274
7.3.1A	Minimum requirements (QPSK) for CA	304
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	357
7.3.1D	Minimum requirements (QPSK) for ProSe.....	357
7.3.1E	Minimum requirements (QPSK) for UE category 0, M1, M2 and 1bis.....	358
7.3.1F	Minimum requirements for UE category NB1 and NB2	365
7.3.1F.1	Reference sensitivity for UE category NB1 and NB2.....	365
7.3.1F.2	Void.....	365
7.3.1G	Minimum requirements (QPSK) for V2X	365
7.3.2	Void	367
7.4	Maximum input level	367
7.4.1	Minimum requirements.....	367
7.4.1A	Minimum requirements for CA	367
7.4.1B	Minimum requirements for UL-MIMO	368
7.4.1D	Minimum requirements for ProSe	368
7.4.1F	Minimum requirements for category NB1 and NB2.....	369
7.4.1G	Minimum requirements for V2X	369
7.4A	Void.....	370
7.4A.1	Void	370
7.5	Adjacent Channel Selectivity (ACS).....	370
7.5.1	Minimum requirements.....	370
7.5.1A	Minimum requirements for CA	371
7.5.1B	Minimum requirements for UL-MIMO	374
7.5.1D	Minimum requirements for ProSe	374
7.5.1F	Minimum requirements for category NB1 and NB2.....	375
7.5.1G	Minimum requirements for V2X	376
7.6	Blocking characteristics	377
7.6.1	In-band blocking.....	377

7.6.1.1	Minimum requirements	378
7.6.1.1A	Minimum requirements for CA	379
7.6.1.1D	Minimum requirements for ProSe	382
7.6.1.1F	Minimum requirements for category NB1 and NB2	383
7.6.1.1G	Minimum requirements for V2X	383
7.6.2	Out-of-band blocking	385
7.6.2.1	Minimum requirements	385
7.6.2.1A	Minimum requirements for CA	386
7.6.2.1D	Minimum requirements for ProSe	389
7.6.2.1F	Minimum requirements for category NB1 and NB2	390
7.6.2.1G	Minimum requirements for V2X	390
7.6.3	Narrow band blocking	391
7.6.3.1	Minimum requirements	391
7.6.3.1A	Minimum requirements for CA	392
7.6.3.1D	Minimum requirements for ProSe	393
7.6A	Void	394
7.6B	Blocking characteristics for UL-MIMO	394
7.7	Spurious response	394
7.7.1	Minimum requirements	394
7.7.1A	Minimum requirements for CA	395
7.7.1B	Minimum requirements for UL-MIMO	396
7.7.1D	Minimum requirements for ProSe	396
7.7.1F	Minimum requirements for UE category NB1 and NB2	397
7.7.1G	Minimum requirements for V2X	397
7.8	Intermodulation characteristics	398
7.8.1	Wide band intermodulation	398
7.8.1.1	Minimum requirements	398
7.8.1A	Minimum requirements for CA	399
7.8.1B	Minimum requirements for UL-MIMO	401
7.8.1D	Minimum requirements for ProSe	401
7.8.1F	Minimum requirements for category NB1 and NB2	402
7.8.1G	Minimum requirements	402
7.8.2	Void	403
7.9	Spurious emissions	403
7.9.1	Minimum requirements	403
7.9.1A	Minimum requirements	404
7.10	Receiver image	404
7.10.1	Void	404
7.10.1A	Minimum requirements for CA	404
7.10.1G	Minimum requirements for V2X Communication	404
8	Performance requirement	406
8.1	General	406
8.1.1	Receiver antenna capability	406
8.1.1.1	Simultaneous unicast and MBMS operations	407
8.1.1.2	Dual-antenna receiver capability in idle mode	407
8.1.2	Applicability of requirements	407
8.1.2.1	Applicability of requirements for different channel bandwidths	407
8.1.2.2	Definition of CA capability	407
8.1.2.2A	Definition of dual connectivity capability	410
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets	411
8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	413
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets	414
8.1.2.3C	Applicability and test rules for SDR tests for 4Rx capable UEs	415
8.1.2.3D	Applicability and test rules for different CA with LAA SCell(s) configurations and bandwidth combination sets	416
8.1.2.4	Test coverage for different number of component carriers	416
8.1.2.5	Applicability of performance requirements for Type B receiver	418
8.1.2.6	Applicability of performance requirements for 4Rx capable UEs	418
8.1.2.6.1	Applicability rule and antenna connection for single carrier tests with 2Rx	418

8.1.2.6.2	Applicability rule and antenna connection for CA and DC tests with 2Rx	419
8.1.2.6.3	Applicability rule and antenna connection for single carrier tests with 4Rx	420
8.1.2.6.4	Applicability rule for 256QAM tests	420
8.1.2.6.5	Applicability rule and antenna connection for CA and DC tests with 4Rx	420
8.1.2.6.6	Applicability rule for Type C with 4Rx.....	422
8.1.2.7	Applicability of Enhanced Downlink Control Channel Performance Requirements	423
8.1.2.8	Applicability of performance requirements for CDM-multiplexed DM RS with interfering simultaneous transmission (FRC) with multiple CSI-RS configurations	424
8.1.2.8A	Applicability of performance requirements for UE supporting coverage enhancement	424
8.1.2.9	Applicability of SDR requirements for CA and LAA	425
8.1.2.10	Applicability of performance requirements for Multi-user Superposed Transmission	425
8.1.2.11	Applicability CRS interference mitigation receivers performance requirements	426
8.1.3	UE category and UE DL category	426
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	426
8.2.1	FDD (Fixed Reference Channel)	426
8.2.1.1	Single-antenna port performance	427
8.2.1.1.1	Minimum Requirement	427
8.2.1.1.2	Void	431
8.2.1.1.3	Void	431
8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	431
8.2.1.1.4A	Minimum Requirement 1 PRB allocation in presence of FeMBMS Unicast-mixed Cell under CA	431
8.2.1.2	Transmit diversity performance	432
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port	432
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	433
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	433
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	435
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	436
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	437
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	438
8.2.1.2.7	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	439
8.2.1.3	Open-loop spatial multiplexing performance	440
8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	440
8.2.1.3.1A	Soft buffer management test	443
8.2.1.3.1B	Enhanced Performance Requirement Type C -2Tx Antenna Ports	444
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	445
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	446
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	446
8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	449
8.2.1.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	450
8.2.1.4	Closed-loop spatial multiplexing performance	451
8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	451
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	452
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	452
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)....	454
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	455
8.2.1.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	456
8.2.1.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	458
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	459

8.2.1.4.2A	Enhanced Performance Requirement Type C – Multi-layer Spatial Multiplexing 2Tx Antenna Ports.....	459
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	460
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	463
8.2.1.4.4	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	465
8.2.1.5	MU-MIMO.....	465
8.2.1.6	[Control channel performance: D-BCH and PCH]	465
8.2.1.7	Carrier aggregation with power imbalance	465
8.2.1.7.1	Minimum Requirement	466
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset.....	466
8.2.1.8.1	Minimum Requirement	467
8.2.1.9	HST-SFN performance	467
8.2.1.9.1	Minimum Requirement	467
8.2.2	TDD (Fixed Reference Channel)	468
8.2.2.1	Single-antenna port performance	468
8.2.2.1.1	Minimum Requirement	468
8.2.2.1.2	Void	472
8.2.2.1.3	Void	472
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	472
8.2.2.2	Transmit diversity performance	472
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	472
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	473
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	474
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	475
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model	476
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	477
8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model.....	478
8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model.....	479
8.2.2.2.8	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	480
8.2.2.3	Open-loop spatial multiplexing performance.....	481
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port	481
8.2.2.3.1A	Soft buffer management test.....	484
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	484
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	485
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	486
8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS).....	486
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	489
8.2.2.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	490
8.2.2.4	Closed-loop spatial multiplexing performance	491
8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port.....	491
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	492
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	492
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	494
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model.....	495
8.2.2.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	496
8.2.2.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	498
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	499

8.2.2.4.2A	Enhanced Performance Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	500
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	500
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	503
8.2.2.4.4	Void	505
8.2.2.4.5	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	505
8.2.2.5	MU-MIMO.....	505
8.2.2.6	[Control channel performance: D-BCH and PCH]	505
8.2.2.7	Carrier aggregation with power imbalance	505
8.2.2.7.1	Minimum Requirement	506
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing.....	506
8.2.2.8.1	Minimum Requirement	507
8.2.2.9	HST-SFN performance	507
8.2.2.9.1	Minimum Requirement	507
8.2.3	TDD FDD CA (Fixed Reference Channel).....	508
8.2.3.1	Single-antenna port performance	509
8.2.3.1.1	Minimum Requirement for FDD PCell	509
8.2.3.1.2	Minimum Requirement for TDD PCell	512
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port.....	515
8.2.3.2.1	Minimum Requirement for FDD PCell	515
8.2.3.2.1A	Soft buffer management test for FDD PCell	518
8.2.3.2.2	Minimum Requirement for TDD PCell	519
8.2.3.2.2A	Soft buffer management test for TDD PCell	522
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port.....	523
8.2.3.3.1	Minimum Requirement for FDD PCell	523
8.2.3.3.2	Minimum Requirement for TDD PCell	526
8.2.3.4	Minimum Requirement for Closed-loop spatial multiplexing performance 4Tx Antenna Port for dual connectivity	529
8.2.4	LAA.....	531
8.2.4.1	Closed-loop spatial multiplexing performance 4Tx Antenna Port.....	531
8.2.4.1.1	FDD PCell (FDD single carrier).....	531
8.2.4.1.2	TDD PCell (TDD single carrier)	534
8.3	Demodulation of PDSCH (User-Specific Reference Symbols).....	537
8.3.1	FDD	537
8.3.1.1	Single-layer Spatial Multiplexing	537
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	539
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	540
8.3.1.1C	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference model.....	542
8.3.1.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	543
8.3.1.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference model.....	544
8.3.1.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	546
8.3.1.1G	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	547
8.3.1.1H	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured).....	548
8.3.1.1I	Single-layer Spatial Multiplexing (with assistance information for simultaneous transmission interfering PDSCH).....	549
8.3.1.2	Dual-Layer Spatial Multiplexing	550
8.3.1.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing.....	551
8.3.1.3	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	552
8.3.1.3.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	552
8.3.1.3.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources)	554
8.3.1.3.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	556
8.3.1.3.4	Minimum requirement with Different Cell ID and non-colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	557

8.3.1.3.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	559
8.3.1.4	Performance Requirements for semiOpenLoop transmission	561
8.3.2	TDD.....	562
8.3.2.1	Single-layer Spatial Multiplexing	562
8.3.2.1A	Single-layer Spatial Multiplexing (with multiple CSI-RS configurations)	564
8.3.2.1B	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	566
8.3.2.1C	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	567
8.3.2.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference.....	569
8.3.2.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	571
8.3.2.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference.....	572
8.3.2.1G	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	573
8.3.2.1H	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	574
8.3.2.1I	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured).....	576
8.3.2.1J	Single-layer Spatial Multiplexing (with assistance information for simultaneous transmission interfering PDSCH).....	577
8.3.2.2	Dual-Layer Spatial Multiplexing	578
8.3.2.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	579
8.3.2.3	Dual-Layer Spatial Multiplexing (with multiple CSI-RS configurations)	579
8.3.2.4	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	581
8.3.2.4.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	581
8.3.2.4.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources).....	582
8.3.2.4.3	Minimum requirement with Different Cell IDs and Colliding CRS (with single NZP CSI-RS resource)	584
8.3.2.4.4	Minimum requirement with Different Cell ID and non-Colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	585
8.3.2.4.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	587
8.3.2.5	Performance Requirements for semiOpenLoop transmission	589
8.3.3	LAA	590
8.3.3.1	Dual-Layer Spatial Multiplexing with DM-RS	590
8.3.3.1.1	FDD PCell (FDD single carrier)	590
8.3.3.1.2	TDD Pcell (TDD single carrier)	593
8.4	Demodulation of PDCCH/PCFICH	596
8.4.1	FDD	597
8.4.1.1	Single-antenna port performance	597
8.4.1.2	Transmit diversity performance	597
8.4.1.2.1	Minimum Requirement 2 Tx Antenna Port	597
8.4.1.2.2	Minimum Requirement 4 Tx Antenna Port	597
8.4.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	598
8.4.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	601
8.4.1.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port under Asynchronous Network	603
8.4.1.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	604
8.4.1.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Colliding CRS Dominant Interferer.....	605
8.4.1.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	606
8.4.1.2.9	Enhanced Downlink Control Channel Performance Requirement Type A - 4 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	607
8.4.2	TDD.....	608
8.4.2.1	Single-antenna port performance	609
8.4.2.2	Transmit diversity performance	609
8.4.2.2.1	Minimum Requirement 2 Tx Antenna Port	609