

ISO/TC 20/SC 14

Secretariat: ANSI

Voting begins on:
2020-07-28

Voting terminates on:
2020-09-22

Space systems — Explosive systems and devices

Systèmes spatiaux — Dispositifs et équipements explosifs

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/c11b921d-1be2-4012-bc07-8bce02231b98/iso-fdis-26871>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number
ISO/FDIS 26871:2020(E)

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/c11b921d-1be2-4012-bc07-8bce02231b98/iso-fdis-26871>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions, abbreviated terms and symbols	1
3.1 Terms and definitions.....	1
3.2 Abbreviated terms.....	8
3.3 Symbols.....	10
4 Requirements	10
4.1 General.....	10
4.1.1 Background information.....	10
4.1.2 Overview.....	10
4.1.3 Applicability.....	11
4.1.4 Properties.....	11
4.2 Design.....	11
4.2.1 General.....	11
4.2.2 Debris requirements.....	12
4.2.3 Reliability and confidence levels.....	13
4.2.4 Performance.....	13
4.2.5 Wanted and unwanted response.....	13
4.2.6 Dimensioning.....	13
4.3 Mission.....	17
4.4 Functionality.....	17
4.5 Safety.....	17
4.5.1 General.....	17
4.5.2 Prevention of unintentional function.....	18
4.6 Survival and operational conditions.....	19
4.7 Interface requirements.....	19
4.7.1 General.....	19
4.7.2 Functional.....	20
4.7.3 Internal.....	20
4.7.4 External.....	20
4.8 Mechanical, electrical, and thermal requirements.....	20
4.8.1 Mechanical.....	20
4.8.2 Electrical.....	21
4.8.3 Thermal.....	25
4.8.4 Status check.....	25
4.9 Materials.....	26
4.10 Production lot.....	27
4.11 Non-explosive components and equipment.....	27
4.11.1 Connectors.....	27
4.11.2 Wiring.....	28
4.11.3 Shielding.....	28
4.11.4 Faraday cap.....	28
4.11.5 Safety cap.....	28
4.11.6 Power.....	29
4.11.7 Arm plug receptacle.....	29
4.11.8 Safe plug.....	29
4.11.9 Arm plug.....	30
4.11.10 Test plug.....	30
4.11.11 Safe and arm device.....	30
4.11.12 Initiator harness connector.....	32
4.11.13 Initiator test substitute.....	32

4.12	Explosive components.....	32
4.12.1	General.....	32
4.12.2	Initiators, cartridges, detonators and packaged charges.....	33
4.12.3	Through-Bulkhead initiators.....	38
4.12.4	Integral initiator connectors.....	38
4.12.5	Transfer devices.....	39
4.12.6	Safe and arm devices containing explosive.....	40
4.12.7	Gas generators.....	41
4.12.8	Shaped charges.....	41
4.12.9	Expanding tube separation system.....	42
4.12.10	Distribution boxes.....	43
4.12.11	Explosive delays.....	44
4.13	Explosively actuated devices.....	45
4.13.1	General.....	45
4.13.2	Separation nuts and separation bolts.....	46
4.13.3	Pullers.....	47
4.13.4	Pushers (Thrusters).....	48
4.13.5	Cutters.....	48
4.13.6	Pyro-valves.....	49
4.14	Items external to the flight equipment.....	50
4.14.1	GSE.....	50
4.14.2	Test equipment.....	50
4.14.3	Launch site.....	50
4.15	Verification.....	51
4.15.1	General.....	51
4.15.2	Inspection.....	51
4.15.3	Tests.....	51
4.15.4	Qualification and lot acceptance.....	53
4.16	Transport, facilities, handling and storage.....	56
4.16.1	General.....	56
4.16.2	Transport.....	56
4.16.3	Facilities.....	57
4.16.4	Handling and storage.....	57
4.17	In-service.....	58
4.17.1	Information feedback.....	58
4.17.2	Launch site procedures.....	58
4.17.3	Monitoring.....	58
4.18	Product assurance.....	58
4.18.1	General.....	58
4.18.2	Dependability.....	59
4.18.3	Assembly integration and tests.....	59
4.19	Deliverables.....	59
	Annex A (normative) Loads and factors of safety relationship.....	61
	Annex B (normative) Factors of safety.....	63
	Annex C (informative) Explosive component colour code.....	64
	Annex D (informative) Component qualification test levels to be customized to the space system considered.....	65
	Annex E (informative) Product user manual (PUM/UM) — DRD.....	67
	Annex F (informative) Safety data sheet.....	73
	Bibliography.....	77

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 14, *Space systems and operations*.

This second edition cancels and replaces the first edition (ISO 26871:2012), which has been technically revised.

The main changes compared to the previous edition are as follows:

- simplification for some requirements;
- updating terminology;
- introduction of a paragraph about debris issues.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

0.1 Background

The evolution of this document is motivated by changes inputted by the last issue of 2 main mother documents^{[1],[2]}.

0.2 Tailoring

This document may be tailored, by the contractor, in consultation with the procuring authority, for the specific characteristics and constraints of a space project.

Tailoring is a process by which individual requirements or specifications, standards, and related documents are evaluated and made applicable to a specific program or project by selection, and in some cases, modification and addition (e.g., for manned spaceflight) of requirements in the standards.

However, the tailored requirements may achieve a level of verification equivalent to the baseline described herein. Rationale for each tailored requirement may be established. If the requirements in this document are not tailored by a contract, they stand as written.

This document will be updated and revised periodically, each five years as appropriate to incorporate technological advances and innovations as well as lessons learned.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/c11b921b-1be2-4012-bc07-8bce02231b98/iso-fdis-26871>

Space systems — Explosive systems and devices

IMPORTANT — The electronic file of this document contains colours which are considered to be useful for the correct understanding of the document. Users should therefore consider printing this document using a colour printer.

1 Scope

This document specifies criteria and requirements for the use of explosive systems and explosive devices commonly used on spacecraft and other space products, including launch vehicles and space vehicle systems. It addresses the aspects of design, analysis, verification, manufacturing, operations and safety.

To the greatest extent possible, requirements from past and existing standards have been analyzed, selected and tailored to be incorporated herein. In addition, the requirements herein include those generated as a result of lessons learned from launch and space vehicle programs.

NOTE Specific requirements for man-rating are not addressed.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 14300-1, *Space systems — Programme management — Part 1: Structuring of a project*

ISO 24113, *Space systems — Space debris mitigation requirements*

3 Terms, definitions, abbreviated terms and symbols

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <http://www.electropedia.org/>

3.1.1

actuator

component (3.1.10) that performs the moving function of a mechanism

Note 1 to entry: An actuator can be either an electric motor, or any other mechanical (e.g. spring) or electric component or part providing the torque or force for the motion of the mechanism.

3.1.2

all-fire level

lowest level of the fire stimulus (including rise time, shape, duration), which results in initiation of a *first element (initiator)* (3.1.36) within a specific reliability and confidence level as determined by test and analysis

Note 1 to entry: The stimulus duration shall be compliant with the system.

Note 2 to entry: The test sequence should be carried out at the lowest temperature of the operating range.

Note 3 to entry: The probability of functioning should be equal to or better than 0,999 at the 95 % confidence level.

3.1.3

armed

status of an explosive subsystem, when all the safety devices have been disabled and which is able to trigger

3.1.4

auto-ignition

spontaneous explosive reaction of *energetic materials* (3.1.19) in an explosively loaded device due to exposure to environments or interfacing materials

3.1.5

bridgewire

resistive element incorporated into the *first element* (3.1.30) that converts electrical energy into heat or shock to cause initiation of an explosive *charge* (3.1.8)

3.1.6

cartridge

explosive device designed to produce pressure for performing a mechanical function or actuate a mechanical device

Note 1 to entry: A cartridge is called an *initiator* (3.1.36) if it is the first or only explosive element in an *explosive train* (3.1.28).

3.1.7

catastrophic failure

failure which results in the loss of human life, mission or a major ground facility, or long-term detrimental environmental effects

3.1.8

charge

explosive (3.1.23) loaded in a *cartridge* (3.1.6), *detonator* (3.1.14) or separate container for use in an explosive device

3.1.9

closed bomb

fixed volume test chamber to measure output characteristics of pressure producing devices

3.1.10

component

set of materials, assembled according to defined and controlled processes, which cannot be disassembled without destroying its capability and which performs a simple function that can be evaluated against expected performance requirements

Note 1 to entry: The term “part” is preferred when referring to purely mechanical or explosive devices.

Note 2 to entry: The term “component” is preferred for EEE devices.

3.1.11

cook-off temperature

maximum temperature to which an explosively loaded device can be exposed for a period of one hour without reaction

Note 1 to entry: The determination of the cook-off temperature is time and application dependent.

3.1.12

deflagration

chemical decomposition propagating through the *explosive* (3.1.23) at a subsonic velocity

3.1.13**detonation**

chemical decomposition propagating through the *explosive* (3.1.23) at a supersonic velocity such that a shock wave is generated

3.1.14**detonator**

initiator (3.1.36) whose function is to transform external energy (e.g., mechanical, electrical, thermal) directly into a shock wave strong enough to detonate a secondary *high explosive* (3.1.34)

Note 1 to entry: Detonators are generally used to effect *detonation* (3.1.13) transfers within *explosive trains* (3.1.28).

3.1.15**duding**

explosive charge (3.1.8) or *component* (3.1.10) that fails to fire or function upon receipt of the prescribed initiating stimulus, after an external effect (human failure, manufacturing failure, environmental, chemical, ageing, etc.)

3.1.16**electro-explosive device****EED**

first element (3.1.30) of an *explosive train* (3.1.28); *initiator* (3.1.36) electrically actuated, which has a *bridgewire* (3.1.5) to transform electrical energy inputted into a reaction of the mixture used (e.g., *explosive* (3.1.23) or *pyrotechnics* (3.1.47))

Note 1 to entry: The output of the initiation is heat, shock or mechanical action, see 3.1.13.

3.1.17**electrostatic discharge****ESD**

transfer of electrostatic *charge* (3.1.8) between objects at different potentials caused by direct contact or induced by an electrostatic field

3.1.18**end user**

person who, or organization that, actually uses a product

Note 1 to entry: The end user may not to be the owner or buyer.

3.1.19**energetic material**

material containing, an *explosive* (3.1.23), oxidizer, fuel or combination of them, that can undergo, contribute to, or cause rapid exothermic decomposition such as: combustion, *deflagration* (3.1.12) or *detonation* (3.1.13)

3.1.20**expanding tube separation system**

separation system that emits no contamination and that includes detonating cord in a ductile metal tube and a structure containing geometrically controlled stress risers

3.1.21**exploding bridgewire device****EBW**

high voltage device in which the *bridgewire* (3.1.5) explodes when functioned

3.1.22**exploding foil initiator****EFI**

high voltage device that generates a supersonic flyer plate when functioned

3.1.23

explosive

material which is capable of undergoing an explosion when subjected to heat, impact, friction, *detonation* (3.1.13) or other suitable initiation

3.1.24

explosively actuated device

mechanism that converts the products of explosion (combustion, *deflagration* (3.1.12) or *detonation* (3.1.13)) into useful mechanical work

Note 1 to entry: Pyro-mechanisms and linear detonating separation devices are explosively actuated devices.

3.1.25

explosive component

any discrete item containing an explosive substance

3.1.26

explosive function

any function that uses energy released from explosive substances for its operation

3.1.27

explosive system

collection of all the *explosive trains* (3.1.28) on the *spacecraft* (3.1.60) or *launcher* (3.1.38) system, and the interface aspects of any on-board computers, launch operation equipment, ground support and test equipment and all software associated with *explosive functions* (3.1.26)

3.1.28

explosive train

ET
series of *explosive components* (3.1.25) that transfer explosive signal from the *first element* (3.1.30) to the final *explosively actuated device* (3.1.24)

3.1.29

extreme envelope

positive margin over the conditions of the qualification envelope

Note 1 to entry: The device or system design is based on the conditions that define the extreme envelope.

3.1.30

first element

initial element of an *explosive system* (3.1.27) that converts electrical, optical, or mechanical energy to explosive energy

3.1.31

fail operational

mission capable after one failure

3.1.32

fail safe

design property of a system/subsystem (or part of it), which prevents its failures from resulting in critical or catastrophic consequences (i.e. remain *safe* (3.1.50) after one failure)

Note 1 to entry: Maintaining safety following two independent failures is referred to “fail safe – fail safe”.

3.1.33

gas generator

explosive device wherein pyro *charge* (3.1.8), as a result of chemical reaction, is converted in gaseous products of reaction or exothermic output, or both

3.1.34**high explosive****HE**

any chemical material in which the fuel and oxidizer are contained in the same molecule, the decomposition of which is a *detonation* (3.1.13)

3.1.35**hot bridgewire device****HBW**

low voltage *EED* (3.1.16)

3.1.36**initiator**

first explosive element in an *explosive train* (3.1.28) which, upon receipt of the proper mechanical, optical or electrical impulse, produces a deflagrating or detonating action

Note 1 to entry: The initiator is divided into three categories: 1) igniter, a first element whose output is hot gases and hot particles (igniters may be initiators for solid or liquid *propellant* (3.1.45)); 2) squib, a first element whose output is primarily gas and heat (squibs may be initiators for *gas generators* (3.1.33) and igniters or may be *cartridges* (3.1.6) for actuated devices); 3) detonator, a first element whose output is a high-order *detonation* (3.1.13) (*detonators* (3.1.14) are generally used to effect detonation transfers within explosive trains).

Note 2 to entry: The deflagrating or detonating action is transmitted to the elements following in the train.

Note 3 to entry: Initiators can be electrically (*EEDs* (3.1.16)), optically or mechanically actuated.

3.1.37**laser initiated device****LID**

first element (3.1.30) containing *explosives* (3.1.23) that is ignited by laser energy

3.1.38**launcher****launch vehicle**

vehicle designed to transport payloads to space

3.1.39**lifetime**

period over which any properties are required to be within defined limits

3.1.40**lot****batch**

group of *components* (3.1.10) produced in continuous, without uninterrupted production run, with no change in process or drawings

3.1.41**lot acceptance**

demonstration by measurement or test that a *lot* (3.1.40) of items meet its requirements

3.1.42**no-fire level**

maximal level of input energy with an ignition stimulus (including nominal rise time and shape as required by the system, but with a 5 min extended duration), to a *first element (initiator)* (3.1.36) at which initiation will not occur within a specific reliability and confidence level as determined by test and analysis

Note 1 to entry: The test sequence should be carried out at the hottest temperature of the operating range.

Note 2 to entry: The probability of functioning should be less than or equal to 0,001 at the 95 % confidence level.

Note 3 to entry: A first element tested at this level shall remain *safe* (3.1.50) and functional and shall guarantee the level of performances required after the no-fire level test.

3.1.43

packaged charge

explosive material in a closed container

3.1.44

primary explosive

reaction extremely sensitive explosive material that will detonate in response to normal environmental stimuli

Note 1 to entry: In their intended role, these materials are sensitive to a range of thermal, mechanical and electrical stimuli, including exposures during processing.

3.1.45

propellant

deflagrating explosive material whose output is essentially gaseous

3.1.46

pyro-mechanism

device intended to perform one or more mechanical actions, using the energy produced by the reaction of an *energetic material* (3.1.19)

3.1.47

pyrotechnics

mixture of fuels and oxidizers that can deflagrate

3.1.48

pyrotechnic device

basic pyrotechnic object (from *explosive train* (3.1.28) or explosive device) containing explosive substances and intended to perform an initiation (e.g., ignition, priming), a pyrotechnic effect transmission, amplification effect, or generation of a function

3.1.49

refurbish

replace *components* (3.1.10) or elements in an explosive device or system to maintain reliability or extend *service life* (3.1.58)

3.1.50

safe

property of an item and its environment that limits its potential for damage to an acceptable risk

3.1.51

safe and arm device

S&A

mechanical or electromechanical device that provides a moveable barrier within the *explosive train* (3.1.28) downstream of the *first element* (3.1.30)

3.1.52

scoop-proof connector

connector shell design in which the male contacts are recessed into the connector body to prevent mismatching damage to pins (especially in blind mating applications)

3.1.53

secondary characteristic

any characteristic other than the function

3.1.54**secondary explosive**

explosive material that is insensitive to heat or handling impact but will detonate under strong shock impulse

3.1.55**semiconductor bridge initiator****SCB**

EED (3.1.16) that uses a semiconductor as the bridge element

3.1.56**sensitivity**

characteristic of an *explosive* (3.1.23) that expresses its susceptibility to initiation by externally applied energy such as heat, mechanical shock, or other stimuli

3.1.57**sequential firing**

application of the firing pulses to *initiators* (3.1.36) separated in time

3.1.58**service life**

life that is established by testing or analysis during qualification or acceptance testing and is periodically extended by testing

3.1.59**sneak circuit**

undesired function or function that inhibits a desired function

Note 1 to entry: The path may consist of hardware, software, operator actions, or combinations of these elements. Sneak circuits are not the result of hardware failure but are latent conditions, inadvertently designed into the system, coded into the software program, or triggered by human error.

3.1.60**spacecraft**

manned or unmanned vehicle purposely delivered by the upper stage of a *launch vehicle* (3.1.38) or transfer vehicle, and designed to orbit or travel in space

Note 1 to entry: A spacecraft is a space segment element.

EXAMPLE Satellite, ballistic probe, re-entry vehicle, space probes and space stations.

3.1.61**space vehicle**

manned or unmanned vehicle constructed or assembled for the purpose of manoeuvring, moving, operating, or being placed in outer space

Note 1 to entry: A space vehicle can be a *launcher* (3.1.38), a rocket, a payload, a space capsule, a space shuttle, a space plane, a space station, etc., or any assembled combination thereof.

3.1.62**success**

simultaneous achievement by all characteristics of required performance

3.1.63**sympathetic firing**

firing of other explosive devices due to the output of any other

3.1.64**transfer line**

linear explosive assembly in which the explosive material is confined in a metallic sheath plus various layers of over-wrap materials intended to limit radial expulsion of *detonation* (3.1.13) products, but sustain linear propagation of detonation waves