

ETSI TS 128 531 V17.10.0 (2025-01)



5G; Management and orchestration; Provisioning (3GPP TS 28.531 version 17.10.0 Release 17)

[ETSI TS 128 531 V17.10.0 \(2025-01\)](https://standards.iteh.ai/catalog/standards/etsi/35b19a1b-0838-4c6a-a470-118d6239b369/etsi-ts-128-531-v17-10-0-2025-01)

<https://standards.iteh.ai/catalog/standards/etsi/35b19a1b-0838-4c6a-a470-118d6239b369/etsi-ts-128-531-v17-10-0-2025-01>



Reference

RTS/TSGS-0528531vha0

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver repository](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	6
1 Scope	7
2 References	7
3 Definitions and abbreviations.....	7
3.1 Definitions	7
3.2 Abbreviations	8
4 General	8
4.1 Overview	8
4.2 Configuration information for the constituents of an NSI	9
4.3 General information for network slice instance.....	10
4.4 General information for network slice subnet instance	10
4.5 Void.....	10
4.6 Void.....	10
5 Specification level requirements	11
5.1 Use cases	11
5.1.1 Network slice instance allocation	11
5.1.2 Network slice subnet instance allocation	13
5.1.3 Network slice instance deallocation.....	15
5.1.4 Network slice subnet instance deallocation	16
5.1.5 Obtaining network slice subnet instance information.....	17
5.1.6 Network slice feasibility check.....	18
5.1.7 Network slice instance activation	19
5.1.8 Network slice instance deactivation.....	20
5.1.9 Network slice instance modification.....	21
5.1.10 Network slice subnet instance activation	22
5.1.11 Network slice subnet instance deactivation	23
5.1.12 Network slice subnet instance modification	24
5.1.13 Network slice subnet configuration	25
5.1.14 Obtaining network slice management data	26
5.1.15 Void	26
5.1.16 Void	26
5.1.17 Creation of a 3GPP NF	27
5.1.18 Configuration of a 3GPP NF instance.....	28
5.1.19 Creation of a 3GPP sub-network	29
5.1.20 Configuration of a 3GPP sub-network.....	30
5.1.21 Network slice subnet feasibility check.....	31
5.1.22 Void	31
5.1.23 Network slice subnet management with assigned priority.....	32
5.1.24 Management interaction with NFV MANO for network service priority.....	32
5.1.25 Void	32
5.1.26 Obtaining network slice subnet provider capability information.....	33
5.2 Requirements.....	33
5.2.1 Requirements for network slice provisioning service	33
5.2.2 Requirements for network slice subnet provisioning service.....	34
5.2.3 Requirements for NF provisioning service	35
5.2.4 Requirements for sub-network provisioning service	35
6 Management services for provisioning of networks and network slicing	35
6.1 Management services for network slice provisioning	35
6.2 Management services for network slice subnet provisioning	36

6.3	Management services for network function provisioning	37
6.4	Management services for network and sub-network provisioning	38
6.5	Operations of provisioning	39
6.5.1	AllocateNsi operation	39
6.5.1.1	Description	39
6.5.1.2	Input parameters	40
6.5.1.3	Output parameters	40
6.5.2	AllocateNssi operation	40
6.5.2.1	Description	40
6.5.2.2	Input parameters	40
6.5.2.3	Output parameters	40
6.5.3	DeallocateNsi operation	41
6.5.3.1	Description	41
6.5.3.2	Input parameters	41
6.5.3.3	Output parameters	41
6.5.4	DeallocateNssi operation	41
6.5.4.1	Description	41
6.5.4.2	Input parameters	41
6.5.4.3	Output parameters	41
6.5.5	AllocateNetwork operation	42
6.5.5.1	Description	42
6.5.5.2	Input parameters	42
6.5.5.3	Output parameters	42
7	Provisioning procedures of networks and network slicing	42
7.1	General	42
7.2	Procedure of Network Slice Instance Allocation	42
7.3	Procedure of Network Slice Subnet Instance Allocation	44
7.4	Procedure of Network Slice Instance Deallocation	46
7.5	Procedure of network slice subnet instance deallocation	47
7.6	Procedure of Network Slice Instance Modification	49
7.7	Procedure of Network Slice Subnet Instance Modification	50
7.8	Procedure of Obtaining Network Slice Subnet Management Service Producer Capability	51
7.8.1	Introduction	51
7.8.2	Querying Network Slice Subnet Capability Information	51
7.8.3	Void	52
7.9	Procedure of TN coordination supporting network slicing	52
7.9.1	Introduction	52
7.9.2	Interaction with NFVO as TN Manager	52
7.10	Procedure of NF instance creation	52
7.11	Procedure of NF instance modification	53
7.12	Procedure of NF instance deletion	54
7.13	Procedure of feasibility check and reservation of NSI	56
7.14	Procedure of feasibility check and reservation of network slice subnet	58
7.15	Void	59
7.16	Procedure of allocating network with or without slicing for communication services	59
7.17	Procedure of management interaction with NFV MANO for network service priority	60
8	Void	61
9	RESTful HTTP-based solution set of provisioning	62
9.1	Network slice provisioning management service	62
9.1.1	Mapping of operations	62
9.1.1.1	Introduction	62
9.1.1.2	Operation allocateNsi	62
9.1.1.3	Operation deallocateNsi	63
9.1.2	Resources	63
9.1.2.1	Resource definitions	63
9.1.2.1.1	Resource “../ServiceProfile	63
9.2	Network slice subnet provisioning management service	65
9.2.1	Mapping of operations	65
9.2.1.1	Introduction	65

9.2.1.2	Operation allocateNssi	65
9.2.1.3	Operation deallocateNssi	66
9.2.2	Resources	66
9.2.2.1	Resource definitions	66
9.2.2.1.1	Resource “../SliceProfile.....	66
Annex A (informative):	A network slice journey example.....	68
Annex B (informative):	General information for network slice related identifiers	71
Annex C (informative):	Change history	72
History		75

iTech Standards
(https://standards.iteh.ai)
Document Preview

ETSI TS 128 531 V17.10.0 (2025-01)
<https://standards.iteh.ai/catalog/standards/etsi/35b19a1b-0838-4c6a-a470-118d6239b369/etsi-ts-128-531-v17-10-0-2025-01>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 128 531 V17.10.0 \(2025-01\)](https://standards.iteh.ai/catalog/standards/etsi/35b19a1b-0838-4c6a-a470-118d6239b369/etsi-ts-128-531-v17-10-0-2025-01)

<https://standards.iteh.ai/catalog/standards/etsi/35b19a1b-0838-4c6a-a470-118d6239b369/etsi-ts-128-531-v17-10-0-2025-01>

1 Scope

The present document specifies use cases, requirements, management services and procedures for provisioning of 5G networks.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 28.525: "Telecommunication management; Life Cycle Management (LCM) for mobile networks that include virtualized network functions; Requirements".
- [3] ETSI GS NFV-IFA 013 (V2.4.1) (2018-02): "Network Function Virtualisation (NFV); Release 2; Management and Orchestration; Os-Ma-nfvo reference point - Interface and Information Model Specification".
- [4] 3GPP TS 28.530: "Management and orchestration; Concepts, use cases and requirements".
- [5] 3GPP TS 22.261 "Service requirements for next generation new services and markets".
- [6] 3GPP TS 28.541: "Management and orchestration; 5G Network Resource Model (NRM); Stage 2 and stage 3".
- [7] 3GPP TS 28.526: "Life Cycle Management (LCM) for mobile networks that include virtualized network functions; Procedures".
- [8] 3GPP TS 28.532: "Management and orchestration; Generic management services".
- [9] GSMA NG.116 Generic Network Slice Template v6.0
- [10] 3GPP TS 23.501: "Technical Specification Group Services and System Aspects; System Architecture for the 5G System; Stage 2".
- [11] 3GPP TS 38.300: "Technical Specification Group Radio Access Network; NR; NR and NG-RAN Overall Description; Stage 2".
- [12] ETSI GS NFV-IFA 014 (V4.2.1) (2021-05): "Network Function Virtualisation (NFV); Release 4; Management and Orchestration; Network Service Templates Specification".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1], TS 28.530 [4] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1] and TS 28.530 [4].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1], TS 28.530 [4] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

5GAA	5G Automotive Association
5G-ACIA	5G Association for Connected Industries and Automation
5GC	5G Core Network
AMF	Access and Mobility Management Function
CSC	Communication Service Customer
CSP	Communication Service Provider
CP	Control Plane
GST	Generic Slice Template
IOC	Information Object Class
MANO	Management and Orchestration
MnS	Management Service
NEST	Network Slice Type
NF	Network Function
NFV	Network Functions Virtualisation
NRM	Network Resource Model
NSaaS	Network Slice as a Service
NSC	Network Slice Customer
NSI	Network Slice Instance
NSP	Network Slice Provider
NSSI	Network Slice Subnet Instance
P-NEST	Private NEST
S-NEST	Standardized NEST
TN	Transport Network
VNF	Virtualized Network Function
UP	User Plane

4 General

4.1 Overview

A 5G system consists of a 5G Access Network (AN), and a 5G Core Network (5GC). Network slicing is one of the key 5G features.

The management aspects of a Network Slice Instance (NSI) are described by the four phases shown in Figure 4.3.1.1 of TS 28.530 [4].

The provisioning of network slicing includes the four phases which are preparation, commissioning, operation and decommissioning:

- In the preparation phase the NSI does not exist. The preparation phase includes network slice design, onboarding, evaluation of the network slice requirements, preparing the network environment and other necessary preparations required to be done before the creation of an NSI.
- During the NSI lifecycle stage which include commissioning phase, operation phase and decommissioning phase, the NSI provisioning operations include:
 - Create an NSI;
 - Activate an NSI;
 - Deactivate an NSI;

- Modify an NSI;
- Terminate an NSI.

The operations of the provisioning of an NSI occurs during different phases of a NSI:

a) During the commissioning phase:

- Create an NSI.

During NSI creation all resources to the NSI have been created and configured to satisfy the network slice requirements. NSI creation may trigger NSSI(s) creation or using existing NSSI(s) and setting up the corresponding associations.

b) During the operation phase:

- Activate an NSI;
- Modify an NSI;
- Deactivate an NSI.

NSI activation includes any actions that make the NSI active to provide communication services. NSI activation may trigger NSSI activation.

NSI modification in operation phase could map to several workflows, e.g. changes of NSI capacity, changes of NSI topology, NSI reconfiguration. NSI modification can be triggered by receiving new network slice related requirements, new communication service requirements, or the result of NSI supervision automatically. NSI modification may trigger NSSI modification.

The NSI deactivation operation may be needed before NSI modification operation and the NSI activation operation may be needed after the NSI modification operation. NSI deactivation includes any actions that make the NSI inactive and not providing any communication services. NSI deactivation trigger NSSI deactivation to deactivate constituent NSSI(s) which is not used by other NSI(s). Operator may decide to keep the NSI without termination after deactivation and reactivate it when receives new communication service request.

c) During the decommissioning phase:

- Terminate an NSI.

NSI termination step includes any action that make the NSI does not exist anymore and release resources that are not used by other NSI(s). NSI termination may trigger NSSI termination to terminate constituent NSSI(s) which is not used by other NSI(s).

Similarly, provisioning for network slice subnet instance includes the following operations:

- Create an NSSI;
- Activate an NSSI and associate it with certain NSI to be used by the NSI;
- Disassociate the NSSI with certain NSI and deactivate the NSSI if it's not associated with any NSI;
- Modify an NSSI;
- Terminate an NSSI.

4.2 Configuration information for the constituents of an NSI

To use network slice to support communication service or deliver a network slice as a service, the 3GPP defined constituents of the NSI should be configured by 3GPP management system according to the types and requirements of the network slice so that the NSI can be operated and maintained.

The configuration information of these components may include:

- *Information on the requirements to be applied to every NSI constituent to satisfy the requirements of multiple NSIs if the constituent is shared by multiple NSIs;*

- *Network function selection information*: Information on the selection of the NFs (e.g., AMF) according to the requirements of this NSI;
- *Connection information*: The information of the logical links to carry the NSI's CP and UP data between the component and other NFs and NSSIs belonging to the NSI.

NOTE 1: The list of information above is not exhaustive.

NOTE 2: The list of information above is not all necessary for an NSI.

4.3 General information for network slice instance

The general information used to describe a network slice instance may include:

- Resource model information, which describes the static parameters and functional components of network slice, includes service profile, network slice type (e.g. eMBB), additional system feature (e.g. multicast, Edge Computing), priority.
- Management model information, which describes the information model that is used for network slice lifecycle management, includes configuration profile (e.g. application configuration parameters).
- Capability model information, which describes the capability including supported communication service characteristic information (e.g. service type, UE mobility level, density of users, traffic density), QoS attributes (e.g. bandwidth, latency, throughput and so on) and capacity (e.g. maximum number of UEs), can be exposed to CSC .

4.4 General information for network slice subnet instance

The general information used to describe a network slice subnet instance may include:

- Resource model information, which describes the static parameters and functional component of network slice subnet, includes slice profile, network slice subnet type (e.g. RAN eMBB, CN eMBB), additional system feature (e.g. multicast, Edge Computing), priority, QoS attributes (e.g. bandwidth, latency, number of subscribers and so on), NSD ID.
- Management model information, which describes the information model that is used for network slice subnet lifecycle management, includes configuration profile (e.g. application configuration parameters).
- Capability model information, which describes the capability including supported communication service characteristic information (e.g. service type, UE mobility level, density of users, traffic density), QoS attributes (e.g. bandwidth, latency, throughput and so on) and capacity (e.g. maximum number of UEs).

4.5 Void

4.6 Void

5 Specification level requirements

5.1 Use cases

5.1.1 Network slice instance allocation

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 128 531 V17.10.0 \(2025-01\)](https://standards.iteh.ai/catalog/standards/etsi/35b19a1b-0838-4c6a-a470-118d6239b369/etsi-ts-128-531-v17-10-0-2025-01)

<https://standards.iteh.ai/catalog/standards/etsi/35b19a1b-0838-4c6a-a470-118d6239b369/etsi-ts-128-531-v17-10-0-2025-01>

Use case stage	Evolution/Specification	<<Uses>> Related use
Goal	To satisfy request for allocation of a network slice instance with certain characteristics, by creating a new or using an existing network slice instance.	
Actors and Roles	A network slice provisioning management service consumer.	
Telecom resources	Network slice instance Network slice subnet instance Transport network A network slice provisioning management service provider. A network slice subnet provisioning management service provider.	
Assumptions	N/A	
Pre-conditions	N/A	
Begins when	The network slice provisioning management service provider receives the request for allocation of the network slice instance with network slice related requirements. The network slice provisioning management service provider has the capability to process the network slice related requirements (e.g. SLA information from GSMA GST) which are represented by service profile parameters [6]. The service profile can be translated to the corresponding requirements for dedicated domains and NSSIs.	
Step 1 (M)	If the requested NSI can be shared and if an existing NSI can be used, the network slice provisioning management service provider decides to use the existing NSI. Modification of the existing NSI may be needed to satisfy the network slice instance related requirements. Use case is completed go to "Step 8". Otherwise, the network slice provisioning management service provider triggers to create a new NSI, for which the following steps 2 – 8 are needed.	
Step 2 (M)	The network slice provisioning management service provider decides on the constituent NSSIs and the topology of the NSI to be created using the information from service profile [6]. For the constituent NSSIs, the network slice provisioning management service provider derives network slice subnet related requirements from the network slice related requirements. If reconfiguration of the transport network is needed, the network slice provisioning management service provider derives transport network related requirements (e.g., latency, bandwidth) from the network slice related requirements.	
Step 3 (M)	For the required NSSI(s), the network slice provisioning management service provider sends network slice subnet related requirements to the network slice subnet provisioning management service provider to request allocation of the required NSSI(s).	Network slice subnet instance allocation use case
Step 4 (M)	The network slice provisioning management service provider receives the information of the allocated NSSI(s) (e.g., the management identifier of NSSI, service access point information of NSSI, external connection point information of NSSI) from NSSMF.	
Step 5 (M)	The network slice provisioning management service provider, via the network slice subnet provisioning management service provider, sends the transport network related requirements (e.g., external connection point, latency and bandwidth) to the TN Manager. The TN manager reconfigures the TN accordingly and responds to the network slice provisioning management service provider via the network slice subnet provisioning management service provider.	
Step 6 (M)	The network slice provisioning management service provider receives the response from TN Manager via the network slice subnet provisioning management service provider.	
Step 7 (M)	The network slice provisioning management service provider associates the NSSI(s) with the corresponding NSI (e.g., allocation of the management identifier of NSI and mapping the management identifier of NSI with the received management Identifier of NSSI(s)) and triggers to establish the links between the service access points of the NSSI(s).	
Step 8 (M)	The network slice provisioning management service provider notifies the network slice instance information of NSI (e.g., the management identifier of NSI).	
Ends when	All the steps identified above are successfully completed.	
Exceptions	One of the steps identified above fails.	
Post-conditions	An NSI is ready to satisfy the network slice related requirements.	
Traceability	REQ-PRO_NSSI-FUN-1, REQ-PRO_NSI-FUN-3.	

5.1.2 Network slice subnet instance allocation

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI TS 128 531 V17.10.0 \(2025-01\)](https://standards.iteh.ai/catalog/standards/etsi/35b19a1b-0838-4c6a-a470-118d6239b369/etsi-ts-128-531-v17-10-0-2025-01)

<https://standards.iteh.ai/catalog/standards/etsi/35b19a1b-0838-4c6a-a470-118d6239b369/etsi-ts-128-531-v17-10-0-2025-01>