

ETSI TS 126 114 V17.9.0 (2025-01)



**Universal Mobile Telecommunications System (UMTS);
LTE;**

5G;

IP Multimedia Subsystem (IMS);

Multimedia telephony;

Media handling and interaction

(3GPP TS 26.114 version 17.9.0 Release 17)



ReferenceRTS/TSGS-0426114vh90

Keywords5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver repository](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2025-01)

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	17
Introduction	17
1 Scope	18
2 References	18
3 Definitions and abbreviations.....	26
3.1 Definitions	26
3.2 Abbreviations	28
4 System description	30
4.1 System	30
4.2 Client	31
4.3 MRFP and MGW	32
5 Media codecs.....	32
5.1 Media components	32
5.2 Codecs for MTSI clients in terminals.....	33
5.2.1 Speech.....	33
5.2.1.1 General codec requirements.....	33
5.2.1.2 Detailed codec requirements, AMR.....	34
5.2.1.3 Detailed codec requirements, AMR-WB.....	34
5.2.1.4 Detailed codec requirements, EVS.....	34
5.2.1.5 Offering multiple audio bandwidths and multiple channels.....	34
5.2.1.6 Codec preference order	34
5.2.2 Video	35
5.2.3 Real-time text.....	36
5.2.4 Still Images	37
6 Media configuration	37
6.1 General	37
6.2 Session setup procedures.....	37
6.2.1 General.....	37
6.2.1a RTP profile negotiation	38
6.2.1a.1 General.....	38
6.2.1a.2 Using SDPCapNeg in SDP offer.....	38
6.2.1a.3 Answering to an SDP offer using SDPCapNeg	39
6.2.2 Speech.....	39
6.2.2.1 General	39
6.2.2.2 Generating SDP offers	40
6.2.2.3 Generating SDP answer	42
6.2.3 Video	51
6.2.3.1 Introduction.....	51
6.2.3.2 Common Session Setup Procedures.....	52
6.2.3.3 Coordination of Video Orientation (CVO)	53
6.2.3.4 Video Region-of-Interest (ROI)	53
6.2.3.5 RTP Retransmission.....	56
6.2.3.6 Forward Error Correction (FEC).....	56
6.2.4 Text.....	56
6.2.5 Bandwidth negotiation.....	57
6.2.5.1 General	57
6.2.5.2 Speech	59
6.2.5.3 Video.....	61
6.2.6 The Synchronization Info attribute "3gpp_sync_info"	62

6.2.7	Negotiated QoS parameters	63
6.2.7.1	General	63
6.2.7.2	Alignment of negotiated QoS parameters and b=AS bandwidth modifier	63
6.2.7.3	Alignment of negotiated QoS parameters and a=bw-info attribute	64
6.2.7.4	The a=3gpp-qos-hint SDP attribute	64
6.2.7.4.1	General	64
6.2.7.4.2	3gpp-qos-hint ABNF syntax and semantics	65
6.2.7.4.3	Creating an SDP offer	66
6.2.7.4.4	Creating an SDP answer	66
6.2.7.4.5	Offerer receiving an SDP answer	67
6.2.8	Delay Budget Information (DBI) Signaling	68
6.2.9	ANBR Support attribute "anbr"	69
6.2.10	Data channel	69
6.2.10.1	General	69
6.2.10.2	Generating SDP offer	72
6.2.10.3	Generating SDP answer	73
6.2.10.4	Receiving SDP answer	73
6.2.11	Still Images	73
6.3	Session control procedures	74
7	Data transport	74
7.1	General	74
7.2	RTP profiles	74
7.3	RTCP usage	74
7.3.1	General	74
7.3.2	Speech	75
7.3.3	Video	76
7.3.4	Real-time text	77
7.3.5	Void	77
7.3.6	Reduced-Size RTCP	77
7.3.7	Video Region-of-Interest (ROI) Signaling	78
7.3.8	Delay Budget Information (DBI) Signaling	81
7.4	RTP payload formats for MTSI clients	83
7.4.1	General	83
7.4.2	Speech	83
7.4.3	Video	84
7.4.4	Real-time text	85
7.4.5	Coordination of Video Orientation	85
7.4.6	RTP Retransmission	87
7.4.7	Forward Error Correction (FEC)	87
7.4.8	Still Images	87
7.5	Media flow	87
7.5.1	General	87
7.5.2	Media specific	87
7.5.2.1	Speech	87
7.5.2.1.1	General	87
7.5.2.1.2	Default operation	88
7.5.2.1.3	HSPA	89
7.5.2.1.4	EGPRS	89
7.5.2.1.5	GIP	89
7.5.2.1.6	Initial codec mode for AMR and AMR-WB	89
7.5.2.1.7	E-UTRAN and NR	90
7.5.2.1.8	Initial codec mode for EVS	90
7.5.2.1.9	Dual-mono	90
7.5.2.2	Video	90
7.5.2.3	Text	91
7.5.3	Media synchronization	91
7.5.3.1	General	91
7.5.3.2	Text	91
7.5.4	ECN usage in RTP sessions	91
7.5.5	Handling of bit-rate variations	91
7.5.5.1	General	91

7.5.5.2	Video.....	92
7.5.5.3	Speech.....	92
8	Jitter buffer management in MTSI clients in terminals.....	92
8.1	General	92
8.2	Speech	92
8.2.1	Terminology	92
8.2.2	Functional requirements for jitter-buffer management	94
8.2.3	Minimum performance requirements for jitter-buffer management	94
8.2.3.1	General	94
8.2.3.2	Objective performance requirements	95
8.2.3.2.1	General	95
8.2.3.2.2	Jitter buffer delay criteria	95
8.2.3.2.3	Jitter induced concealment operations.....	96
8.2.3.3	Delay and error profiles	96
8.2.3.4	Speech material for JBM minimum performance evaluation.....	97
8.3	Video	97
8.4	Text	97
9	Packet-loss handling.....	97
9.1	General	97
9.2	Speech	98
9.2.1	General.....	98
9.2.2	Transmitting redundant frames	98
9.2.3	Receiving redundant frames	101
9.3	Video	101
9.3.1	General.....	101
9.3.2	Receiver behaviour	101
9.3.3	Sender behaviour	102
9.3.4	Recommendations for packet loss recovery mechanisms usage	102
9.4	Text	103
10	Adaptation	103
10.1	General	103
10.2	Speech	104
10.2.0	General.....	104
10.2.1	RTCP-APP with codec control requests	105
10.2.1.1	General	105
10.2.1.2	General Format of RTCP-APP packet with codec control requests.....	105
10.2.1.2a	Padding	106
10.2.1.3	Redundancy Request.....	107
10.2.1.4	Frame Aggregation Request.....	107
10.2.1.5	Codec Mode Request	108
10.2.1.6	Generation of RTP payloads for multiple codec control requests.....	108
10.2.1.7	EVS Primary Rate Request	109
10.2.1.8	EVS Bandwidth Request.....	110
10.2.1.9	EVS Channel Aware Request	111
10.2.1.10	EVS Primary mode to EVS AMR-WB IO mode Switching Request	111
10.2.1.11	EVS AMR-WB IO mode to EVS Primary mode Switching Request	112
10.2.2	Example use cases	113
10.2.3	SDP negotiation for RTCP-APP.....	115
10.3	Video	116
10.3.1	General.....	116
10.3.2	Signaling mechanisms	116
10.3.3	Adaptation triggers	117
10.3.4	Sender behavior, downswitching.....	118
10.3.4.1	Downswitching divided into phases.....	118
10.3.4.2	Rate reduction phase	118
10.3.4.3	Delay recovery phase	119
10.3.5	Sender behavior, up-switching.....	119
10.3.6	Receiver behavior, down-switching.....	120
10.3.7	Receiver behavior, up-switch.....	120
10.3.8	ECN triggered adaptation	120

10.4	Text	121
10.5	Explicit Congestion Notification.....	121
10.6	Using the a=bw-info attribute for adaptation	122
10.7	Access network bitrate recommendation.....	122
10.7.1	General.....	122
10.7.2	Relation to session signaling bitrate information.....	123
10.7.3	Use with dynamic bitrate adaptation.....	123
10.7.3.1	General	123
10.7.3.2	Adaptation of sent media	124
10.7.3.3	Adaptation of received media	127
10.7.4	Message mapping for LTE access	127
10.7.5	Message mapping for NR access	127
11	Front-end handling	128
11.1	General	128
12	Inter-working.....	129
12.1	General	129
12.2	3G-324M	129
12.2.1	General.....	129
12.2.2	Codec usage.....	129
12.2.2.1	General	129
12.2.2.2	Text	129
12.2.3	Payload format.....	129
12.2.4	MTSI media gateway trans-packetization.....	129
12.2.4.1	General	129
12.2.4.2	Speech de-jitter buffer.....	129
12.2.4.3	Video bitrate equalization	130
12.2.4.4	Data loss detection	130
12.2.4.5	Data integrity indication.....	130
12.2.4.6	Packet size considerations	130
12.2.4.6.0	General	130
12.2.4.6.1	The Maximum Receive SDU Size attribute "3gpp_MaxRecvSDUSize"	131
12.2.4.7	Setting RTP timestamps	131
12.2.4.8	Protocol termination.....	131
12.2.4.9	Media synchronization	131
12.2.5	Session control.....	132
12.3	GERAN/UTRAN CS inter-working.....	132
12.3.0	3G-324M	132
12.3.1	Codecs for MTSI media gateways	132
12.3.1.1	Speech interworking between 3GPP PS access and CS GERAN/UTRAN.....	132
12.3.1.1a	Speech inter-working between fixed access and CS GERAN/UTRAN.....	133
12.3.1.2	Text	133
12.3.2	RTP payload formats for MTSI media gateways.....	134
12.3.2.1	Speech.....	134
12.3.2.2	Text	135
12.3.3	Explicit Congestion Notification	135
12.3.4	Codec switching procedures with SRVCC	135
12.4	PSTN.....	136
12.4.1	3G-324M	136
12.4.2	Text.....	136
12.5	GIP inter-working.....	136
12.5.1	Text.....	136
12.5.2	Speech.....	136
12.6	Void.....	137
12.6.1	Void	137
12.6.2	Void	137
12.7	Inter-working with other IMS and non-IMS IP networks	137
12.7.1	General.....	137
12.7.2	Speech.....	137
12.7.2.1	General	137
12.7.2.2	Speech codecs and formats	137

12.7.2.2.1	MTSI MGW for interworking between MTSI client in terminal using 3GPP access and other IMS or non-IMS IP networks	137
12.7.2.2.2	MTSI MGW for interworking between MTSI client in terminal using fixed access and other IMS or non-IMS IP networks	138
12.7.2.2.3	Common procedures	138
12.7.2.3	Codec preference order for session negotiation	138
12.7.2.4	RTP profiles	139
12.7.2.5	RTP payload formats	139
12.7.2.6	Packetization	139
12.7.2.7	RTCP usage and adaptation	140
12.7.2.8	RTP usage	140
12.7.2.9	Session setup and session modification	141
12.7.2.10	Audio level alignment	141
12.7.3	Explicit Congestion Notification	141
12.7.4	Text	142
12.7.5	Inter-working IPv4 and IPv6 networks	142
12.8	MGW handling for NO_REQ interworking	142
13	Void	143
13a	Media types, codecs and formats used for MSRP transport	143
13a.1	General	143
13a.2	Difference relative to 3GPP TS 26.141	143
13a.2.1	Video	143
14	Supplementary services	143
14.1	General	143
14.2	Media formats and transport	143
14.3	Media handling in hold procedures	144
15	Network preference management object	144
15.1	General	144
15.2	Nodes Definition	144
15.3	Example Configuration of 3GPP MTSINP MO	156
16	Quality of Experience	157
16.1	General	157
16.2	Metrics Definition	158
16.2.1	Corruption duration metric	158
16.2.2	Successive loss of RTP packets	158
16.2.3	Frame rate	159
16.2.4	Jitter duration	159
16.2.5	Sync loss duration	159
16.2.6	Round-trip time	160
16.2.7	Average codec bitrate	160
16.2.8	Codec information	160
16.2.9	Call setup time	161
16.3	Metric Configuration	161
16.3.1	QoE metrics reporting management object	161
16.3.2	QoE metric reporting configuration	167
16.3.3	QoE reporting rule definition	167
16.4	Metrics Reporting	168
16.4.1	XML schema for QoE report message	169
16.4.2	Example XML for QoE report message	171
16.5	QoE Measurement Collection Functionalities	171
16.5.1	Configuration and reporting	171
16.5.2	XML configuration	175
17	Management of Media Adaptation	176
17.1	General	176
17.2	Media adaptation management object	176
17.3	Management procedures	204
17.3.1	Management of speech adaptation	204
17.3.2	Management of video adaptation	206

17.4	Management of media robustness adaptation.....	208
17.4.1	General.....	208
18	MTSI client in terminal using fixed access	209
18.1	General	209
18.2	Media codecs.....	209
18.2.1	General.....	209
18.2.2	Speech.....	209
18.2.2.1	Speech codecs	209
18.2.2.2	Error concealment procedures.....	210
18.2.2.3	Source controlled rate operation	210
18.2.3	Video	211
18.2.4	Real-time text.....	211
18.3	Media configuration	211
18.3.1	General.....	211
18.3.2	Session setup procedures	211
18.3.2.1	General	211
18.3.2.2	Speech.....	211
18.3.2.3	Video.....	212
18.3.2.4	Text	212
18.3.2.5	Bandwidth negotiation	212
18.3.3	Session control procedures	212
18.4	Data transport	213
18.4.1	General.....	213
18.4.2	Packetization.....	213
18.4.3	RTP payload format.....	213
18.5	Jitter buffer management.....	214
18.6	Packet-loss handling.....	214
18.7	Adaptation	214
18.8	Front-end handling	214
18.9	Supplementary services.....	214
19	Additional bandwidth information	215
19.1	General	215
19.2	Bandwidth properties	215
19.2.1	General description	215
19.2.2	Maximum Supported Bandwidth.....	216
19.2.3	Maximum Desired Bandwidth.....	216
19.2.4	Minimum Desired Bandwidth.....	217
19.2.5	Minimum Supported Bandwidth.....	217
19.2.6	IP version	217
19.2.7	Maximum Packet Rate.....	218
19.2.8	Minimum Packet Rate	218
19.3	SDP attribute	218
19.3.1	Definition.....	218
19.3.2	SDP grammar.....	219
19.3.3	Declarative use.....	220
19.3.4	Usage in offer/answer	220
19.4	Modifications of the bandwidth information by intermediate network nodes.....	221
Annex A (informative): Examples of SDP offers and answers.....		223
A.1	SDP offers for speech sessions initiated by MTSI client in terminal	223
A.1.1	HSPA or unknown access technology.....	223
A.1.1.1	Only AMR-NB supported by MTSI client in terminal	223
A.1.1.2	AMR and AMR-WB are supported by MTSI client in terminal.....	224
A.1.1.2.1	One-phase approach	224
A.1.1.2.2	Two-phase approach	225
A.1.2	EGPRS	226
A.1.3	Generic Access	227
A.2	SDP offers for speech sessions initiated by media gateway.....	227
A.2.1	General	227

A.2.2	MGW between GERAN UE and MTSI	227
A.2.3	MGW between legacy UTRAN UE and MTSI	228
A.2.4	MGW between CS UE and MTSI	228
A.2.5	MGW between GERAN UE and MTSI when wideband speech is supported	229
A.3	SDP answers to SDP speech session offers	229
A.3.1	General	229
A.3.1a	SDP answer from an MTSI client in terminal when only narrowband speech was offered	230
A.3.2	SDP answer from an MTSI client in terminal	230
A.3.2a	SDP answer from a non-MTSI UE with AVP	231
A.3.3	SDP answer from an MTSI client in terminal supporting only AMR	232
A.3.4	SDP answer from an MTSI client in terminal using EGPRS access when both AMR and AMR-WB are supported	233
A.3.4a	SDP answer from an MTSI client in terminal using EGPRS access when only AMR is supported	234
A.3.4b	SDP answer from an MTSI client in terminal using WLAN	234
A.3.5	SDP answer from MTSI MGW supporting only one codec mode set for AMR and AMR-WB each	235
A.3.5a	SDP answer from MTSI MGW supporting only one codec mode set for AMR	237
A.3.6	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing UE on GERAN	237
A.3.7	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing legacy UE on UTRAN	238
A.4	SDP offers and answers for video sessions	239
A.4.1	Void	239
A.4.2	Void	239
A.4.2a	H.264/AVC	239
A.4.2b	High Granularity CVO example	241
A.4.2c	RTP Retransmission	241
A.4.2d	RTP Forward Error Correction (FEC)	242
A.4.2e	SDP Examples with ROI	243
A.4.3	Void	249
A.4.4	Void	249
A.4.4a	H.264/AVC with "imageattr" attribute	249
A.4.4a.1	H.264/AVC with "imageattr" attribute – different image sizes in SDP offer and answer	251
A.4.4a.2	H.264/AVC with "imageattr" attribute – different payload type numbers in offer and answer	252
A.4.4b	H.264/AVC with "imageattr" attribute with multiple rtpmaps	253
A.4.5	H.264 with asymmetric video streams	255
A.4.6	H.264/AVC with "imageattr" attribute for non-CVO operation	256
A.4.7	H.264 (AVC) and H.265 (HEVC)	258
A.4.7.1	MTSI client with 848x480 resolution 5 inch display	258
A.4.7.2	MTSI client with 1280x720 resolution 5 inch display	259
A.4.7.3	MTSI client with 848x480 resolution 10 inch display	260
A.4.7.4	MTSI client with 1280x720 resolution 10 inch display	261
A.4.8	H.264 (AVC) and H.265 (HEVC) with asymmetric video streams	262
A.5	SDP offers for text	263
A.5.1	T.140 with and without redundancy	263
A.6	SDP example with bandwidth information	265
A.6.1	General	265
A.6.2	SDP examples with bandwidth information declared with bandwidth modifiers	265
A.6.3	SDP examples giving additional bandwidth information using the a=bw-info attribute	266
A.7	SDP examples with "3gpp_sync_info" attribute	269
A.7.1	Synchronized streams	269
A.7.2	Nonsynchronized streams	269
A.8	SDP example with QoS negotiation	270
A.9	Void	274
A.9a	SDP offer/answer regarding the use of Reduced-Size RTCP	274
A.10	Examples of SDP offers and answers for inter-working with other IMS or non-IMS IP networks	275
A.10.1	General	275

A.10.2	Session initiated by MTSI client in terminal	275
A.10.2.1	SDP offers from an MTSI client in terminal.....	275
A.10.2.2	SDP offers modified by MTSI MGW when pre-emptively adding inter-working formats	276
A.10.2.3	SDP modified by MGW when adding inter-working formats only when the original SDP offer was rejected.....	277
A.11	Adding or removing a video component to/from an on-going video call session.....	279
A.12	SDP examples when using ECN	283
A.12.1	SDP examples when using ECN for speech	283
A.12.1.1	With RTP/AVP and zero RTCP bandwidth.....	283
A.12.1.2	With RTP/AVPF and non-zero RTCP bandwidth	284
A.12.1.3	With RTCP ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients	285
A.12.2	SDP examples when using ECN for video in RTP.....	286
A.12.2.1	Without RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports	286
A.12.2.2	With RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients	287
A.13	SDP examples for MTSI client in terminal using fixed access	288
A.13.1	General	288
A.13.2	SDP examples for PCM	288
A.13.3	SDP example for G.722.....	289
A.13.4	SDP example for EVS, AMR-WB, G.722, AMR, PCM and DTMF	289
A.14	SDP offers and answers for speech sessions with EVS	290
A.14.1	SDP offers initiated by MTSI client in terminal.....	290
A.14.1.1	Unknown access technology.....	290
A.14.1.2	EGPRS.....	291
A.14.1.3	NR/E-UTRAN/HSPA.....	292
A.14.1.4	Dual-mono	292
A.14.2	SDP offers initiated by media gateway	293
A.14.2.1	Network between MTSI using fixed access and MTSI modifying SDP offer to configure EVS AMR-WB IO mode.....	294
A.14.3	SDP answers from MTSI client in terminal	295
A.14.3.1	SDP answer from MTSI client in terminal when narrowband speech is negotiated	295
A.14.3.2	SDP answer from MTSI client in terminal when up to wideband speech is negotiated	295
A.14.3.3	SDP answer from MTSI client in terminal when only wideband speech is negotiated	296
A.14.3.4	SDP answer from MTSI client in terminal when up to super-wideband speech is negotiated	296
A.14.3.5	SDP answer from MTSI client in terminal when only super-wideband speech is negotiated	296
A.14.3.6	SDP answer from MTSI client in terminal using WLAN	297
A.14.3.7	SDP answer from MTSI client in terminal supporting dual-mono	297
A.14.3.8	SDP answer from MTSI client in terminal supporting dual-mono for send direction	297
A.14.3.9	SDP answer from MTSI client in terminal when SC-VBR is negotiated	298
A.14.4	SDP answers from MTSI client in terminal using fixed access.....	298
A.14.4.1	SDP answer from MTSI client in terminal using fixed access when narrowband speech is negotiated ...	298
A.14.4.2	SDP answer from MTSI client in terminal using fixed access when only wideband speech is negotiated.....	299
A.14.4.3	SDP answer from MTSI client in terminal using fixed access when only super-wideband speech is negotiated.....	299
A.15	SDP offers and answers with ANBR capability signaling	300
A.16	SDP offers and answers with QoS hint signalling.....	301
A.17	SDP offers and answers with data channel capability signalling	303
A.18	SDP offers and answers for ITT4RT	305
Annex B (informative): Examples of adaptation scenarios		307
B.1	Video bitrate adaptation	307
Annex C (informative): Example adaptation mechanisms for speech.....		308
C.1	Example of feedback and adaptation for speech and video.....	308

C.1.1	Introduction	308
C.1.2	Signalling state considerations	309
C.1.3	Adaptation state machine implementations	311
C.1.3.1	General	311
C.1.3.2	Adaptation state machine with four states	313
C.1.3.3	Adaptation state machine with four states (simplified version without frame aggregation)	316
C.1.3.4	Adaptation state machine with two states	318
C.1.3.5	Adaptation when using ECN	319
C.2	Example criteria for video bit rate feedback and adaptation	321
C.2.1	Introduction	321
C.2.2	Media sender side	321
C.2.3	Media receiver side	322
C.2.4	Video encoder bitrate adaptation, down-switch	322
C.2.5	Video encoder bitrate adaptation, receiver-driven up-switch	323
C.2.6	Video encoder bitrate adaptation, recovery phase	324
Annex D (informative): Reference delay computation algorithm		326
Annex E (informative): QoS profiles		328
E.1	General	328
E.2	Bi-directional speech (AMR12.2, IPv4, RTCP and MBR=GBR bearer)	328
E.3	Void	329
E.4	Bi-directional real-time text (3 kbps, IPv4 or IPv6, RTCP and MBR=GBR bearer)	330
E.5	Bi-directional speech (AMR-WB23.85, IPv4, RTCP and MBR=GBR bearer)	332
E.6	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv4, RTCP and MBR=GBR bearer)	332
E.7	Bi-directional speech (AMR12.2, IPv6, RTCP and MBR=GBR bearer)	333
E.8	Bi-directional speech (AMR-WB23.85, IPv6, RTCP and MBR=GBR bearer)	334
E.9	Void	335
E.10	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv6, RTCP and MBR=GBR bearer)	335
E.11	Bi-directional speech (AMR, IPv4, RTCP and MBR>GBR bearer)	336
E.12	Bi-directional speech (AMR-WB, IPv4, RTCP and MBR>GBR bearer)	337
E.13	Void	338
E.14	Bi-directional video (H.264 AVC level 1.1, IPv4, RTCP and MBR>GBR bearer)	338
E.15	Bi-directional speech (AMR, IPv6, RTCP and MBR>GBR bearer)	339
E.16	Bi-directional speech (AMR-WB, IPv6, RTCP and MBR>GBR bearer)	340
E.17	Void	341
E.18	Bi-directional video (H.264 AVC level 1.1, IPv6, RTCP and MBR>GBR bearer)	341
E.19	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv4, RTCP and MBR=GBR bearer)	342
E.20	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv6, RTCP and MBR=GBR bearer)	343
E.21	Bi-directional video (H.264 AVC level 1.2, IPv4, RTCP and MBR>GBR bearer)	345
E.22	Bi-directional video (H.264 AVC level 1.2, IPv6, RTCP and MBR>GBR bearer)	348
E.23	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500 kbps, IPv6, RTCP and MBR=GBR bearer)	349
E.24	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500/40 kbps, IPv6, RTCP and MBR>GBR bearer)	350

E.25	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600 kbps, IPv6, RTCP and MBR=GBR bearer)	351
E.26	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600/40 kbps, IPv6, RTCP and MBR>GBR bearer)	352
E.27	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650 kbps, IPv6, RTCP and MBR=GBR bearer)	353
E.28	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650/40 kbps, IPv6, RTCP and MBR>GBR bearer)	354
E.29	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750 kbps, IPv6, RTCP and MBR=GBR bearer)	355
E.30	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750/40 kbps, IPv6, RTCP and MBR>GBR bearer)	356
E.31	Bi-directional speech (EVS 13.2, IPv4, RTCP and MBR=GBR bearer)	357
E.32	Bi-directional speech (EVS 24.4, IPv4, RTCP and MBR=GBR bearer)	358
E.33	Bi-directional speech (EVS 13.2, IPv6, RTCP and MBR=GBR bearer)	359
E.34	Bi-directional speech (EVS 24.4, IPv6, RTCP and MBR=GBR bearer)	360

Annex F (Normative): Void 362

Annex G (Normative): DTMF events363

G.1	General	363
G.2	Encoding of DTMF events	363
G.3	Session setup	363
G.4	Data transport for DTMF events	365

Annex H (informative): Network Preference Management Object Device Description Framework...367

Annex I (informative): QoE Reporting Management Object Device Description Framework.....368

Annex J (informative): Media Adaptation Management Object Device Description Framework.....369

Annex K (informative): Computation of b=AS for AMR and AMR-WB.....370

K.1	General	370
K.2	Procedure for computing the bandwidth	370
K.3	Computation of RTP payload size.....	370
K.4	Detailed computation	371

Annex L (Normative): Facsimile transmission380

L.1	General	380
L.2	FoIP support in MTSI clients	380
L.2.1	FoIP support in MTSI client in terminal	380
L.2.2	FoIP support in MTSI MGW	380
L.2.3	Recommended configuration.....	380
L.3	Session setup	381
L.3.1	Session setup for any MTSI client supporting facsimile transmission	381
L.3.2	Session setup when the recommended profile is supported	381
L.4	Data transport using UDP/IP	382
L.5	CS GERAN inter-working	382

L.6	PSTN inter-working	383
L.7	SDP examples	383
L.7.1	Facsimile-only session	383
Annex M (informative): IANA registration information for SDP attributes.....		385
M.1	Introduction	385
M.2	3gpp_sync_info	385
M.3	3gpp_MaxRecvSDUSize.....	385
M.4	3gpp_mtsi_app_adapt.....	386
M.5	predefined_ROI.....	387
M.6	bw-info	387
M.7	ccc_list.....	388
M.8	anbr.....	388
M.9	PLR_adapt.....	389
M.10	MAXimum-e2e-PLR.....	390
M.11	3gpp-qos-hint	390
Annex N (informative): Computation of b=AS for Video Codec		397
N.1	General	397
N.2	Examples	397
Annex O (informative): IANA registration information for RTP Header Extensions.....		398
O.1	Introduction	398
O.2	urn:3gpp:video-orientation.....	398
O.3	urn:3gpp:video-orientation:6.....	398
O.4	urn:3gpp:roi-sent	398
O.5	urn:3gpp:predefined-roi-sent.....	399
O.6	urn:3gpp:audio-mixing-gain.....	399
Annex P (informative): Video packet loss handling operation principles and examples.....		400
P.1	General	400
P.2	Video error recovery	400
P.3	RTP Retransmission.....	402
Annex Q (informative): Computation of b=AS for EVS.....		404
Q.1	General	404
Q.2	Procedure for computing the bandwidth	404
Q.3	Computation of RTP payload size.....	404
Q.4	Detailed computation	405
Annex R (informative): IANA registration information for RTCP Feedback Message Types.....		407
R.1	Video Region-of-Interest (ROI)	407
R.2	Delay Budget Information (DBI)	407
R.3	Viewport (VP).....	408