



SLOVENSKI STANDARD
oSIST prEN ISO 16122-4:2023

01-marec-2023

Kmetijski in gozdarski stroji - Kontrola škropilnikov v uporabi - 4. del: Nameščeni in polprenosni škropilniki (ISO/DIS 16122-4:2022)

Agricultural and forestry machines - Inspection of sprayers in use - Part 4: Fixed and semi-mobile sprayers (ISO/DIS 16122-4:2022)

Land- und Forstmaschinen - Kontrolle von in Gebrauch befindlichen Pflanzenschutzgeräten - Teil 4: Fest installierte und teilbewegliche Geräte (ISO/DIS 16122-4:2022)

Matériel agricole et forestier - Contrôle des pulvérisateurs en service - Partie 4: Pulvérisateurs fixes et semi-mobiles (ISO/DIS 16122-4:2022)

Ta slovenski standard je istoveten z: prEN ISO 16122-4

ICS:

65.060.40 Oprema za nego rastlin Plant care equipment

oSIST prEN ISO 16122-4:2023 **en,fr,de**

DRAFT INTERNATIONAL STANDARD

ISO/DIS 16122-4

ISO/TC 23/SC 6

Secretariat: AFNOR

Voting begins on:
2022-12-26Voting terminates on:
2023-03-20

Agricultural and forestry machines — Inspection of sprayers in use —

Part 4: Fixed and semi-mobile sprayers

*Matériel agricole et forestier — Contrôle des pulvérisateurs en service —
Partie 4: Pulvérisateurs fixes et semi-mobiles*

ICS: 65.060.40

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN ISO 16122-4:2023](https://standards.iteh.ai/catalog/standards/sist/3e344c4e-746f-43b0-8ca1-3e134508c578/osist-pren-iso-16122-4-2023)

<https://standards.iteh.ai/catalog/standards/sist/3e344c4e-746f-43b0-8ca1-3e134508c578/osist-pren-iso-16122-4-2023>

This document is circulated as received from the committee secretariat.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

ISO/CEN PARALLEL PROCESSING



Reference number
ISO/DIS 16122-4:2022(E)

© ISO 2022

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 16122-4:2023](https://standards.iteh.ai/catalog/standards/sist/3e344c4e-746f-43b0-8ca1-3e134508c578/osist-pren-iso-16122-4-2023)

<https://standards.iteh.ai/catalog/standards/sist/3e344c4e-746f-43b0-8ca1-3e134508c578/osist-pren-iso-16122-4-2023>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	v
Introduction.....	vii
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Requirements and method of verification.....	1
4.1 General.....	1
4.2 Leaks and dripping.....	2
4.2.1 Static leaks.....	2
4.2.2 Dynamic leaks.....	2
4.2.3 Spraying and dripping on parts.....	2
4.3 Pump(s).....	2
4.3.1 Capacity.....	2
4.3.2 Pulsations.....	3
4.3.3 Air chamber.....	3
4.4 Spray mix agitation.....	3
4.4.1 Hydraulic.....	3
4.4.2 Mechanical.....	3
4.5 Spray tank(s).....	3
4.5.1 Lid.....	3
4.5.2 Tank filling strainer(s).....	4
4.5.3 Pressure compensation.....	4
4.5.4 Tank content indicator(s).....	4
4.5.5 Tank emptying.....	4
4.5.6 Tank filling.....	4
4.5.7 Induction hopper.....	4
4.5.8 Cleaning device for plant protection product containers.....	4
4.5.9 Cleaning equipment.....	5
4.6 Measuring systems, controls and regulation systems.....	5
4.6.1 General.....	5
4.6.2 Pressure indicator for spray liquid.....	5
4.6.3 Other measuring devices.....	6
4.6.4 Pressure adjusting devices.....	6
4.6.5 Direct injection systems.....	6
4.7 Lines (pipes and hoses).....	6
4.7.1 Lines.....	6
4.8 Filters.....	7
4.8.1 Filter presence.....	7
4.8.2 Isolating device.....	7
4.8.3 Filter insert changeability.....	7
4.9 Application unit.....	7
4.9.1 Dripping.....	7
4.9.2 Horizontal spray booms.....	7
4.9.3 Vertical spray boom.....	9
4.9.4 Spray guns and lances.....	10
4.10 Blower.....	10
4.10.1 Condition.....	10
4.10.2 Adjustability.....	10
4.11 Distribution.....	10
4.11.1 Uniformity of spray jet.....	10
4.11.2 Nozzle output.....	11
4.11.3 Spray distribution measurement on a patternator (optional).....	11
4.11.4 Optional vertical distribution information.....	11

ISO/DIS 16122-4:2022(E)

4.12	Autonomous application units.....	11
4.12.1	Drive system.....	11
4.12.2	Travel speed spray robots.....	12
4.13	Cleaning equipment.....	12
5	Test methods.....	12
5.1	Test facilities.....	12
5.2	Spray agitation pumps.....	12
5.2.1	Pump capacity test.....	12
5.2.2	Pump pulsations.....	14
5.3	Sprayer's pressure indicators.....	14
5.3.1	Specification of pressure indicators used for verification.....	14
5.3.2	Verification method of the sprayer pressure indicator.....	14
5.4	Flow meters for controlling the volume/area rate.....	14
5.4.1	General.....	14
5.4.2	Operating procedure No. 1: Verification by nozzle flow rate measurement.....	15
5.4.3	Operating Procedure No. 2: Verification by installing a calibrated flow meter in the circuit of the sprayer.....	15
5.5	System for controlling forward speed.....	15
5.6	Uniformity of the transverse volume distribution with a horizontal patternator.....	15
5.6.1	Specification of the horizontal patternators used for verification.....	15
5.6.2	Calculation of Coefficient of Variation (CV).....	16
5.6.3	Verification method of the uniformity of the transverse distribution.....	16
5.6.4	Verification method of spray gun/lance flow rate.....	16
5.7	Flow rate of the spray nozzles.....	16
5.7.1	General.....	16
5.7.2	Measurement with nozzles fitted on the sprayer.....	16
5.7.3	Measurement with nozzles removed from the sprayer.....	17
5.8	Pressure drop.....	17
5.9	Pressure variation when the sections are closed.....	17
5.10	Pressure variation when the spray is switched off.....	17
5.11	Pressure distribution.....	18
Annex ZA (informative) Relationship between this European Standard and the essential health and safety and environmental requirements of Directive 2009/128/EC.....		19
Bibliography.....		21

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee [or Project Committee] ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 6, *Equipment for crop protection*.

This second edition cancels and replaces the first edition ISO 16122-4:2015, which has been technically revised.

The main changes compared to the previous edition are as follows:

- Normative references (updated)
- Terms and definitions (modified)
- Filling high capacity spray-tanks during leak test (modified)
- Tank filling strainer/Filling hole (modified)
- Tank emptying (modified)
- Pressure indicators (modified)
- Diameter analogue pressure indicators (modified)
- Maximum error flow-meters for controlling the volume/hectare rate (modified)
- [Figure 1](#) (modified)
- Dripping (modified)
- Spray guns and lances (modified)
- Pump capacity test (modified)

A list of all parts in the ISO 16122 series can be found on the ISO website.

ISO/DIS 16122-4:2022(E)

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

oSIST prEN ISO 16122-4:2023

<https://standards.iteh.ai/catalog/standards/sist/3e344c4e-746f-43b0-8ca1-3e134508c578/osist-pren-iso-16122-4-2023>

Introduction

There are two main reasons for the inspection:

- less potential risk of environmental contamination by plant protection products;
- good control of the pest with the minimum possible input of plant protection product.

In order to use plant protection products in agricultural production safely, it is necessary to define the requirements and test methods for sprayers in use. This is a relevant step after having standardized minimum requirements for new sprayers, in respect of safety hazards (see ISO 4254-6) and potential risks of environmental contamination (see ISO 16119 series).

Standardising the requirements and methods for inspection of sprayers in use takes into consideration not only the original performance of the sprayer but also its use, care and maintenance. This is a logical link to ensure the continued benefit arising from the supply of new sprayers of good quality.

The inspection of sprayers in use can be a mandatory requirement or adopted on a voluntary basis. In both cases further requirements, outside the scope of this standard, are necessary for the management of inspections. These include, for example, requirements for the competence of persons carrying out inspections and the frequency of inspections.

NOTE National or local regulations may also apply concerning the qualifications and competence of inspectors.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN ISO 16122-4:2023](https://standards.iteh.ai/catalog/standards/sist/3e344c4e-746f-43b0-8ca1-3e134508c578/osist-pren-iso-16122-4-2023)

<https://standards.iteh.ai/catalog/standards/sist/3e344c4e-746f-43b0-8ca1-3e134508c578/osist-pren-iso-16122-4-2023>

Agricultural and forestry machines — Inspection of sprayers in use —

Part 4: Fixed and semi-mobile sprayers

1 Scope

This part of ISO 16122, when used together with ISO 16122-1:2015, specifies the requirements and test methods for the inspection of fixed and semi-mobile sprayers, when in use.

The requirements relate mainly to the condition of the sprayer with respect to its potential risk for the environment and its performance to achieve good application.

NOTE Requirements for the protection of inspectors during an inspection are given in ISO 16122-1:2015.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5681:2020, *Equipment for crop protection — Vocabulary*

ISO 5682-2:2017, *Equipment for crop protection — Spraying equipment — Part 2: Test methods to assess the horizontal transverse distribution for hydraulic sprayers*

ISO 12809:2020, *Crop protection equipment — Reciprocating positive displacement pumps and centrifugal pumps — Test method*

ISO 16122-1:2015¹⁾, *Agricultural and forestry machinery — Inspection of sprayers in use — Part 1: General*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5681:2020 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 Requirements and method of verification

4.1 General

Before starting the inspection, the Pre-inspection requirements of ISO 16122-1:2015, clause 5, shall be met.

1) A new edition of ISO 16122-1 will be published simultaneously with this 2nd edition of ISO 16122-4.

ISO/DIS 16122-4:2022(E)

4.2 Leaks and dripping

4.2.1 Static leaks

The sprayer shall be filled with water to its nominal capacity.

With the pump not running and the sprayer parked on a level horizontal surface (in case of semi-mobile sprayer), a visual inspection for any leakage from the tank, pump and associated pipes shall be carried out: and there shall be no visible leakage from any part of the sprayer.

For tanks with a volume > 2 000 l, water filling may be reduced to half the nominal volume or to 2 000 l, whichever is the greater. For these cases, an additional visual inspection of the tank shall be carried out in order to identify any cracks, holes or other damage that can cause leakage.

Compliance shall be checked by inspection.

4.2.2 Dynamic leaks

4.2.2.1 Leak test when not spraying

With the sprayer running at a pressure which is equal to the maximum working pressure specified by the sprayer manufacturer, or if this is not known, max. 10 bar, with the section valves closed, there shall be no visible leakage from any part of the sprayer.

Compliance shall be checked by inspection.

4.2.2.2 Leak test while spraying

While spraying at a pressure that is equal to the maximum working pressure recommended by the sprayer manufacturer, or the nozzle manufacturer for the nozzles mounted on the sprayer if lower, there shall be no leakage from any part of the sprayer or spray boom.

Compliance shall be checked by inspection.

4.2.3 Spraying and dripping on parts

Regardless of the distance between the spray boom to the target to be sprayed, in the range between the nozzles and the target surface, no liquid shall be sprayed directly on to the sprayer itself (e.g. parts of the sprayer, hoses). This does not apply if needed by function (e.g. sensors) and if dripping is minimised.

Compliance shall be checked by inspection and function test.

4.3 Pump(s)

4.3.1 Capacity

4.3.1.1 General

The pump capacity shall be suited to the needs of the sprayer.

4.3.1.2 Sprayers built according to ISO 16119-4:2014

The agitation capacity (liquid backflow in the tank) of the pump shall be at least equal to the value given in the instruction handbook.

Compliance shall be checked by measurement according to 5.2.1.3.