



Designation: D6769/D6769M – 02 (Reapproved 2010)<sup>ε1</sup>

# Standard Guide for Application of Fully Adhered, Cold-Applied, Prefabricated Reinforced Modified Bituminous Membrane Waterproofing Systems<sup>1</sup>

This standard is issued under the fixed designation D6769/D6769M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

<sup>ε1</sup> NOTE—Units information was editorially revised in July 2010.

## 1. Scope

1.1 This guide lists application and installation requirements for fully adhered, cold-applied, prefabricated modified bituminous membrane waterproofing systems for below-grade or below-wearing-surface (such as plaza decks) vertical or horizontal applications.

1.2 For the purposes of this application guide, the substrate is assumed to be structurally sound, sloped to drain (if new construction), and meeting the local building code requirements. Similarly, the system components are assumed to comply with all federal, state, and local requirements in effect at the time of installation.

1.3 The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

1.4 *This guide may involve hazardous materials, operations, and equipment. This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use.*

## 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

**D1079 Terminology Relating to Roofing and Waterproofing**

<sup>1</sup> This guide is under the jurisdiction of ASTM Committee D08 on Roofing and Waterproofing and is the direct responsibility of Subcommittee D08.22 on Waterproofing and Dampproofing Systems.

Current edition approved June 1, 2010. Published July 2010. Originally approved in 2002. Last previous edition approved in 2002 as D6769–02. DOI: 10.1520/D6769\_D6769M-02R10E01.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

**D5295 Guide for Preparation of Concrete Surfaces for Adhered (Bonded) Membrane Waterproofing Systems**

**D5898 Guide for Details for Adhered Sheet Waterproofing**

**D5957 Guide for Flood Testing Horizontal Waterproofing Installations**

## 3. Terminology

3.1 *Definitions:*

3.1.1 *lift, n*—the height or length of sheet that may be comfortably handled by the person applying the sheet to a vertical surface. This is normally the height of this person, or 1.5 to 2.1 m [5 to 7 ft].

3.1.2 *skin over, n*—a condition in which the surface of the material is no longer tacky, but will move under slight finger pressure.

3.1.3 *tack, n*—a condition in which if the surface is touched, there will be a string of material attached to the finger.

3.2 For definitions of other terms relating to waterproofing, see Terminology **D1079**.

## 4. Significance and Use

4.1 This guide outlines general procedures for the storage and application of various prefabricated sheets made using modified bituminous materials and intended for use as below-grade and below-wearing-surface waterproofing.

4.2 The substrate used for applications described in this guide shall be concrete or masonry.

4.3 This application consists of a prefabricated reinforced modified bituminous sheet applied to a suitable substrate using a bituminous-based, cold-applied adhesive or mastic. Application rates given are typical for such installations.

4.4 This guide is intended to supplement instructions from designers and manufacturers.

## 5. Delivery of Materials

5.1 Deliver materials in supplier's original containers and packaging.