
Konektorji za električno in elektronsko opremo - Zahteve za izdelek - 8-109. del:
Močnostni konektorji - Podrobna specifikacija za konektorje 2P 130 A, 1000 V plus
2P 5 A 50 V v pravokotnih ohišjih s stopnjo zaščite IP65/IP68, če so združeni in
blokirani, in IPXXB, če niso združeni

Connectors for electrical and electronic equipment - Product requirements - Part 8-109:
Power connectors - Detail specification for 2P 130 A, 1 000 V plus 2P 5 A 50 V
rectangular housing shielded connectors with IP65/IP68 degree of protection when
mated and locked, and IPXXB when unmated

<https://standards.iteh.ai/catalog/standards/sist/5894ff9a-8a19-455e-b52b-aa89848458b3/osist-pr-en-iec-61076-8-109-2022>

Connecteurs pour équipements électriques et électroniques - Exigences de produit -
Partie 8-109: Connecteurs d'alimentation - Spécification particulière pour les
connecteurs blindés rectangulaires à 2 pôles de 130 A et 1 000 V plus 2 pôles de 5 A et
50 V, avec un degré de protection IP65/IP68 lorsqu'ils sont accouplés et verrouillés et
IPXXB lorsqu'ils sont désaccouplés, logés dans un boîtier

Ta slovenski standard je istoveten z: prEN IEC 61076-8-109:2022

ICS:

31.220.10	Vtiči in vtičnice, konektorji	Plug-and-socket devices. Connectors
-----------	-------------------------------	--

oSIST prEN IEC 61076-8-109:2022 en



48B/2949/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER:

IEC 61076-8-109 ED1

DATE OF CIRCULATION:

2022-05-06

CLOSING DATE FOR VOTING:

2022-07-29

SUPERSEDES DOCUMENTS:

48B/2904/CD, 48B/2929/CC

IEC SC 48B : ELECTRICAL CONNECTORS

SECRETARIAT:

United States of America

SECRETARY:

Mr Jeffrey Toran

OF INTEREST TO THE FOLLOWING COMMITTEES:

PROPOSED HORIZONTAL STANDARD:



Other TC/SCs are requested to indicate their interest, if any, in this CDV to the secretary.

FUNCTIONS CONCERNED:

☐ EMC☐ ENVIRONMENT☐ QUALITY ASSURANCE☐ SAFETY☒ SUBMITTED FOR CENELEC PARALLEL VOTING☐ NOT SUBMITTED FOR CENELEC PARALLEL VOTING**Attention IEC-CENELEC parallel voting**

The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting.

The CENELEC members are invited to vote through the CENELEC online voting system.

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

Connectors for electrical and electronic equipment – Product requirements - Part 8-109: Power connectors – Detail specification for 2P 130 A, 1 000 V plus 2P 5 A 50 V rectangular housing shielded connectors with IP65/IP68 degree of protection when mated and locked, and IPXXB when unmated

PROPOSED STABILITY DATE: 2025

NOTE FROM TC/SC OFFICERS:

Copyright © 2022 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

CONTENTS

1		
2		
3	FOREWORD.....	5
4	1 Scope.....	8
5	2 Normative references	8
6	3 Terms and definitions	10
7	4 Technical information.....	10
8	4.1 Recommended method of termination.....	10
9	4.1.1 General	10
10	4.1.2 Number of contacts and contact cavities.....	10
11	4.2 Ratings and characteristics	11
12	4.3 Systems of levels	11
13	4.3.1 Performance levels	11
14	4.3.2 Compatibility levels	11
15	4.4 Classification into climatic categories	11
16	4.5 Clearance and creepage distance.....	11
17	4.6 Current-carrying capacity	11
18	4.7 Marking.....	11
19	5 Dimensional information	12
20	5.1 General.....	12
21	5.2 Isometric view and common features	12
22	5.2.1 Isometric view of free connectors	12
23	5.2.2 Isometric view of fixed connectors	12
24	5.3 Engagement (mating) information	12
25	5.3.1 Engagement (mating) direction	12
26	5.3.2 Perpendicular to the engaging (mating) direction	12
27	5.3.3 Inclination	12
28	5.4 Free connectors	16
29	5.4.1 Dimensions.....	16
30	5.4.2 Terminations.....	18
31	5.5 Fixed connectors.....	13
32	5.5.1 Dimensions.....	13
33	5.5.2 Terminations.....	15
34	5.6 Accessories	16
35	5.7 Mounting information.....	18
36	5.8 Gauges.....	18
37	5.8.1 Sizing gauges and retention force gauges	18
38	6 Technical characteristics	19
39	6.1 Classification into climatic categories	19
40	6.2 Electrical characteristics.....	19
41	6.2.1 Clearance and creepage distance.....	19
42	6.2.2 Voltage proof	19
43	6.2.3 Contact resistance	19
44	6.2.4 Housing (shell) electrical continuity and shielding effectiveness	19
45	6.2.5 Insulation resistance	20
46	6.2.6 Current-carrying capacity	Error! Bookmark not defined.
47	6.2.7 Electrical load and temperature	20

48	6.3	Mechanical characteristics	21
49	6.3.1	Mechanical operation	21
50	6.3.2	Effectiveness of connector coupling devices	21
51	6.3.3	Gauge retention force (resilient contact)	21
52	6.3.4	Engaging and separating forces	21
53	6.3.5	Contact retention in insert	21
54	6.3.6	Polarizing and keying method	21
55	6.4	Dynamic stress test	22
56	6.4.1	Vibration (sine)	22
57	6.4.2	Shock	22
58	6.4.3	Free fall (repeated)	22
59	6.4.4	IP degree of protection	22
60	6.4.5	Glow-wire flammability test method for end-products (GWEPT)	22
61	6.5	Climatic test	23
62	6.5.1	Damp heat, steady state	23
63	6.5.2	Rapid change of temperature	23
64	6.5.3	Corrosion, salt mist	23
65	6.5.4	Dry heat	23
66	6.5.5	Cold	23
67	6.5.6	Low air pressure	23
68	6.6	Environmental aspects	23
69	6.6.1	Marking of insulation material (plastic)	23
70	6.6.2	Design/use of material	23
71	7	Test schedule	24
72	7.1	General	24
73	7.2	Test schedules	24
74	7.2.1	Basic (minimum) test schedule	24
75	7.2.2	Full test schedule	24
76	7.3	Test procedures and measurement methods	33
77	7.4	Pre-conditioning	33
78	7.5	Wiring and mounting of test specimens	33
79	7.5.1	Wiring	33
80	7.5.2	Mounting	33
81			
82		Figure 1 – Free connectors	12
83		Figure 2 – Fixed connectors	12
84		Figure 3 – Free connector	13
85		Figure 4 – Free connector codings	14
86		Figure 5 – Fixed connector	16
87		Figure 6 – Fixed connector codings	17
88		Figure 7 – Gauge for signal contacts	18
89		Figure 8 – Gauge for power contacts	19
90		Figure 9 – Current-temperature derating (50 mm ² wire size)	19
91			
92		Table 1 – Climatic category	11
93		Table 2 – Free connector dimensions	13
94		Table 3.1 – Free connector codings dimensions (codings 1 and 2)	15
95		Table 3.2 – Free connector codings dimensions (codings 3 and 4)	15

96	Table 4 – Fixed connector dimensions.....	16
97	Table 5.1 – Fixed connector codings dimensions (codings 1 and 2).....	18
98	Table 5.2 – Fixed connector codings dimensions (codings 3 and 4).....	18
99	Table 6 – Gauge dimensions.....	19
100	Table 7 – Voltage proof.....	19
101	Table 8 – Vibration	22
102	Table 9 – Number of test specimens	24
103	Table 10 – Test group P.....	24
104	Table 11 – Test group AP	25
105	Table 12 – Test group BP	27
106	Table 13 – Test group CP	28
107	Table 14 – Test group DP	28
108	Table 15 – Test group EP	29
109	Table 16 – Test group GP	31
110	Table 17 – Test group HP	31
111	Table 18 – Test group JP	31
112	Table 19 – Test group KP	32
113		

iTeh STANDARD PREVIEW
(standards.iteh.ai)

oSIST prEN IEC 61076-8-109:2022

<https://standards.iteh.ai/catalog/standards/sist/5894ff9a-8a19-455e-b52b-aa898d8458b3/osist-pren-iec-61076-8-109-2022>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**CONNECTORS FOR ELECTRICAL AND ELECTRONIC EQUIPMENT –
PRODUCT REQUIREMENTS**

**Part 8-107: Power connectors – Detail specification for 2P 130 A, 1 000 V plus
2P 5 A 50 V rectangular housing shielded connectors with IP65/IP68 degree of
protection when mated and locked, and IPXXB when unmated**

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
 - 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
 - 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
 - 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
 - 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
 - 6) All users should ensure that they have the latest edition of this publication.
 - 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
 - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
 - 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.
- International Standard IEC 61076-8-109 has been prepared by subcommittee 48B: Electrical connectors, of IEC technical committee 48: Electrical connectors and mechanical structures for electrical and electronic equipment.

The text of this International Standard is based on the following documents:

Draft	Report on voting
XX/XX/FDIS	XX/XX/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is **English**.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be



- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

ITEH STANDARD PREVIEW
(standards.iteh.ai)

[osIST prEN IEC 61076-8-109:2022](https://standards.iteh.ai/catalog/standards/sist/5894ff9a-8a19-455e-b52b-aa898d8458b3/osist-pren-iec-61076-8-109-2022)

<https://standards.iteh.ai/catalog/standards/sist/5894ff9a-8a19-455e-b52b-aa898d8458b3/osist-pren-iec-61076-8-109-2022>

182

The International Electrotechnical Commission IEC SC 48B — Electrical connectors		IEC 61076-8-109
Detail specification in accordance with IEC 61076-8		
Free connector	 Free connector	For rated current of 130 A DC; 2P power plus 2P signal; Female contacts for power; First break last make male contacts for signal; Straight insertion and withdrawal; 360° shielding; Four codings.
Fixed connector	 Fixed connector	For rated current of 130 A DC; 2P power plus 2P signal; Male contacts for power; Female contacts for signal; Straight insertion and withdrawal; 360° shielding; Four codings.

183

iTeh STANDARD PREVIEW
(standards.iteh.ai)

oSIST prEN IEC 61076-8-109:2022

<https://standards.iteh.ai/catalog/standards/sist/5894ff9a-8a19-455e-b52b-aa898d8458b3/osist-pren-iec-61076-8-109-2022>

CONNECTORS FOR ELECTRICAL AND ELECTRONIC EQUIPMENT– PRODUCT REQUIREMENTS –

Part 8-109: Power connectors –Detail specification for 2P power plus 2P signal plastic housing rectangular shielded connectors with 130A rated current and IP65/IP68/IPXXB degree of protection

1 Scope

This part of IEC 61076-8 describes free and fixed rectangular connectors with:

- 2P power plus 2P signal contacts;
- plastic housing with locking lever and four possible codings;
- 130 A rated current, 1 000 V DC rated voltage on the power section;
- 5 A rated current, 50 V DC rated voltage on the signal section;
- individual shielding around each power contact with relevant shielding termination;
- IP65/IP68 degree of protection when mated and locked and IPXXB on both plug and receptacle parts when unmated.

hereinafter referred to as a connector, for use in electrical and electronic equipment, including overall dimensions, interface dimensions, technical characteristics, performance requirements and test methods.

Connectors according to this document are intended for use in class II equipment. Hence, they are not equipped with PE contact.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-581:2008, *International Electrotechnical Vocabulary – Part 581: Electromechanical components for electronic equipment*

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC 60228:2004, *Conductors of insulated cables*

IEC 60352-1, *Solderless connections – Part 1: Wrapped connections – General requirements, test methods and practical guidance*

IEC 60352-2, *Solderless connections – Part 2: Crimped connections – General requirements, test methods and practical guidance*

IEC 60352-3, *Solderless connections – Part 3: Solderless accessible insulation displacement connections – General requirements, test methods and practical guidance*

IEC 60352-4, *Solderless connections – Part 4: Solderless non-accessible insulation displacement connections – General requirements, test methods and practical guidance*

IEC 60352-5, *Solderless connections – Part 5: Press-in connections – General requirements, test methods and practical guidance*

IEC 60352-6, *Solderless connections – Part 6: Insulation piercing connections – General requirements, test methods and practical guidance*

- 226 IEC 60352-7, *Solderless connections – Part 7: Spring clamp connections – General*
 227 *requirements, test methods and practical guidance*
- 228 IEC 60512-1-2, *Connectors for electronic equipment – Test and measurements – Part 1-2:*
 229 *General examination – Test 1b: Examination of dimension and mass*
- 230 IEC 60512-2-1, *Connectors for electronic equipment – Tests and measurements – Part 2-1:*
 231 *Electrical continuity and contact resistance tests – Test 2a: Contact resistance – Millivolt level*
 232 *method*
- 233 IEC 60512-2-6, *Connectors for electronic equipment – Tests and measurements – Part 2-6:*
 234 *Electrical continuity and contact resistance tests – Test 2f: Housing (shell) electrical continuity*
- 235 IEC 60512-3-1, *Connectors for electronic equipment – Tests and measurements – Part 3-1:*
 236 *Insulation tests – Test 3a: Insulation resistance*
- 237 IEC 60512-4-1, *Connectors for electronic equipment – Tests and measurements – Part 4-1:*
 238 *Voltage stress tests – Test 4a: Voltage proof*
- 239 IEC 60512-5-2, *Connectors for electronic equipment – Tests and measurements – Part 5-2:*
 240 *Current-carrying capacity tests – Test 5b: Current-temperature derating*
- 241 IEC 60512-6-3, *Connectors for electronic equipment – Tests and measurements – Part 6-3:*
 242 *Dynamic stress tests – Test 6c: Shock*
- 243 IEC 60512-6-4, *Connectors for electronic equipment – Tests and measurements – Part 6-4:*
 244 *Dynamic stress tests – Test 6d: Vibration (sinusoidal)*
- 245 IEC 60512-7-1, *Connectors for electronic equipment – Tests and measurements – Part 7-1:*
 246 *Impact tests (free connectors) – Test 7a: Free fall (repeated)*
- 247 IEC 60512-9-1, *Connectors for electronic equipment – Tests and measurements – Part 9-1:*
 248 *Endurance tests – Test 9a: Mechanical operation*
- 249 IEC 60512-9-2, *Connectors for electronic equipment – Tests and measurements – Part 9-2:*
 250 *Endurance tests – Test 9b: Electrical load and temperature*
- 251 IEC 60512-11-3, *Connectors for electronic equipment – Tests and measurements – Part 11-3:*
 252 *Climatic tests – Test 11c: Damp heat, steady state*
- 253 IEC 60512-11-4, *Connectors for electronic equipment – Tests and measurements – Part 11-4:*
 254 *Climatic tests – Test 11d: Rapid change of temperature*
- 255 IEC 60512-11-6, *Connectors for electronic equipment – Tests and measurements – Part 11-6:*
 256 *Climatic tests – Test 11f: Corrosion, salt mist*
- 257 IEC 60512-11-9, *Connectors for electronic equipment – Tests and measurements – Part 11-9:*
 258 *Climatic tests – Test 11i: Dry heat*
- 259 IEC 60512-11-10, *Connectors for electronic equipment – Tests and measurements – Part 11-*
 260 *10: Climatic tests – Test 11j: Cold*
- 261 IEC 60512-11-11, *Connectors for electronic equipment – Tests and measurements – Part 11-*
 262 *11: Climatic tests – Test 11k: Low air pressure*
- 263 IEC 60512-13-1, *Connectors for electronic equipment – Tests and measurements – Part 13-1:*
 264 *Mechanical operation tests – Test 13a: Engaging and separating forces*
- 265 IEC 60512-13-5, *Connectors for electronic equipment – Tests and measurements – Part 13-5:*
 266 *Mechanical operation tests – Test 13e: Polarizing and keying method*
- 267 IEC 60512-15-1, *Connectors for electronic equipment – Tests and measurements – Part 15-1:*
 268 *Connector tests (mechanical) – Test 15a: Contact retention in insert*

IEC 60512-15-6, *Connectors for electronic equipment – Tests and measurements – Part 15-6: Connector tests (mechanical) – Test 15f: Effectiveness of connector coupling devices*

IEC 60512-16-5, *Connectors for electronic equipment – Tests and measurements – Part 16-5: Mechanical tests on contacts and terminations – Test 16e: Gauge retention force (resilient contacts)*

IEC 60529:1989+AMD1:1999+AMD2:2013, *Degrees of protection provided by enclosures (IP code)*

IEC 60695-2-11:2014, *Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end-products (GWEPT)*

IEC 60999-1, *Connecting devices – Electrical copper conductors – Safety requirements for screw-type and screwless-type clamping units – Part 1: General requirements and particular requirements for clamping units for conductors from 0,2 mm² up to 35 mm² (included)*

IEC 60999-2, *Connecting devices – Electrical copper conductors – Safety requirements for screw-type and screwless-type clamping units – Part 2: Particular requirements for clamping units for conductors above 35 mm² up to 300 mm² (included)*

IEC 61076-1:2006, *Connectors for electronic equipment – Part 1: Generic specification*

IEC 61984, *Connectors – Safety requirements and tests*

IEC Guide 109, *Environmental aspects – Inclusion in electrotechnical product standards*

IEC 62430:2009, *Environmentally conscious design for electrical and electronic products*

ISO 1302:2002, *Geometrical Product Specifications (GPS) – Indication of surface texture in technical product documentation*

ISO 6508-1:2015, *Metallic materials – Rockwell hardness test – Part 1: Test method*

ISO 11469:2000, *Plastics – Generic identification and marking of plastic products*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-581 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

4 Technical information

4.1 Recommended method of termination

4.1.1 General

According to IEC 60352 series, IEC 60999-1 or IEC 60999-2.

4.1.2 Number of contacts and contact cavities

Number of contacts: power contacts: 2, shielding contacts: 2 (surrounding each power contact), signal contacts: 2.

Number of contact cavities (for removable contacts): 4.

Suitable wire: cross-sectional area for power contacts: 50 mm², cross-sectional area for signal contacts: 0,5 mm². The core of each power wire is deemed to be individually shielded, each shielding requiring a dedicated termination.