



# FINAL DRAFT International Standard

## ISO/FDIS 23063.2

### Foundry machinery — Safety requirements for high pressure die casting machines

*Machines de fonderie — Prescriptions de sécurité pour les  
machines à couler sous haute pression*

ISO/TC 306

Secretariat: **SAC**

Voting begins on:  
**2024-08-12**

Voting terminates on:  
**2024-10-07**

iteh Standards  
(<https://standards.iteh.ai>)  
Document Preview

[ISO/FDIS 23063.2](#)

<https://standards.iteh.ai/catalog/standards/iso/bd2cacfc-c273-4aad-aeel-6672246b2b47/iso-fdis-23063-2>

**ISO/CEN PARALLEL PROCESSING**

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

[ISO/FDIS 23063.2](https://standards.iteh.ai/catalog/standards/iso/bd2cacfc-c273-4aad-aeel-6672246b2b47/iso-fdis-23063-2)

<https://standards.iteh.ai/catalog/standards/iso/bd2cacfc-c273-4aad-aeel-6672246b2b47/iso-fdis-23063-2>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>v</b>
<b>Introduction</b> .....	<b>vi</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>3</b>
<b>4 List of significant hazards</b> .....	<b>7</b>
4.1 General.....	7
4.2 Mechanical hazards.....	7
4.3 Electrical and control system hazards.....	7
4.3.1 Electrical hazards.....	7
4.3.2 Control system hazards.....	7
4.4 Thermal hazards.....	8
4.5 Fire hazards.....	8
4.6 Noise hazards.....	8
4.7 Hazards caused by gases, vapours, fumes and dusts.....	8
4.8 Hazards generated by neglecting ergonomic principles in machinery design.....	8
4.9 Hazards during the setting mode.....	9
4.10 Falls from heights.....	9
4.11 Hazards related to cold-chamber die casting machines.....	9
4.11.1 Bursting of biscuits.....	9
4.11.2 Injection drive area.....	9
4.12 Hazards related to hot-chamber die casting machines.....	9
4.12.1 Nozzle.....	9
4.12.2 Initiation of the casting process due to a fault in the control system.....	9
4.13 Hazards due to hydraulics and pneumatics.....	9
<b>5 Safety requirements and/or protective measures</b> .....	<b>10</b>
5.1 General.....	10
5.2 Mechanical.....	10
5.2.1 General.....	10
5.2.2 Guards and protective devices for the die area.....	10
5.2.3 Access to the die closing mechanism area.....	12
5.2.4 Additional requirements for movable guards and access doors.....	12
5.2.5 Die casting units.....	13
5.3 Electric equipment and control systems.....	14
5.3.1 Electric equipment.....	14
5.3.2 Safety related parts of the control system: General.....	14
5.3.3 Emergency stop functions.....	14
5.3.4 Safety related control system of the dangerous movements of the die.....	14
5.3.5 Control of ancillary equipment.....	15
5.4 Measures against thermal hazards.....	16
5.4.1 Spurting of molten metal.....	16
5.4.2 Contact with hot surfaces.....	16
5.5 Hydraulics, pneumatics and combustible fluids.....	16
5.5.1 Hydraulics, pneumatics.....	16
5.5.2 Pressure fluids.....	16
5.5.3 Spray systems for release agents.....	16
5.6 Noise.....	17
5.6.1 Noise reduction as a safety requirement.....	17
5.6.2 Noise emission measurement and declaration on die casting machines.....	17
5.6.3 Noise test code.....	17
5.7 Gases, vapours, fumes and dusts.....	19
5.8 Ergonomic aspects.....	19

## ISO/FDIS 23063.2:2024(en)

5.9	Protective measures when setting-up of die casting machines, inserting and removing appliances, tie bar pulling devices and other ancillary equipment.....	19
5.9.1	Setting-up without protective devices for the die area.....	19
5.9.2	Movement of core pullers and ejectors.....	20
5.9.3	Movement of tie bars.....	20
5.9.4	Movement of the plunger of cold-chamber machines.....	20
5.10	Elevated working places.....	20
5.11	Additional protective measures for cold-chamber die casting machines.....	21
5.11.1	Bursting and removal of biscuit.....	21
5.11.2	Guards and protective devices for the injection area.....	21
5.12	Additional protective measures for hot-chamber die casting machines.....	21
5.12.1	Metal splashing.....	21
5.12.2	Movement of the injection piston.....	21
<b>6</b>	<b>Verification of the safety requirements and/or protective measures.....</b>	<b>22</b>
<b>7</b>	<b>Information for use.....</b>	<b>23</b>
7.1	General.....	23
7.2	Warning devices and safety signs.....	23
7.3	Accompanying documents.....	23
7.3.1	Instruction handbook.....	23
7.4	Marking.....	25
<b>Annex A</b>	<b>(informative) Examples.....</b>	<b>27</b>
<b>Annex B</b>	<b>(normative) Requirements for the European Union and associated countries.....</b>	<b>40</b>
<b>Annex C</b>	<b>(normative) Requirements for China (noise test code).....</b>	<b>41</b>
<b>Annex ZA</b>	<b>(informative) Relationship between this European Standard and the essential requirements of EU Directive 2006/42/EC aimed to be covered.....</b>	<b>42</b>
<b>Bibliography</b>	<b>.....</b>	<b>44</b>

## Document Preview

<https://standards.iteh.ai/>

<https://standards.iteh.ai/catalog/standards/iso/bd2cacfc-c273-4aad-aeel-6672246b2b47/iso-fdis-23063-2>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 306, *Foundry machinery*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 202, *Foundry machinery*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

[ISO/FDIS 23063.2](https://standards.iteh.ai/catalog/standards/iso/bd2cacfc-c273-4aad-aeel-6672246b2b47/iso-fdis-23063-2)

<https://standards.iteh.ai/catalog/standards/iso/bd2cacfc-c273-4aad-aeel-6672246b2b47/iso-fdis-23063-2>

## Introduction

This document is a type C standard as stated in ISO 12100.

This document is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (e.g. regulators, accident prevention organisations, market surveillance).

Others can be affected by the level of machinery safety achieved with the means of the document by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, for example, for maintenance (small, medium and large enterprises);
- consumers (in case of machinery intended for use by consumers).

The above-mentioned stakeholder groups have been given the possibility to participate at the drafting process of this document.

The machinery concerned and the extent to which hazards, hazardous situations or hazardous events are covered are indicated in the Scope of this document.

When requirements of this type-C standard are different from those which are stated in type-A or type-B standards, the requirements of this type-C standard take precedence over the requirements of the other standards for machines that have been designed and built according to the requirements of this type-C standard.

Where, for clarity, an example of a preventive measure is given in this document, this should not be considered as the only possible solution. Any other solution leading to the same risk reduction is permissible if an equivalent level of safety is achieved. [ISO/FDIS 23063.2](https://standards.iso.org/standards/info/4/2/cnc6-c-273-4andnext-6672246b3147/iso-fdis-23063.2)

It is assumed that the machinery according to the scope is operated and maintained by trained personnel.

# Foundry machinery — Safety requirements for high pressure die casting machines

## 1 Scope

This document applies to high pressure die casting machines:

- a) hot-chamber die casting machines (horizontal die closing system);
- b) horizontal cold-chamber die casting machines (horizontal die closing system).

This document applies to high pressure die casting units, i.e. high pressure die casting machines (HPDCM), and their interfaces with the following ancillary equipment:

- a) die;
- b) melting, holding and dosing furnaces (see ISO 13577-1:2016);
- c) metal feeding equipment;
- d) inserting and removal devices;
- e) spraying appliances;
- f) heating and cooling devices for the die.

This ancillary equipment itself is not covered.

Additional risks arising from the material being cast are not covered.

This document does not apply to either low pressure die casting machines or gravity die casting machines, or both.

This document deals with all significant hazards, hazardous situations and events relevant to pressure die casting machines when used as intended and under conditions of misuse which are reasonably foreseeable by the manufacturer (see [Clause 4](#)).

This includes hazards coming from intentional interactions as well as unintentional but foreseeable interactions between movable parts of the machine and persons.

This document provides the requirements to be met by the manufacturer to ensure the safety of persons and property during transport, commissioning, use, de-commissioning and maintenance periods, as well as in the event of foreseeable failures or malfunctions that can occur in the equipment.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3864-1:2011, *Graphical symbols — Safety colours and safety signs — Part 1: Design principles for safety signs and safety markings*

ISO 4413:2010, *Hydraulic fluid power — General rules and safety requirements for systems and their components*

## ISO/FDIS 23063.2:2024(en)

ISO 4414:2010, *Pneumatic fluid power — General rules and safety requirements for systems and their components*

ISO 7000:2019, *Graphical symbols for use on equipment — Registered symbols*

ISO 7731:2003, *Ergonomics — Danger signals for public and work areas — Auditory danger signals*

ISO 7745:2024, *Hydraulic fluid power — Fire-resistant fluids — Requirements and guidelines for use*

ISO 11201:2010, *Acoustics — Noise emitted by machinery and equipment — Determination of emission sound pressure levels at a work station and at other specified positions in an essentially free field over a reflecting plane with negligible environmental corrections*

ISO 11202:2010, *Acoustics — Noise emitted by machinery and equipment — Determination of emission sound pressure levels at a work station and at other specified positions applying approximate environmental corrections*

ISO 11204:2010, *Acoustics — Noise emitted by machinery and equipment — Determination of emission sound pressure levels at a work station and at other specified positions applying accurate environmental corrections*

ISO 11429:1996, *Ergonomics — System of auditory and visual danger and information signals*

ISO/TR 11688-1:1995, *Acoustics — Recommended practice for the design of low-noise machinery and equipment — Part 1: Planning*

ISO 12100:2010, *Safety of machinery — General principles for design — Risk assessment and risk reduction*

ISO 13732-1:2006, *Ergonomics of the thermal environment — Methods for the assessment of human responses to contact with surfaces — Part 1: Hot surfaces*

ISO 13849-1:2023, *Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design*

ISO 13850:2015, *Safety of machinery — Emergency stop function — Principles for design*

ISO 13851:2019, *Safety of machinery — Two-hand control devices — Principles for design and selection*

ISO 13854:2017, *Safety of machinery — Minimum gaps to avoid crushing of parts of the human body*

ISO 13855:2010, *Safety of machinery — Positioning of safeguards with respect to the approach speeds of parts of the human body*

ISO 13856-2:2013, *Safety of machinery — Pressure-sensitive protective devices — Part 2: General principles for design and testing of pressure-sensitive edges and pressure-sensitive bars*

ISO 13857:2019, *Safety of machinery — Safety distances to prevent hazard zones being reached by upper and lower limbs*

ISO 14119:2013, *Safety of machinery — Interlocking devices associated with guards — Principles for design and selection*

ISO 14120:2015, *Safety of machinery — Guards — General requirements for the design and construction of fixed and movable guards*

ISO 14122-1:2016, *Safety of machinery — Permanent means of access to machinery — Part 1: Choice of fixed means and general requirements of access*

ISO 14122-2:2016, *Safety of machinery — Permanent means of access to machinery — Part 2: Working platforms and walkways*

ISO 14122-3:2016, *Safety of machinery — Permanent means of access to machinery — Part 3: Stairs, stepladders and guard-rails*

IEC 60204-1:2016, *Safety of machinery — Electrical equipment of machines — Part 1: General requirements*



IEC 61310-1:2007, *Safety of machinery — Indication, marking and actuation — Part 1: Requirements for visual, acoustic and tactile signals*

IEC 61310-2:2007, *Safety of machinery — Indication, marking and actuation — Part 2: Requirements for marking*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12100 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <https://www.electropedia.org/>

#### 3.1 casting

component or product that has obtained its shape through the process of *die casting* (3.2)

#### 3.2 die casting

process in which molten *metal* (3.7) is injected into a die and held under pressure until complete solidification

#### 3.3 die casting machine

machine with the purpose to inject molten *metal* (3.7) under pressure into a parted die which is connected to the platens of the machine

#### 3.4 die casting cell

*die casting machine* (3.3), together with auxiliary and *ancillary equipment* (3.6), which form a complete production unit

#### 3.5 auxiliary equipment

set of all the devices which carry out additional process functions within a *die casting cell* (3.4)

#### 3.6 ancillary equipment

devices which automatically carry out process functions additional to those of the *die casting machine* (3.3) itself, e.g. feeding the *metal* (3.7), removing the castings, spraying the die

#### 3.7 metal

material, which is suitable for being cast in the *die casting* (3.2) process

#### 3.8 hot-chamber die casting machine

*die casting machine* (3.3) with an inclined or horizontal *die closing system* (3.10) having the *shot sleeve* (3.19) and *plunger* (3.20) which are submerged in the molten *metal* (3.7) of the furnace

Note 1 to entry: See [Figure A.1](#).

#### 3.9 cold-chamber die casting machine

*die casting machine* (3.3) with a horizontal *die closing system* (3.10), where molten *metal* (3.7) is delivered to the *shot sleeve* (3.19) in measured amounts from a separate furnace

Note 1 to entry: There are cold-chamber die casting machines with toggle (see [Figure A.2](#)) and toggle-free (see [Figure A.3](#)) closing systems.

**3.10**

**die closing system**

assembly which opens and closes the die, and holds the die against the force exerted on the molten *metal* (3.7) during injection and solidification

**3.11**

**injection system**

assembly which forces molten *metal* (3.7) from the *shot sleeve* (3.19) into the die cavity and applies pressure to the molten metal during solidification

**3.12**

**ejector**

system of assembled machine components (e.g. ejector plate and ejector rod) connected to the ejector device of the die, which allows the ejection of castings from the die cavity

**3.13**

**core puller**

assembly which controls movements of cores

**3.14**

**tie bar pulling device**

device for pulling *tie bars* (3.17) in order to facilitate die set-up procedure

**3.15**

**die clamping device**

device for clamping the die to the platens of the machine (automatically or manually)

**3.16**

**moving platen**

movable platen

platen to which the moving die-half is connected

**3.17**

**tie bar**

bar which carries the locking load and guide the *moving platen* (3.16)

**3.18**

**injection drive**

system (e.g. hydraulic) which moves the *plunger* (3.20) and applies force to it

**3.19**

**shot sleeve**

cylindrical container of a *cold-chamber die casting machine* (3.9) in which pressure is applied to molten *metal* (3.7)

**3.20**

**plunger**

plunger tip

piston which forces molten *metal* (3.7) from the *shot sleeve* (3.19) into the die and applies pressure to the molten metal during solidification

**3.21**

**gooseneck**

part of an *injection system* (3.11) (containing the *shot sleeve* (3.19) and *metal* (3.7) flow channel) which is submerged in molten metal

Note 1 to entry: Only applies to *hot-chamber die casting machines* (3.8).

**3.22**

**nozzle**

connection between the *gooseneck* (3.21) and the fixed die-half

**3.23**

**biscuit**

slug

*metal* (3.7) surplus which solidifies in the cold-chamber *shot sleeve* (3.19) and is ejected with the casting

**3.24**

**fixed platen**

platen to which the fixed die-half and the *metal* (3.7) *injection system* (3.11) are connected

**3.25**

**die area**

area between the *fixed platen* (3.23) and the *moving platen* (3.16)

**3.26**

**cylinder platen**

platen to which the die closing mechanism and the closing cylinder are connected

Note 1 to entry: Also known as thrust platen, reaction platen, link housing or rear platen.

**3.27**

**die closing mechanism area**

area between the *moving platen* (3.16) and the *cylinder platen* (3.26)

**3.28**

**injection drive area**

area between the *fixed platen* (3.23) and the shot cylinder

**3.29**

**closing safety device**

device actuated by the movable guard which prevents the die from closing if a failure occurs in the control system

**3.30**

**setting mode**

operating mode where any step in the process can be selected and hand operated in any sequence with restricted operation of the safety functions

EXAMPLE To perform individual steps of the process (not necessarily in operating cycle sequence), like changing a die.

**3.31**

**manual mode**

operating mode where the individual steps in the machine cycle are hand initiated

EXAMPLE To perform the individual steps of the process (only in the sequence which is fixed by the program), such as to finish the casting cycle or to run the casting cycle in order to examine or to look for faults.

**3.32**

**semi-automatic mode**

operating mode where each cycle is hand initiated but thereafter automatically proceeds to completion

EXAMPLE To produce castings in which at least one of the steps of the process which is performed outside the machine is executed by the *operator* (3.35).

**3.33**

**automatic mode**

operating mode where the completion of a casting cycle initiates the next casting cycle

EXAMPLE To continuously produce castings with any external process steps being automatically carried out by ancillary device.

**3.34**

**machine-setter**

designated person, trained and skilled to carry out adjusting, die changing, setting and starting-up the *die casting* (3.2) process

**3.35**

**operator**

designated person trained and skilled to run the *die casting machine* (3.3)

**3.36**

**access door**

door of the distance guards of a *die casting cell* (3.4)

**3.37**

**inspection**

measure to observe and assess the current condition as well as fault finding

Note 1 to entry: Measures (e.g. measuring, testing, diagnostics) including the determination of the causes of wear or damage and the derivation of the necessary consequences for the continued use.

Note 2 to entry: This definition does not cover “material inspection”.

**3.38**

**maintenance**

combination of service, *inspection* (3.37), reconditioning and functional test of the equipment

Note 1 to entry: The purpose is to preserve the working condition or returning to this condition so that the required function can be performed (including safety requirements).

Note 2 to entry: Service is a measure to maintain the nominal condition. The nominal condition can be maintained in general without dismantling/disassembling major parts of the equipment (e.g. cleaning, lubrication of the work equipment as well as addition or replacement of agents) or by replacing tools or operational changing parts.

Note 3 to entry: Reconditioning is a measure to return to the nominal condition. Foreseeable measures to replace worn parts or parts having expired the foreseen lifetime (can require dismantling/disassembling). These parts should meet manufacturers' specification.

Note 4 to entry: A functional test is checking the functionality of the exchanged or repaired parts. Adjustment work can be required (e.g. test runs, verifying safety functions).

**3.39**

**dry cycle**

operation mode of the *die casting machine* (3.3), with all movements of the die casting machine, which are typical for a production cycle [e.g. with injection cylinder movements but without molten *metal* (3.7) and with die opening, die closing and interlocking using a die or a *test block* (3.40) mounted in the *die area* (3.25)]

**3.40**

**test block**

object for simulating the presence of a die in the *die area* (3.25) of the machine

**3.41**

**performance level**

**PL**

discrete level used to specify the ability of safety-related parts of control systems to perform a safety function under foreseeable conditions

Note 1 to entry: The symbols “a”, “b”, “c”, “d”, and “e” in this document indicate the performance level of safety-related components with respect to their average probability of dangerous failure. More information on these symbols is given in ISO 13849-1.

[SOURCE: ISO 13849-1:2023, 3.1.5, modified — Note 1 to entry has been replaced.]

## 4 List of significant hazards

### 4.1 General

[Clause 4](#) contains all the significant hazards, hazardous situations and events, as far as they are dealt with in this document, identified by risk assessment as significant for this type of machinery and which require action to eliminate or reduce the risk.

If, because of the special design of either a die casting machine or its ancillary equipment, or both, additional hazards can exist, then an additional risk assessment shall be made.

### 4.2 Mechanical hazards

Mechanical hazards at die casting machines and at their ancillary equipment can occur because of the design and construction of the machine (e.g. risk of stumbling and striking) and because of dangerous movements (e.g. crushing, shearing).

Dangerous movements include movement of the following:

- a) die;
- b) core pullers;
- c) ejectors;
- d) ancillary equipment;
- e) injection system;
- f) power operated guards;
- g) die closing system;
- h) die clamping device;
- i) tie bar pulling devices.

Some principal examples of mechanical hazards and danger zones are shown in [Figure A.4](#).

The bursting of reservoirs, pipelines and flexible hoses containing pressurized fluids can cause hazards, e.g. whipping of hoses.

### 4.3 Electrical and control system hazards

#### 4.3.1 Electrical hazards

Electrical hazards at die casting machines can occur, for example, by:

- electrical contact, direct or indirect;
- external influences on electrical equipment;
- damage of electrical components by thermal radiation or other phenomena (e.g. projection or leaking of molten metal particles).

#### 4.3.2 Control system hazards

Failures which cause unexpected machine movements can occur in either the electric/electronic, hydraulic or pneumatic control system, or both.

#### 4.4 Thermal hazards

Thermal hazards which can occur at die casting machines by:

- a) flashing, splashing or flowing out of molten metal, for example:
  - out of the parting-line of the die (see [Figures A.5](#) and [A.6](#));
  - between shot sleeve and plunger (see [Figures A.5](#));
  - between nozzle and die (see [Figure A.6](#));
- b) bursting of biscuits;
- c) contact with structural components of the machine which are being heated during the process;
- d) contact with ancillary equipment which are used to heat the working substances or dies;
- e) release of hot operating fluids;
- f) heat from furnaces.

#### 4.5 Fire hazards

Fire hazards result from the presence of a combination of molten metal, heating devices, hot surfaces and combustible materials (e.g. flammable greases, flammable hydraulic fluids and pressurized combustible release agents) in case of a line breakage.

#### 4.6 Noise hazards

Noise hazards can be caused by the operation of the high pressure die casting machine and/or the intended die casting process.

Sources of noise at high pressure die casting machines are, for example:

- the casting process;
- the moving parts of the machinery and their power sources;
- the manner in which the machine has been installed.

#### 4.7 Hazards caused by gases, vapours, fumes and dusts

Hazards caused by dangerous gases, vapours, fumes and dust can occur at die casting machines, for example:

- by use of lubricants;
- by use of release agents;
- by fumes, vapours and dust given off when melting and holding molten metal (e.g. lead alloys);
- during cleaning.

Risk of explosion is not present as they are all diffused emissions and generation of explosive gaseous emissions is technological not possible.

#### 4.8 Hazards generated by neglecting ergonomic principles in machinery design

Health can be impaired by neglecting ergonomic principles. Possible causes of injury are:

- a) incorrect lifting of heavy loads due to the design of the machine, for example during:
  - setting up the die casting machine;