
Service activities relating to drinking water supply, wastewater and stormwater systems — Guidelines for the implementation of continuous monitoring systems for drinking water quality and operational parameters in drinking water distribution networks

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sic/5bb8432-418-46da-a23f-8ec046131cc3/iso-prf-ts-24541>

PROOF / ÉPREUVE



iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/5bb05032-a1e8-46da-a23f-8ec046131cc3/iso-prf-ts-24541>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principles	6
5 Considerations for the justification of need for continuous monitoring	7
5.1 General	7
5.2 Cost-benefit	7
5.3 Risks of continuous monitoring	8
5.4 Local contexts	9
6 Choosing parameters to be monitored	9
7 Locating the continuous monitoring stations in the drinking water distribution network	11
7.1 General	11
7.1.1 Network layout	11
7.1.2 Development or implementation of an existing hydraulic or statistical model of the drinking water distribution network (preferred)	12
7.1.3 The pragmatic approach	12
7.2 Locations for monitoring stations	12
7.2.1 General	12
7.2.2 The pragmatic approach	13
7.2.3 The hydraulic model approach	13
7.3 Network alert definition	13
7.4 Decision support tools	14
7.5 Periodic evaluation of the continuous monitoring system	14
8 Installation, maintenance, operation, calibration and data transmission of MDs	14
8.1 Installation considerations	14
8.1.1 General	14
8.1.2 Geographical location	14
8.1.3 Site installation location	14
8.2 Maintenance and operational considerations	15
8.3 Calibration considerations	15
8.4 Communication considerations	16
Annex A (informative) Examples of positives and negatives of continuous monitoring systems	17
Annex B (informative) Examples of commonly deployed drinking water quality parameter measuring devices	19
Annex C (informative) Evaluation of the performance of measuring devices	23
Bibliography	24

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 224, *Service activities relating to drinking water supply, wastewater and stormwater systems*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Cases of drinking water contamination around the world have raised awareness of water utilities' exposure to risk. Contamination can arise from many causes, including societal mishaps, errors in operation, maintenance or management by the water utility, natural disasters, vandalism, sabotage, criminality and terrorist activity. The distributed nature of drinking water systems makes them especially vulnerable to contamination and can permit the rapid dispersion of a contaminant. The velocities and volumes of water in a drinking water distribution network can result in contamination affecting significant numbers of users in a short time (e.g. tens of minutes). Recognition of these risks has raised awareness of the need to consider the use of continuous monitoring systems to rapidly detect potential contamination events.

The occurrence of an event can rarely be predicted. However, the more frequently relevant data can be collected and examined, the greater is the chance of quickly detecting an event's occurrence. This supports consideration of the adoption of continuous monitoring systems to provide the data streams that can be used in event detection.

A contamination event can make a waterworks or a drinking water distribution network unusable for a time and require implementation of contingency plans. Such plans could involve, for example, accessing an alternative source water or providing an alternative water service other than via the drinking water distribution network.

To date, very few water utilities have installed continuous monitoring systems either in part or throughout their drinking water distribution network(s). This situation can result from a rational decision based on risk assessment and, in some cases, a cost-benefit analysis. However, it should be acknowledged that circumstances can change gradually over time or rapidly in the face of events. Water utilities wishing to explore such an option can face uncertainties and gaps in their knowledge on how to proceed. In such circumstances water utilities typically face three main challenges:

- which types of measuring devices (MDs) to install in each continuous monitoring station;
- how many continuous monitoring stations to install per drinking water system;
- where to locate the continuous monitoring stations in the drinking water distribution network in order to achieve the best results.

The installation of continuous monitoring systems could reduce the risk to public health and mitigate the impact on users and other stakeholders during a contamination event. The value of continuous monitoring systems can be determined using appropriate risk assessment and cost-benefit analysis. Such an evaluation should take into account existing controls and establish the additional risk mitigation that might be achieved and likely costs.

Advances in MD technology have recently made the adoption and deployment of continuous monitoring more practicable. MDs are not limited to the measurement of drinking water quality alone. Continuous measurement of operational parameters such as water flow and water pressure can improve the water utility's capability to interpret results from the measurement of drinking water quality.

This document provides water utilities, their contractors, consultants and regulators with guidelines for the installation of continuous monitoring systems in drinking water systems, including guidance on their appropriate selection, maintenance and optimal calibration.

These guidelines can aid a water utility's processes for risk assessment and cost-benefit analysis. Taken together these can help a water utility's top management take informed, risk-based decisions on the worthwhileness of investment in a continuous monitoring system.

The guidance provided in this document is intended to be universally applicable, regardless of the structure and size of a water utility's drinking water system. An event detection process (EDP) that relies upon grab samples and intermittent data inputs could be implemented at lower cost. However, where a water utility's assets, finances, management system and technical capability make it practicable, the ability to provide continuous data streams offers advantages for event detection.

To gain experience, initial deployment could be limited to higher-risk areas within a wider drinking water system.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/5bb05032-a1e8-46da-a23f-8ec046131cc3/iso-prf-ts-24541>

Service activities relating to drinking water supply, wastewater and stormwater systems — Guidelines for the implementation of continuous monitoring systems for drinking water quality and operational parameters in drinking water distribution networks

1 Scope

This document specifies guidelines for the implementation of continuous monitoring systems for drinking water quality and operational parameters in drinking water distribution networks.

It provides guidance for determining the:

- effective number of continuous monitoring stations in the drinking water distribution network;
- location of monitoring stations in the drinking water distribution network;
- types of operational and drinking water quality parameter measuring devices (MDs) that can be installed in a continuous monitoring station;
- quality control, maintenance and calibration requirements of the continuous monitoring system.

This document excludes guidance on the design, structure, number and type of MDs to be installed in a continuous monitoring system.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 24513 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

accuracy

measurement accuracy

accuracy of measurement

closeness of agreement between a measured quantity value and a true quantity value of a measurand

[SOURCE: ISO/IEC Guide 99:2007, 2.13, modified]

3.2

capability

quality of being able to perform a given activity

[SOURCE: ISO 15531-1:2007, 3.63, modified]

3.3
continuous monitoring

continuous near-real-time measurements of one or more sampling characteristics

Note 1 to entry: To determine the status, it is possible that one or more relevant parameters need to be checked, supervised, critically observed or measured compared with one or more pre-defined indicators.

Note 2 to entry: *Measuring device* (3.14) which provides a non-continuous but regular output signal at a given frequency can be used for the purpose of continuous monitoring.

Note 3 to entry: The location where a measuring device is installed shall be defined as a continuous monitoring station.

[SOURCE: ISO 2889:2010, 3.22, modified]

3.4
drinking water

DEPRECATED: potable water
water intended for human consumption

Note 1 to entry: Requirements for drinking water quality specifications are generally laid down by the national relevant authorities. Guidelines are established by the World Health Organization (WHO).

3.5
drinking water distribution network

asset system for distributing *drinking water* (3.4)

Note 1 to entry: Drinking water distribution networks can include pipes, valves, hydrants, washouts, pumping stations, reservoirs, and other metering and ancillary infrastructure and components.

Note 2 to entry: Pumping stations and reservoirs can be sited either in the *waterworks* (3.23) or in the drinking water distribution network.

3.6
drinking water system

asset system providing the functions of abstracting, treating, storing, distributing or supplying of *drinking water* (3.4)

3.7
event

situation when a behaviour deviates from the normal

Note 1 to entry: An event can be one or more occurrences and can have several causes.

Note 2 to entry: An event can consist of something not happening.

Note 3 to entry: An event can sometimes be referred to as an “incident” or “accident”.

Note 4 to entry: An event without consequences can also be referred to as a “near miss”, “incident”, “near hit” or “close call”.

3.8
event detection

recognition of event indicator or information about a new situation, or both

Note 1 to entry: New situations can be sorted into one of the following:

- event indicator or situation, or both, are considered known and non-hazardous;
- event indicator or situation, or both, are considered hazardous, but a procedure to handle them already exists;
- event indicator or situation, or both, are considered unknown, and a procedure for them does not yet exist.

3.9 event detection process

EDP

set of interrelated or interacting activities which transforms inputs [data or information on an actual or suspected *event* (3.7)] into outputs [to support the *water utility's* (3.22) operational activities]

3.10 event indicator

signal to the *water utility* (3.22) or one or more *stakeholders* (3.20) of expectations of service performance

Note 1 to entry: The signal can exist yet remain unobserved for a period.

3.11 maintenance

combination of all technical, administrative and managerial actions during the life cycle of an asset intended to retain it in, or restore it to, a state in which it can perform the required function

3.12 management

coordinated activities to direct and control a *water utility* (3.22)

Note 1 to entry: Management can include establishing policies and objectives, and *processes* (3.17) to achieve these *objectives*.

Note 2 to entry: The word “management” sometimes refers to people, i.e. a person or group of people with authority and responsibility for the conduct and control of a service. When “management” is used in this sense, it should always be used with some form of qualifier to avoid confusion with the concept “management” as a set of activities defined above. For example, “management should ...” is deprecated whereas “crisis management team should ...” is acceptable. Otherwise different words should be adopted to convey the concept when related to people, e.g. managerial or managers.

Note 3 to entry: The term “management” can be qualified by a specific domain it addresses. Examples include public health management, environmental management and *risk* (3.18) management.

3.13 measurement process (3.17) to determine a value

3.14 measuring device

MD

component, or a group of components, used in an in-line or online operating position, which continuously (or at a given frequency) gives an output signal proportional to the value of one or more measurands in waters which it measures

Note 1 to entry: The device can be portable or fixed in position.

Note 2 to entry: The term “in-line measuring device” is often used for a measuring device used in an in-line position. The term “online measuring device” is often used for a measuring device used in an online position.

[SOURCE: EN 17075:2018, 3.1]

3.15 monitoring

determining the status of a system, a *process* (3.17) or an activity

Note 1 to entry: To determine the status, there can be a need to check, supervise or critically observe.

**3.16
operation**

action(s) taken in the course of normal functioning of *drinking water* (3.4) or wastewater systems

EXAMPLE Monitoring and regulation or diversion of drinking water or wastewater.

**3.17
process**

set of interrelated or interacting activities that use inputs to deliver an intended result

Note 1 to entry: Whether the “intended result” of a process is called an output, product or service depends on the context of the reference.

Note 2 to entry: Inputs to a process are generally the outputs of other processes and outputs of a process are generally the inputs to other processes.

Note 3 to entry: Two or more interrelated and interacting processes in series can also be referred to as a process.

Note 4 to entry: Processes in an organization are generally planned and carried out under controlled conditions to add value.

Note 5 to entry: A process where the conformity of the resulting output cannot be readily or economically validated is frequently referred to as a “special process”.

Note 6 to entry: In benchmarking, organizational and technical processes and combinations of both are considered. A process within the meaning of benchmarking comprises a combination of one task with one plant or object (e.g. operate sewer network, treat wastewater, treat *drinking water* (3.4), provide domestic connection, further train staff, purchase material).

Note 7 to entry: In service standards, the term “process” can have a broader meaning than its narrower interpretation in management system standards. For example, it can also include some elements.

**3.18
risk**

combination of the likelihood of a hazardous *event* (3.7) and the severity of consequences, if the hazard occurs in the *drinking water system* (3.6), wastewater system or stormwater system

Note 1 to entry: Risk is often characterized by reference to potential events and consequences or a combination of these.

Note 2 to entry: The English term “likelihood” does not have a direct equivalent in some languages; instead, the equivalent of the term “probability” is often used. However, in English, “probability” is often narrowly interpreted as a mathematical term. Therefore, in risk management terminology, “likelihood” is used with the intent that it should have the same broad interpretation as the term “probability” has in many languages other than English.

Note 3 to entry: Risk can also be defined as the effect of uncertainty on objectives, where uncertainty is the state, even partial, of deficiency of information related to understanding or knowledge of an event, its consequence or likelihood.

**3.19
sensor**

electronic device that senses a physical condition or chemical's presence and delivers an electronic signal proportional to the observed characteristic

[SOURCE: ISO/IEC TR 29181-9: 2017, 3.14, modified]

3.20 stakeholder

interested party

person or organization that can affect, be affected by or perceive itself to be affected by a decision or activity

EXAMPLE *Users (3.21) and building owners, relevant authorities, responsible bodies, operators, employees of the operator, external product suppliers and providers of other services, contractors, communities, customers and environmental associations, financial institutions, scientific and technical organizations, laboratories.*

Note 1 to entry: Stakeholders will typically have an interest in the performance or success of an organization.

Note 2 to entry: For the application of this document, environment is considered as a specific stakeholder.

3.21 user

DEPRECATED: consumer

DEPRECATED: consumer

person, group or organization that benefits from *drinking water (3.4)* delivery and related services, wastewater service activities, stormwater service activities or from reclaimed water delivery and related services

Note 1 to entry: Users are a category of stakeholder.

Note 2 to entry: Users can belong to various economic sectors: domestic users, commerce, industry, tertiary activities or agriculture.

Note 3 to entry: The term “consumer” can also be used, but in most countries the term “user” is more common when referring to public services.

3.22 water utility

whole set of organization, processes, activities, means and resources necessary for abstracting, treating, distributing or supplying *drinking water (3.4)* or for collecting, conveying, treating, disposing or reusing of wastewater or for the control, collection, storage, transport and use of stormwater and for providing the associated services

Note 1 to entry: Some key features of a water utility are:

- its mission, to provide drinking water services or wastewater services or the control, collection, storage, transport and use of stormwater services or a combination thereof;
- its physical area of responsibility and the population within this area;
- its responsible body;
- the general organization with the function of operator being carried out by the responsible body, or by legally distinct operators;
- the type of physical systems used to provide the services, with various degrees of centralization.

Note 2 to entry: Drinking water utility addresses a utility dealing only with drinking water; wastewater utility addresses a utility dealing only with wastewater; stormwater utility addresses a utility dealing only with stormwater.

Note 3 to entry: When it is unnecessary or difficult to make a distinction between responsible body and operator, the term “water utility” covers both.

Note 4 to entry: In common English, “water service” can be used as a synonym for “water utility”, but this document does not recommend using the term in this way.