

FINAL  
DRAFT

INTERNATIONAL  
STANDARD

ISO/FDIS  
9241-971

ISO/TC 159/SC 4

Secretariat: BSI

Voting begins on:  
2020-10-06

Voting terminates on:  
2020-12-01

---

---

## Ergonomics of human-system interaction —

### Part 971: Guidance on physical (tactile/haptic) accessibility

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/c3e2ba7f-33e0-4b67-ba8b-420ed75d12cd/iso-fdis-9241-971>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number  
ISO/FDIS 9241-971:2020(E)

© ISO 2020

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/c3e2baf7-33e0-4b67-ba8b-420ed75d12cd/iso-fdis-9241-971>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword .....	v
Introduction .....	vi
<b>1 Scope .....</b>	<b>1</b>
<b>2 Normative references .....</b>	<b>1</b>
<b>3 Terms and definitions .....</b>	<b>1</b>
<b>4 Conformity .....</b>	<b>3</b>
<b>5 Physical accessibility .....</b>	<b>3</b>
<b>6 General requirements and recommendations .....</b>	<b>4</b>
6.1 Compatibility with other standards .....	4
6.1.1 General .....	4
6.1.2 Hardware accessibility .....	4
6.1.3 Software accessibility .....	4
6.2 Approachability of tactile/haptic interactive systems .....	4
6.2.1 Size and space for approach and use of tactile/haptic interactive systems .....	4
6.2.2 Reachability .....	4
6.2.3 Reachability by remote control .....	5
6.2.4 Stability .....	5
6.3 Presentation of tactile/haptic information .....	5
6.3.1 Presentation of physical information .....	5
6.3.2 Multiple formats for presenting tactile/haptic information .....	5
6.3.3 Encoding of tactile/haptic information .....	5
6.3.4 Contextual interference with tactile/haptic presentations .....	6
6.4 Perceivability of tactile/haptic information .....	6
6.4.1 General .....	6
6.4.2 Discoverability of tactile/haptic components and controls .....	6
6.4.3 Distinction between tactile/haptic components or controls .....	6
6.4.4 Pausing and repeating tactile/haptic information .....	6
6.4.5 Speed of tactile/haptic information .....	7
6.4.6 Location of tactile output .....	7
6.5 Controllability of tactile/haptic interactions .....	7
6.5.1 Controllability .....	7
6.5.2 Support of sequential control .....	7
6.5.3 Physical attributes of tactile/haptic controls .....	7
6.5.4 Activating tactile/haptic controls .....	7
6.5.5 Force for activating physical controls .....	8
6.5.6 Continuous force for activating physical controls .....	8
6.5.7 Physical movements .....	8
6.5.8 Activating controls without hands .....	8
6.5.9 Activating controls with only one hand .....	8
6.5.10 Timing of activating physical controls .....	8
6.5.11 Taking breaks .....	9
6.6 Individualization of tactile/haptic interactions .....	9
6.6.1 Individualization .....	9
6.6.2 Individualizing tactile/haptic parameters .....	9
6.6.3 Identifying the current parameter values .....	9
6.6.4 Default parameter values .....	10
6.6.5 Reverting to original default parameter values .....	10
6.6.6 Saving modifications of parameter values .....	10
6.6.7 Loading saved parameter values .....	10
6.6.8 Changing individualized parameter values .....	10
6.6.9 Optimizing the number of adjustable parameters .....	10
6.7 Error tolerance of tactile/haptic interactions .....	10

6.7.1	Error tolerance .....	10
6.7.2	Avoiding unintentional activation of physical controls .....	11
6.7.3	Providing warnings on potentially dangerous actions .....	11
6.7.4	Ignoring harmless actions .....	11
6.7.5	Undoing unintended or incorrect activations .....	11
6.8	Tactile/haptic safety .....	11
6.8.1	Safety .....	11
6.8.2	Avoiding sensory overstimulation .....	12
6.8.3	Avoiding sensory overloads .....	12
6.8.4	Avoiding fatigue and repetitive stress injuries .....	12
6.8.5	Avoiding positioning and over extension injuries .....	12
6.8.6	Safe interaction with device .....	12
6.8.7	Avoiding damage to the system .....	13
6.9	Tactile/haptic authentication .....	13
6.9.1	Security and authentication .....	13
6.9.2	Accessible authentication .....	13
6.9.3	Alternatives to biometrics .....	13
<b>7</b>	<b>Input specific requirements and recommendations .....</b>	<b>13</b>
7.1	Keyboard specific guidance .....	13
7.1.1	Text as a basis for interoperability .....	13
7.1.2	Provision of keyboard equivalent inputs .....	14
7.1.3	The design of physical keys .....	14
7.1.4	Modifier key functions .....	14
7.1.5	Virtual keyboards .....	14
7.2	Pointing device specific guidance .....	14
7.2.1	Avoiding need for fine motor skills .....	15
7.3	Motion tracking specific guidance .....	15
7.4	Gesture specific guidance .....	15
7.4.1	Considerations for gestures .....	15
7.4.2	Considerations for gesture controls .....	15
7.5	Single-switch specific guidance .....	16
7.5.1	General .....	16
7.5.2	Single switch devices and time-dependent actions .....	16
7.5.3	Simultaneous multi-device input guidance .....	16
<b>8</b>	<b>Output specific guidance .....</b>	<b>16</b>
8.1	Vibration specific guidance .....	16
8.1.1	Combinations of modalities .....	16
8.1.2	Simultaneous multi-device output .....	17
8.1.3	Simultaneous multimodal output .....	17
8.1.4	Error .....	17
8.1.5	Illusion .....	17
8.1.6	Avoiding conflicting information .....	17
8.2	Masking .....	17
8.2.1	Temporal and spatial masking .....	17
8.2.2	Adaptation to saturation stimulation .....	18
8.3	Braille specific guidance .....	18
8.3.1	Considerations for tactile labels .....	18
8.3.2	Use of braille .....	18
8.3.3	Tactile cursor in braille supporting systems .....	18
8.3.4	Editing braille text .....	18
8.3.5	Refreshing braille text .....	19
8.3.6	Exploration of information when using braille .....	19
8.3.7	Evaluation of braille supporting systems .....	19
	<b>Bibliography .....</b>	<b>20</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 159, *Ergonomics*, Subcommittee SC 4, *Ergonomics of human-system interaction*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

A list of all parts in the ISO 9241 series can be found on the ISO website.

## Introduction

The tactile/haptic modality is the most widely used modality for inputs to interactive systems and is used as an important output modality for many contexts of use. Often, haptic devices and applications are designed for the “typical” or “average” user. It is important that interactive systems and their designs follow general ergonomic practice as well as meet the widest range of user needs, characteristics, and capabilities for tactile/haptic interactions.

Examples of the use of tactile/haptic inputs range from the use of keyboards, pointing devices (such as a mouse or track pad) and direct touch (gestures) to the use of non-touch gestures, eye-tracking, single-switch inputs, and whole-body movements. Examples of tactile/haptic outputs include the use of vibration and tactile pattern (e.g. braille) outputs. Tactile/haptic inputs/outputs can be combined (e.g. force feedback systems).

Achieving accessibility involves good ergonomic practice. This document works with other ISO and ISO/IEC standards relating to tactile/haptic interactions (such as ISO 9241-910, ISO 9241-920 and ISO 9241-960) and to accessibility (such as ISO 9241-171 and ISO/IEC 29136) to collect tactile/haptic-related accessibility requirements and recommendations and to provide more specific guidance relating to the accessibility of tactile/haptic interactions. It provides a means of addressing tactile/haptic-related user needs from ISO/IEC 29138-1. As such, it is intended to provide a comprehensive source of guidance on tactile/haptic accessibility.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/c3e2ba7f-33e0-4bb7-ba8b-420ed75d12cd/iso-fdis-9241-971>

# Ergonomics of human-system interaction —

## Part 971: Guidance on physical (tactile/haptic) accessibility

### 1 Scope

This document provides both general and specific ergonomic requirements and recommendations for accessible tactile/haptic interactive systems, including accessible tactile/haptic interactions.

This document provides guidance for increasing the accessibility of interactive systems making use of tactile/haptic input/output modalities such as gestures, vibration, and force feedback. The guidance provided also supports alternative input modalities and the use of different output representations.

This document provides guidance for tactile/haptic interactions that is applicable to a variety of interactive systems, including assistive technologies (AT).

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9241-171, *Ergonomics of human-system interaction — Part 171: Guidance on software accessibility*

ISO/IEC 29136, *Information technology — User interfaces — Accessibility of personal computer hardware*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <http://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

#### 3.1 accessibility

extent to which products, systems, services, environments and facilities can be used by people from a population with the widest range of user needs, characteristics and capabilities to achieve identified goals in identified contexts of use

Note 1 to entry: Context of use includes direct use or use supported by assistive technologies.

[SOURCE: ISO 9241-112:2017, 3.15]

#### 3.2 assistive technology

##### AT

hardware or software added to, or incorporated within, a system that increases accessibility for an individual

EXAMPLE Braille display, screen reader, screen magnification software, eye tracking devices.

[SOURCE: ISO 9241-171:2008, 3.5]

### 3.3

#### **tactile**

appertaining to touch

[SOURCE: ISO 9241-910:2011, 2.5]

### 3.4

#### **haptic**

appertaining to *haptics* (3.5)

Note 1 to entry: While there is no difference between haptic and *tactile* (3.3) in most dictionary definitions, in the area of haptics, researchers and developers use haptic to include all haptic sensations, while tactile is limited to mechanical stimulation of the skin. In ISO 9241, the word haptic covers all touch sensations and tactile is used in a more specific manner. Also, both terms can be used together to assist in searches.

[SOURCE: ISO 9241-910:2011, 2.2]

### 3.5

#### **haptics**

sensory and/or motor activity based in the skin, muscles, joints and tendons

Note 1 to entry: Haptics consists of two parts: touch and kinaesthesia.

[SOURCE: ISO 9241-910:2011, 2.1]

### 3.6

#### **force feedback**

force presented to and detected by a user

Note 1 to entry: Although this does not necessarily involve feedback, the term “force feedback” is commonly used in this context.

[SOURCE: ISO 9241-910:2011, 2.9]

### 3.7

#### **gesture**

movement or posture, of the whole body or parts of the body

[SOURCE: ISO/IEC 30113-1:2015, 3.1]

### 3.8

#### **interactive system**

combination of hardware and/or software and/or services and/or people that users interact with in order to achieve specific goals

Note 1 to entry: This includes, where appropriate, packaging, user documentation, on-line and human help, support, and training.

[SOURCE: ISO 9241-11:2018, 3.1.5]

### 3.9

#### **tactile cursor**

tactile indication of where the user interaction via input device (e.g. keyboard or equivalent) occurs

### 3.10

#### **sensory overload**

user's experience where sensory experiences from the environment are too great for the individual's nervous system to successfully process or make meaning from



**3.11****personal computer**

microcomputer primarily intended for stand-alone use by an individual

[SOURCE: ISO/IEC 29136:2012, 3.5]

**3.12****reach envelope**

<tactile/haptic> three-dimensional space in which a person can reach an interface without discomfort with respect to a specified user position

Note 1 to entry: Different users can use different body parts such as the arm, leg or head to reach for an object while sitting or standing.

Note 2 to entry: Users can augment their reach envelope using different assistive technologies, prosthetics or tools.

**4 Conformity**

If an organization claims conformity with this document, then the decisions about how it addresses the requirements and recommendations in this document or the justifications for any course of action that deviates from any of the recommendations shall be documented.

Documentation of a claim of conformity with this document shall be specific about the basis on which the claim is made and shall provide evidence to support the claim. An organization can claim conformity based on a self-assessment or an assessment carried out by another party.

**5 Physical accessibility**

While most users can use tactile/haptic interactions to some extent, users vary considerably in their tactile/haptic capabilities. Some important tactile/haptic capabilities which can vary across users and across contexts of use include:

- a) reach;
- b) range of motion;
- c) accuracy of motion;
- d) coordination of motion;
- e) speed of interaction;
- f) strength;
- g) stamina/endurance;
- h) sensitivity to physical stimulation;
- i) attention to physical stimulation;
- j) processing of the physical stimuli.

While there can be many causes for limitations in these capabilities, the important goal for developers of tactile/haptic interactions is to create systems that remain accessible despite any such limitations.

## 6 General requirements and recommendations

### 6.1 Compatibility with other standards

#### 6.1.1 General

This document is intended to work with other more general International Standards.

NOTE 1 The main International Standards dealing with the ergonomics of tactile and haptic interactions are ISO 9241-910 and ISO 9241-920.

NOTE 2 International Standards dealing with the accessibility of interactive systems are identified in various sub-clauses below.

#### 6.1.2 Hardware accessibility

ISO/IEC 29136 shall apply for issues relating to personal computer hardware.

#### 6.1.3 Software accessibility

ISO 9241-171 shall apply for issues relating to software accessibility.

### 6.2 Approachability of tactile/haptic interactive systems

#### 6.2.1 Size and space for approach and use of tactile/haptic interactive systems

The environment of use should provide people with the widest range of user needs, characteristics and capabilities with:

- a) adequate room to fit themselves and their assistive products or assistive technologies;
- b) an accessible path and a means to position oneself within reach of installed products;
- c) the ability to adjust the location and position of devices and controls.

NOTE 1 ISO/IEC Guide 71 describes the goal of approachability as “a system is approachable if diverse users can overcome any physical or psychological barriers and physically or remotely access it to accomplish the task”.

NOTE 2 Further approachability-related user accessibility needs applying to tactile/haptic interactions are found in ISO/IEC 29138-1 and other International Standards and in related research literature.

NOTE 3 ISO 9241-500:2018, 4.2.3, states that “an environment of use shall be planned to enable the intended user population to perform a range of tasks comfortably and efficiently”. Further information on the design of environments of use is available in ISO 941-500.

#### 6.2.2 Reachability

When the user is physically interacting with the system (including AT), tactile/haptic inputs and outputs should be located within the reach envelope of the user.

Users with the widest range of needs, characteristics, and capabilities should be considered when determining the expected reach envelope.

NOTE 1 It is important to consider standing as well as sitting positions when determining the user’s reach envelope.

NOTE 2 The use of AT can modify the user’s reach envelope. AT can be used to provide support of all or part of their body when reaching. For example, a user can use a prosthesis to support and stabilize their arm. This affects their reach envelope.