# INTERNATIONAL STANDARD

Third edition 2021-06

# Space data and information transfer systems — Space link extension (SLE) — Return operational control fields service specification

Systèmes de transfert des données et informations spatiales — Extension de liaisons spatiales (SLE) — Service des champs de **iTeh ST** contrôle de retour opérationnel EW

# (standards.iteh.ai)

<u>ISO 26143:2021</u> https://standards.iteh.ai/catalog/standards/sist/e1209335-0f19-4367-97df-754934e426fd/iso-26143-2021



Reference number ISO 26143:2021(E)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 26143:2021</u> https://standards.iteh.ai/catalog/standards/sist/e1209335-0f19-4367-97df-754934e426fd/iso-26143-2021



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted (see <a href="https://www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="http://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the eTechnical Barriers to Trade (TBT) see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by the Consultative Committee for Space Data Systems (CCSDS) (as CCSDS 911.5-B-3, August 2016) and was adopted (without modifications) by Technical Committee ISO/TC 20, *Space vehicles,* Subcommittee SC 13, *Space data and information transfer systems.* 

This third edition cancels and replaces the second edition (ISO 26143:2013), which has been technically revised.

The main changes compared to the previous edition are as follows:

- adds clarifications and corrections;
- adds production status annex.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

## CONTENTS

Section		Page	
1	INT	RODUCTION	1-1
	1.1	PURPOSE OF THIS RECOMMENDED STANDARD	1-1
	1.2	SCOPE	1-1
	1.3	APPLICABILITY	
	1.4	RATIONALE	
	1.5	DOCUMENT STRUCTURE	1-2
	1.6	DEFINITIONS, NOMENCLATURE, AND CONVENTIONS	1-5
	1.7	REFERENCES	1-14
2	DES	CRIPTION OF THE ROCF SERVICE	2-1
	2.1	OVERVIEW	
	2.2	SPACE LINK EXTENSION REFERENCE MODEL	
	2.3	SERVICE MANAGEMENT	
	2.4	ARCHITECTURE MODEL—FUNCTIONAL VIEW	
	2.5	ARCHITECTURE MODEL-CROSS SUPPORT VIEW	
	2.6	FUNCTIONAL DESCRIPTION	
	2.7	OPERATIONAL SCENARIO	
	2.8	SECURITY ASPECTS OF THE SLE ROCF TRANSFER SERVICE	
3	ROO	CF SERVICE OPERATIONS Standards/sist/e1209335-0f19-4367-97df- S4934e426fd/iso-26143-2021	
	3.1	GENERAL CONSIDERATIONS	
	3.2	ROCF-BIND	
	3.3	ROCF-UNBIND	
	3.4	ROCF-START	
	3.5	ROCF-STOP	3-34
	3.6	ROCF-TRANSFER-DATA	3-36
	3.7	ROCF-SYNC-NOTIFY	3-40
	3.8	ROCF-SCHEDULE-STATUS-REPORT	3-44
	3.9	ROCF-STATUS-REPORT	3-48
	3.10	ROCF-GET-PARAMETER	3-51
	3.11	ROCF-PEER-ABORT	3-56
4	ROO	CF PROTOCOL	4-1
	4.1	GENERIC PROTOCOL CHARACTERISTICS	4-1
	4.2	ROCF SERVICE PROVIDER BEHAVIOR	

# **CONTENTS (continued)**

## Section

ANNEX A	DATA TYPE DEFINITIONS (NORMATIVE)	A-1
ANNEX B	PRODUCTION STATUS (NORMATIVE)	B-1
ANNEX C	CONFORMANCE MATRIX (NORMATIVE)	C-1
ANNEX D	INDEX TO DEFINITIONS (INFORMATIVE)	<b>D-1</b>
ANNEX E	ACRONYMS (INFORMATIVE)	E-1
ANNEX F	<b>INFORMATIVE REFERENCES (INFORMATIVE)</b>	F-1

## <u>Figure</u>

1-1	SLE Services Documentation	
2-1	Return Frame Processing SLE-FG	
2-2	ROCF Service Production and Provision	
2-3	Example of the Management and Provision of ROCF Service	
2-4	Simplified ROCF Service Provider State Transition Diagram	
2-5	Communications Realization of ROCF Service	
2-6	Buffers and Delivery Modes.	
B-1	ROCF Production Status Transitions.	B-1
	(standards.iteh.ai)	

## Table

#### ISO 26143:2021

2-1	ROCF Operations dards.iteh ai/catalog/standards/sist/e1209335-0f19-4367-97df	
3-1	Setting of ROCF Service Configuration Parameters	
3-2	ROCF-BIND Parameters	
3-3	ROCF-UNBIND Parameters	
3-4	ROCF-START Parameters	
3-5	ROCF-STOP Parameters	
3-6	ROCF-TRANSFER-DATA Parameters	
3-7	ROCF-SYNC-NOTIFY Parameters	
3-8	ROCF-SCHEDULE-STATUS-REPORT Parameters	
3-9	ROCF-STATUS-REPORT Parameters	
3-10	ROCF-GET-PARAMETER Parameters	
3-11	ROCF Parameters	
3-12	ROCF-PEER-ABORT Parameters	
4-1	Provider Behavior	
4-2	Event Description References	
4-3	Predicate Descriptions	
4-4	Boolean Flags	
4-5	Compound Action Definitions	
B-1	Production Status Changes and Notifications	B-2
B-2	Effect of Production Status on Operations	B-3
C-1	Conformance Matrix for ROCF Service (Operations)	C-1
C-2	Conformance Matrix for ROCF Service (Other Requirements)	C-2

#### CCSDS RECOMMENDED STANDARD FOR SLE ROCF SERVICE

## **1 INTRODUCTION**

## 1.1 PURPOSE OF THIS RECOMMENDED STANDARD

The purpose of this Recommended Standard is to define the Space Link Extension (SLE) Return Operational Control Fields (ROCF) service in conformance with the SLE Reference Model (reference [1]). The ROCF service is an SLE transfer service that delivers to a mission user all operational control fields from one master channel or one virtual channel.

NOTE – Reference [1] defines the Return Master Channel Operational Control Field (Rtn MC-OCF) service and the Return Virtual Channel Operational Control Field (Rtn VC-OCF) service as two distinct services. Subsequent study has indicated that it is preferable to define one service that provides the functionality of both. The ROCF service defined here does just that. It is anticipated that a future issue of reference [1] will take the same approach, deleting the Rtn MC-OCF and Rtn VC-OCF services and replacing them with the Rtn OCF service.

## **1.2 SCOPE**

This Recommended Standard defines, in an abstract manner, the ROCF service in terms of:

- a) the operations necessary to provide the service;
- b) the parameter data associated with each operation;
  - <u>ISO 26143:2021</u>
- c) the behaviors that result from the invocation of each operation;) and
- d) the relationship between, and the valid sequence of, the operations and resulting behaviors.

It does not specify:

- a) individual implementations or products;
- b) the implementation of entities or interfaces within real systems;
- c) the methods or technologies required to acquire telemetry frames from signals received from a spacecraft;
- d) the methods or technologies required to provide a suitable environment for communications; or
- e) the management activities required to schedule, configure, and control the ROCF service.

## **1.3 APPLICABILITY**

## **1.3.1 APPLICABILITY OF THIS RECOMMENDED STANDARD**

This Recommended Standard provides a basis for the development of real systems that implement the ROCF service. Implementation of the ROCF service in a real system additionally requires the availability of a communications service to convey invocations and returns of ROCF service operations between ROCF service users and providers. This Recommended Standard requires that such a communications service must ensure that invocations and returns of operations are transferred:

- a) in sequence;
- b) completely and with integrity;
- c) without duplication;
- d) with flow control that notifies the application layer in the event of congestion; and
- e) with notification to the application layer in the event that communications between the ROCF service user and the ROCF service provider are disrupted, possibly resulting in a loss of data. **TANDARD PREVIEW**

It is the specific intent of this Recommended Standard to define the ROCF service in a manner that is independent of any particular communications services, protocols, or technologies.

<u>ISO 26143:2021</u> https://standards.iteh.ai/catalog/standards/sist/e1209335-0f19-4367-97df-

## 1.3.2 LIMITS OF APPLICABIL 1794e426fd/iso-26143-2021

This Recommended Standard specifies the ROCF service that may be provided by an SLE Complex for inter-Agency cross support. It is neither a specification of, nor a design for, real systems that may be implemented for the control and monitoring of existing or future missions.

## **1.4 RATIONALE**

The goal of this Recommended Standard is to create a standard for interoperability between the tracking stations or ground data handling systems of various Agencies and the consumers of spacecraft telemetry.

## **1.5 DOCUMENT STRUCTURE**

## **1.5.1 ORGANIZATION**

This document is organized as follows:

- a) section 1 presents the purpose, scope, applicability and rationale of this Recommended Standard and lists the definitions, conventions, and references used throughout the Recommended Standard;
- b) section 2 provides an overview of the ROCF service including a functional description, the service management context, and protocol considerations;
- c) section 3 specifies the operations of the ROCF service;
- d) section 4 specifies the dynamic behavior of the ROCF service in terms of the state transitions of the ROCF service provider;
- e) annex A provides a formal specification of ROCF service data types using Abstract Syntax Notation One (ASN.1);
- f) annex B specifies the relationship of the ROCF service provision to the production status;
- g) annex C provides a conformance matrix that defines what capabilities must be provided for an implementation to be considered compliant with this Recommended Standard;
- h) annex D lists all terms used in this Recommended Standard and identifies where they are defined; (standards.iteh.ai)
- i) annex E lists all acronyms used within this document;
- j) annex F provides a list of informative references. https://standards.iteh.ai/catalog/standards/sist/e1209335-0f19-4367-97df-754934e426fd/iso-26143-2021

#### **1.5.2 SLE SERVICES DOCUMENTATION TREE**

This Recommended Standard is based on the cross support model defined in the SLE Reference Model (reference [1]). It expands upon the concept of an SLE transfer service as an interaction between an SLE Mission User Entity (MUE) and an SLE transfer service provider for the purpose of providing the ROCF transfer service.

This Recommended Standard is part of a suite of documents specifying the SLE services. The SLE services constitute one of the three types of Cross Support Services:

- a) Part 1: SLE Services;
- b) Part 2: Ground Domain Services;
- c) Part 3: Ground Communications Services.

The basic organization of the SLE services documentation is shown in figure 1-1. The various documents are described in the following paragraphs.



## Figure 1-1: SLE Services Documentation

- a) Cross Support Concept—Part 1: Space Link Extension Services (reference [F2]): a Report introducing the concepts of cross support and the SLE services; https://standards.iteh.ai/catalog/standards/sist/e1209335-0f19-4367-97df-
- b) Cross Support Reference <u>75</u>Model <u>64</u>Part <u>26</u> <u>143-2</u>Space Link Extension Services (reference [1]): a Recommended Standard that defines the framework and terminology for the specification of SLE services;
- c) *SLE Return Service Specifications*: a set of Recommended Standards that will provide specification of all return link SLE services (this Recommended Standard is one of the specifications in that set);
- d) *SLE Forward Service Specifications*: a set of Recommended Standards that will provide specification of all forward link SLE services;
- *e)* SLE API for Transfer Services Specifications: a set of Recommended Practices that provide specifications of an Application Program Interface; a set of Recommended Standards that provide specifications of an Application Program Interface and a mapping to TCP/IP as underlying communications service for SLE services;
- f) Internet Protocol for Transfer Services: defines a protocol for transfer of SLE Protocol Data Units using TCP/IP as underlying communications service for SLE services;
- g) *SLE Service Management Specifications*: a set of Recommended Standards that establish the basis of SLE service management.

CCSDS 911.5-B-3

#### 1.6 DEFINITIONS, NOMENCLATURE, AND CONVENTIONS

## **1.6.1 DEFINITIONS**

#### 1.6.1.1 Definitions from Open Systems Interconnection (OSI) Basic Reference Model

This Recommended Standard makes use of a number of terms defined in reference [8]. The use of those terms in this Recommended Standard shall be understood in a generic sense, i.e., in the sense that those terms are generally applicable to technologies that provide for the exchange of information between real systems. Those terms are:

- a) abstract syntax;
- b) application entity;
- c) application layer;
- d) application process;
- e) flow control;
- f) Open Systems Interconnection (OSI);
- g) real system; Teh STANDARD PREVIEW
- h) Service Access Point (SAP).

#### <u>ISO 26143:2021</u>

## 1.6.1.2 Definitions from Abstract Syntax Notation One-Of19-4367-97df-

754934e426fd/iso-26143-2021

This Recommended Standard makes use of the following terms defined in reference [9]:

- a) Abstract Syntax Notation One (ASN.1);
- b) object identifier;
- c) (data) type;
- d) (data) value.
- NOTE In annex A of this Recommended Standard, ASN.1 is used for specifying the abstract syntax of ROCF service operation invocations and returns. The use of ASN.1 as a descriptive language is intended to support the specification of the abstract ROCF service; it is not intended to constrain implementations. In particular, there is no requirement for implementations to employ ASN.1 encoding rules. ASN.1 is simply a convenient tool for formally describing the abstract syntax of ROCF service operation invocations and returns.

## 1.6.1.3 Definitions from TM Synchronization and Channel Coding

This Recommended Standard makes use of the following terms defined in reference [2]:

CCSDS 911.5-B-3

Page 1-5

August 2016

- a) Attached Sync Marker;
- b) Reed-Solomon check symbols;
- c) Reed-Solomon code.

## 1.6.1.4 Definitions from TM Space Data Link Protocol

This Recommended Standard makes use of the following term defined in reference [3]:

- a) Frame Error Control Field (FECF);
- b) (Virtual Channel or Master Channel) Operational Control Field (OCF);
- c) TM Transfer Frame.

## 1.6.1.5 Definitions from TC Space Data Link Protocol

This Recommended Standard makes use of the following terms defined in reference [4]:

- a) Communications Link Control Word (CLCW); PREVIEW
- b) Control Word Type. (standards.iteh.ai)

## 1.6.1.6 Definitions from AOS Space Data Link Protocol

https://standards.iteh.ai/catalog/standards/sist/e1209335-0f19-4367-97df-

This Recommended Standard makes use of the following terms defined in reference [6]:

- a) AOS Transfer Frame;
- b) Frame Error Control Field (FECF);
- c) (Virtual Channel or Master Channel) Operational Control Field (OCF).

## **1.6.1.7 Definitions from SLE Reference Model**

This Recommended Standard makes use of the following terms defined in reference [1]:

- a) abstract binding;
- b) abstract object;
- c) abstract port;
- d) abstract service;
- e) invoker;
- f) Master Channel Operational Control Field SLE data channel (MCOCF channel)

CCSDS 911.5-B-3

- g) Mission Data Operation System (MDOS);
- h) Mission User Entity (MUE);
- i) offline delivery mode;
- j) online delivery mode;
- k) operation;
- l) performer;
- m) physical channel;
- n) return data;
- o) Return All Frames channel (RAF channel);
- p) Return All Frames service (RAF service);
- q) Return Master Channel Operational Control Field service (MCOCF service);
- r) Return Virtual Channel Operational Control Field service (VCOCF service);
- s) service agreement; STANDARD PREVIEW
- t) service provider (provider);ndards.iteh.ai)
- u) service user (user); <u>ISO 26143:2021</u>
- v) SLE Complex, 75 100 1 10 201 10 2021
- 754934e426fd/iso-26143-2021
- w) SLE Complex Management;
- x) SLE data channel;
- y) SLE Functional Group (SLE-FG);
- z) SLE Protocol Data Unit (SLE-PDU);
- aa) SLE Service Data Unit (SLE-SDU);
- bb) SLE service package;
- cc) SLE transfer service instance;
- dd) SLE transfer service production;
- ee) SLE transfer service provision;
- ff) SLE Utilization Management;
- gg) space link;
- hh) space link data channel;

- ii) Space Link Data Unit (SL-DU);
- jj) space link session;
- kk) Virtual Channel Operational Control Field SLE data channel (VCOCF channel).

## **1.6.1.8** Additional Definitions

## 1.6.1.8.1 Association

An association is a cooperative relationship between an SLE service-providing application entity and an SLE service-using application entity. An association is formed by the exchange of SLE protocol data units through the use of an underlying communications service.

## 1.6.1.8.2 Communications Service

A communications service is a capability that enables an SLE service-providing application entity and an SLE service-using application entity to exchange information.

NOTE – If an SLE service user and an SLE service provider are implemented using different communications services; then interoperability between them is possible only by means of a suitable gateway. Adherence to this Recommended Standard ensures, at least in principle, that it is possible to construct such a gateway.

https://standards.iteh.ai/catalog/standards/sist/e1209335-0f19-4367-97df-754934e426fd/iso-26143-2021

## 1.6.1.8.3 Confirmed Operation

A confirmed operation is an operation that requires the performer to return a report of its outcome to the invoker.

## **1.6.1.8.4** Delivery Criteria

Delivery criteria are rules that determine whether a data unit acquired from the space link by an SLE service provider shall be delivered to a user.

- NOTE For ROCF service, the delivery criteria are:
  - a) the Earth Receive Time (ERT) of the frame from which the OCF is extracted is within the period defined by the start and stop times specified in the ROCF-START operation;
  - b) the spacecraft identifier (SCID) of the frame matches the SCID of the global VCID specified in the ROCF-START operation;
  - c) the virtual channel identifier (VCID) of the frame matches the VCID of the global VCID specified in the ROCF-START operation;

CCSDS 911.5-B-3

- d) the type of the control word contained in the extracted OCF matches the type specified in the ROCF-START operation;
- e) for CLCW reports, i.e., for OCFs containing a control word of type '0' (reference [4]), the telecommand virtual channel that the report refers to matches the telecommand virtual channel specified in the ROCF-START operation.

## **1.6.1.8.5** Frame Error Control Field

The Frame Error Control Field (FECF) of a frame is the FECF of a TM Transfer Frame (reference [3]) or the FECF of an AOS Transfer Frame (reference [6]), as applicable.

## 1.6.1.8.6 Initiator

The initiator is the object that issues the request to bind to another object (the responder).

NOTE – In other words, the initiator is always the invoker of the request to bind to another object. Therefore, in the context of the request to bind, the terms 'initiator' and 'invoker' refer to the same object and are synonyms.

# (standards.iteh.ai)

## 1.6.1.8.7 Invocation

## ISO 26143:2021

The invocation to carry out the operation is the making of a request by an object (the invoker) to another object (the performer) to carry out the operation 1

## 1.6.1.8.8 Master Channel

The sequence of all telemetry frames with the same Transfer Frame Version Number (TFVN) and the same SCID on the same physical channel constitutes a master channel.

NOTE – Depending on the TFVN, the definition of SCID is as given in either reference [3] or reference [6].

## 1.6.1.8.9 Operational Control Field

The Operational Control Field (OCF) of a telemetry frame is the frame OCF of either a TM Transfer Frame (reference [3]) or an AOS Transfer Frame (reference [6]).

## 1.6.1.8.10 Parameter

A parameter of an operation is data that may accompany the operation's invocation or return.

NOTE – The term parameter is also used to refer to mission-dependent configuration information used in the production or provision of the service.

## 1.6.1.8.11 Performance

The performance of an operation is the carrying out of the operation by an object (the performer).

## 1.6.1.8.12 Port Identifier

A port identifier identifies a source or a destination in a communications system.

NOTE – See 2.6.4.5 for more information.

# 1.6.1.8.13 Responder Teh STANDARD PREVIEW

The responder is the object that receives a request to bind and completes the binding (if possible) with the initiator in order for a service association to exist between the two objects.

NOTE – In other words, the responder is always the performer of the binding. Therefore, in the context of binding5 the terms / responder and 'performer' refer to the same object and are synonyms.

## 1.6.1.8.14 Return

The return of an operation is a report, from the performer to the invoker, of the outcome of the performance of the operation.

## 1.6.1.8.15 Service Instance Provision Period

A service instance provision period is the time during which a service instance (i.e., the capability to transfer one or more SLE data channels of a given type) is scheduled to be provided.

NOTE - Reaching of the beginning of this period constitutes the event 'start of service instance provision period' (see 4.2.2).