



SLOVENSKI STANDARD

SIST EN IEC 61139-3:2024

01-april-2024

Industrijska omrežja - Enožični digitalni komunikacijski vmesnik - 3. del: Brezžične razširitve (IEC 61139-3:2023)

Industrial networks - Single-drop digital communication interface - Part 3: Wireless extensions (IEC 61139-3:2023)

Industrielle Netzwerke - Digitale Single-Drop-Kommunikationsschnittstelle - Teil 3: Drahtlose Erweiterungen (IEC 61139-3:2023)

Réseaux industriels - Interface de communication numérique point à point - Partie 3: Extensions sans fil (IEC 61139-3:2023)

Ta slovenski standard je istoveten z: EN IEC 61139-3:2023

[SIST EN IEC 61139-3:2024](#)

<https://standardi.sist.si/catalog/standards/list/1112-06-5c2-4286-8-f6-a2-08222726/list/en-ic-61139-3-2024>

ICS:

| | | |
|-----------|--|--|
| 25.040.40 | Merjenje in krmiljenje industrijskih postopkov | Industrial process measurement and control |
| 35.110 | Omreževanje | Networking |
| 35.200 | Vmesniška in povezovalna oprema | Interface and interconnection equipment |

SIST EN IEC 61139-3:2024

en,fr,de

**EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM**

EN IEC 61139-3

December 2023

ICS 35.200

English Version

**Industrial networks - Single-drop digital communication interface
- Part 3: Wireless extensions
(IEC 61139-3:2023)**

Réseaux industriels - Interface de communication numérique point à point - Partie 3: Extensions sans fil
(IEC 61139-3:2023)

Industrielle Netzwerke - Digitale Single-Drop-Kommunikationsschnittstelle - Teil 3: Drahtlose Erweiterungen
(IEC 61139-3:2023)

This European Standard was approved by CENELEC on 2023-12-06. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

[SIST EN IEC 61139-3:2024](#)

<https://standards.iteh.ai/catalog/standards/sist/1dcb2a96-5e63-4286-8af6-ec2a98232726/sist-en-iec-61139-3-2024>



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN IEC 61139-3:2023 (E)**European foreword**

The text of document 65C/1268/FDIS, future edition 1 of IEC 61139-3, prepared by SC 65C "Industrial networks" of IEC/TC 65 "Industrial-process measurement, control and automation" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61139-3:2023.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2024-09-06
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2026-12-06

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 61139-3:2023 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standard indicated:

IEC 61139 (series) NOTE Approved as EN IEC 61139 (series)

IEC 61375-1 NOTE Approved as EN 61375-1

IEC/TR 62453-61 NOTE Approved as CLC/TR 62453-61

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cencenelec.eu.

| <u>Publication</u> | <u>Year</u> | <u>Title</u> | <u>EN/HD</u> | <u>Year</u> |
|--------------------|-------------|---|----------------|-------------|
| IEC 61131-1 | - | Programmable controllers - Part 1: General information | EN 61131-1 | - |
| IEC 61131-2 | - | Industrial-process measurement and control - Programmable controllers - Part 2: Equipment requirements and tests | - | - |
| IEC 61131-9 | 2022 | Programmable controllers - Part 9: Single-drop digital communication interface for small sensors and actuators (SDCI) | EN IEC 61131-9 | 2022 |
| IEC 61158-1 | - | Industrial communication networks - Fieldbus specifications - Part 1: Overview and guidance for the IEC 61158 and IEC 61784 series | EN IEC 61158-1 | - |
| IEC 62657-2 | - | Industrial communication networks - Wireless communication networks - Part 2: Coexistence management | EN 62657-2 | - |
| ETSI EG 203 367 | - | Short Range Devices (SRD) ETSI EG 203 - 367 "Guide to the application of harmonized standards covering articles 3.1b and 3.2 of the Directive 2014/53/EU (RED) to multi-ratio and combined ratio and non-radio equipment" | - | - |
| ETSI EN 300 328 | - | Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using wide band modulation techniques; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU" | - | - |
| ETSI EN 300 440 | - | Short Range Devices (SRD); Radio equipment to be used in the 1 GHz to 40 GHz frequency range; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU | - | - |

EN IEC 61139-3:2023 (E)

FCC §15.247 - Radio frequency devices; Operation within -
the bands 902-928 MHz, 2400-2483.5
MHz, and 5725-5850 MHz

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[SIST EN IEC 61139-3:2024](#)

<https://standards.iteh.ai/catalog/standards/sist/1dcba96-5e63-4286-8af6-ec2a98232726/sist-en-iec-61139-3-2024>



INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Industrial networks – Single-drop digital communication interface –
Part 3: Wireless extensions**

**Réseaux industriels – Interface de communication numérique point à point –
Partie 3: Extensions sans fil**

Document Preview

[SIST EN IEC 61139-3:2024](#)

<https://standards.iteh.ai/catalog/standards/sist/1dcb2a96-5e63-4286-8af6-ec2a98232726/sist-en-iec-61139-3-2024>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 35.200

ISBN 978-2-8322-7751-5

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

| | |
|--|----|
| FOREWORD | 20 |
| INTRODUCTION | 22 |
| 1 Scope | 23 |
| 2 Normative references | 23 |
| 3 Terms and definitions, abbreviated terms and conventions | 24 |
| 3.1 Terms and definitions | 24 |
| 3.2 Abbreviated terms | 30 |
| 3.3 Conventions | 32 |
| 3.3.1 General | 32 |
| 3.3.2 Service primitives | 32 |
| 3.3.3 Service parameters | 33 |
| 3.3.4 Service procedures | 33 |
| 3.3.5 Service attributes | 34 |
| 3.3.6 Figures | 34 |
| 3.3.7 Transmission octet order | 35 |
| 3.3.8 Behavioral descriptions | 35 |
| 3.3.9 Triple table format | 36 |
| 4 Overview of wireless digital communication interface | 36 |
| 4.1 Purpose and topology | 36 |
| 4.2 Positioning in the automation hierarchy | 36 |
| 4.2.1 General | 36 |
| 4.2.2 Relationship to IEC 61131-9 | 37 |
| 4.2.3 Role of a W-Master | 38 |
| 4.2.4 Role of a W-Device | 39 |
| 4.2.5 Role of a W-Bridge | 39 |
| 4.2.6 System configuration tool | 39 |
| 4.2.7 Mapping to fieldbuses | 39 |
| 4.3 Cell concept | 39 |
| 4.4 Wireless Mechanisms | 41 |
| 4.4.1 General | 41 |
| 4.4.2 Scan (W-Device Discovery) | 41 |
| 4.4.3 Pairing | 41 |
| 4.4.4 Unpairing | 42 |
| 4.4.5 Roaming | 42 |
| 4.4.6 Automatic Pairing | 43 |
| 4.4.7 Transmission Error Handling | 44 |
| 4.4.8 "I am alive" supervision (IMA) | 44 |
| 4.4.9 Wireless Quality supervision | 44 |
| 4.5 Concept of air interface | 44 |
| 4.5.1 General | 44 |
| 4.5.2 Frequency division multiple access (FDMA) | 45 |
| 4.5.3 Time Division Multiple Access (TDMA) | 45 |
| 4.5.4 SSlots, DSlots, transmission capacity | 47 |
| 4.5.5 Assignment of W-Devices to W-Tracks and slots | 47 |
| 4.5.6 Assignment of W-Ports to W-Devices | 48 |
| 4.5.7 W-Cycle | 48 |

| | | |
|--------|--|-----|
| 4.5.8 | W-Frame | 49 |
| 4.6 | Characteristics of the SDCI-W technology..... | 49 |
| 4.7 | Layer model..... | 50 |
| 4.8 | Conformity assessment..... | 50 |
| 5 | Physical Layer (PL) | 51 |
| 5.1 | General..... | 51 |
| 5.2 | Base technology, Physical Layer (PL) | 51 |
| 5.2.1 | General | 51 |
| 5.2.2 | Transmission rate | 51 |
| 5.2.3 | Carrier frequency accuracy | 51 |
| 5.2.4 | W-Device Carrier frequency calibration..... | 51 |
| 5.2.5 | W-Master Carrier frequency calibration..... | 51 |
| 5.2.6 | Modulation..... | 51 |
| 5.2.7 | Transmission power..... | 52 |
| 5.2.8 | Antenna..... | 52 |
| 5.2.9 | SDCI wireless receiver sensitivity | 52 |
| 5.2.10 | Transceiver timings | 52 |
| 5.3 | Downlink and uplink | 55 |
| 5.3.1 | Transmission octet order for WORD based data types | 55 |
| 5.3.2 | Downlink and uplink transmission | 56 |
| 5.3.3 | Preamble | 56 |
| 5.3.4 | Syncword..... | 57 |
| 5.3.5 | Downlink and uplink CRC | 58 |
| 5.3.6 | CRC Transmission..... | 58 |
| 5.3.7 | Data Whitening | 59 |
| 5.3.8 | Regular downlink packet..... | 60 |
| 5.3.9 | Configuration downlink packet | 61 |
| 5.3.10 | Uplink Single Slot | 61 |
| 5.3.11 | Uplink Double Slot | 62 |
| 5.4 | W-Sub-cycle | 62 |
| 5.4.1 | General | 62 |
| 5.4.2 | W-Sub-cycle structure | 62 |
| 5.4.3 | Regular W-Frame | 63 |
| 5.4.4 | Configuration W-Frame..... | 64 |
| 5.5 | Medium Access Control (MAC) | 64 |
| 5.5.1 | General | 64 |
| 5.5.2 | Frequency channels | 65 |
| 5.5.3 | Alternative Hopping algorithms | 66 |
| 5.5.4 | Configuration Frequencies | 66 |
| 5.5.5 | Blocklisting | 66 |
| 5.5.6 | Wireless Quality | 66 |
| 5.6 | Physical Layer (PL) services | 68 |
| 5.6.1 | Overview | 68 |
| 5.6.2 | PL Services for W-Master | 68 |
| 5.6.3 | PL Services for W-Device | 82 |
| 5.7 | Physical Layer PL protocol..... | 89 |
| 5.7.1 | Usage of the Configuration Channel | 89 |
| 5.7.2 | PL W-Master state machine..... | 94 |
| 5.7.3 | PL W-Device state machine | 106 |

| | | |
|--------|---|-----|
| 6 | Data Link Layer DL-A | 111 |
| 6.1 | General..... | 111 |
| 6.2 | General W-Master..... | 112 |
| 6.2.1 | General | 112 |
| 6.2.2 | W-Track and W-Device-Mapper (TDMapper)..... | 112 |
| 6.3 | General (W-Device) | 112 |
| 6.4 | DL-A services | 113 |
| 6.4.1 | Overview | 113 |
| 6.4.2 | MCmd (W-Master and W-Device)..... | 113 |
| 6.4.3 | ISDUMsg (W-Master and W-Device) | 114 |
| 6.4.4 | DownLinkAck (W-Master) | 116 |
| 6.4.5 | UpLinkAck (W-Device)..... | 118 |
| 6.4.6 | EventMsg (W-Master and W-Device) | 118 |
| 6.4.7 | PDOOutMsg (W-Master and W-Device)..... | 119 |
| 6.4.8 | PDIInMsg (W-Master and W-Device)..... | 121 |
| 6.5 | Acknowledgments (DownLinkAck and UpLinkAck) | 122 |
| 6.6 | Message handler | 122 |
| 6.6.1 | General | 122 |
| 6.6.2 | State machine of the W-Master Message handler (DL-A)..... | 123 |
| 6.6.3 | Compilation of DLink control octet | 126 |
| 6.6.4 | State machine of the W-Device Message handler (DL-A)..... | 127 |
| 6.6.5 | Compilation of ULink control octet | 131 |
| 7 | Data Link Layer DL-B | 132 |
| 7.1 | DL-B services | 132 |
| 7.1.1 | Overview of services within W-Master and W-Device | 132 |
| 7.1.2 | DL_PDCycle (W-Master and W-Device)..... | 132 |
| 7.1.3 | DL_PDIInputTransport (W-Master)..... | 132 |
| 7.1.4 | DL_Control (W-Master and W-Device) | 133 |
| 7.1.5 | DL_PDOOutputUpdate (W-Master)..... | 133 |
| 7.1.6 | DL_PDOOutputTransport (W-Device) | 134 |
| 7.1.7 | DL_PDIInputUpdate (W-Device) | 135 |
| 7.1.8 | DL_Event (W-Master and W-Device)..... | 135 |
| 7.1.9 | DL_ISDUTransport (W-Master and W-Device) | 136 |
| 7.1.10 | DL_ISDUAabort (W-Master and W-Device) | 137 |
| 7.1.11 | DL_TDConfig (W-Master) | 137 |
| 7.1.12 | DL_Read (W-Master and W-Device) | 138 |
| 7.1.13 | DL_Write (W-Master and W-Device) | 140 |
| 7.1.14 | DL_SetMode (W-Master) | 141 |
| 7.1.15 | DL_Mode (W-Master and W-Device) | 142 |
| 7.1.16 | DL_MaxRetry (W-Device) | 142 |
| 7.1.17 | DL_SetParam (W-Master and W-Device) | 142 |
| 7.2 | DL-mode handler | 143 |
| 7.2.1 | General | 143 |
| 7.2.2 | State machine of the W-Master DL-mode handler | 144 |
| 7.2.3 | State machine of the W-Device DL-mode handler | 146 |
| 7.3 | Process Data handler..... | 147 |
| 7.3.1 | General | 147 |
| 7.3.2 | State machine of the W-Master Process Data Out handler..... | 147 |

| | | |
|--------|---|-----|
| 7.3.3 | State machine of the W-Master Process Data In handler | 151 |
| 7.3.4 | State machine of the W-Device Process Data Out handler..... | 153 |
| 7.3.5 | State machine of the W-Device Process Data In handler | 155 |
| 7.4 | Indexed Service Data Unit (ISDU) handler | 157 |
| 7.4.1 | General | 157 |
| 7.4.2 | State machine of the W-Master ISDU handler | 157 |
| 7.4.3 | State machine of the W-Device ISDU handler | 160 |
| 7.4.4 | General structure and encoding of ISDUs | 162 |
| 7.5 | Command handler..... | 163 |
| 7.5.1 | General | 163 |
| 7.5.2 | State machine of the W-Master command handler | 163 |
| 7.5.3 | State machine of the W-Device command handler | 166 |
| 7.6 | Event handler | 167 |
| 7.6.1 | General | 167 |
| 7.6.2 | State machine of the W-Master Event handler | 167 |
| 7.6.3 | State machine of the W-Device Event handler | 170 |
| 7.7 | Transmission of segmented data and retry handling..... | 171 |
| 7.7.1 | General | 171 |
| 7.7.2 | Transmission of segmented data | 172 |
| 7.7.3 | Retry-Handling | 173 |
| 8 | Application Layer (AL) | 174 |
| 8.1 | General..... | 174 |
| 8.2 | Application Layer services | 174 |
| 8.2.1 | General | 174 |
| 8.2.2 | AL_Read (W-Master and W-Device) | 174 |
| 8.2.3 | AL_Write (W-Master and W-Device) | 176 |
| 8.2.4 | AL_Abort (W-Master and W-Device) | 177 |
| 8.2.5 | AL_NewInput (W-Master)..... | 177 |
| 8.2.6 | AL_GetInput (W-Master) | 178 |
| 8.2.7 | AL_SetInput (W-Device) | 179 |
| 8.2.8 | AL_PDCycle (W-Master and W-Device) | 179 |
| 8.2.9 | AL_GetOutput (W-Device) | 180 |
| 8.2.10 | AL_NewOutput (W-Device) | 180 |
| 8.2.11 | AL_SetOutput (W-Master)..... | 181 |
| 8.2.12 | AL_Event (W-Master and W-Device)..... | 181 |
| 8.2.13 | AL_Control (W-Master and W-Device) | 183 |
| 8.3 | Application layer protocol..... | 183 |
| 8.3.1 | Overview | 183 |
| 8.3.2 | ISDU processing..... | 183 |
| 8.3.3 | Event processing | 189 |
| 8.3.4 | Process Data transfer | 191 |
| 9 | System management | 195 |
| 9.1 | General..... | 195 |
| 9.2 | Modes..... | 195 |
| 9.2.1 | Service Mode | 195 |
| 9.2.2 | Cyclic Mode..... | 196 |
| 9.3 | System management of the W-Master..... | 197 |
| 9.3.1 | Overview | 197 |

| | | |
|---------|---|-----|
| 9.3.2 | System management W-Master services | 198 |
| 9.3.3 | SM W-Master protocol | 211 |
| 9.4 | System management of the W-Device | 223 |
| 9.4.1 | Overview | 223 |
| 9.4.2 | System management W-Device services | 224 |
| 9.4.3 | SM W-Device protocol | 231 |
| 10 | W-Device | 238 |
| 10.1 | Overview | 238 |
| 10.2 | Process Data Exchange (PDE) | 239 |
| 10.3 | IMA handling | 240 |
| 10.4 | Parameter Manager (PM) | 240 |
| 10.4.1 | General | 240 |
| 10.4.2 | Parameter manager state machine | 241 |
| 10.4.3 | Dynamic parameter | 241 |
| 10.4.4 | Single parameter | 241 |
| 10.4.5 | Block parameter | 241 |
| 10.4.6 | Concurrent parameterization access | 241 |
| 10.4.7 | Command handling | 241 |
| 10.5 | Data Storage (DS) | 241 |
| 10.6 | Event Dispatcher (ED) | 241 |
| 10.7 | W-Device features | 242 |
| 10.7.1 | General | 242 |
| 10.7.2 | Scan | 242 |
| 10.7.3 | Pairing by UniqueID | 242 |
| 10.7.4 | Pairing by Button / Re-Pairing | 242 |
| 10.7.5 | Roaming | 242 |
| 10.7.6 | Unpairing | 242 |
| 10.7.7 | W-Device backward compatibility | 243 |
| 10.7.8 | Protocol revision compatibility | 243 |
| 10.7.9 | Device human machine interface (HMI) | 243 |
| 10.7.10 | Parameter access locking | 243 |
| 10.7.11 | Data Storage locking | 243 |
| 10.7.12 | W-Device parameter locking | 243 |
| 10.7.13 | W-Device user interface locking | 243 |
| 10.7.14 | Data Storage concept | 244 |
| 10.7.15 | Block Parameter | 244 |
| 10.8 | W-Device reset options | 244 |
| 10.9 | W-Device design rules and constraints | 244 |
| 10.9.1 | General | 244 |
| 10.9.2 | Process Data | 244 |
| 10.9.3 | MaxRetry error detection | 244 |
| 10.9.4 | Communication loss | 245 |
| 10.9.5 | Direct Parameter Page | 245 |
| 10.9.6 | ISDU communication channel | 245 |
| 10.9.7 | DeviceID rules related to W-Device variants | 245 |
| 10.9.8 | Protocol constants | 245 |
| 10.10 | I/O W-Device description (IODD) | 246 |
| 10.10.1 | General | 246 |
| 10.10.2 | Profile Characteristics | 247 |

| | | |
|---------|--|-----|
| 10.10.3 | CommNetwork Profile Instance for the IODD | 247 |
| 10.11 | W-Device diagnosis | 249 |
| 10.11.1 | Concepts | 249 |
| 10.11.2 | Events | 249 |
| 10.11.3 | W-Device HMI | 250 |
| 10.12 | W-Device connectivity..... | 251 |
| 11 | W-Master..... | 251 |
| 11.1 | Overview..... | 251 |
| 11.2 | Services of the Standardized Master Interface (SMI)..... | 254 |
| 11.2.1 | Overview | 254 |
| 11.2.2 | SMI_WMasterConfiguration | 255 |
| 11.2.3 | SMI_ReadbackWMasterConfiguration..... | 256 |
| 11.2.4 | SMI_WTrackStatus | 258 |
| 11.2.5 | SMI_WScan..... | 260 |
| 11.2.6 | SMI_WPortPairing | 262 |
| 11.2.7 | SMI_WScanStatus..... | 264 |
| 11.2.8 | SMI_WQualityStatus..... | 266 |
| 11.3 | Configuration Manager (CM) | 268 |
| 11.3.1 | General | 268 |
| 11.3.2 | Coordination of Master applications | 268 |
| 11.3.3 | State machines of the Configuration Manager..... | 269 |
| 11.4 | Data Storage (DS) | 275 |
| 11.5 | On-request Data Exchange (ODE) | 276 |
| 11.6 | Diagnosis Unit (DU) | 276 |
| 11.7 | Process Data Exchange (PDE) | 276 |
| 11.7.1 | General | 276 |
| 11.7.2 | Process Data input mapping | 276 |
| 11.7.3 | Process Data output mapping | 276 |
| 11.7.4 | Process Data invalid/valid qualifier status | 276 |
| 11.8 | Port and Device Configuration Tool (PDCT) | 277 |
| 11.8.1 | General | 277 |
| 11.8.2 | Basic layout examples | 277 |
| 11.9 | Gateway application..... | 279 |
| 11.9.1 | General | 279 |
| 11.9.2 | Changing W-Device configuration including Data Storage..... | 279 |
| 11.9.3 | Parameter server and recipe control | 279 |
| 11.9.4 | Interoperability to 5G Systems | 280 |
| 11.10 | Human machine Interface (HMI), Faulty W-Device replacement | 280 |
| 12 | W-Bridge | 280 |
| 12.1 | Overview..... | 280 |
| 12.2 | Process Data Exchange (PDE) | 281 |
| 12.2.1 | General | 281 |
| 12.2.2 | Process Data mapping..... | 281 |
| 12.3 | On-request Data Exchange (ODE) | 281 |
| 12.3.1 | General | 281 |
| 12.3.2 | Wireless Parameters | 281 |
| 12.3.3 | Parameters of connected SDCL Device | 281 |
| 12.4 | Data Storage | 282 |
| 12.5 | Diagnosis Unit (DU) | 282 |

| | | |
|---------------------|---|-----|
| 12.5.1 | General | 282 |
| 12.5.2 | Device Events (Wireless)..... | 282 |
| 12.5.3 | Device Events | 282 |
| 12.5.4 | Port Events..... | 282 |
| 12.6 | Design Rules | 283 |
| 12.6.1 | General | 283 |
| 12.6.2 | Timing constraints | 283 |
| 12.6.3 | Static behaviour..... | 283 |
| 12.6.4 | Dynamic behavior | 285 |
| 12.6.5 | UniqueID | 292 |
| 12.7 | I/O W-Device description (W-IODD) | 292 |
| Annex A (normative) | W-Messages Codings | 294 |
| A.1 | Overview..... | 294 |
| A.2 | Definition of a W-Message | 294 |
| A.3 | Downlink W-Messages: control octets | 294 |
| A.3.1 | DLink control octet..... | 294 |
| A.3.2 | DLink control octets contains MasterCommand..... | 296 |
| A.4 | Uplink W-Messages | 297 |
| A.4.1 | General | 297 |
| A.4.2 | ULink control octet..... | 297 |
| A.5 | Example for combination of several W-Messages within a DLink / PreDLink | 297 |
| A.6 | Example for DLink data transmission within cyclic process data and segmentation | 298 |
| A.7 | Examples for uplink data transmissions | 300 |
| A.7.1 | General | 300 |
| A.7.2 | DSlot W-Device sends 8 octets not segmented Process Data In to W-Master..... | 300 |
| A.7.3 | DSlot W-Device sends 32 octets segmented Process Data In to W-Master..... | 300 |
| A.7.4 | SSlot W-Device responds with 3 octets segmented ISDU Data to W-Master..... | 300 |
| A.7.5 | DSlot W-Device sends 4 octets Process Data In every 5 ms and responds with 25 octets segmented ISDU Data to W-Master..... | 301 |
| A.8 | User data (PD or OD)..... | 302 |
| A.9 | PDVALID PDINVALID | 302 |
| A.10 | General structure and encoding of ISDUs | 302 |
| A.11 | General structure and encoding of Events..... | 303 |
| A.11.1 | EventQualifier..... | 303 |
| A.11.2 | EventCode..... | 304 |
| Annex B (normative) | W-Frame Codings, CRC calculation and errors | 305 |
| B.1 | Description of ConnectionParameter | 305 |
| B.2 | Downlink packet encodings for Normal Operation | 305 |
| B.3 | Downlink packet encodings for Configuration Operation..... | 306 |
| B.3.1 | General | 306 |
| B.3.2 | Scan Request downlink packet | 307 |
| B.3.3 | Pairing Request downlink packet | 308 |
| B.3.4 | Pairing Negotiation downlink packet | 309 |
| B.4 | Uplink packet encodings for Normal Operations | 310 |
| B.4.1 | Regular Single Slot uplink packet | 310 |
| B.4.2 | Regular Double Slot uplink packet | 311 |