

**SLOVENSKI STANDARD**  
**oSIST prEN IEC 61139-3:2022**  
**01-december-2022**

---

**Industrijska omrežja - Enožični digitalni komunikacijski vmesnik - 3. del: Brezžične razširitve**

Industrial networks - Single-drop digital communication interface - Part 3: Wireless extensions

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[oSIST prEN IEC 61139-3:2022](#)

**Ta slovenski standard je istoveten z:** [prEN IEC 61139-3:2022](https://standards.iteh.ai/catalog/standards/iec/61139-3-2022/86-8af6-ec2a98232726/osit-pren-iec-61139-3-2022)

---

**ICS:**

25.040.40	Merjenje in krmiljenje industrijskih postopkov	Industrial process measurement and control
35.110	Omreževanje	Networking
35.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment

**oSIST prEN IEC 61139-3:2022**

**en,fr,de**





65C/1181/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER: <b>IEC 61139-3 ED1</b>	
DATE OF CIRCULATION: <b>2022-09-30</b>	CLOSING DATE FOR VOTING: <b>2022-12-23</b>
SUPERSEDES DOCUMENTS: <b>65C/1140/CD, 65C/1166A/CC</b>	

IEC SC 65C : INDUSTRIAL NETWORKS												
SECRETARIAT: France	SECRETARY: Ms Valérie DEMASSIEUX											
OF INTEREST TO THE FOLLOWING COMMITTEES: SC 22G,TC 57,TC 65,SC 65B,SC 121A	PROPOSED HORIZONTAL STANDARD: <input type="checkbox"/>			Other TC/SCs are requested to indicate their interest, if any, in this CDV to the secretary.								
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT	<input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY											
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING <input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING												
<b>Attention IEC-CENELEC parallel voting</b> The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting. The CENELEC members are invited to vote through the CENELEC online voting system.												

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

**TITLE:**

**Industrial networks – Single-drop digital communication interface – Part 3: Wireless extensions**

PROPOSED STABILITY DATE: 2027

**NOTE FROM TC/SC OFFICERS:**

NC comments will be addressed during the SC65C/WG16 web meeting scheduled on February 10th, 2023. A corresponding meeting notice will be provided in due time by the convenor.

## CONTENTS

3	FOREWORD .....	20
4	INTRODUCTION .....	22
5	1 Scope .....	23
6	2 Normative references .....	23
7	3 Terms and definitions, abbreviated terms and conventions .....	23
8	3.1 Terms and definitions .....	24
9	3.2 Abbreviated terms .....	29
10	3.3 Conventions .....	31
11	3.3.1 General .....	31
12	3.3.2 Service primitives .....	31
13	3.3.3 Service parameters .....	31
14	3.3.4 Service procedures .....	32
15	3.3.5 Service attributes .....	32
16	3.3.6 Figures .....	33
17	3.3.7 Transmission octet order .....	34
18	3.3.8 Behavioral descriptions .....	34
19	3.3.9 Triple table format .....	34
20	4 Overview of wireless digital communication interface .....	34
21	4.1 Purpose and topology .....	34
22	4.2 Positioning in the automation hierarchy .....	35
23	4.2.1 General .....	35
24	4.2.2 Relationship to IEC 61131-9 .....	36
25	4.2.3 Role of a W-Master .....	37
26	4.2.4 Role of a W-Device .....	38
27	4.2.5 Role of a W-Bridge .....	38
28	4.2.6 System configuration tool .....	38
29	4.2.7 Mapping to fieldbuses .....	38
30	4.3 Cell concept .....	38
31	4.4 Wireless Mechanisms .....	39
32	4.4.1 General .....	39
33	4.4.2 Scan (W-Device Discovery) .....	39
34	4.4.3 Pairing .....	40
35	4.4.4 Unpairing .....	40
36	4.4.5 Roaming .....	40
37	4.4.6 Transmission Error Handling .....	41
38	4.4.7 “I am alive” supervision (IMA) .....	42
39	4.4.8 Wireless Quality supervision .....	42
40	4.5 Concept of Air Interface .....	42
41	4.5.1 General .....	42
42	4.5.2 Frequency Division Multiple Access (FDMA) .....	42
43	4.5.3 Time Division Multiple Access (TDMA) .....	43
44	4.5.4 SSlots, DSlots, Transmission capacity .....	44
45	4.5.5 Assignment of W-Devices to W-Tracks and slots .....	44
46	4.5.6 Assignment of W-Ports to W-Devices .....	45
47	4.5.7 W-Cycle .....	45

48	4.5.8	W-Frame .....	46
49	4.6	Characteristics of the SDCI-W technology .....	46
50	4.7	Layer model .....	47
51	4.8	Conformity assessment.....	48
52	5	Physical Layer (PL).....	48
53	5.1	General.....	48
54	5.2	Base technology, Physical Layer (PL) .....	48
55	5.2.1	General.....	48
56	5.2.2	Transmission rate.....	48
57	5.2.3	Carrier frequency accuracy .....	48
58	5.2.4	W-Device Carrier frequency calibration .....	48
59	5.2.5	W-Master Carrier frequency calibration .....	48
60	5.2.6	Modulation .....	49
61	5.2.7	Transmission power.....	49
62	5.2.8	Antenna .....	49
63	5.2.9	SDCI wireless receiver sensitivity.....	49
64	5.2.10	Transceiver timings .....	49
65	5.3	Downlink and Uplink .....	51
66	5.3.1	Transmission octet order for WORD based data types .....	51
67	5.3.2	Downlink and Uplink transmission .....	52
68	5.3.3	Preamble .....	52
69	5.3.4	Syncword .....	52
70	5.3.5	Downlink and Uplink CRC.....	53
71	5.3.6	CRC Transmission.....	54
72	5.3.7	Data Whitening.....	54
73	5.3.8	Regular Downlink packet .....	56
74	5.3.9	Configuration Downlink packet .....	56
75	5.3.10	Uplink Single Slot .....	56
76	5.3.11	Uplink Double Slot.....	57
77	5.4	W-Sub-cycle .....	57
78	5.4.1	General.....	57
79	5.4.2	W-Sub-cycle structure .....	57
80	5.4.3	Regular W-Frame .....	58
81	5.4.4	Configuration W-Frame.....	59
82	5.5	Medium Access Control (MAC).....	59
83	5.5.1	General.....	59
84	5.5.2	Frequency channels .....	59
85	5.5.3	Alternative Hopping algorithms .....	60
86	5.5.4	Configuration Frequencies .....	60
87	5.5.5	Blocklisting.....	61
88	5.5.6	Wireless Quality .....	61
89	5.6	Physical Layer PL services .....	62
90	5.6.1	Overview.....	62
91	5.6.2	PL Services for W-Master .....	62
92	5.6.3	PL Services for W-Device .....	76
93	5.7	Physical Layer PL protocol.....	83
94	5.7.1	Usage of the Configuration Channel.....	83
95	5.7.2	PL W-Master state machine .....	88
96	5.7.3	PL W-Device state machine .....	99

97	6	Data Link Layer DL-A .....	104
98	6.1	General .....	104
99	6.2	General W-Master .....	104
100	6.2.1	General .....	104
101	6.2.2	W-Track and W-Device-Mapper (TDMapper) .....	104
102	6.3	General (W-Device) .....	105
103	6.4	DL-A services .....	105
104	6.4.1	Overview .....	105
105	6.4.2	MCmd (W-Master and W-Device) .....	105
106	6.4.3	ISDUMsg (W-Master and W-Device) .....	107
107	6.4.4	DownLinkAck (W-Master) .....	108
108	6.4.5	UpLinkAck (W-Device) .....	110
109	6.4.6	EventMsg (W-Master and W-Device) .....	110
110	6.4.7	PDOOutMsg (W-Master and W-Device) .....	111
111	6.4.8	PDInMsg (W-Master and W-Device) .....	113
112	6.5	Acknowledgments (DownLinkAck and UpLinkAck) .....	114
113	6.6	Message handler .....	114
114	6.6.1	General .....	114
115	6.6.2	State machine of the W-Master Message handler (DL-A) .....	114
116	6.6.3	Compilation of DLink Control Octet .....	118
117	6.6.4	State machine of the W-Device Message handler (DL-A) .....	118
118	6.6.5	Compilation of ULink Control Octet .....	122
119	7	Data Link Layer DL-B .....	122
120	7.1	DL-B services .....	122
121	7.1.1	Overview of services within W-Master and W-Device .....	122
122	7.1.2	<a href="http://stds.oSiST.com/61139-3-2022/">http://stds.oSiST.com/61139-3-2022/</a> DL_PDCycle (W-Master and W-Device) .....	123
123	7.1.3	DL_PDInputTransport (W-Master) .....	123
124	7.1.4	DL_Control (W-Master and W-Device) .....	124
125	7.1.5	DL_PDOOutputUpdate (W-Master) .....	124
126	7.1.6	DL_PDOOutputTransport (W-Device) .....	125
127	7.1.7	DL_PDInputUpdate (W-Device) .....	125
128	7.1.8	DL_Event (W-Master and W-Device) .....	126
129	7.1.9	DL_ISDUTransport (W-Master and W-Device) .....	126
130	7.1.10	DL_ISDUAabort (W-Master and W-Device) .....	128
131	7.1.11	DL_TDConfig (W-Master) .....	128
132	7.1.12	DL_Read (W-Master and W-Device) .....	129
133	7.1.13	DL_Write (W-Master and W-Device) .....	130
134	7.1.14	DL_SetMode (W-Master) .....	131
135	7.1.15	DL_Mode (W-Master and W-Device) .....	132
136	7.1.16	DL_MaxRetry (W-Device) .....	132
137	7.1.17	DL_SetParam (W-Master and W-Device) .....	133
138	7.2	DL-mode handler .....	134
139	7.2.1	General .....	134
140	7.2.2	State machine of the W-Master DL-mode handler .....	134
141	7.2.3	State machine of the W-Device DL-mode handler .....	136
142	7.3	Process Data handler .....	137
143	7.3.1	General .....	137
144	7.3.2	State machine of the W-Master Process Data Out handler .....	137
145	7.3.3	State machine of the W-Master Process Data In handler .....	141

146	7.3.4	State machine of the W-Device Process Data Out handler .....	143
147	7.3.5	State machine of the W-Device Process Data In handler.....	145
148	7.4	Indexed Service Data Unit (ISDU) handler.....	147
149	7.4.1	General.....	147
150	7.4.2	State machine of the W-Master ISDU handler.....	147
151	7.4.3	State machine of the W-Device ISDU handler.....	150
152	7.4.4	General structure and encoding of ISDUs.....	152
153	7.5	Command handler .....	152
154	7.5.1	General.....	152
155	7.5.2	State machine of the W-Master command handler .....	152
156	7.5.3	State machine of the W-Device command handler .....	154
157	7.6	Event handler .....	156
158	7.6.1	General.....	156
159	7.6.2	State machine of the W-Master Event handler .....	156
160	7.6.3	State machine of the W-Device Event handler .....	158
161	7.7	Transmission of segmented data and retry handling.....	159
162	7.7.1	General.....	159
163	7.7.2	Transmission of segmented data.....	160
164	7.7.3	Retry-Handling .....	161
165	8	Application Layer (AL).....	161
166	8.1	General.....	161
167	8.2	Application Layer services .....	161
168	8.2.1	General.....	161
169	8.2.2	AL_Read (W-Master and W-Device) .....	162
170	8.2.3	AL_Write (W-Master and W-Device) .....	163
171	8.2.4	AL_Abort (W-Master and W-Device) .....	164
172	8.2.5	AL_NewInput (W-Master) .....	165
173	8.2.6	AL_GetInput (W-Master) .....	165
174	8.2.7	AL_SetInput (W-Device) .....	166
175	8.2.8	AL_PDCycle (W-Master and W-Device) .....	166
176	8.2.9	AL_GetOutput (W-Device) .....	167
177	8.2.10	AL_NewOutput (W-Device) .....	168
178	8.2.11	AL_SetOutput (W-Master) .....	168
179	8.2.12	AL_Event (W-Master and W-Device) .....	169
180	8.2.13	AL_Control (W-Master and W-Device) .....	170
181	8.3	Application layer protocol.....	171
182	8.3.1	Overview.....	171
183	8.3.2	ISDU processing .....	171
184	8.3.3	Event processing.....	175
185	8.3.4	Process Data transfer .....	177
186	9	System management.....	181
187	9.1	General.....	181
188	9.2	Modes .....	181
189	9.2.1	Service Mode .....	181
190	9.2.2	Cyclic Mode .....	181
191	9.3	System management of the W-Master .....	182
192	9.3.1	Overview.....	182
193	9.3.2	System management W-Master services .....	184
194	9.3.3	SM W-Master protocol .....	197

195	9.4 System management of the W-Device .....	209
196	9.4.1 Overview.....	209
197	9.4.2 System management W-Device services .....	210
198	9.4.3 SM W-Device protocol .....	217
199	10 W-Device .....	223
200	10.1 Overview .....	223
201	10.2 Process Data Exchange (PDE).....	224
202	10.3 IMA handling .....	225
203	10.4 Parameter Manager (PM).....	225
204	10.4.1 General.....	225
205	10.4.2 Parameter manager state machine.....	226
206	10.4.3 Dynamic parameter .....	226
207	10.4.4 Single parameter.....	226
208	10.4.5 Block parameter .....	226
209	10.4.6 Concurrent parameterization access .....	226
210	10.4.7 Command handling.....	226
211	10.5 Data Storage (DS) .....	226
212	10.6 Event Dispatcher (ED) .....	226
213	10.7 W-Device features .....	226
214	10.7.1 General.....	226
215	10.7.2 Scan.....	226
216	10.7.3 Pairing by UniqueID.....	226
217	10.7.4 Pairing by Button / Re-Pairing.....	227
218	10.7.5 Roaming .....	227
219	10.7.6 Unpairing .....	227
220	10.7.7 W-Device backward compatibility .....	227
221	10.7.8 Protocol revision compatibility .....	227
222	10.7.9 Device human machine interface (HMI) .....	227
223	10.7.10 Parameter access locking .....	228
224	10.7.11 Data Storage locking .....	228
225	10.7.12 W-Device parameter locking .....	228
226	10.7.13 W-Device user interface locking .....	228
227	10.7.14 Data Storage concept .....	228
228	10.7.15 Block Parameter.....	228
229	10.8 W-Device reset options .....	228
230	10.9 W-Device design rules and constraints .....	228
231	10.9.1 General.....	228
232	10.9.2 Process Data.....	228
233	10.9.3 MaxRetry error detection .....	229
234	10.9.4 Communication loss .....	229
235	10.9.5 Direct Parameter Page .....	229
236	10.9.6 ISDU communication channel .....	229
237	10.9.7 DevicID rules related to W-Device variants .....	229
238	10.9.8 Protocol constants.....	230
239	10.10 I/O W-Device description (W-IODD) .....	230
240	10.10.1 General.....	230
241	10.10.2 CommNetwork Profile Instance for the IODD file for SDCL wireless .....	231
242	10.11 W-Device diagnosis .....	233
243	10.11.1 Concepts.....	233

244	10.11.2 Events .....	233
245	10.11.3 W-Device HMI .....	233
246	10.12 W-Device connectivity.....	235
247	11 W-Master.....	235
248	11.1 Overview .....	235
249	11.2 Services of the Standardized Master Interface (SMI).....	238
250	11.2.1 Overview.....	238
251	11.2.2 SMI_W-MasterConfiguration .....	238
252	11.2.3 SMI_ReadbackMasterConfiguration .....	240
253	11.2.4 SMI_WTrackStatus.....	241
254	11.2.5 SMI_WScan .....	243
255	11.2.6 SMI_WPortPairing .....	244
256	11.2.7 SMI_WScanStatus.....	246
257	11.2.8 SMI_WQualityStatus.....	247
258	11.3 Configuration Manager (CM) .....	249
259	11.3.1 General.....	249
260	11.3.2 Coordination of Master applications .....	249
261	11.3.3 State machines of the Configuration Manager.....	250
262	11.4 Data Storage (DS) .....	256
263	11.5 On-request Data Exchange (ODE).....	257
264	11.6 Diagnosis Unit (DU).....	257
265	11.7 Process Data Exchange (PDE).....	257
266	11.7.1 General.....	257
267	11.7.2 Process Data input mapping .....	257
268	11.7.3 Process Data output mapping .....	257
269	11.7.4 Process Data invalid/valid qualifier status.....	258
270	11.8 Port and Device Configuration Tool (PDCT).....	258
271	11.8.1 General.....	258
272	11.8.2 Basic layout examples .....	259
273	11.9 Gateway application .....	260
274	11.9.1 General.....	260
275	11.9.2 Changing W-Device configuration including Data Storage .....	261
276	11.9.3 Parameter server and recipe control.....	261
277	11.9.4 Interoperability to 5G Systems .....	261
278	11.10 Human machine Interface (HMI), Faulty W-Device replacement .....	261
279	12 W-Bridge .....	262
280	12.1 Overview .....	262
281	12.2 Process Data Exchange (PDE).....	263
282	12.2.1 General.....	263
283	12.2.2 Process Data mapping.....	263
284	12.3 On-request Data Exchange (ODE).....	263
285	12.3.1 General.....	263
286	12.3.2 Wireless Parameters .....	263
287	12.3.3 Parameters of connected SDCL Device.....	263
288	12.4 Data Storage .....	263
289	12.5 Diagnosis Unit (DU).....	263
290	12.5.1 General.....	263
291	12.5.2 Device Events (Wireless).....	263
292	12.5.3 Device Events .....	263

293	12.5.4	Port Events .....	263
294	12.6	Design Rules.....	264
295	12.6.1	General.....	264
296	12.6.2	Timing constraints .....	264
297	12.6.3	Static behaviour .....	264
298	12.6.4	Dynamic behavior.....	266
299	12.6.5	UniqueID.....	273
300	12.7	I/O W-Device description (W-IODD) .....	273
301	Annex A (normative)	W-Messages Codings.....	275
302	A.1	Overview .....	275
303	A.2	Definition of a W-Message .....	275
304	A.3	Downlink W-Messages: Control Octets .....	275
305	A.3.1	DLink Control Octet .....	275
306	A.3.2	DLink Control Octets contains MasterCommand .....	276
307	A.4	Uplink W-Messages .....	277
308	A.4.1	General.....	277
309	A.4.2	ULink Control Octet .....	277
310	A.5	Example for combination of several W-Messages within a DLink / PreDLink .....	278
311	A.6	Example for DLink data transmission within cyclic process data and segmentation.....	279
312	A.7	Examples for uplink data transmissions .....	280
313	A.7.1	General.....	280
314	A.7.2	DSlot W-Device sends 8 octet not segmented Process Data In to W- Master .....	280
315	A.7.3	DSlot W-Device sends 32 octet segmented Process Data In to W- Master .....	281
316	A.7.4	SSlot W-Device responds with 3 octet segmented ISDU Data to W- Master .....	281
317	A.7.5	DSlot W-Device sends 4 octet Process Data In every 5 ms and responds with 25 octet segmented ISDU Data to W-Master.....	281
318	A.8	User data (PD or OD) .....	282
319	A.9	PDVALID PDINVALID .....	282
320	A.10	General structure and encoding of ISDUs .....	283
321	A.11	General structure and encoding of Events .....	283
322	A.11.1	EventQualifier .....	283
323	A.11.2	EventCode .....	284
324	Annex B (normative)	W-Frame Codings, CRC calculation and errors.....	285
325	B.1	Description of ConnectionParameter .....	285
326	B.2	Downlink packet encodings for Normal Operation .....	285
327	B.3	Downlink packet encodings for Configuration Operation.....	286
328	B.3.1	General.....	286
329	B.3.2	Scan Request Downlink packet .....	287
330	B.3.3	Pairing Request Downlink packet.....	288
331	B.3.4	Pairing Negotiation Downlink packet .....	289
332	B.4	Uplink packet encodings for Normal Operations.....	290
333	B.4.1	Regular Single Slot Uplink packet .....	290
334	B.4.2	Regular Double Slot Uplink packet .....	290
335	B.4.3	IMA Uplink packet .....	291
336	B.5	Uplink packet encodings for Configuration Operations .....	292
337	B.5.1	General.....	292

343	B.5.2	Scan Response Uplink packet.....	293
344	B.5.3	Pairing Response Uplink packet.....	293
345	B.5.4	Negotiation Response Uplink packet .....	293
346	B.6	Acknowledge Generation .....	293
347	B.7	CRC16 and CRC32 calculation .....	294
348	B.8	Errors.....	294
349	B.8.1	General.....	294
350	B.8.2	Checksum errors .....	294
351	B.8.3	IMA Timeout errors.....	295
352	B.8.4	False positive Error .....	295
353	Annex C (normative)	W-Device Parameter and commands .....	296
354	C.1	Overview.....	296
355	C.2	Direct Parameter Page 1.....	296
356	C.2.1	General.....	296
357	C.2.2	MasterCommand .....	298
358	C.2.3	Revision ID .....	299
359	C.2.4	ProcessDataIn.....	299
360	C.2.5	ProcessDataOut .....	299
361	C.2.6	VendorID.....	299
362	C.2.7	DeviceID .....	299
363	C.2.8	FunctionID .....	299
364	C.2.9	SystemCommand .....	299
365	C.3	Direct Parameter Page 2.....	299
366	C.4	SDCI wireless specific parameters .....	300
367	C.4.1	Overview.....	300
368	C.4.2	<a href="http://www.oSIST.prEN.IEC.61139-3:2022">http://www.oSIST.prEN.IEC.61139-3:2022</a> /catalog/standards/sust/1dcb2a96-5e63-4286-8af6..	301
369	C.4.3	WDeviceMode 08222726/bsint.htm?prEN.IEC.61139-3:2022	301
370	C.4.4	Wireless System.....	302
371	C.4.5	WRadioInfo .....	304
372	C.4.6	ISDU Mapping for system management.....	304
373	C.4.7	SerialNumber .....	304
374	C.4.8	Wireless Quality .....	305
375	C.4.9	W-Bridge Information.....	305
376	C.4.10	AdaptiveHopTable .....	306
377	C.4.11	Blocked ISDU indexes for low energy W-Device .....	306
378	C.4.12	WCycleTime.....	306
379	Annex D (normative)	EventCodes .....	308
380	D.1	General.....	308
381	D.2	EventCodes for W-Devices .....	308
382	D.3	EventCodes for W-Ports .....	308
383	Annex E (normative)	Coding of ArgBlocks .....	309
384	E.1	Overview Arg Blocks.....	309
385	E.1.1	General.....	309
386	E.1.2	WPortConfigList .....	310
387	E.1.3	WPortStatusList.....	310
388	E.1.4	WPortStatusList WMasterConfigList .....	311
389	E.1.5	WTrackStatusList .....	312
390	E.1.6	WPortPairing .....	312
391	E.1.7	WScanConfigList .....	312

392	E.1.8	WScanStatusList .....	313
393	E.1.9	WQualityStatusList .....	313
394	Annex F (normative) Data Types.....		315
395	Annex G (normative) Device design rules for low energy W-Devices .....		316
396	G.1	Low energy W-Devices .....	316
397	G.1.1	General.....	316
398	G.1.2	Low voltage design.....	316
399	G.1.3	Event triggered activation .....	316
400	G.1.4	Long IMATime .....	316
401	G.1.5	Pre-Downlink.....	316
402	G.1.6	W-Master not reachable.....	316
403	G.1.7	Quick Synchronization.....	316
404	G.1.8	Establish communication .....	316
405	G.1.9	HMI sleep.....	317
406	G.2	Battery lifetime calculation .....	317
407	Annex H (normative) Frequency Hopping Calculation .....		319
408	H.1	Blocklisting .....	319
409	H.2	Creation of frequency hopping table HT01 with blocklisting .....	320
410	H.2.1	General.....	320
411	H.2.2	Example with 2 WLAN Channels .....	321
412	H.2.3	Example with one WLAN channel.....	322
413	H.3	Modified Sequence for ServiceMode .....	323
414	H.4	Adaptive Hopping Table.....	324
415	Annex I (normative) How to get a certified product .....		328
416	I.1	General.....	328
417	I.2	Radio Certification.....	328
418	I.3	IO-Link Certification.....	328
419	Annex J (normative) Regulatory Compliance .....		329
420	J.1	General.....	329
421	J.2	Compliance with FCC 15.247 .....	329
422	J.3	Compliance with ETSI EN 300 328.....	329
423	J.4	Compliance with ETSI EN 300 440.....	329
424	Annex K (informative) Radio field planning.....		330
425	K.1	General.....	330
426	K.2	Range and reliability examination.....	330
427	K.2.1	General.....	330
428	K.2.2	Rayleigh -> Non-Line of Sight: .....	332
429	K.2.3	Conclusion (EXAMPLE CHIP 2): .....	334
430	Annex L (informative) Coexistence management .....		335
431	L.1	Coexistence management.....	335
432	L.2	Wireless System Type .....	335
433	L.3	Wireless Device Type .....	335
434	Bibliography.....		337
435			
436	Figure 1 – Generalized example of a confirmed service .....		31
437	Figure 2 – Example of initiator / receiver of services (W-Device).....		33
438	Figure 3 – Example of service between W-Master and W-Device in generalized and detailed view.....		33

440	Figure 4 – Example of confirmed / non-confirmed services (W-Device) .....	34
441	Figure 5 – SDCI wired and wireless topology .....	35
442	Figure 6 – SDCI wireless system .....	36
443	Figure 7 – Object transfer at the Application Layer (AL) level.....	37
444	Figure 8 – Radius of a cell with a 1 W-Track W-Master.....	38
445	Figure 9 – Cell consisting of 2 W-Master cells .....	39
446	Figure 10 – Cell concept.....	39
447	Figure 11 – Roaming between W-Master cells.....	41
448	Figure 12 – Downlink.....	43
449	Figure 13 – Uplink.....	44
450	Figure 14 – Transmission capacity with SSlots and DSlots .....	44
451	Figure 15 – Uplink assignments .....	45
452	Figure 16 – TDMA and FDMA in the W-Cycle .....	46
453	Figure 17 – W-Frame and W-Sub-cycle.....	46
454	Figure 18 – Logical structure of W-Master and W-Device.....	47
455	Figure 19 – Base technology and modulation .....	49
456	Figure 20 – Transceiver timings .....	50
457	Figure 21 – Memory Storage and transmission order for values for WORD based data types .....	52
459	Figure 22 – Bit ordering within an octet.....	52
460	Figure 23 – Octet array transmission over the air .....	52
461	Figure 24 – Octet ordering of CRC16 result values.....	54
462	Figure 25 – Octet ordering of CRC32 result values.....	54
463	Figure 26 – Data Whitening LFSR .....	54
464	Figure 27 – Regular Downlink packet.....	56
465	Figure 28 – Configuration Downlink packet .....	56
466	Figure 29 – Uplink packet + Guard (SSlot) .....	57
467	Figure 30 – Uplink packet + Guard (DSlot) .....	57
468	Figure 31 – Format of a W-Sub-cycle with DSlots .....	58
469	Figure 32 – SSlots and DSlots .....	58
470	Figure 33 – W-Frame structure .....	59
471	Figure 34 – W-Frame type for pairing and configuration.....	59
472	Figure 35 – LQI versus PERSubCycle for different MaxRetry .....	62
473	Figure 36 – Usage of the Configuration Channels.....	84
474	Figure 37 – Configuration sequence for Scan .....	85
475	Figure 38 – Configuration sequence for pairing by UniqueID.....	86
476	Figure 39 – Configuration sequence for pairing by Button .....	87
477	Figure 40 – Message Sequence Chart for Roaming .....	88
478	Figure 41 – PL W-Master state machine.....	89
479	Figure 42 – Submachine of CyclicMode_2 or RoamingMode_3 of W-Master Physical Layer .....	89
481	Figure 43 – Submachine of Handle_Sub_Cycle_4 of W-Master Physical Layer .....	90
482	Figure 44 – Submachine for Mode_Scan_12 .....	91
483	Figure 45 – Submachine for Mode_Pairing_15 .....	92

484	Figure 46 – PL W-Device state machine.....	100
485	Figure 47 – W-Track and W-Device-Mapper (TDMapper).....	105
486	Figure 48 – State machine of the W-Master Message handler.....	115
487	Figure 49 – State machine of the W-Device Message handler.....	119
488	Figure 50 – W-Device Message handler sub state machine “CreateMessage_8” (DL-A).....	120
489	Figure 51 – State machine of the W-Master DL-mode handler.....	134
490	Figure 52 – State machine of the W-Device DL-mode handler.....	136
491	Figure 53 – State machine for W-Master PDOOut handler.....	138
492	Figure 54 – Sequence diagram for PDOOut distribution .....	141
493	Figure 55 – State machine for W-Master PDIn handler .....	142
494	Figure 56 – State machine of the W-Device Process Data Out handler.....	144
495	Figure 57 – State machine of the W-Device Process Data In handler .....	146
496	Figure 58 – State machine of the W-Master ISDU handler .....	148
497	Figure 59 – State machine of the W-Device ISDU handler .....	150
498	Figure 60 – State machine of the W-Master command handler.....	153
499	Figure 61 – State machine of the W-Device Command handler.....	155
500	Figure 62 – State machine of the W-Master Event handler.....	156
501	Figure 63 – Sequence diagram: Single event scheduling.....	158
502	Figure 64 – State machine of the W-Device Event handler.....	158
503	Figure 65 – ISDU state machine of the W-Master AL.....	171
504	Figure 66 – ISDU state machine of the W-Device AL .....	172
505	Figure 67 – Sequence diagram: ISDU Read Data .....	173
506	Figure 68 – Sequence diagram: ISDU read Data in case of timeout .....	174
507	Figure 69 – Sequence diagram: ISDU read Data in case of error .....	174
508	Figure 70 – Sequence diagram for low energy W-Devices: ISDU Data .....	175
509	Figure 71 – Event state machine of the W-Master AL .....	175
510	Figure 72 – Event state machine of the W-Device AL .....	176
511	Figure 73 – Sequence diagram: Single Event scheduling.....	177
512	Figure 74 – PD state machine of the W-Master AL .....	178
513	Figure 75 – PD state machine of the W-Device-AL .....	179
514	Figure 76 – Sequence diagram for output Process Data .....	180
515	Figure 77 – Sequence diagram for input Process Data .....	181
516	Figure 78 – Sequence chart of the use case “port x setup” .....	184
517	Figure 79 – State Machine of the W-Master W-Track handler.....	198
518	Figure 80 – State Machine of the W-Port-handler .....	200
519	Figure 81 – Submachine CheckCompatibility_3 of the W-Port-handler .....	202
520	Figure 82 – Activities for state „CheckVxy_21“ .....	204
521	Figure 83 – Activities for state „CheckComp_22“ .....	205
522	Figure 84 – Activities (write parameter) in state "RestartDevice_23" .....	206
523	Figure 85 – Submachine CheckSerNum_6 of the W-Port-handler.....	207
524	Figure 86 – Activities (check SerialNumber) for state CheckSerNum_6 .....	208
525	Figure 87 – State Machine of the W-Master AHT-handler .....	208
526	Figure 88 – Sequence chart of a W-Device pairing .....	210

527	Figure 89 – State machine for W-Device System Management .....	217
528	Figure 90 – State Machine of the W-Device AHT-handler .....	220
529	Figure 91 – Sequence chart of a regular W-Device startup .....	221
530	Figure 92 – Sequence chart of a W-Device startup in compatibility mode .....	222
531	Figure 93 – Sequence chart of a Device startup when compatibility fails .....	223
532	Figure 94 – Structure and services of a W-Device .....	224
533	Figure 95 – Schematic representation of the use of (a) a W-Device and (b) a W-Bridge to connect a SDCI Device.....	231
534	Figure 96 – Device LED blink timing .....	234
535	Figure 97 – Device LED double flash timing .....	234
536	Figure 98 – Structure and services of a W-Master .....	236
538	Figure 99 – Relationship of the common W-Master applications.....	237
539	Figure 100 – Sequence diagram of configuration manager actions.....	250
540	Figure 101 – State machine of the W-Track Configuration Manager .....	251
541	Figure 102 – State machine of the W-Port Configuration Manager .....	253
542	Figure 103 – Activity for state "CheckPortMode_0".....	256
543	Figure 104 – Propagation of PD qualifier status between W-Master and W-Device .....	258
544	Figure 105 – Example 1 of a PDCT display layout.....	259
545	Figure 106 – Example 2 of a PDCT display layout.....	260
546	Figure 107 – Generic relationship of W-Master and automation technology .....	261
547	Figure 108 – Faulty W-Device replacement .....	262
548	Figure 109 – Structure of a W-Bridge .....	262
549	Figure 110 – Data object mapping for W-Bridge with connected SDCI Device .....	265
550	Figure 111 – Data object mapping for W-Bridge stand alone.....	266
551	Figure 112 – State machine of the W-Bridge application .....	267
552	Figure 113 – Sequence chart of a W-Bridge startup with connected SDCI Device V1.1.....	269
553	Figure 114 – Sequence chart reconnect an SDCI Device while W-Bridge is in operation .....	270
554	Figure 115 – Sequence chart wireless reconnection of W-Bridge with connected SDCI Device .....	271
556	Figure 116 – Sequence chart of Device Ident with compatibility .....	272
557	Figure 117 – Sequence chart of Device Ident with no compatibility .....	273
558	Figure 118 – Schematic representation of the use of a W-Bridge to connect a SDCI Device .....	273
560	Figure A.1 – W-Message and Control Octet .....	275
561	Figure A.2 – Definition of DLink Control Octet .....	275
562	Figure A.3 – DLink Control Octets contains MasterCommand .....	277
563	Figure A.4 – Definition of ULink Control Octet .....	277
564	Figure A.5 – Placement of different W-Messages in a downlink.....	279
565	Figure A.6 – Structure of the EventQualifier .....	283
566	Figure B.1 – Downlink packet encodings .....	285
567	Figure B.2 – Scan Request packet.....	288
568	Figure B.3 – Pairing Request packet.....	288
569	Figure B.4 – Pairing Negotiation packet type 1 => DLink-Message-Type = MSG_DLink_Pair_Neg_1 .....	289