

ISO/TC 213

Secretariat: BSI

Voting begins on:
2021-08-31

Voting terminates on:
2021-10-26

Geometrical product specifications (GPS) — Surface texture: Areal —

Part 2: Terms, definitions and surface texture parameters

iTeh STANDARD PREVIEW
(standards.iteh.ai)
*Spécification géométrique des produits (GPS) — État de surface:
Surfacique —
Partie 2: Termes, définitions et paramètres d'états de surface*

ISO/FDIS 25178-2

<https://standards.iteh.ai/catalog/standards/sist/743744d0-8174-4697-9179-0c33c31ea7b/iso-fdis-25178-2>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

ISO/CEN PARALLEL PROCESSING



Reference number
ISO/FDIS 25178-2:2021(E)

© ISO 2021

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 25178-2

<https://standards.iteh.ai/catalog/standards/sist/743744d0-8174-4697-9179-0c33c31ea7b/iso-fdis-25178-2>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 General terms	1
3.2 Geometrical parameter terms	5
3.3 Geometrical feature terms	11
4 Field parameters	15
4.1 General	15
4.2 Height parameters	15
4.2.1 General	15
4.2.2 Root mean square height	15
4.2.3 Skewness	15
4.2.4 Kurtosis	15
4.2.5 Maximum peak height	16
4.2.6 Maximum pit depth	16
4.2.7 Maximum height	16
4.2.8 Arithmetic mean height	16
4.3 Spatial parameters	16
4.3.1 General	16
4.3.2 Autocorrelation length	16
4.3.3 Texture aspect ratio	17
4.3.4 Texture direction	18
4.3.5 Dominant spatial wavelength	18
4.4 Hybrid parameters	18
4.4.1 General	18
4.4.2 Root mean square gradient	18
4.4.3 Developed interfacial area ratio	18
4.5 Material ratio functions and related parameters	19
4.5.1 Areal material ratio	19
4.5.2 Inverse areal material ratio	19
4.5.3 Material ratio height difference	20
4.5.4 Areal parameter for stratified surfaces	21
4.5.5 Areal material probability parameters	23
4.5.6 Void volume	24
4.5.7 Material volume	25
4.6 Gradient distribution	26
4.7 Multiscale geometric (fractal) methods	28
4.7.1 Morphological volume-scale function	28
4.7.2 Relative area	28
4.7.3 Relative length	28
4.7.4 Scale of observation	28
4.7.5 Volume-scale fractal complexity	29
4.7.6 Area-scale fractal complexity	29
4.7.7 Length-scale fractal complexity	29
4.7.8 Crossover scale	29
5 Feature parameters	30
5.1 General	30
5.2 Type of texture feature	31
5.3 Segmentation	31
5.4 Determining significant features	31

5.5	Section of feature attributes.....	33
5.6	Attribute statistics.....	34
5.7	Feature characterization convention.....	34
5.8	Named feature parameters.....	34
5.8.1	General.....	34
5.8.2	Density of peaks.....	34
5.8.3	Density of pits.....	35
5.8.4	Arithmetic mean peak curvature.....	35
5.8.5	Arithmetic mean pit curvature.....	35
5.8.6	Five-point peak height.....	35
5.8.7	Five-point pit depth.....	36
5.8.8	Ten-point height.....	36
5.9	Additional feature parameters.....	36
5.9.1	General.....	36
5.9.2	Shape parameters.....	37
Annex A (informative) Multiscale geometric (fractal) methods.....		39
Annex B (informative) Determination of areal parameters for stratified functional surfaces.....		46
Annex C (informative) Basis for areal surface texture standards — Timetable of events.....		49
Annex D (informative) Implementation details.....		50
Annex E (informative) Changes made to the 2012 edition of this document.....		54
Annex F (informative) Summary of areal surface texture parameters.....		56
Annex G (informative) Specification analysis workflow.....		58
Annex H (informative) Relation with the GPS matrix.....		59
Annex I (informative) Overview of profile and areal standards in the GPS matrix model.....		60
Bibliography.....		61

ISO/FDIS 25178-2
<https://standards.iteh.ai/catalog/standards/sist/743744d0-8174-4697-9179-0c33c31ea7b/iso-fdis-25178-2>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 213, *Dimensional and geometrical product specifications and verification*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 290, *Dimensional and geometrical product specification and verification*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 25178-2:2012), which has been technically revised. The main changes to the previous edition are described in [Annex E](#). A short history of the work done on areal surface texture can be found in [Annex C](#).

A list of all parts in the ISO 25178 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document is a geometrical product specification (GPS) standard and is to be regarded as a general GPS standard (see ISO 14638). It influences the chain link B of the chains of standards on areal surface texture.

The ISO/GPS matrix model given in ISO 14638 gives an overview of the ISO/GPS system of which this document is a part. The fundamental rules of ISO/GPS given in ISO 8015 apply to this document and the default decision rules given in ISO 14253-1 apply to the specifications made in accordance with this document, unless otherwise indicated.

For more detailed information of the relation of this document to other standards and the GPS matrix model, see [Annex H](#). An overview of standards on profiles and areal surface texture is given in [Annex I](#).

This document develops the terminology, concepts and parameters for areal surface texture.

Throughout this document, parameters are written as abbreviations with lower case suffixes (as in S_q or V_{mp}) when used in a sentence and are written as symbols with subscripts (as in S_q or V_{mp}) when used in equations, to avoid misinterpretations of compound letters as an indication of multiplication between quantities in equations. The parameters in lower case are used in product documentation, drawings and data sheets.

Parameters are calculated from coordinates defined in the specification coordinate system, or from derived quantities (e.g. gradient, curvature).

Parameters are defined for the continuous case, but in verification they are calculated on discrete surfaces such as the primary extracted surface.

A short history of the work done on areal surface texture can be found in [Annex C](#).

ISO/FDIS 25178-2
<https://standards.iteh.ai/catalog/standards/sist/743744d0-8174-4697-9179-0c33c31ea7b/iso-fdis-25178-2>

Geometrical product specifications (GPS) — Surface texture: Areal —

Part 2: Terms, definitions and surface texture parameters

1 Scope

This document specifies parameters for the determination of surface texture by areal methods.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 16610-1:2015, *Geometrical product specifications (GPS) — Filtration — Part 1: Overview and basic concepts*

ISO 17450-1:2011, *Geometrical product specifications (GPS) — General concepts — Part 1: Model for geometrical specification and verification*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 16610-1:2015 and ISO 17450-1:2011 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 General terms

3.1.1

skin model

<of a workpiece> model of the physical interface of the workpiece with its environment

[SOURCE: ISO 17450-1:2011, 3.2.2]

3.1.2

surface texture

<areal> geometrical irregularities contained in a *scale-limited surface* (3.1.9)

Note 1 to entry: Surface texture does not include those geometrical irregularities contributing to the form or shape of the surface.

3.1.3

mechanical surface

boundary of the erosion, by a sphere of radius r , of the locus of the centre of an ideal tactile sphere, also with radius r , rolled over the *skin model* (3.1.1) of a workpiece

[SOURCE: ISO 14406:2010, 3.1.1, modified — Notes to entry removed.]

3.1.3.1

electromagnetic surface

surface obtained by the electromagnetic interaction with the *skin model* (3.1.1) of a workpiece

[SOURCE: ISO 14406:2010, 3.1.2, modified — Notes to entry removed.]

3.1.3.2

auxiliary surface

surface, other than mechanical or electromagnetic, obtained by an interaction with the *skin model* (3.1.1) of a workpiece

Note 1 to entry: A mathematical surface (softgauge) is an example of an auxiliary surface.

Note 2 to entry: Other physical measurement principles, such as tunnelling microscopy or atomic force microscopy, can also serve as an auxiliary surface. See [Figure 1](#) and [Annex G](#).

3.1.4

specification coordinate system

system of coordinates in which surface texture parameters are specified

Note 1 to entry: If the nominal form of the surface is a plane (or portion of a plane), it is common (practice) to use a rectangular coordinate system in which the axes form a right handed Cartesian set, the x-axis and the y-axis also lying on the nominal surface, and the z-axis being in an outward direction (from the material to the surrounding medium). This convention is adopted throughout the rest of this document.

3.1.5

primary surface

surface portion obtained when a surface portion is represented as a specified primary mathematical model with specified *nesting index* (3.1.6.4)

Note 1 to entry: In this document, an S-filter is used to derive the primary surface. See [Figure 1](#).

[SOURCE: ISO 16610-1:2015, 3.3, modified — Note 1 to entry added.]




Figure 1 — Definition of primary surface

3.1.5.1**primary extracted surface**

finite set of data points sampled from the *primary surface* (3.1.5)

[SOURCE: ISO 14406:2010, 3.7, modified — Notes to entry removed.]

3.1.6**surface filter**

filtration operator applied to a surface

3.1.6.1**S-filter**

surface filter (3.1.6) which removes small-scale lateral components from the surface, resulting in the *primary surface* (3.1.5)

3.1.6.2**L-filter**

surface filter (3.1.6) which removes large-scale lateral components from the *primary surface* (3.1.5) or *S-F surface* (3.1.7)

Note 1 to entry: When the L-filter is not tolerant to form, it needs to be applied on an S-F surface; when it is tolerant to form, it can be applied either on the primary surface or on an S-F surface.

3.1.6.3**F-operation**

operation which removes form from the *primary surface* (3.1.5)

Note 1 to entry: Some F-operations (such as association) have a very different action to that of filtration. Though their action can limit the larger lateral scales of a surface, this action is very fuzzy. It is represented in [Figure 2](#) using the same convention as for a filter.

Note 2 to entry: Some L-filters are not tolerant to form and require an F-operation first as a prefilter before being applied.

Note 3 to entry: An F-operation can be a filtration operation such as a robust Gaussian filter.

3.1.6.4**nesting index**

N_{is} , N_{ic} , N_{if}

number or set of numbers indicating the relative level of nesting for a particular primary mathematical model

[SOURCE: ISO 16610-1:2015, 3.2.1, modified — definition revised and notes to entry removed.]

3.1.7**S-F surface**

surface derived from the *primary surface* (3.1.5) by removing the form using an *F-operation* (3.1.6.3)

Note 1 to entry: [Figure 2](#) illustrates the relationship between the S-F surface and the S-filter and F-operation.

Note 2 to entry: If filtered with N_{is} nesting index to remove the shortest wavelengths from the surface, the surface is equivalent to a “primary surface”. In this case, N_{is} is the areal equivalent of the λ_s cut-off. See [4](#) in [Figure 2](#) and [Annex G](#).

Note 3 to entry: If filtered with N_{ic} nesting index to separate longer from shorter wavelengths, the surface is equivalent to a “waviness surface”. In this case, N_{ic} is the areal equivalent of the λ_c cut-off. See [5](#) in [Figure 2](#) and [Annex G](#).

Note 4 to entry: The concepts of “roughness” or “waviness” are less important in areal surface texture than in profile surface texture. Some surfaces can exhibit roughness in one direction and waviness in the perpendicular direction. That is why the concepts of S-L surface and S-F surface are preferred in this document.

3.1.8


S-L surface

surface derived from the *S-F surface* (3.1.7) by removing the large-scale components using an *L-filter* (3.1.6.2)

Note 1 to entry: Figure 2 illustrates the relationship between the S-L surface and the S-filter and L-filter.


Note 2 to entry: If the S-filter nesting index N_{is} is chosen to remove the shortest wavelengths from the surface and the L-filter nesting index N_{ic} is chosen in order to separate longer from shorter wavelengths, the surface is equivalent to a “roughness surface”. See 6 in Figure 2 and Annex G.

Note 3 to entry: A series of S-L surfaces can be generated with narrow bandwidth using an S-filter and an L-filter of close nesting indices (or equal), in order to achieve a multiscale exploration of the surface. See Figure 3.

**Key**

- 1 S-filter
- 2 L-filter
- 3 F-operation
- 4 *S-F surface* (see 3.1.7, Note 2 to entry)
- 5 *S-F surface* (see 3.1.7, Note 3 to entry)
- 6 *S-L surface* (see 3.1.8, Note 2 to entry)
- a Small scale.
- b Large scale.

Figure 2 — Relationships between the S-filter, L-filter, F-operation and S-F and S-L surfaces



Key

- S S-filter
- L L-filter
- a Small scale.
- b Large scale.

Figure 3 — Example of bandpass filters used to generate a bank of S-L surfaces

3.1.9

scale-limited surface

S-F surface (3.1.7) or *S-L surface* (3.1.8)

3.1.10

reference surface

<surface texture> surface associated to the *scale-limited surface* (3.1.9) according to a criterion

Note 1 to entry: This reference surface is used as the origin of heights for surface texture parameters.

EXAMPLE Plane, cylinder and sphere.

3.1.11

evaluation area

A

\tilde{A}

portion of the *scale-limited surface* (3.1.9) for specifying the area under evaluation

Note 1 to entry: See ISO 25178-3 for more information.

Note 2 to entry: Throughout this document, the symbol A is used for the numerical value of the evaluation area and the symbol \tilde{A} for the domain (of integration or definition).

3.2 Geometrical parameter terms

3.2.1

field parameter

parameter defined from all the points on a *scale-limited surface* (3.1.9)

Note 1 to entry: Field parameters are defined in [Clause 4](#).

3.2.2

feature parameter

parameter defined from a subset of predefined topographic features from the *scale-limited surface* (3.1.9)

Note 1 to entry: Feature parameters are defined in [Clause 5](#).

3.2.3

V-parameter

material volume or void volume *field parameter* (3.2.1)

3.2.4

S-parameter

field parameter (3.2.1) or *feature parameter* (3.2.2) that is not a *V-parameter* (3.2.3)

3.2.5

height

ordinate value

$z(x,y)$

signed normal distance from the *reference surface* (3.1.10) to the *scale-limited surface* (3.1.9)

Note 1 to entry: Throughout this document, the term “height” is either used for a distance or for an absolute coordinate. For example, S_z , maximum height, is a distance and S_p , maximum peak height, is an absolute height.

3.2.5.1

depth

opposite value of *height* (3.2.5)

3.2.6

local gradient vector

$\left(\frac{\partial z(x,y)}{\partial x}, \frac{\partial z(x,y)}{\partial y} \right)$

first derivative along x and y of the *scale-limited surface* (3.1.9) at position (x,y)

Note 1 to entry: See [Annex D](#) for implementation details.

3.2.7

local mean curvature

arithmetic mean of the principal curvatures at position (x,y)

Note 1 to entry: Principal curvatures are two numbers, k_1 and k_2 , representing the maximum and minimum curvatures at a point. The local mean curvature is therefore $\frac{k_1 + k_2}{2}$.

Note 2 to entry: See [Annex D](#) for implementation details.

3.2.8

material ratio

$M_r(c)$

ratio of the area A_c of the surface portion intersected by a plane at level c , to the *evaluation area* (3.1.11),

A

Note 1 to entry: The curve representing material ratio as a function of the level is also called Abbott Firestone curve.


Note 2 to entry: The level c is usually defined as a height taken with respect to a reference c_0 . By default, the reference is at the highest point of the surface. In the first edition of this document, the reference height was set to the *reference surface* (3.1.10).

Note 3 to entry: The material ratio may be given as a percentage or a value between 0 and 1.

Note 4 to entry: See Figure 4 and [Formula \(1\)](#).

Note 5 to entry: See [Annex D](#) for the determination of the material ratio curve.

$$M_r(c) = \frac{A_c(c)}{A} \cdot 100 \% \quad (1)$$

**Key**

- c intersecting level
 c_0 reference height
 A_c areal portions intersected by plane at height c

Figure 4 — Area of the surface portion intersected by plane at level c

STANDARD PREVIEW

3.2.9**areal material ratio curve**


material ratio function

function representing the areal material ratio (3.2.8) of the scale-limited surface (3.1.9) as a function of a level c

<https://standards.iteh.ai/catalog/standards/sist/743744d0-8174-4697-9179-0cf33c31ea7b/iso-fdis-25178-2>

Note 1 to entry: This function can be interpreted as the cumulative probability function of the ordinates $z(x,y)$ within the evaluation area. See [Annex D](#).

Note 2 to entry: See [Figure 5](#).

**Key**

- a Height.
 b Areal material ratio.
 c Intersection level c .
 d Material ratio at level c .

Figure 5 — Material ratio curve

3.2.10

inverse material ratio

$C(p)$

intersecting level at which a given *areal material ratio* (3.2.8) p is satisfied

Note 1 to entry: See [Formula \(2\)](#).

$$C(p) = M_r^{-1}(p) \quad (2)$$

3.2.11

height density curve

height density function


$h(c)$

curve representing the density of points laying at level c on the *scale-limited surface* (3.1.9)

Note 1 to entry: When represented as a histogram with bins, the percentage per bin depends on their width.

Note 2 to entry: See [Figure 6](#) and [Formula \(3\)](#).

$$h(c) = -\frac{dM_r(c)}{dc} \quad (3)$$



Key

- a Height.
- b Density.

Figure 6 — Height density curve

3.2.12

core surface

scale-limited surface excluding core-protruding hills and dales


Note 1 to entry: The terms hills and dales in this definition refer to [3.3.1.2](#) and [3.3.2.2](#) but are defined by graphical construction. See [Figure 13](#) and Annex [B.3](#).

3.2.13

areal material probability curve

representation of the *areal material ratio curve* (3.2.9) in which the areal material area ratio is expressed as a Gaussian probability in standard deviation values, plotted linearly on the horizontal axis

Note 1 to entry: This scale is expressed linearly in standard deviations according to the Gaussian distribution. In this scale, the areal material ratio curve of a Gaussian distribution becomes a straight line. For stratified surfaces composed of two Gaussian distributions, the areal material probability curve will exhibit two linear regions (see E and F in [Figure 7](#)).

**Key**

- A amplitude
- B reference line
- C material ratio expressed as a Gaussian probability in per cent
- D material ratio expressed as a Gaussian probability in standard deviation
- E plateau region
- F dale region
- G outlying hills (possibly including debris or dirt particles)
- H outlying dales (possibly deep scratches)
- I unstable region (curvature) introduced at the plateau-to-dale transition point based on the combination of two distributions horizontal axis s is the standard deviation

iTeh STANDARD PREVIEW
(standards.iTech.ai)
ISO/FDIS 25178-2
<https://standards.iTech.ai/catalog/standards/sist/743744d0-8174-4697-9179-0cf33c31ea7b/iso-fdis-25178-2>

Figure 7 — Areal material probability curve

3.2.14**autocorrelation function**
 $f_{ACF}(t_x, t_y)$

function which describes the correlation between a surface and the same surface translated by (t_x, t_y)

Note 1 to entry: The autocorrelation used here is normalized between -1 and 1. The maximum value is always met but the minimum may not always be at -1, it depends on the surface (it may be -0,76).

Note 2 to entry: See [Formula \(4\)](#).

$$f_{ACF}(t_x, t_y) = \frac{\frac{1}{B} \iint_{\tilde{B}} z(x, y) z(x + t_x, y + t_y) dx dy}{\frac{1}{A} \iint_{\tilde{A}} z^2(x, y) dx dy} \quad (4)$$

where \tilde{B} is the intersecting area of the two surfaces at shifts t_x and t_y .

3.2.15**Fourier transformation**
 $F(p, q)$

operator which transforms *ordinate values* ([3.2.5](#)) of the *scale-limited surface* ([3.1.9](#)) into Fourier space

Note 1 to entry: The Fourier transformation defined here is using a limited support \tilde{A} , therefore it approximates the mathematical function called Fourier transformation which has an infinite support.

Note 2 to entry: See [Formula \(5\)](#).