

# ETSI TS 128 552 V17.17.0 (2025-04)



**5G;  
Management and orchestration;  
5G performance measurements  
(3GPP TS 28.552 version 17.17.0 Release 17)**

[ETSI TS 128 552 V17.17.0 \(2025-04\)](https://standards.iteh.ai/catalog/standards/etsi/d62517ed-54f2-4ea9-a6cc-6c15f86013c9/etsi-ts-128-552-v17-17-0-2025-04)

<https://standards.iteh.ai/catalog/standards/etsi/d62517ed-54f2-4ea9-a6cc-6c15f86013c9/etsi-ts-128-552-v17-17-0-2025-04>



---

**Reference**

RTS/TSGS-0528552vhh0

---

**Keywords**

5G

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from the  
[ETSI Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver repository](#).

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2025-04)

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	20
1 Scope .....	21
2 References .....	21
3 Definitions, abbreviations and measurement family .....	23
3.1 Definitions .....	23
3.2 Abbreviations .....	23
3.3 Measurement family.....	24
4 Concepts and overview .....	25
4.1 Performance indicators.....	25
4.2 Filters and filter naming .....	25
4.2.0 General.....	25
4.2.1 Filters .....	25
4.2.2 Filter naming.....	26
5 Performance measurements for 5G network functions .....	26
5.1 Performance measurements for gNB.....	26
5.1.0 Relation to RAN L2 measurement specification .....	26
5.1.1 Performance measurements valid for all gNB deployment scenarios.....	27
5.1.1.1 Packet Delay .....	27
5.1.1.1.1 Average delay DL air-interface .....	27
5.1.1.1.2 Distribution of delay DL air-interface .....	27
5.1.1.1.3 Average delay UL on over-the-air interface .....	28
5.1.1.1.4 Average RLC packet delay in the UL.....	28
5.1.1.1.5 Average PDCP re-ordering delay in the UL.....	29
5.1.1.1.6 Distribution of DL delay between NG-RAN and UE .....	29
5.1.1.1.7 Distribution of UL delay between NG-RAN and UE .....	30
5.1.1.1.8 DL packet delay between NG-RAN and PSA UPF.....	31
5.1.1.2 Radio resource utilization .....	32
5.1.1.2.1 DL Total PRB Usage.....	32
5.1.1.2.2 UL Total PRB Usage.....	33
5.1.1.2.3 Distribution of DL Total PRB Usage .....	33
5.1.1.2.4 Distribution of UL total PRB usage.....	34
5.1.1.2.5 Mean DL PRB used for data traffic.....	34
5.1.1.2.6 DL total available PRB.....	35
5.1.1.2.7 Mean UL PRB used for data traffic.....	35
5.1.1.2.8 UL total available PRB.....	35
5.1.1.2.9 Peak DL PRB used for data traffic .....	36
5.1.1.2.10 Peak UL PRB used for data traffic .....	36
5.1.1.2.11 PDSCH PRB Usage per cell for MIMO .....	37
5.1.1.2.12 PUSCH PRB Usage per cell for MIMO .....	37
5.1.1.2.13 SDM PDSCH PRB Usage .....	38
5.1.1.2.14 SDM PUSCH PRB Usage .....	39
5.1.1.3 UE throughput.....	40
5.1.1.3.1 Average DL UE throughput in gNB.....	40
5.1.1.3.2 Distribution of DL UE throughput in gNB .....	41
5.1.1.3.3 Average UL UE throughput in gNB.....	43
5.1.1.3.4 Distribution of UL UE throughput in gNB .....	44
5.1.1.3.5 Percentage of unrestricted DL UE data volume in gNB.....	45
5.1.1.3.6 Percentage of unrestricted UL UE data volume in gNB.....	46
5.1.1.4 RRC connection number .....	47
5.1.1.4.1 Mean number of RRC Connections.....	47

5.1.1.4.2	Max number of RRC Connections .....	47
5.1.1.4.3	Mean number of stored inactive RRC Connections .....	48
5.1.1.4.4	Max number of stored inactive RRC Connections .....	48
5.1.1.5	PDU Session Management.....	48
5.1.1.5.1	Number of PDU Sessions requested to setup .....	48
5.1.1.5.2	Number of PDU Sessions successfully setup .....	49
5.1.1.5.3	Number of PDU Sessions failed to setup .....	49
5.1.1.5.4	Mean number of PDU sessions being allocated .....	50
5.1.1.5.5	Peak number of PDU sessions being allocated.....	50
5.1.1.6	Mobility Management.....	50
5.1.1.6.1	Inter-gNB handovers .....	50
5.1.1.6.1.1	Number of requested legacy handover preparations .....	50
5.1.1.6.1.2	Number of successful legacy handover preparations .....	51
5.1.1.6.1.3	Number of failed legacy handover preparations .....	51
5.1.1.6.1.4	Number of requested legacy handover resource allocations .....	52
5.1.1.6.1.5	Number of successful legacy handover resource allocations .....	52
5.1.1.6.1.6	Number of failed legacy handover resource allocations .....	52
5.1.1.6.1.7	Number of requested legacy handover executions.....	53
5.1.1.6.1.8	Number of successful legacy handover executions.....	53
5.1.1.6.1.9	Number of failed legacy handover executions .....	54
5.1.1.6.1.10	Mean Time of requested legacy handover executions .....	54
5.1.1.6.1.11	Max Time of requested legacy handover executions .....	55
5.1.1.6.1.12	Number of successful handover executions per beam pair .....	55
5.1.1.6.1.13	Number of failed handover executions per beam pair .....	55
5.1.1.6.2	Intra-gNB handovers .....	56
5.1.1.6.2.1	Number of requested legacy handover executions.....	56
5.1.1.6.2.2	Number of successful legacy handover executions.....	57
5.1.1.6.3	Handovers between 5GS and EPS.....	57
5.1.1.6.3.1	Number of requested preparations for handovers from 5GS to EPS.....	57
5.1.1.6.3.2	Number of successful preparations for handovers from 5GS to EPS .....	57
5.1.1.6.3.3	Number of failed preparations for handovers from 5GS to EPS.....	58
5.1.1.6.3.4	Number of requested resource allocations for handovers from EPS to 5GS.....	58
5.1.1.6.3.5	Number of successful resource allocations for handovers from EPS to 5GS .....	58
5.1.1.6.3.6	Number of failed resource allocations for handovers from EPS to 5GS.....	59
5.1.1.6.3.7	Number of requested executions for handovers from 5GS to EPS .....	59
5.1.1.6.3.8	Number of successful executions for handovers from 5GS to EPS .....	59
5.1.1.6.3.9	Number of failed executions for handovers from 5GS to EPS .....	60
5.1.1.6.3.10	Number of requested preparations for EPS fallback handovers.....	60
5.1.1.6.3.11	Number of successful preparations for EPS fallback handovers .....	60
5.1.1.6.3.12	Number of failed preparations for EPS fallback handovers.....	61
5.1.1.6.3.13	Number of successful executions for EPS fallback handovers .....	61
5.1.1.6.3.14	Number of failed executions for EPS fallback handovers .....	61
5.1.1.6.3.15	Mean Time of EPS fallback handover .....	62
5.1.1.6.3.16	Mean Time of EPS fallback handover executions .....	62
5.1.1.6.4	RRC redirection measurement.....	63
5.1.1.6.5	Intra/Inter-frequency Handover related measurements .....	63
5.1.1.6.5.1	Number of requested intra-frequency handover executions.....	63
5.1.1.6.5.2	Number of successful intra-frequency handover executions .....	63
5.1.1.6.5.3	Number of requested inter-frequency handover executions.....	64
5.1.1.6.5.4	Number of successful inter-frequency handover executions .....	64
5.1.1.6.6	Inter-gNB conditional handovers .....	64
5.1.1.6.6.1	Number of requested conditional handover preparations.....	64
5.1.1.6.6.2	Number of successful conditional handover preparations .....	65
5.1.1.6.6.3	Number of failed conditional handover preparations.....	65
5.1.1.6.6.7	Number of configured conditional handover candidates .....	67
5.1.1.6.6.8	Number of UEs configured with conditional handover. ....	67
5.1.1.6.6.9	Number of successful conditional handover executions .....	67
5.1.1.6.6.10	Void .....	68
5.1.1.6.6.11	Mean Time of requested conditional handover executions.....	68
5.1.1.6.6.12	Max Time of requested conditional handover executions.....	68
5.1.1.6.6.13	Number of UEs for which conditional handover preparations are requested.....	69
5.1.1.6.6.14	Number of UEs for which conditional handover preparations were successful.....	69

5.1.1.6.6.15	Number of UEs for which conditional handover preparations failed.....	69
5.1.1.6.7	Intra-gNB conditional handovers .....	70
5.1.1.6.7.1	Number of configured conditional handover candidates .....	70
5.1.1.6.7.2	Number of UEs configured with conditional handover .....	70
5.1.1.6.7.3	Number of successful handover executions .....	71
5.1.1.6.8	Inter-gNB DAPS handovers .....	71
5.1.1.6.8.1	Number of requested DAPS handover preparations .....	71
5.1.1.6.8.2	Number of successful DAPS handover preparations .....	71
5.1.1.6.8.3	Number of failed DAPS handover preparations .....	72
5.1.1.6.8.4	Number of requested DAPS handover resource allocations .....	72
5.1.1.6.8.5	Number of successful DAPS handover resource allocations .....	73
5.1.1.6.8.6	Number of failed DAPS handover resource allocations .....	73
5.1.1.6.8.7	Number of requested DAPS handover executions.....	73
5.1.1.6.8.8	Number of successful DAPS handover executions.....	74
5.1.1.6.8.9	Number of failed DAPS handover executions .....	74
5.1.1.6.9	Intra-gNB DAPS handovers .....	75
5.1.1.6.9.1	Number of requested handovers .....	75
5.1.1.6.9.2	Number of successful DAPS handovers .....	75
5.1.1.7	TB related Measurements .....	76
5.1.1.7.1	Total number of DL initial TBs.....	76
5.1.1.7.2	Initial error number of DL TBs .....	76
5.1.1.7.3	Total number of DL TBs .....	76
5.1.1.7.4	Total error number of DL TBs .....	77
5.1.1.7.5	Residual error number of DL TBs.....	77
5.1.1.7.6	Total number of UL initial TBs.....	78
5.1.1.7.7	Error number of UL initial TBs.....	78
5.1.1.7.8	Total number of UL TBs .....	78
5.1.1.7.9	Total error number of UL TBs .....	79
5.1.1.7.10	Residual error number of UL TBs.....	79
5.1.1.8	Void.....	79
5.1.1.9	Void.....	79
5.1.1.10	DRB related measurements.....	79
5.1.1.10.1	Number of DRBs attempted to setup.....	79
5.1.1.10.2	Number of DRBs successfully setup .....	80
5.1.1.10.3	Number of released active DRBs .....	80
5.1.1.10.4	In-session activity time for DRB .....	81
5.1.1.10.7	Number of DRBs attempted to be resumed .....	83
5.1.1.10.8	Number of DRBs successfully resumed .....	83
5.1.1.10.9	Mean number of DRBs being allocated.....	84
5.1.1.10.10	Peak number of DRBs being allocated.....	84
5.1.1.10.11	Mean number of DRBs undergoing from User Plane Path Failures .....	84
5.1.1.11	CQI related measurements .....	85
5.1.1.11.1	Wideband CQI distribution .....	85
5.1.1.12	MCS related Measurements.....	85
5.1.1.12.1	MCS Distribution in PDSCH .....	85
5.1.1.12.2	MCS Distribution in PUSCH .....	85
5.1.1.12.3	PDSCH MCS Distribution for MU-MIMO .....	86
5.1.1.12.4	PUSCH MCS Distribution for MU-MIMO .....	86
5.1.1.13	QoS flow related measurements.....	87
5.1.1.13.1	QoS flow release.....	87
5.1.1.13.1.2	Number of QoS flows attempted to release .....	87
5.1.1.13.2	QoS flow activity.....	88
5.1.1.13.3	QoS flow setup .....	89
5.1.1.13.3.1	Number of QoS flow attempted to setup.....	89
5.1.1.13.3.2	Number of QoS flow successfully established.....	89
5.1.1.13.3.3	Number of QoS flow failed to setup .....	90
5.1.1.13.4	QoS flow modification .....	91
5.1.1.13.4.1	Number of QoS flows attempted to modify.....	91
5.1.1.13.4.2	Number of QoS flows successfully modified .....	92
5.1.1.13.4.3	Number of QoS flows failed to modify.....	92
5.1.1.14	Void.....	93
5.1.1.15	RRC connection establishment related measurements.....	93

5.1.1.15.1	Attempted RRC connection establishments .....	93
5.1.1.15.2	Successful RRC connection establishments .....	93
5.1.1.15.3	Failed RRC connection establishments .....	93
5.1.1.16	UE-associated logical NG-connection related measurements .....	94
5.1.1.16.1	Attempted UE-associated logical NG-connection establishment from gNB to AMF .....	94
5.1.1.16.2	Successful UE-associated logical NG-connection establishment from gNB to AMF .....	94
5.1.1.17	RRC Connection Re-establishment .....	95
5.1.1.17.1	Number of RRC connection re-establishment attempts .....	95
5.1.1.17.2	Successful RRC connection re-establishment with UE context .....	95
5.1.1.17.3	Successful RRC connection re-establishment without UE context .....	95
5.1.1.17.4	Number of RRC connection re-establishment attempts followed by RRC Setup .....	96
5.1.1.18	RRC Connection Resuming .....	96
5.1.1.18.1	Number of RRC connection resuming attempts .....	96
5.1.1.18.2	Successful RRC connection resuming .....	96
5.1.1.18.3	Successful RRC connection resuming with fallback .....	97
5.1.1.18.4	RRC connection resuming followed by network release .....	97
5.1.1.18.5	RRC connection resuming followed by network suspension .....	97
5.1.1.18.6	Number of RRC connection resuming attempts followed by RRC Setup .....	97
5.1.1.19	Power, Energy and Environmental (PEE) measurements .....	98
5.1.1.19.1	Applicability of measurements .....	98
5.1.1.19.2	PNF Power Consumption .....	98
5.1.1.19.2.1	Average Power .....	98
5.1.1.19.2.2	Minimum Power .....	98
5.1.1.19.2.3	Maximum Power .....	99
5.1.1.19.3	PNF Energy consumption .....	99
5.1.1.19.4	PNF Temperature .....	99
5.1.1.19.4.1	Average Temperature .....	99
5.1.1.19.4.2	Minimum Temperature .....	99
5.1.1.19.4.3	Maximum Temperature .....	100
5.1.1.19.5	PNF Voltage .....	100
5.1.1.19.6	PNF Current .....	100
5.1.1.19.7	PNF Humidity .....	101
5.1.1.20	Received Random Access Preambles .....	101
5.1.1.20.1	Received Random Access Preambles per cell .....	101
5.1.1.20.2	Received Random Access Preambles per SSB .....	101
5.1.1.20.3	Distribution of number of RACH preambles per cell .....	102
5.1.1.20.4	Distribution of RACH access delay .....	103
5.1.1.21	Intra-NRCell SSB Beam switch Measurement .....	103
5.1.1.21.1	Number of requested Intra-NRCell SSB Beam switch executions .....	103
5.1.1.21.2	Number of successful Intra-NRCell SSB Beam switch executions .....	103
5.1.1.22	RSRP Measurement .....	104
5.1.1.22.1	SS-RSRP distribution per SSB .....	104
5.1.1.22.2	SS-RSRP distribution per SSB of neighbor NR cell .....	104
5.1.1.22.3	RSRP distribution per neighbor E-UTRAN cell .....	105
5.1.1.23	Number of Active UEs .....	105
5.1.1.23.1	Mean number of Active UEs in the DL per cell .....	105
5.1.1.23.2	Max number of Active UEs in the DL per cell .....	106
5.1.1.23.3	Mean number of Active UEs in the UL per cell .....	106
5.1.1.23.4	Max number of Active UEs in the UL per cell .....	107
5.1.1.24	5QI 1 QoS Flow Duration Monitoring .....	107
5.1.1.24.1	Average Normally Released Call (5QI 1 QoS Flow) Duration .....	107
5.1.1.24.2	Average Abnormally Released Call (5QI 1 QoS Flow) Duration .....	108
5.1.1.24.3	Distribution of Normally Released Call (5QI 1 QoS Flow) Duration .....	108
5.1.1.24.4	Distribution of Abnormally Released Call (5QI 1 QoS Flow) Duration .....	109
5.1.1.25	Measurements related to MRO .....	109
5.1.1.25.1	Handover failures related to MRO for intra-system mobility .....	109
5.1.1.25.2	Handover failures related to MRO for inter-system mobility .....	110
5.1.1.25.3	Unnecessary handovers for inter-system mobility .....	110
5.1.1.25.4	Handover ping-pong for inter-system mobility .....	110
5.1.1.25.5	Handover failures per beam-cell pair related to MRO for intra-system mobility .....	111
5.1.1.26	PHR Measurement .....	111
5.1.1.26.1	Type 1 power headroom distribution .....	111