

ETSI TS 136 101 V15.25.0 (2025-04)



LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 15.25.0 Release 15)

[ETSI TS 136 101 V15.25.0 \(2025-04\)](https://standards.iteh.ai/catalog/standards/etsi/79aa8c4f-afb0-4366-a903-ac686c0f1dc1/etsi-ts-136-101-v15-25-0-2025-04)

<https://standards.iteh.ai/catalog/standards/etsi/79aa8c4f-afb0-4366-a903-ac686c0f1dc1/etsi-ts-136-101-v15-25-0-2025-04>



Reference

RTS/TSGR-0436101 vfp0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver repository](#).

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables. (2025-04)

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	31
1 Scope	32
2 References	32
3 Definitions, symbols and abbreviations	32
3.1 Definitions	32
3.2 Symbols.....	34
3.3 Abbreviations	37
4 General	38
4.1 Relationship between minimum requirements and test requirements	38
4.2 Applicability of minimum requirements	39
4.3 Void.....	39
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1, UE category M2, UE category 1bis, UE category NB1 and NB2, V2X Communication, MBMS UE)	39
4.4 RF requirements in later releases	41
5 Operating bands and channel arrangement.....	41
5.1 General	41
5.2 Void.....	41
5.3 Void.....	41
5.4 Void.....	41
5.5 Operating bands.....	41
5.5A Operating bands for CA	43
5.5B Operating bands for UL-MIMO	55
5.5C Operating bands for Dual Connectivity	55
5.5D Operating bands for ProSe.....	56
5.5E Operating bands for UE category 0, UE category M1 and M2 and UE category 1bis	57
5.5F Operating bands for category NB1 and NB2.....	57
5.5G Operating bands for V2X Communication.....	58
5.6 Channel bandwidth.....	59
5.6.1 Channel bandwidths per operating band.....	60
5.6A Channel bandwidth for CA.....	61
5.6A.1 Channel bandwidths per operating band for CA.....	63
5.6B Channel bandwidth for UL-MIMO	140
5.6B.1 Void	140
5.6C Channel bandwidth for Dual Connectivity.....	140
5.6C.1 Void	140
5.6D Channel bandwidth for ProSe.....	140
5.6D.1 Channel bandwidths per operating band for ProSe.....	140
5.6F Channel bandwidth for category NB1 and NB2.....	141
5.6G Channel bandwidth for V2X Communication.....	142
5.6G.1 Channel bandwidths per operating band for V2X Communication	142
5.7 Channel arrangement.....	144
5.7.1 Channel spacing.....	144
5.7.1A Channel spacing for CA.....	144
5.7.1F Channel spacing for category NB1 and NB2.....	145
5.7.2 Channel raster	145
5.7.2A Channel raster for CA.....	145
5.7.2F Channel raster for category NB1 and NB2.....	145
5.7.3 Carrier frequency and EARFCN.....	145
5.7.3F Carrier frequency and EARFCN for category NB1 and NB2.....	146

5.7.4	TX–RX frequency separation	147
5.7.4A	TX–RX frequency separation for CA	148
5.7.4E	TX–RX frequency separation for category M1 and M2	148
5.7.4F	TX–RX frequency separation for category NB1 and NB2	148
6	Transmitter characteristics	148
6.1	General	148
6.2	Transmit power	148
6.2.1	Void	148
6.2.2	UE maximum output power	148
6.2.2A	UE maximum output power for CA	150
6.2.2B	UE maximum output power for UL-MIMO	153
6.2.2C	Void	155
6.2.2D	UE maximum output power for ProSe	155
6.2.2E	UE maximum output power for Category M1 and M2 UE	155
6.2.2F	UE maximum output power for category NB1 and NB2	156
6.2.2G	UE maximum output power for V2X Communication	157
6.2.3	UE maximum output power for modulation / channel bandwidth	158
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	160
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	164
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe	164
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1 and M2	165
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1 and NB2	167
6.2.3G	UE maximum output power for modulation / channel bandwidth for V2X Communication	167
6.2.3G.1	MPR for Power class 3 V2X UE	167
6.2.3G.2	MPR for Power class 2 V2X UE	169
6.2.4	UE maximum output power with additional requirements	169
6.2.4A	UE maximum output power with additional requirements for CA	185
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	187
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	187
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	188
6.2.4A.4	A-MPR for CA_NS_04	189
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	191
6.2.4A.6	A-MPR for CA_NS_06	191
6.2.4A.7	A-MPR for CA_NS_07	192
6.2.4A.8	A-MPR for CA_NS_08	193
6.2.4A.9	Void	194
6.2.4B	UE maximum output power with additional requirements for UL-MIMO	194
6.2.4D	UE maximum output power with additional requirements for ProSe	194
6.2.4E	UE maximum output power with additional requirements for category M1 and M2 UE	194
6.2.4F	UE maximum output power with additional requirements for category NB1 and NB2 UE	202
6.2.4G	UE maximum output power with additional requirements for V2X Communication	203
6.2.5	Configured transmitted power	205
6.2.5A	Configured transmitted power for CA	227
6.2.5B	Configured transmitted power for UL-MIMO	230
6.2.5C	Configured transmitted power for Dual Connectivity	231
6.2.5D	Configured transmitted power for ProSe	232
6.2.5F	Configured transmitted Power for category NB1 and NB2	234
6.2.5G	Configured transmitted power for V2X Communication	235
6.3	Output power dynamics	239
6.3.1	(Void)	239
6.3.2	Minimum output power	239
6.3.2.1	Minimum requirement	239
6.3.2A	UE Minimum output power for CA	239
6.3.2A.1	Minimum requirement for CA	239
6.3.2B	UE Minimum output power for UL-MIMO	240
6.3.2B.1	Minimum requirement	240
6.3.2C	Void	240
6.3.2D	UE Minimum output power for ProSe	240
6.3.2F	UE Minimum output power for category NB1 and NB2	240
6.3.2G	UE Minimum output power for V2X Communication	240
6.3.3	Transmit OFF power	241

6.3.3.1.	Minimum requirement	241
6.3.3A	UE Transmit OFF power for CA	241
6.3.3A.1	Minimum requirement for CA	241
6.3.3B	UE Transmit OFF power for UL-MIMO	242
6.3.3B.1	Minimum requirement	242
6.3.3D	Transmit OFF power for ProSe	242
6.3.3F	Transmit OFF power for category NB1 and NB2	243
6.3.3G	Transmit OFF power for V2X Communication	243
6.3.4	ON/OFF time mask	243
6.3.4.1	General ON/OFF time mask	243
6.3.4.2	PRACH and SRS time mask	245
6.3.4.2.1	PRACH time mask	245
6.3.4.2.2	SRS time mask	245
6.3.4.3	Slot / Sub frame boundary time mask for subframe TTI	246
6.3.4.4	PUCCH / PUSCH / SRS time mask for subframe TTI	248
6.3.4.5	Symbol / Subslot boundary time mask for subslot TTI	250
6.3.4.6	Subslot PUCCH / subslot PUSCH / SRS time mask for subslot TTI	252
6.3.4.7	Symbol / Slot boundary time mask for slot TTI	255
6.3.4.8	Slot PUCCH / slot PUSCH / SRS time mask for slot TTI	255
6.3.4.9	Consecutive subslot and slot TTI or consecutive subslot and subframe TTI time mask	256
6.3.4.10	Consecutive subframe and subslot TTI or consecutive slot and subslot TTI time mask	256
6.3.4.11	Consecutive TTI and slot TTI or consecutive slot TTI and TTI time mask	257
6.3.4A	ON/OFF time mask for CA	257
6.3.4B	ON/OFF time mask for UL-MIMO	257
6.3.4D	ON/OFF time mask for ProSe	258
6.3.4D.1	General time mask for ProSe	258
6.3.4D.2	PSSS/SSSS time mask	258
6.3.4D.3	PSSS / SSSS / PSBCH time mask	259
6.3.4D.4	PSSCH / SRS time mask	260
6.3.4F	ON/OFF time mask for category NB1 and NB2	260
6.3.4F.1	General ON/OFF time mask	260
6.3.4F.2	NPRACH time mask	261
6.3.4G	ON/OFF time mask for V2X Communication	261
6.3.4G.1	PSSS / SSSS / PSBCH time mask	261
6.3.5	Power Control	262
6.3.5.1	Absolute power tolerance	262
6.3.5.1.1	Minimum requirements	262
6.3.5.2	Relative Power tolerance	263
6.3.5.2.1	Minimum requirements	263
6.3.5.3	Aggregate power control tolerance	264
6.3.5.3.1	Minimum requirement	264
6.3.5A	Power control for CA	264
6.3.5A.1	Absolute power tolerance	264
6.3.5A.1.1	Minimum requirements	264
6.3.5A.2	Relative power tolerance	265
6.3.5A.2.1	Minimum requirements	265
6.3.5A.3	Aggregate power control tolerance	265
6.3.5A.3.1	Minimum requirements	265
6.3.5B	Power control for UL-MIMO	266
6.3.5D	Power Control for ProSe	266
6.3.5D.1	Absolute power tolerance	266
6.3.5E	Power control for category M1 and M2	266
6.3.5E.1	Absolute power tolerance	266
6.3.5E.2	Relative Power tolerance	266
6.3.5E.3	Aggregate power control tolerance	266
6.3.5E.3.1	Minimum requirement	267
6.3.5F	Power Control for category NB1 and NB2	267
6.3.5F.1	Absolute power tolerance	267
6.3.5F.2	Relative power tolerance	268
6.3.5F.3	Aggregate power control tolerance for category NB1 and NB2	268
6.3.5F.3.1	Minimum requirement	269
6.3.5G	Power Control for V2X Communication	269

6.3.5G.1	Absolute power tolerance	269
6.4	Void	270
6.5	Transmit signal quality	270
6.5.1	Frequency error	270
6.5.1A	Frequency error for CA	270
6.5.1B	Frequency error for UL-MIMO	270
6.5.1D	Frequency error for ProSe	270
6.5.1E	Frequency error for UE category M1 and M2	270
6.5.1F	Frequency error for UE category NB1 and NB2	271
6.5.1G	Frequency error for V2X Communication	271
6.5.2	Transmit modulation quality	271
6.5.2.1	Error Vector Magnitude	271
6.5.2.1.1	Minimum requirement	272
6.5.2.2	Carrier leakage	272
6.5.2.2.1	Minimum requirements	272
6.5.2.3	In-band emissions	273
6.5.2.3.1	Minimum requirements	273
6.5.2.4	EVM equalizer spectrum flatness	274
6.5.2.4.1	Minimum requirements	274
6.5.2A	Transmit modulation quality for CA	275
6.5.2A.1	Error Vector Magnitude	275
6.5.2A.2	Carrier leakage for CA	276
6.5.2A.2.1	Minimum requirements	276
6.5.2A.3	In-band emissions	276
6.5.2A.3.1	Minimum requirement for CA	276
6.5.2B	Transmit modulation quality for UL-MIMO	278
6.5.2B.1	Error Vector Magnitude	278
6.5.2B.2	Carrier leakage	278
6.5.2B.3	In-band emissions	279
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	279
6.5.2D	Transmit modulation quality for ProSe	279
6.5.2D.1	Error Vector Magnitude	279
6.5.2D.2	Carrier leakage	279
6.5.2D.3	In-band emissions	279
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	279
6.5.2E	Transmit modulation quality for category M1 and M2	279
6.5.2E.1	Error Vector Magnitude	279
6.5.2E.2	Carrier leakage	279
6.5.2E.2.1	Minimum requirements	280
6.5.2E.3	In-band emissions	280
6.5.2E.3.1	Minimum requirements	280
6.5.2F	Transmit modulation quality for Category NB1 and NB2	281
6.5.2F.1	Error Vector Magnitude	281
6.5.2F.2	Carrier leakage	281
6.5.2F.3	In-band emissions	281
6.5.2G	Transmit modulation quality for V2X Communication	282
6.5.2G.1	Error Vector Magnitude	282
6.5.2G.2	Carrier leakage	282
6.5.2G.3	In-band emissions	283
6.5.2G.4	EVM equalizer spectrum flatness	283
6.6	Output RF spectrum emissions	283
6.6.1	Occupied bandwidth	283
6.6.1.1	Additional minimum requirement for E-UTRA (network signalled value "NS_29")	284
6.6.1A	Occupied bandwidth for CA	284
6.6.1B	Occupied bandwidth for UL-MIMO	284
6.6.1F	Occupied bandwidth for category NB1 and NB2	284
6.6.1G	Occupied bandwidth for V2X Communication	285
6.6.2	Out of band emission	285
6.6.2.1	Spectrum emission mask	285
6.6.2.1.1	Minimum requirement	285
6.6.2.1A	Spectrum emission mask for CA	286
6.6.2.2	Additional spectrum emission mask	287