
**Akustika - Preskusne metode za kvalifikacijo akustičnega okolja - 1. del:
Kvalifikacija okolij prostega polja (ISO 26101-1:2021)**

Acoustics - Test methods for the qualification of the acoustic environment - Part 1:
Qualification of free-field environments (ISO 26101-1:2021)

Akustik - Verfahren für die Qualifizierung von Freifeld-Prüfumgebungen - Teil 1:
Qualifizierung von Freifeldumgebungen (ISO 26101-1:2021)

Acoustique - Méthodes d'essai pour la qualification de l'environnement acoustique -
Partie 1: Qualification des environnements en champ libre (ISO 26101-1:2021)

[oSIST prEN ISO 26101-1:2022](http://standards.iteh.ai/catalog/standards/sist/066599eb-19db-400c-b01d-df008e0313df/osist-pren-iso-26101-1-2022)
Ta slovenski standard je istoveten z: prEN ISO 26101-1

ICS:

17.140.01	Akustična merjenja in blaženje hrupa na splošno	Acoustic measurements and noise abatement in general
-----------	--	---

oSIST prEN ISO 26101-1:2022**en,fr,de**

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

oSIST prEN ISO 26101-1:2022

<https://standards.iteh.ai/catalog/standards/sist/0b6599eb-19db-400c-b01d-df008e0313df/osist-pren-iso-26101-1-2022>

INTERNATIONAL
STANDARD

ISO
26101-1

First edition
2021-05

**Acoustics — Test methods for
the qualification of the acoustic
environment —**

Part 1:
**Qualification of free-field
environments**

*Acoustique — Méthodes d'essai pour la qualification de
l'environnement acoustique —*

Partie 1: Qualification des environnements en champ libre

oSIST prEN ISO 26101-1:2022

<https://standards.iteh.ai/catalog/standards/sist/0b6599eb-19db-400c-b01d-df008e0313df/osist-pren-iso-26101-1-2022>



Reference number
ISO 26101-1:2021(E)

© ISO 2021

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 26101-1:2022](https://standards.iteh.ai/catalog/standards/sist/0b6599eb-19db-400c-b01d-df008e0313df/osist-pren-iso-26101-1-2022)

<https://standards.iteh.ai/catalog/standards/sist/0b6599eb-19db-400c-b01d-df008e0313df/osist-pren-iso-26101-1-2022>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Allowable deviations from inverse square law.....	2
5 Measurement of free sound field performance.....	3
5.1 Divergence loss method.....	3
5.1.1 Principle.....	3
5.1.2 Instrumentation and measuring equipment.....	3
5.1.3 Location of test sound sources and microphone traverses.....	4
5.1.4 Test procedure.....	5
5.1.5 Expression of results.....	6
5.1.6 Measurement uncertainty.....	7
5.2 Information to be recorded.....	7
5.3 Information to be reported.....	8
Annex A (normative) Qualification criteria and measurement requirements.....	9
Annex B (normative) General procedure for evaluation of test sound source directionality.....	12
Annex C (informative) Measurement uncertainty.....	15
Annex D (informative) Guidelines for referring to this test method.....	18
Bibliography.....	20

[oSIST prEN ISO 26101-1:2022](https://standards.iteh.ai/catalog/standards/sist/0b6599eb-19db-400c-b01d-df008e0313df/osist-pren-iso-26101-1-2022)

<https://standards.iteh.ai/catalog/standards/sist/0b6599eb-19db-400c-b01d-df008e0313df/osist-pren-iso-26101-1-2022>

ISO 26101-1:2021(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This first edition of ISO 26101-1 cancels and replaces the second edition of ISO 26101:2017, of which it constitutes a minor revision. The changes compared to the previous edition are as follows:

- The title of the document was changed from "Acoustics — Test methods for the qualification of free-field environments" to "Acoustics — Test methods for the qualification of the acoustic environment — Part 1: Qualification of free-field environments", so that an additional part, "ISO 26101-2, *Acoustics — Test methods for the qualification of the acoustic environment — Part 2: Determination of the environmental correction*", can be introduced.

A list of all parts in the ISO 26101 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document describes the divergence loss method of measurement of performance of an environment designed to provide a free sound field or free sound field over a reflecting plane. An acoustical environment is a free sound field if it has bounding surfaces that absorb all sound energies incident upon them. This is normally achieved using specialized test environments, such as anechoic or hemi-anechoic chambers. In practice, these provide a controlled free sound field for acoustical measurements in a confined space within the facility.

The purpose of this document is to promote uniformity in the method and conditions of measurement when qualifying free sound field environments.

It is expected that the qualification procedures outlined in this document will be referred to by other International Standards and industry test codes. In such cases, these documents making reference to this document may specify qualification criteria appropriate for the test method and may require specific traverse paths.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 26101-1:2022](https://standards.iteh.ai/catalog/standards/sist/0b6599eb-19db-400c-b01d-df008e0313df/osist-pren-iso-26101-1-2022)

<https://standards.iteh.ai/catalog/standards/sist/0b6599eb-19db-400c-b01d-df008e0313df/osist-pren-iso-26101-1-2022>

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

[oSIST prEN ISO 26101-1:2022](https://standards.iteh.ai/catalog/standards/sist/0b6599eb-19db-400c-b01d-df008e0313df/osist-pren-iso-26101-1-2022)

<https://standards.iteh.ai/catalog/standards/sist/0b6599eb-19db-400c-b01d-df008e0313df/osist-pren-iso-26101-1-2022>

Acoustics — Test methods for the qualification of the acoustic environment —

Part 1: Qualification of free-field environments

1 Scope

This document specifies methodology for qualifying acoustic spaces as anechoic and hemi-anechoic spaces meeting the requirements of a free sound field.

This document specifies discrete-frequency and broad-band test methods for quantifying the performance of anechoic and hemi-anechoic spaces, defines the qualification procedure for an omnidirectional sound source suitable for free-field qualification, gives details of how to present the results and describes uncertainties of measurement.

This document has been developed for qualifying anechoic and hemi-anechoic spaces for a variety of acoustical measurement purposes. It is expected that, over time, various standards and test codes will refer to this document in order to qualify an anechoic or hemi-anechoic space for a particular measurement. [Annex D](#) provides guidelines for the specification of test parameters and qualification criteria for referencing documents.

In the absence of specific requirements or criteria, [Annex A](#) provides qualification criteria and measurement requirements to qualify anechoic and hemi-anechoic spaces for general purpose acoustical measurements.

This document describes the divergence loss method for measuring the free sound field performance of an acoustic environment.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC Guide 98-3, *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

IEC 61260-1, *Electroacoustics — Octave-band and fractional-octave-band filters — Part 1: Specifications*

IEC 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <http://www.electropedia.org/>

ISO 26101-1:2021(E)

3.1

free sound field

sound field in a homogeneous, isotropic medium free of boundaries

[SOURCE: ISO/TR 25417:2007, 2.17]

3.2

anechoic space

volume which has been qualified as a sound field in a homogeneous, isotropic medium free of boundaries

3.3

hemi-anechoic space

volume above a reflecting plane which has been qualified as a sound field in a homogeneous, isotropic medium free of boundaries

3.4

acoustic centre

<for a test sound source and for a given test signal> position of the point from which approximately spherical wave fronts appear to diverge

3.5

background noise

sum of all the signals except the one under investigation

Note 1 to entry: Background noise can include contributions from airborne sound, structure-borne vibration and electrical noise in instrumentation.

3.6

divergence loss

reduction in sound pressure along a straight path due to the spreading of sound when a sound wave propagates away from a source

3.7

frequency range of interest

contiguous one-third-octave-band frequencies from the lowest to the highest frequencies to be qualified, inclusive

3.8

referencing document

standard or test code that refers to this document for the purpose of specifying the qualification method of an *anechoic space* (3.2) or *hemi-anechoic space* (3.3)

4 Allowable deviations from inverse square law

The theoretical reduction in mean-square sound pressure along a straight path due to spherical propagation of a sound wave in a free sound field shall be hereafter referred to as the inverse square law.

For a space to be deemed anechoic or hemi-anechoic, as defined by criteria in a referencing document, the deviations of the measured sound pressure levels from those estimated using the inverse square law, obtained according to this document, shall not exceed the values specified by the referencing document.

In the absence of specific criteria for the allowable deviations in a referencing document, the criteria in [Annex A](#) shall be used to qualify anechoic and hemi-anechoic spaces for general purpose acoustical measurements.

The allowable deviations specified by a referencing document may be more or less stringent than the criteria given in [Annex A](#).

5 Measurement of free sound field performance

5.1 Divergence loss method

5.1.1 Principle

The divergence loss method shall be used to quantify the performance of an anechoic or hemi-anechoic space within a test environment and to determine the spatial limits of this qualified anechoic or hemi-anechoic space.

The free sound field performance is evaluated by quantifying the contributions of both the direct and the reflected components of acoustic energy.

The spatial decrease of sound pressure emitted from a test sound source shall be compared with the decrease of sound pressure that would occur in an ideal free sound field.

5.1.2 Instrumentation and measuring equipment

5.1.2.1 General

The instrumentation system for measuring sound pressure level, including the microphone and cable, shall be operated within the limit of the linearity errors specified for a Class 1 sound level meter according to IEC 61672-1.

The microphone shall be nominally omni-directional (taking into account any supplementary equipment connected to it, such as the protective grid and mounting arrangement).

For measurements in one-third-octave bands, the filters used shall meet the requirements for Class 1 specified in IEC 61260-1.

For measurements above 5 kHz, this method will normally require a microphone of diameter equivalent to that of a WS2F microphone, as described in IEC 61094-4^[2], or less.

5.1.2.2 Test sound source

A sound source approximating a point source over the frequency range of interest shall be used for the qualification measurement. The test sound source shall be

- a) compact and of acoustical performance, such that the location of the acoustic centre of the source is known to be located close enough to the origin of the microphone traverses specified in [5.1.3.2](#) to allow fitting of the sound pressure level versus distance data without an adjustment for the acoustic centre of the source,
- b) in conformity with the directionality criteria in [Table B.1](#), when measured according to the procedure in [Annex B](#), so as to ensure the source radiates energy in all directions,
- c) able to generate sufficient sound power over the frequency range of interest to yield sound pressure levels at least 6 dB above the background noise levels for all points on each microphone traverse, or while the microphone is moving for continuous traverse systems^[3], and
- d) of high stability so that the radiated sound power (due to the source, associated signal generation and amplification electronics) as measured by a monitor microphone located at an arbitrary fixed position in the test environment does not vary significantly at the frequency of measurement during the time taken to complete the measurements for each microphone traverse. If the stability of the source varies by more than $\pm 0,2$ dB then the monitor microphone shall be used to apply a correction according to [Formula \(1\)](#):

ISO 26101-1:2021(E)

$$L_{p,i} = L'_{p,i} - L_{p,ref,i} + L_{p,ref,0} \quad (1)$$

where

- $L_{p,i}$ is the corrected sound pressure level at measurement point i , expressed in decibels (dB);
- $L'_{p,i}$ is the measured sound pressure level at measurement point i , expressed in decibels (dB);
- $L_{p,ref,i}$ is the sound pressure level measured by the monitor microphone at the reference location for measurement point i , expressed in decibels (dB);
- $L_{p,ref,0}$ is the sound pressure level measured by the monitor microphone at the reference location for the initial measurement point 0, expressed in decibels (dB).

Since, in general, two or more sources can be required to cover the overall frequency range of interest, the requirements given above shall be met for each source over its applicable frequency range.

NOTE It is possible to estimate the acoustic centre of a source by evaluating it in an anechoic space already known to meet the requirements given in [Annex A](#).

Care should be taken:

- to ensure that the sound pressure levels are more than 6 dB, and preferably more than 15 dB, above the background noise levels;
- in positioning the monitor microphone to avoid acoustic interference with the traversing mechanism affecting the results;
- to ensure that changes in atmospheric conditions over the duration of the traverse are not confused with those related to the source stability.

5.1.3 Location of test sound sources and microphone traverses

[https://standards.iteh.ai/catalog/standards/sist/0b6599eb-](https://standards.iteh.ai/catalog/standards/sist/0b6599eb-191b-490c-b01d-df008e0313df/osist-pren-iso-26101-1-2022)

5.1.3.1 Test sound source location

[191b-490c-b01d-df008e0313df/osist-pren-iso-26101-1-2022](https://standards.iteh.ai/catalog/standards/sist/0b6599eb-191b-490c-b01d-df008e0313df/osist-pren-iso-26101-1-2022)

Referencing documents may specify the test sound source location(s) to be used in order to qualify the anechoic or hemi-anechoic space.

In the absence of specific requirements for the sound source location in a referencing document, the requirements given in [Annex A](#) shall be used to qualify anechoic and hemi-anechoic spaces for general purpose acoustical measurements.

The test sound source should be placed in a chosen orientation and held in that orientation for all microphone traverses.

An environment may be qualified for more than one source location.

5.1.3.2 Microphone traverses

Microphone traverses shall be made along paths that will characterize and qualify the anechoic or hemi-anechoic space for the types of acoustical measurements to be conducted in the test environment. The origin of the microphone traverse shall be within the physical volume occupied by the test sound source.

Referencing documents may specify the traverse paths to be conducted in order to qualify the anechoic or hemi-anechoic space.

In the absence of specific requirements for the traverse paths in a referencing document, the requirements given in [Annex A](#) shall be used to qualify anechoic and hemi-anechoic spaces for general purpose acoustical measurements.