
Structures for mine shafts —
Part 7:
Rope guides

Structures de puits de mine —
Partie 7: Guides-câbles

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 19426-7:2021

<https://standards.iteh.ai/catalog/standards/iso/7b29dd0e-50d0-4d69-8395-1dcc41aacc21/iso-19426-7-2021>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 19426-7:2021

<https://standards.iteh.ai/catalog/standards/iso/7b29dd0e-50d0-4d69-8395-1dcc41aacc21/iso-19426-7-2021>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	4
5 Materials	8
6 Disturbing actions	8
6.1 Coriolis force	8
6.2 Aerodynamic loads	9
6.2.1 Steady state	9
6.2.2 Buffeting	9
6.2.3 Air density	10
6.3 Rope torque	10
6.3.1 Head rope torque	10
6.3.2 Tail rope torque	11
6.3.3 Torque applied by multiple ropes	11
6.4 Eccentric conveyance loading	11
6.5 Winder emergency braking	12
6.6 Thermal actions on headframe	12
6.7 Wind load on conveyances	12
7 Restoring forces	12
7.1 Rope guide tension	12
7.2 Rope guide stiffness	13
7.2.1 Stiffness of rope guides	13
7.2.2 Stiffness of head and tail ropes	13
8 Conveyance trajectory	15
8.1 Simulation of conveyance behaviour	15
8.2 Combination of actions	15
9 Design procedure	15
9.1 Function of rope guides	15
9.2 Risk assessment	15
9.3 General design procedure	15
9.4 Simple design procedure	16
9.4.1 Limits on parameters	16
9.4.2 Design requirements	16
9.5 Comprehensive design procedure	16
10 Minimum clearances	17
10.1 Design clearances	17
10.2 Dynamic displacement envelope	17
10.3 Reduced dynamic clearances	17
10.4 Use of rubbing ropes	18
11 Construction and installation tolerances	18
11.1 Shaft vertical cylinder diameter	18
11.2 Tolerance of associated structures	18
11.3 Tolerance on rope guide tension	18
11.4 Commissioning	18
11.4.1 Commissioning procedure	18
11.4.2 Components of the commissioning procedure	18

12	Other design considerations	19
12.1	General	19
12.2	Loading and unloading of conveyances	19
12.3	Accessing intermediate levels	19
12.4	Number of rope guides	19
12.5	Rope guide positions	19
12.6	Rope guide construction	19
12.7	Rope guide tension and factor of safety	20
12.8	Rope guide attachments	20
12.9	Shafts with more than one winder	20
12.10	Design life	20
12.11	Rope guide tensioning	20
	12.11.1 Gravity tensioning devices	20
	12.11.2 Hydraulic tensioning devices	20
13	Assessment of existing installations	21
13.1	General	21
13.2	Application of measurements	21
13.3	Upgrades or modifications	21
14	Inspection and maintenance	22
14.1	Deterioration mechanisms	22
	14.1.1 General	22
	14.1.2 Wear	22
	14.1.3 Corrosion	22
	14.1.4 Mechanical damage	22
	14.1.5 Broken wires	22
14.2	Inspections	22
	14.2.1 General	22
	14.2.2 Inspection intervals	22
	14.2.3 Visual inspection	22
	14.2.4 Non-destructive inspection	22
14.3	Maintenance actions	23
	14.3.1 Maintenance intervals	23
	14.3.2 Lubrication	23
	14.3.3 Rope turning and rope lifting	23
	14.3.4 Equalisation of hoist rope tensions	23
14.4	Rope guide discard criteria	23
14.5	Rope guide attachments	23
	Annex A (informative) Load combinations and displacement multipliers	24
	Annex B (informative) Introduction to Annexes B to F, and basic parameters	26
	Annex C (informative) Preliminary aerodynamic coefficients	35
	Annex D (informative) Rope torque factors	44
	Annex E (informative) Rope guide stiffness and tension	46
	Annex F (informative) Approximate calculation of conveyance displacement	50
	Bibliography	53

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 82, *Mining*.

A list of all parts in the ISO 19426 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Many mining companies, and many of the engineering companies that provide designs for mines, operate globally so ISO 19426 was developed in response to a desire for a unified global approach to the safe and robust design of structures for mine shafts. The characteristics of ore bodies, such as their depth and shape, vary in different areas so different design approaches have been developed and proven with use over time in different countries. Bringing these approaches together in ISO 19426 will facilitate improved safety and operational reliability.

The majority of the material in ISO 19426 deals with the loads to be applied in the design of structures for mine shafts. Some principles for structural design are given, but for the most part it is assumed that local standards will be used for the structural design.

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[ISO 19426-7:2021](https://standards.itih.ai/catalog/standards/iso/7b29dd0e-50d0-4d69-8395-1dcc41aacc21/iso-19426-7-2021)

<https://standards.itih.ai/catalog/standards/iso/7b29dd0e-50d0-4d69-8395-1dcc41aacc21/iso-19426-7-2021>

Structures for mine shafts —

Part 7: Rope guides

1 Scope

This document specifies the design loads and the design procedures for the design of rope guides and rubbing ropes used for guiding conveyances and preventing collisions in vertical mine shafts for permanent operations. It covers personnel and material hoisting, as well as rock hoisting installations. There are no fundamental limitations placed on the size of conveyances, the hoisting speeds, shaft layout configurations, or the shaft depth.

This document can be applicable to shaft sinking operations when kibbles run on the stage ropes.

There are many reasons, based on technical, timing, and cost factors, why rope guides are selected or not for a particular application, following careful assessment at feasibility stage of any project where rope guides are considered. This document provides some comments regarding the advantages and disadvantages of using rope guides compared to rigid guides, and specific design aspects for consideration when using rope guides. However, it is primarily intended to provide the technical information required to ensure good engineering of shafts where rope guided hoisting is the chosen solution.

This document does not cover matters of operational safety.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19426-1, *Structures for mine shafts — Part 1: Vocabulary*

ISO 19426-2, *Structures for mine shafts — Part 2: Headframe structures*

ISO 19426-5, *Structures for mine shafts — Part 5: Shaft system structures*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 19426-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org>

3.1

cheeseweight

stack of weights, usually steel castings, suspended from the bottom of a rope guide forming a dead weight tensioning system

3.2

direct collision

event in which a conveyance strikes another conveyance or some other surface that is essentially transverse to the direction of travel of the conveyance


Note 1 to entry: See [Figure 1 a](#)).

3.3

oblique collision

event in which a conveyance strikes a shaft side wall or some other surface that is oriented essentially parallel with the direction of travel of the conveyance

Note 1 to entry: See [Figure 1 b](#)).



a) Direct collision



b) Oblique collision

Figure 1 — Schematic of possible collision types

3.4

design clearance

static clearance

nominal distance between different conveyances, or between conveyances and fixed objects, in the shaft, as shown on the design drawings

3.5

design location

intended location of elements of the rope guided hoisting installation, as shown on the design drawings

3.6

displacement multiplier

factor by which the predicted conveyance lateral displacement is multiplied to make statistical allowance for inaccuracies in simulation and aerodynamic coefficients and construction tolerances

3.7**dynamic clearance**

minimum distance between different conveyances, or between conveyances and fixed objects, in the shaft during hoisting in the shaft, which is equal to the *design clearance* (3.4) less the maximum *dynamic displacement* (3.8)

3.8**dynamic displacement**

lateral displacement of conveyances while travelling in the shaft

3.9**design dynamic displacement**

lateral *dynamic displacement* (3.8) of conveyances while travelling in the shaft multiplied by the *displacement multiplier* (3.6), which makes provision for simulation uncertainties and construction inaccuracies

3.10**reduced dynamic clearance**

minimum distance between different conveyances, or between conveyances and fixed objects, in the shaft during hoisting in the shaft, which is equal to the *design clearance* (3.4) less the *design dynamic displacement* (3.9)

3.11**entry point**

position at which a conveyance enters fixed guides at the top and bottom ends of the hoisting cycle, and at any intermediate stations

3.12**guide block**

guide bush

guide slipper

attachment of a conveyance to the rope guides

Note 1 to entry: The guide block is usually made in two halves to bolt around the rope guide, and it has a guide block liner forming the rubbing surface on the rope guide.

3.13**intermediate loading station**

loading station between bank level or a tipping station at the top of the shaft and a loading station at the bottom of the shaft, or any loading station located more than 100 m below the top anchor point of the rope guides or more than 100 m above the bottom anchor point of the rope guides

3.15**rope guide shoe**

mounting to secure the *guide block* (3.12) through which the rope guide passes to the conveyance

3.16**rubbing block**

fixed guide slippers

contact point between a conveyance and the fixed guides at top and bottom of winding cycle, which can run within or outside the fixed guide

Note 1 to entry: Where the fixed guides are located close to the rope guides, the rubbing block can also serve the purpose of the rope guide shoe.

3.17**rubbing rope**

rope located between conveyances running on rope guides, intended to deflect conveyances away from each other, thereby reducing the severity of a possible collision

3.18

vertical shaft cylinder

maximum circular cylinder, clear of any obstructions, that fits within the excavated mine shaft and constructed infrastructure

3.19

winder emergency braking

winder trip-out

braking of the winder under emergency conditions, such as loss of electrical power, detection of over-tension or under-tension on the hoist ropes, or accident to shaft signal

4 Symbols

a	Conveyance acceleration, m/s^2
A_C	Area of the relevant side of a conveyance, m^2
A_R	Cross sectional steel area of a single head rope, m^2
A_1, A_2	Area of specified portions of a shaft cross-section, m^2
b	Thickness of skip stiffeners, m
B_E	Distance between the conveyance centre of gravity and the geometrical centre of the set of rope guides, guiding that conveyance, m
B_X, B_Z	Plan dimensions of a conveyance, m
C_{BX}, C_{BZ}	Basic aerodynamic lateral force coefficient in appropriate direction, taken as 0,018
C_L	Aerodynamic force coefficient
C_{LX}, C_{LZ}	Aerodynamic lateral force coefficient in appropriate direction
C_{LP}	Conveyance passing buffeting force coefficient
C_Q	Torque factor applied to head ropes
C_T	Coefficient of thermal expansion of the rope guide, $^{\circ}\text{C}^{-1}$
d_S	Shaft diameter, m
d_R	Rope diameter, m (note that this is usually given in mm in hoist rope catalogues)
D_A	Lateral conveyance displacement due to steady state aerodynamic force, m
D_B	Lateral conveyance displacement due to buffeting forces, m
D_C	Lateral conveyance displacement due to Coriolis force, m
D_{EB}	Lateral conveyance displacement at the bottom of the conveyance due to conveyance eccentricity with respect to the head rope attachment point, m
D_{EC}	Lateral conveyance displacement at the centre of gravity of the conveyance due to conveyance eccentricity with respect to the head rope attachment point, m
D_{ET}	Lateral conveyance displacement at the top of the conveyance due to conveyance eccentricity with respect to the head rope attachment point, m
D_G	General lateral displacement of the centre of gravity of a conveyance in a shaft, m

D'_G	General lateral displacement of the geometric centre of the set of rope guides guiding one conveyance in a shaft, m
D_I	Amplitude of initial rope guide motion prior to hoisting of a conveyance, m
D_M	Nominal design movement allowance between a conveyance and other objects in a shaft, m
D_N	Nominal design clearance between a conveyance and other objects in a shaft, m
D_O	Minimum dynamic clearance, m
D_P	Total combined lateral displacement of a conveyance, m
D_R	Lateral conveyance displacement due to initial rope guide motion, m
D_X	Recommended tolerance allowance, m
D_Y	Lateral displacement due to yaw rotation of the conveyance in the shaft, m
E_S	Elastic modulus of the head rope or the rope guide, Pa
F_A	Steady state aerodynamic force acting on a conveyance, N
F_C	Coriolis force acting on a conveyance, N
F_P	Peak force during buffeting of a conveyance, N
F_X	General lateral force applied to a conveyance, N
F_Y	General moment applied about the centre of gravity of a conveyance, Nm
g	Acceleration due to gravity, m/s ²
h_1	Body height of a conveyance, m
h_2	Ventilation opening height on a cage, m
H	Overall height of a conveyance, m
H_C	Height from the conveyance centre of gravity to the top of the conveyance, m
I_C	Mass moment of inertia of a conveyance about the vertical centroidal axis, kgm ²
K_H	Lateral stiffness at conveyance elevation, of a single head rope, N/m
K_L	Lateral stiffness at conveyance elevation, of the set of ropes attached to one conveyance, N/m (this includes the rope guides, the head ropes, and where applicable the tail ropes)
K_R	Lateral stiffness at conveyance elevation, of a single rope guide, N/m
K_T	Lateral stiffness at conveyance elevation, of a single tail rope, N/m
K_θ	Rotational stiffness at conveyance elevation, of the set of ropes attached to one conveyance, Nm/rad
L	Overall length of the rope guides, m
L_H	Head rope length between the conveyance and the sheave, m
L_T	Tail rope length between the conveyance and the bottom sheave, m

L_1	Rope guide length between the top of a conveyance and the top anchor point, m
L_2	Rope guide length between the bottom of a conveyance and the bottom anchor point, m
m_C	Conveyance mass, including mass of rope attachments and payload, kg
m_H	Mass per unit length of a single head rope, kg/m
m_P	Payload mass, kg
m_R	Mass per unit length of a single rope guide, kg/m
m_T	Mass per unit length of a single tail rope, kg/m
M_O	Overturning moment due to eccentric loading, Nm
n	An integer greater than 1
n_H	Number of head ropes for a single conveyance
n_R	Number of rope guides guiding a single conveyance
n_T	Number of tail ropes for a single conveyance
Q	Rope torque applied to a conveyance, Nm
Q_i	Rope torque from rope i applied to a conveyance, Nm
r_t	Ratio of acceleration time to natural period
R	Ratio of first force peak to second force peak used for buffeting as two conveyances pass each other, taken as 1,5
R_B	Blockage ratio for two conveyances in a shaft
R_G	Gap ratio between conveyances in a shaft
R_D, R_W	Distance and width ratios for air inflow and outflow buffeting
R_S	Shape factor for air inflow and outflow buffeting
S_A	Conveyance size factor
S_{PX}, S_{PZ}	Sidewall proximity factors
S_{SX}, S_{SZ}	Conveyance shape factors in X- and Z-directions
t	Time, s
t_P	Time taken for two conveyances to pass each other in a shaft, s
T	Tension in a rope, N
T_{BOT}	Rope guide tension at the bottom anchor point, N
T_H	Head rope tension at a conveyance, N
T'_H	Increased head rope tension at a conveyance, N
T_L	Rope guide tension at conveyance elevation in the shaft, N
T_M	Rope guide tension at mid-depth of the shaft, N

T_T	Tail rope tension at a conveyance, N
T_{TOP}	Rope guide tension at the top anchor point, N
U_i	Horizontal dimensions of the air inflow or outflow duct, m
v_D	Horizontal component of airflow velocity in a station or side duct, m/s
v_H	Hoisting speed of a conveyance, m/s
v_R	Velocity of a conveyance relative to ventilation airflow speed, m/s
W	Total eccentric payload applied to a conveyance, N
w	Width of the skip stiffener, m
x_C, z_C	Horizontal distances between the conveyance centre of gravity and the geometric centre of the shaft, m
x_{HC}, z_{HC}	Horizontal distance between the conveyance centre of gravity and the centre of hoist rope attachment, m
x_{Hi}, z_{Hi}	Horizontal distance between the conveyance centre of gravity and the centre of hoist rope number i , m
x_P, z_P	Horizontal distance between the payload centre of gravity and the centre of hoist rope attachment, m
x_{Ri}, z_{Ri}	Horizontal distance between the conveyance centre of gravity and the centre of rope guide number i , m
x_{TC}, z_{TC}	Horizontal distance between the conveyance centre of gravity and the centre of tail rope attachment, m
x_{Ti}, z_{Ti}	Horizontal distance between the conveyance centre of gravity and the centre of tail rope number i , m
Y_i	Vertical dimensions of the air inflow or outflow duct, m
α	A dynamic magnification factor
α_T	Winder emergency braking magnification factor for torque and eccentricity
β	Tilt angle of a conveyance subjected to an eccentric payload, rad
β_1, β_2	Angles of the top or bottom of a skip, rad
Δ_C	Change in ambient temperature, °C
Δ_T	Change in rope guide tension, N
θ	General yaw rotation of the conveyance in the shaft, rad
ρ	Air density, kg/m ³
γ_R	Displacement multiplier
ϕ	Latitude of the mine shaft site, positive north and south of the equator, deg
ϕ_A	Angle of the air inflow or outflow duct, rad

ω_E	Radial rotation velocity of the earth, $7,27 \times 10^{-5}$ rad/s
ω_R	Fundamental radial frequency of oscillation of the rope guides, rad/s
ω_{RC}	Fundamental radial frequency of oscillation of the rope guides with the conveyance, rad/s
ω_{RCY}	Fundamental radial frequency of yaw rotation of the rope guides with the conveyance, rad/s
ω_{VT}	Fundamental natural frequency of vertical motion of the conveyance suspended from the head ropes, rad/s

5 Materials

The materials used for rope guides and rubbing ropes shall be materials having guaranteed mechanical properties. It is most common to use high strength steel wire ropes complying with EN 12385-6 and EN 12385-7.

6 Disturbing actions

6.1 Coriolis force

The Coriolis force always acts in a westerly direction for an ascending conveyance, and in an easterly direction for a descending conveyance. The Coriolis force acts on all the moving masses, that is the mass of the conveyance and the head and tail ropes.

The Coriolis force results from the rotation of the earth and masses moving in a vertical direction. The Coriolis force F_C is defined as:

$$F_C = 2mv_h \omega_E \cos \phi \quad (1)$$

where m can be taken as:

$$m = m_C + n_H m_H \frac{L_H}{3} + n_T m_T \frac{L_T}{3} \quad (2)$$

where

- L_H is the head rope length between the conveyance and the sheave, m;
- L_T is the tail rope length below the conveyance, m;
- m_C is the conveyance mass, including mass of rope attachments and payload, kg;
- m_H is the hoist rope unit mass, kg/m;
- m_T is the tail rope unit mass, kg/m;
- n_H is the number of hoist ropes;
- n_T is the number of tail ropes;
- v_H is the hoisting speed of conveyance, m/s;
- ω_E is the radial rotation velocity of the earth, $7,27 \times 10^{-5}$ rad/s;
- ϕ is the latitude of the mine shaft site, positive whether north or south of the equator.