



Designation: ~~D5211-09~~ Designation: D5211 - 10

## Standard Specification for Xylenes for *p*-Xylene Feedstock<sup>1</sup>

This standard is issued under the fixed designation D5211; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope\*

1.1 This specification covers xylenes for *p*-xylene feedstock. These xylenes typically are extracted from reformate.

1.2 The following applies to all specified limits in this specification: for purposes of determining conformance with this specification, an observed value or calculated value shall be rounded off “to the nearest unit” in the last right hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.3 The values stated in SI units are to be regarded as standard. The values given in parentheses are for information only.

1.4 Consult current OSHA regulations, suppliers’ Material Safety Data Sheets (MSDS), and local regulations for all materials used in this specification.

### 2. Referenced Documents

#### 2.1 *ASTM Standards:*<sup>2</sup>

D850 [Test Method for Distillation of Industrial Aromatic Hydrocarbons and Related Materials](#)

D1209 [Test Method for Color of Clear Liquids \(Platinum-Cobalt Scale\)](#)

D3437 [Practice for Sampling and Handling Liquid Cyclic Products](#)

D5194 [Test Method for Trace Chloride in Liquid Aromatic Hydrocarbons](#)

D5386 [Test Method for Color of Liquids Using Tristimulus Colorimetry](#)

D5808 [Test Method for Determining Chloride in Aromatic Hydrocarbons and Related Chemicals by Microcoulometry](#)

D6069 [Test Method for Trace Nitrogen in Aromatic Hydrocarbons by Oxidative Combustion and Reduced Pressure Chemiluminescence Detection](#)

D6563 [Test Method for Benzene, Toluene, Xylene \(BTX\) Concentrates Analysis by Gas Chromatography](#)

D7183 [Test Method for Determination of Total Sulfur in Aromatic Hydrocarbons and Related Chemicals by Ultraviolet Fluorescence](#)

D7184 [Test Method for Ultra Low Nitrogen in Aromatic Hydrocarbons by Oxidative Combustion and Reduced Pressure Chemiluminescence Detection](#)

D7359 [Test Method for Total Fluorine, Chlorine and Sulfur in Aromatic Hydrocarbons and Their Mixtures by Oxidative Pyrohydrolytic Combustion followed by Ion Chromatography Detection \(Combustion Ion Chromatography-CIC\)](#)

D7504 [Test Method for Trace Impurities in Monocyclic Aromatic Hydrocarbons by Gas Chromatography and Effective Carbon Number](#)

D7536 [Test Method for Chlorine in Aromatics by Monochromatic Wavelength Dispersive X-ray Fluorescence Spectrometry](#)

E29 [Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications](#)

#### 2.2 *Other Document:*

OSHA Regulations, 29 CFR paragraphs 1910.1000 and 1910.1200<sup>3</sup>

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee D16 on Aromatic Hydrocarbons and Related Chemicals and is the direct responsibility of Subcommittee D16.01 on Benzene, Toluene, Xylenes, Cyclohexane and Their Derivatives.

Current edition approved Dec-Aug. 1, 2009-2010. Published December 2009; September 2010. Originally approved in 1991. Last previous edition approved in 2007 as D5211 - 07. DOI: 10.1520/D5211-10.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

<sup>3</sup> Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, http://www.access.gpo.gov.

\*A Summary of Changes section appears at the end of this standard.