



**SLOVENSKI STANDARD**  
**SIST EN 17037:2019+A1:2023**

**01-december-2023**

---

**Dnevna svetloba v stavbah**

Daylight in buildings

Tageslicht in Gebäuden

Lumière naturelle dans les bâtiments

**Ta slovenski standard je istoveten z: EN 17037:2018+A1:2021**

---

**ICS:**

<https://standards.sist.si/standards/standard/17037-2019+A1-2023>  
91.160.01 Razsvetljava na splošno Lighting in general

**SIST EN 17037:2019+A1:2023**

**en,fr,de**



EUROPEAN STANDARD

**EN 17037:2018+A1**

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2021

ICS 91.160.01

Supersedes EN 17037:2018

English Version

## Daylight in buildings

Lumière naturelle dans les bâtiments

Tageslicht in Gebäuden

This European Standard was approved by CEN on 29 July 2018 and includes Corrigendum 1 issued by CEN on 13 October 2021 and Amendment 1 approved by CEN on 24 August 2021.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

(<https://standards.iteh.ai>)  
Document Preview

[SIST EN 17037:2019+A1:2023](https://standards.iteh.ai/catalog/standards/sist/d9371f32-79c8-4b8e-98c2-b7b4a45f61e6/sist-en-17037-2019a1-2023)

<https://standards.iteh.ai/catalog/standards/sist/d9371f32-79c8-4b8e-98c2-b7b4a45f61e6/sist-en-17037-2019a1-2023>



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels**

<b>Contents</b>	<b>Page</b>
European foreword.....	5
Introduction .....	6
1 Scope.....	7
2 Normative references.....	7
3 Terms and definitions .....	7
4 Symbols and abbreviations .....	10
5 Assessment of daylight in interior spaces.....	12
5.1 Daylight Provision .....	12
5.1.1 General.....	12
5.1.2 Criteria for daylight provision.....	12
5.1.3 Daylight Provision Calculation Methods.....	13
5.1.4 Verification of daylight provision .....	13
5.2 Assessment for view out.....	13
5.2.1 General.....	13
5.2.2 Criteria for view out.....	14
5.2.3 Verification of view out.....	14
5.3 Exposure to sunlight .....	14
5.3.1 General.....	14
5.3.2 Criteria for exposure to sunlight .....	14
5.3.3 Verification of sunlight duration.....	14
5.4 Protection from glare .....	15
5.4.1 General.....	15
5.4.2 Criteria for protection from glare .....	15
5.4.3 Verification for protection from glare.....	15
Annex A (informative) Recommendations.....	16

<b>A.1</b>	<b>General .....</b>	<b>16</b>
<b>A.2</b>	<b>Recommendations for daylight provision in a space.....</b>	<b>16</b>
<b>A.3</b>	<b>Recommendations for view .....</b>	<b>20</b>
<b>A.4</b>	<b>Recommendation for exposure to sunlight.....</b>	<b>21</b>
<b>A.5</b>	<b>Recommendation for glare protection .....</b>	<b>21</b>
<b>Annex B</b>	<b>(informative) Daylight.....</b>	<b>23</b>
<b>B.1</b>	<b>General .....</b>	<b>23</b>
<b>B.2</b>	<b>Calculation grids .....</b>	<b>23</b>
<b>B.3</b>	<b>Calculation methods .....</b>	<b>24</b>
<b>B.3.1</b>	<b>General .....</b>	<b>24</b>
<b>B.3.2</b>	<b>Calculation method using daylight factor (method 1) .....</b>	<b>24</b>
<b>B.3.3</b>	<b>Calculation method using illuminance level (method 2) .....</b>	<b>25</b>
<b>B.4</b>	<b>Daylight availability.....</b>	<b>25</b>
<b>B.5</b>	<b>Validation of actual daylighting performance .....</b>	<b>26</b>
<b>Annex C</b>	<b>(informative) View out.....</b>	<b>27</b>
<b>C.1</b>	<b>General .....</b>	<b>27</b>
<b>C.2</b>	<b>Quality of view out.....</b>	<b>27</b>
<b>C.3</b>	<b>Width of view out.....</b>	<b>27</b>
<b>C.4</b>	<b>Verification of view out .....</b>	<b>32</b>
<b>C.4.1</b>	<b>Simplified verification method.....</b>	<b>32</b>
<b>C.4.2</b>	<b>Advanced verification method.....</b>	<b>33</b>
<b>Annex D</b>	<b>(informative) Exposure to sunlight .....</b>	<b>36</b>
<b>D.1</b>	<b>General .....</b>	<b>36</b>
<b>D.2</b>	<b>Principle of assessment of hours of sunlight.....</b>	<b>36</b>
<b>D.3</b>	<b>Method using software .....</b>	<b>38</b>
<b>D.4</b>	<b>Method using manual geometric constructions .....</b>	<b>40</b>
<b>D.5</b>	<b>Determination of the position of the sun in the sky.....</b>	<b>40</b>
<b>D.6</b>	<b>Evaluation rules for sunlight duration .....</b>	<b>45</b>

## EN 17037:2018+A1:2021 (E)

<b>D.7</b>	<b>Sunlight duration in the reference point <i>P</i></b> .....	<b>47</b>
<b>D.7.1</b>	<b>Example</b> .....	<b>47</b>
<b>D.7.2</b>	<b>Calculation</b> .....	<b>47</b>
<b>D.7.3</b>	<b>Result</b> .....	<b>47</b>
<b>D.8</b>	<b>On-site verification of duration of exposure to sunlight</b> .....	<b>49</b>
<b>Annex E (informative) Glare</b> .....		<b>50</b>
<b>E.1</b>	<b>General</b> .....	<b>50</b>
<b>E.2</b>	<b>Daylight Glare Probability</b> .....	<b>50</b>
<b>E.3</b>	<b>Annual evaluation</b> .....	<b>51</b>
<b>E.3.1</b>	<b>General</b> .....	<b>51</b>
<b>E.3.2</b>	<b>Simplified annual glare evaluation</b> .....	<b>52</b>
<b>E.3.2.1</b>	<b>General</b> .....	<b>52</b>
<b>E.3.2.2</b>	<b>Solar protection device being opaque in the extended and close position</b> .....	<b>53</b>
<b>E.3.2.3</b>	<b>Solar protection device where the curtain is made of textile, film or perforated opaque material</b> .....	<b>53</b>
<b>E.3.2.4</b>	<b>Non-diffusing glazing device with a low variable light transmittance (e.g. electrochromic glazing)</b> .....	<b>56</b>
<b>E.3.2.5</b>	<b>Sunshine zones</b> .....	<b>59</b>
<b>E.4</b>	<b>Reflections or veiling glare</b> .....	<b>60</b>
<b>E.5</b>	<b>Verification of the glare protection capability of shadings</b> .....	<b>60</b>
<b>Annex F (informative) A-deviations</b> .....		<b>63</b>
<b>Annex G (normative) <math>\square_{A1}</math> Special national conditions <math>\square_{A1}</math></b> .....		<b>64</b>
<b>Bibliography</b> .....		<b>65</b>

## European foreword

This document (EN 17037:2018+A1:2021) has been prepared by Technical Committee CEN/TC 169 “Light and Lighting”, the secretariat of which is held by DIN.

This document includes the corrigendum EN 17037:2018/AC:2021 issued by CEN on 13 October 2021, which corrects symbol " $d_w$ " in Table 1, the table reference in the 5<sup>th</sup> paragraph of E.3.1 and replaces Table E.8.

The start and finish of text introduced or altered by corrigendum is indicated in the text by tags AC AC.

This document includes Amendment 1 approved by CEN on 24 August 2021 (BT C150/2021).

The start and finish of text introduced or altered by amendment is indicated in the text by tags A1 A1.

This document supersedes EN 17037:2018 and EN 17037:2018/AC:2021.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2022, and conflicting national standards shall be withdrawn at the latest by June 2022.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

**EN 17037:2018+A1:2021 (E)****Introduction**

Daylight should be a significant source of illumination for all spaces with daylight opening(s). Daylight is strongly favoured by building occupants as a way to adequately illuminate the indoor surfaces, and to save energy for electrical lighting.

Daylight can provide significant quantities of light indoors, with high colour rendering and variability, changing through the day and the seasons. Daylight openings provide views and connection to the outside and contribute to the psychological well-being of occupants. A daylight opening can also provide exposure to sunlight indoors, which is important, for example, in dwellings, hospital wards and nurseries. In a space, where activities comparable to reading, writing or using display devices are carried out, a shading device should be provided to reduce visual discomfort. The standard addresses daylighting performance over the year. Daylight should illuminate spaces during a significant fraction of the annual daylight hours over the year. Daylight provision depends firstly on the availability of daylight outside (i.e. the prevailing climate at the site) and, thereafter, the environment surrounding the building, the components immediate around the daylight opening and the configuration of the interior spaces.

This standard encourages building designers to assess and ensure successfully daylighted spaces. It also allows building designers and developers to target ambitions with respect to daylighting, as well as addressing other issues related to daylight design, such as view out, protection against glare, and exposure to sunlight.

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[SIST EN 17037:2019+A1:2023](https://standards.iteh.ai/catalog/standards/sist/d9371f32-79c8-4b8e-98c2-b7b4a45f61e6/sist-en-17037-2019a1-2023)

<https://standards.iteh.ai/catalog/standards/sist/d9371f32-79c8-4b8e-98c2-b7b4a45f61e6/sist-en-17037-2019a1-2023>



## 1 Scope

This document specifies elements for achieving, by means of natural light, an adequate subjective impression of lightness indoors, and for providing an adequate view out. In addition, recommendations for the duration of sunshine exposure within occupied rooms are given.

This document gives information on how to use daylighting to provide lighting within interiors, and how to limit glare. This document defines metrics used for the evaluation of daylighting conditions and gives principles of calculation and verification. These principles allow to address the issue of variability of daylight over the days and the year.

This document applies to all spaces that may be regularly occupied by people for extended periods except where daylighting is contrary to the nature and role of the actual work done.

The specification of lighting requirements for humans in indoor work places including visual tasks are given in EN 12464-1 and are not part of this document.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12216, *Shutters, external blinds, internal blinds — Terminology, glossary and definitions*

EN 12464-1, *Light and lighting — Lighting of work places — Part 1: Indoor work places*

EN 12665:2018, *Light and lighting — Basic terms and criteria for specifying lighting requirements*

EN 14501:2005, *Blinds and shutters — Thermal and visual comfort — Performance characteristics and classification*

ISO 15469:2004, *Spatial distribution of daylight — CIE standard general sky*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 12665:2018 and the following apply.

### 3.1

#### **daylight**

visible part of global solar radiation

Note 1 to entry: Also defined as part of global solar radiation capable of causing a visual sensation [CIE ILV 278].

[SOURCE: EN 12665:2018, 3.4.7, modified – note to entry added]

**EN 17037:2018+A1:2021 (E)****3.2****daylight factor**

ratio of the illuminance at a point on a given plane due to the light received directly or indirectly from a sky of assumed or known luminance distribution, to the illuminance on a horizontal plane due to an unobstructed hemisphere of this sky, excluding the contribution of direct sunlight to both illuminances

Note 1 to entry: Glazing, dirt effects, etc. are included.

Note 2 to entry: When calculating the lighting of interiors, the contribution of direct sunlight needs to be considered separately.

Note 3 to entry: The term daylight factor is normally used when considering an overcast sky as sky type 1 or 16 in ISO 15469.

[SOURCE: EN 12665:2018, 3.4.8, CIE ILV 17-279, modified – note 3 to entry added]

**3.3****daylight opening**

any area in the building envelope that is capable of admitting daylight to an interior

**3.4****daylight provision**

level of illuminance achieved across a fraction of a reference plane for a fraction of daylight hours within a space

**3.5****diffuse horizontal illuminance (from the sky)**

illuminance produced by skylight on a horizontal surface on the Earth

[SOURCE: CIE ILV 17-302]

**3.6****discomfort glare**

glare that causes discomfort without necessarily impairing the vision of objects

[SOURCE: EN 12665:2018, 3.2.23, CIE ILV 17-333]

**3.7****glare**

condition of vision in which there is discomfort or a reduction in the ability to see details or objects, caused by an unsuitable distribution or range of luminance, or by extreme contrasts

[SOURCE: EN 12665:2018, 3.1.8, CIE ILV 17-492]

**3.8****global horizontal illuminance**

illuminance produced by daylight on a horizontal surface on the Earth

[SOURCE: CIE ILV 17-495]

**3.9****no-ground line for view**

divider between the part of the space from which the ground can be seen directly by a sitting person and the part from which it cannot

**3.10****no-sky line for view**

divider between the part of the space from which the sky can be seen directly by a sitting person and the part from which it cannot

**3.11****obstruction**

anything outside a building which prevents the direct view of part of the sky

[SOURCE: CIE ILV 17-834]

**3.12****outside distance of view**

distance from the inner surface of view opening to opposite major obstructions located in front of the opening

**3.13****reference plane**

plane in a space on which illuminances and/or daylight factors are calculated, specified or measured

**3.14****reference point for view**

position from which the view is assessed

**3.15****skylight**

part of sky radiation capable of causing a visual sensation

[SOURCE: CIE ILV 17-1194]

**3.16****solar altitude**

vertical angle between the line passing through the centre of the solar disc and the horizontal plane measured from the reference/observation point

**3.17****solar azimuth**

horizontal angle between vertical plane passing through the geographical north and vertical plane passing through the centre of the solar disc

Note 1 to entry: Solar azimuth is measured clockwise from due North from 0° to 360°

**3.18****sunlight**

part of direct solar radiation capable of causing a visual sensation

[SOURCE: CIE ILV 17-1281]

**3.19****sunlight exposure**

sum of the time (hours) (e.g. on a given day) within a given period during which the sun is above the actual horizon with a cloudless sky, which may be limited by permanent obstructions like mountains, buildings, etc.

**EN 17037:2018+A1:2021 (E)****3.20****utilized area**

fraction of the space intended to be occupied

**3.21****veiling reflections**

specular reflections that appear on the object viewed and that partially or wholly obscure the details by reducing contrast

[SOURCE: EN 12665:2018, 3.2.24, CIE ILV 17-1396]

**3.22****view**

visual contact with the surrounding through an opening in the surface of a building, providing information about the surrounding landscape/cityscape, possibility to experience the weather changes and to follow the time over the day

**3.23****view opening**

any area in the building envelope admitting a view, including glazed walls, glazed doors, etc

**4 Symbols and abbreviations**

For the purposes of this document, the specific symbols listed in Table 1 apply.

**Table 1 — Symbols and units**

Symbol	Name of quantity	Unit
$A_{\text{façade}}$	Area of the façade	m <sup>2</sup>
$A_{\text{glazing}}$	Area of the glazing	m <sup>2</sup>
$D$	Daylight factor	%
$DGP$	Daylight glare probability	-
$DGP_{e < 5 \%}$	$DGP$ -value, that is not exceeded in more than 5 % of the occupation time	-
$DGP_S$	Simplified $DGP$ value	-
$DGP_t$	Threshold $DGP$ value for a critical glare situation	-
$D_T$	Target daylight factor	%
$D_{TM}$	Minimum target daylight factor	%
$\langle AC \rangle d_w \langle AC \rangle$	Distance from daylight opening	m
$ET$	Equation of time	h
$E_v$	Vertical illuminance at eye level	lx (lm·m <sup>-2</sup> )

Symbol	Name of quantity	Unit
$E_{v,d}$	Diffuse horizontal illuminance (from the sky)	lx ( $\text{lm}\cdot\text{m}^{-2}$ )
$E_{v,d,med}$	Median diffuse horizontal skylight illuminance	lx ( $\text{lm}\cdot\text{m}^{-2}$ )
$E_{v,g}$	Global horizontal illuminance	lx ( $\text{lm}\cdot\text{m}^{-2}$ )
$E_{v,g,med}$	Median global horizontal daylight illuminance	lx ( $\text{lm}\cdot\text{m}^{-2}$ )
$F_{DGP,exceed}$	Fraction of reference usage time for which a threshold value $DGP_t$ is exceeded	-
$F_{plane,\%}$	Fraction of the reference plane for target illuminance level	%
$F_{time,\%}$	Fraction of time for which a given value of illuminance is exceeded	%
$f_{glaz}$	Glazing fraction	%
$i$	Number of glare sources	-
$J$	$J$ is the day number of the year (e.g. for 1st January, $J = 1$ and for 31st December, $J = 365$ , February is taken to have 28 days)	-
$LT$	Local clock time	h
$L_s$	Luminance of glare source	$\text{cd}/\text{m}^2$
$L_v$	Sky luminance	$\text{cd}/\text{m}^2$
$P$	Position index	-
$TST$	True solar time	h
$t_d$	Daylight hours	h
$t_{end}$	Time when the duration of sunlight is ending by the obstruction or when the solar azimuth $\alpha_s$ reaches the end of the acceptance angle $\alpha_a$	h
$t_{start}$	Time when the sun rays begin to reach reference point	h
$\alpha_a$	Acceptance angle	degrees
$\alpha_{obs}$	Angle of obstruction	degrees
$\alpha_s$	Solar azimuth (measured clockwise from due North)	degrees
$\alpha_{wn,s}$	Azimuth angle of daylight opening normal, measured from South	degrees
$\gamma_s$	Solar altitude	degrees

**EN 17037:2018+A1:2021 (E)**

Symbol	Name of quantity	Unit
$\gamma_{s,\min}$	Minimum Solar altitude	degrees
$\Delta$	Declination of the sun	degrees
$\Lambda$	Geographical longitude of the site East (+) or West (-) of Greenwich	degrees
$\lambda_s$	Longitude of standard meridian	degrees
$\tau_{\text{glazing}}$	Normal-hemispherical light transmittance of the glazing	-
$\tau_{v,n-\text{dif}}$	Normal-diffuse light transmittance	-
$\tau_{v,n-n}$	Normal-normal light transmittance	-
$\varphi$	Geographical latitude of the site	degrees
$\omega_s$	Solid angle subtended by the glare source	sr
$\omega_\eta$	The hour angle $\omega_\eta$ is counted from the meridian as positive towards the afternoon and negative towards the morning.	degrees

**5 Assessment of daylight in interior spaces****5.1 Daylight Provision****5.1.1 General**

Daylight can contribute significantly to the lighting needs of any type of building. This means that daylight openings should have appropriate areas to provide sufficient daylight throughout the year. Thus, the evaluation of daylight provision should make account of the availability of daylight at the site in addition to accounting for the properties of the space (e.g. external obstruction, glazing transmittance, thickness of walls and roofs, internal partition and surface reflectance, furniture).

**5.1.2 Criteria for daylight provision**

A space is considered to provide adequate daylight if a target illuminance level is achieved across a fraction of the reference plane within a space for at least half of the daylight hours.

In addition, for spaces with vertical or inclined daylight openings, a minimum target illuminance level is also to be achieved across the reference plane.

The reference plane of the space is located 0,85 m above the floor, unless otherwise specified. A small fraction of the reference plane may be disregarded to account for singularities.

Values for target illuminances, minimum target illuminances and fractions of reference plane are given in Table A.1.