



**SLOVENSKI STANDARD**  
**oSIST prEN ISO 14456:2023**  
**01-marec-2023**

---

**Plinske jeklenke - Lastnosti plina in pripadajoči razvrstitveni razredi (FTSC)**  
**(ISO/DIS 14456:2023)**

Gas cylinders - Gas properties and associated classification (FTSC) codes (ISO/DIS 14456:2023)

Gasflaschen - Eigenschaften von Gasen und zugehörige Klassifizierungscodes (FTSC) (ISO/DIS 14456:2023)

Bouteilles à gaz - Propriétés des gaz et codes de classification associés (FTSC) (ISO/DIS 14456:2023)

<https://standards.iteh.ai/catalog/standards/sist/26024770-e3e6-4a4c-b1c6-04765c09e212/osist-pr-en-iso-14456-2023>

**Ta slovenski standard je istoveten z: prEN ISO 14456 rev**

---

**ICS:**

23.020.35      Plinske jeklenke                      Gas cylinders

**oSIST prEN ISO 14456:2023**                      **en,fr,de**



# DRAFT INTERNATIONAL STANDARD

## ISO/DIS 14456

ISO/TC 58/SC 2

Secretariat: **AFNOR**Voting begins on:  
**2023-02-01**Voting terminates on:  
**2023-04-26**

---

---

## Gas cylinders — Gas properties and associated classification (FTSC) codes

*Bouteilles à gaz — Propriétés des gaz et codes de classification associés (FTSC)*

ICS: 23.020.35

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[oSIST prEN ISO 14456:2023](https://standards.iteh.ai/catalog/standards/sist/26024770-e3e6-4a4c-b1c6-04765c09e212/osist-pren-iso-14456-2023)<https://standards.iteh.ai/catalog/standards/sist/26024770-e3e6-4a4c-b1c6-04765c09e212/osist-pren-iso-14456-2023>

This document is circulated as received from the committee secretariat.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

**ISO/CEN PARALLEL PROCESSING**



Reference number  
ISO/DIS 14456:2023(E)

© ISO 2023

# iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 14456:2023](https://standards.iteh.ai/catalog/standards/sist/26024770-e3e6-4a4c-b1c6-04765c09e212/osist-pren-iso-14456-2023)

<https://standards.iteh.ai/catalog/standards/sist/26024770-e3e6-4a4c-b1c6-04765c09e212/osist-pren-iso-14456-2023>



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Gas properties</b> .....	<b>2</b>
4.1 Numerical gas code (FTSC).....	2
4.1.1 General.....	2
4.1.2 Fire potential, category I.....	2
4.1.3 Acute toxicity, category II.....	3
4.1.4 State of the gas (in the cylinder at 15 °C), category III.....	3
4.1.5 Corrosiveness, category IV.....	4
<b>5 List of gases and liquids with the corresponding FTSC codes</b> .....	<b>4</b>
5.1 Basic principles and single gases.....	4
5.2 Assignment of a gas mixture to a group.....	5
5.3 Tables of compatible groups of gases and liquids.....	5
<b>Annex A (informative) Chemical and hazard data related to FTSC entries proposed for addition to ISO 14456:2015</b> .....	<b>19</b>
<b>Bibliography</b> .....	<b>46</b>

(standards.iteh.ai)

[oSIST prEN ISO 14456:2023](https://standards.iteh.ai/catalog/standards/sist/26024770-e3e6-4a4c-b1c6-04765c09e212/osist-pren-iso-14456-2023)

<https://standards.iteh.ai/catalog/standards/sist/26024770-e3e6-4a4c-b1c6-04765c09e212/osist-pren-iso-14456-2023>

## ISO/DIS 14456:2022(E)

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 58, Gas cylinders, Subcommittee SC 2, *Cylinder valves*

This second edition cancels and replaces the first edition (ISO 14456:2015), which has been technically revised.

The main changes are as follows:

- Corrections to CAS numbers and FTSC codes;
- Consequential revisions as a result of a new edition of ISO 5145:2017; and
- Addition of new FTSC codes for commonly used gases and liquids.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

This document establishes a method of allocating a four-digit code number (FTSC) to any gases and liquids that are transported under pressure or mixture of gases contained in cylinders. This code number categorizes the gas, liquids that are transported under pressure or gas mixture in terms of its physical-chemical properties and/or flammability, toxicity, state of the gas, and corrosiveness (see 4.1). FTSC is the abbreviation of these properties.

The FTSC code enables gases and liquids that are transported under pressure or gas mixtures to be assigned to one of the 15 “compatible” gas groups.

The properties and the selection criteria are aligned as appropriate with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[oSIST prEN ISO 14456:2023](https://standards.iteh.ai/catalog/standards/sist/26024770-e3e6-4a4c-b1c6-04765c09e212/osist-pren-iso-14456-2023)

<https://standards.iteh.ai/catalog/standards/sist/26024770-e3e6-4a4c-b1c6-04765c09e212/osist-pren-iso-14456-2023>





# Gas cylinders — Gas properties and associated classification (FTSC) codes

## 1 Scope

This document gives a list of FTSC (fire potential, i.e. “oxidizing power and flammability”, toxicity, state of the gas, and corrosiveness) codes determined according to the relevant properties of gases and of some liquids that are transported under pressure.

It does not cover material compatibility with gases which is covered by ISO 11114 (all parts).

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10156, *Gas cylinders — Gases and gas mixtures — Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets*

ISO 10298, *Gas cylinders — Gases and gas mixtures — Determination of toxicity for the selection of cylinder valve outlets*

ISO 10286:2021, *Gas cylinders — Vocabulary*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 10286:2021 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

### 3.1

#### **gas mixture**

combination of different single gases and/or liquids deliberately mixed in specified proportions resulting in a homogeneous gaseous mixture.

[SOURCE: ISO 10286:2021, definition 3.5.2, modified change may be needed later if ISO 10286 definition changes in future edition]

### 3.2

#### **liquefied gas**

gas, which, when packaged for transport, is partially liquid (or solid) at temperatures above  $-50\text{ °C}$

[SOURCE: ISO 10286:2021, definition 3.5.4 change may be needed later if ISO 10286 definition changes in future edition]

## ISO/DIS 14456:2022(E)

### 3.3

#### **compressed gas**

gas, which, when packaged under pressure for transport, is entirely gaseous at  $-50\text{ °C}$

Note 1 to entry: This category includes all gases with a critical temperature less than or equal to  $-50\text{ °C}$ .

[SOURCE: ISO 10286:2021, definition 3.5.3 change may be needed later if ISO 10286 definition changes in future edition]

### 3.4

#### **lethal concentration 50**

##### **LC<sub>50</sub>**

concentration of a substance in air exposure to which, for a specified length of time, it is expected to cause the death of 50 % of the entire defined experimental animal population after a defined time period

Note 1 to entry: Lethal concentration is usually measured as ppm (volume fraction) or  $\text{mg}/\text{m}^3$ .

[SOURCE: ISO 10298:2018, definition 3.1 without Note 1 to entry]

## 4 Gas properties

### 4.1 Numerical gas code (FTSC)

#### 4.1.1 General

The code number assigned to a gas or liquid is based on the following four physical-chemical properties:

- a) Category I (F): fire potential, i.e. “oxidizing power and flammability”, which defines the gas behaviour with respect to combustion;
- b) Category II (T): acute toxicity;
- c) Category III (S): gas state, defining the physical state of the fluid in the cylinder at  $15\text{ °C}$  within a given pressure range;
- d) Category IV (C): corrosiveness (ability to damage or destroy living tissues: eyes, skin, and mucous membranes, or the potential for an acid/base chemical reaction).

Each category is subdivided into different characteristics (subdivisions), each identified by a different digit. In this way, a gas in a given state is characterized by a series of four digits (one digit per category) as illustrated below.

#### 4.1.2 Fire potential, category I

Subdivision 0: inert (any gas not classified under subdivisions 1 to 5 below);

Subdivision 1: supports combustion (gas having an oxidizing power equal to or less than a mixture containing 23,5 % of oxygen in nitrogen);

Subdivision 2: flammable (gas having flammability limits in air);

NOTE 1 See ISO 10156 for more information.

Subdivision 3: pyrophoric (spontaneously flammable);

Subdivision 4: oxidizing (gas having an oxidizing power greater than a mixture containing 23,5 % O<sub>2</sub> in N<sub>2</sub>);

NOTE 2 See ISO 10156 for more information.

Subdivision 5: chemically unstable (flammable and subject to rapid decomposition or polymerization).

NOTE 3 When considering the properties of gases from subdivisions 1 and 4, the following applies:

- a) Subdivision 4 considers the risk of accelerating combustion more than air does;
- b) For gas material compatibility with gases under pressure of subdivisions 1 and 4, it is considered that the risk of ignition exists when the oxygen partial pressure is more than 30 bar;
- c) For valve outlet selection (for example, see ISO 5145), the risk is to mix a flammable gas (subdivision 2 and/or 3) with a gas of subdivision 1 and/or 4.

#### 4.1.3 Acute toxicity, category II

Subdivision 0: supporting human life;

Subdivision 1: non-toxic  $LC_{50}$  (1 h) > 0,5 % by volume (5 000 ppm);

Subdivision 2: toxic; 0,02 % by volume (200 ppm) <  $LC_{50}$  (1 h) ≤ 0,5 % by volume (5 000 ppm);

Subdivision 3: very toxic  $LC_{50}$  (1 h) ≤ 0,02 % by volume (200 ppm)

NOTE See ISO 10298:2018 for more information. For  $LC_{50}$  values see Table B.1 of ISO 10298:2018

#### 4.1.4 State of the gas (in the cylinder at 15 °C), category III

All pressures for compressed gases are working pressures according to the definition given in ISO 10286.

For liquefied gases, this is the developed pressure at 65 °C (normally equal to the cylinder test pressure).

Subdivision 0: liquefied gas of 35 bar or less;

Subdivision 1: liquefied gas at a pressure greater than 35 bar;

Subdivision 2: liquid withdrawal – liquefied gas (optional);

Subdivision 3: dissolved gas;

Subdivision 4: gas phase withdrawal at 35 bar or less;

Subdivision 5: compressed gas between 35 bar and 250 bar (Europe);

Subdivision 6: compressed gas between 35 bar and 207 bar (North America);

Subdivision 7: compressed gas above 207 bar and up to 350 bar (North America) or above 250 bar up to 350 bar (Europe).

NOTE 1 Subdivisions 5 and 6 have been adopted as a result of a compromise between the European and the North American approach. The European preference for a limit of 250 bar reflects the current tendency towards higher pressure applications. The current North American practice requires a limit of 207 bar for which their pressure reducing valves are designed. This is the working pressure at the referenced temperature of 15 °C. Therefore, three pressure classes have been retained. Other jurisdictions might use different values.

Either subdivision 5 or subdivision 6 shall be used, never both. The selection of either subdivision will determine the applicable pressure for subdivision 7.

Subdivision 5 or 6: medium pressure range, each user being required to select one subdivision exclusively to determine the upper limit of the medium pressure range.

Subdivision 7: high pressure range, the lower limit of which depends on the subdivision selected for the medium pressure range.

## ISO/DIS 14456:2022(E)

After the introduction of subdivisions 5, 6, and 7, a number of pressure ranges have been (or are being) established to make the selection of the proper cylinder valve outlet connection (e.g. 500 bar, 800 bar, sub atmospheric pressure). These ranges have been chosen to protect downstream regulators and other ancillary equipment from over-pressurized conditions. Consequently, for the tables in 5.3, the third digit (S) used for all compressed gases is “5” to indicate that this is a compressed gas.

NOTE 2 Subdivisions 8 and 9 have been allocated for liquid withdrawal cylinders of cryogenic gases in the USA.

### 4.1.5 Corrosiveness, category IV

Subdivision 0: non-corrosive;

Subdivision 1: non-halogen acid forming;

Subdivision 2: basic;

Subdivision 3: halogen acid forming.

NOTE See ISO 13338 for more information. For corrosiveness subdivisions, see Table 1 of ISO 13338:2022.

## 5 List of gases and liquids with the corresponding FTSC codes

### 5.1 Basic principles and single gases

The FTSC code enables the assignment of any gas (including gas mixtures) or any liquid to be packaged under pressure to one of the 15 “compatible” gas groups listed in the table below.

NOTE Attention is drawn to the fact that the only purpose of the numerical code is to group compatible gases together in order that particular valve outlets might be assigned to each group. Use of the code is limited only to the assignment of valve outlets.

<https://standards.iteh.ai/catalog/standards/sist/26024770-e3e6-4a4c-b1c6-04765c09e212/osist->

**Table 1 — Characteristics of groups**

Group	Characteristics
1	Non-flammable, non-toxic gases and qualifying gas mixtures, less stable thermally than group 3
2 <sup>a</sup>	Carbon dioxide
3	Non-flammable, non-toxic, and thermally stable gases (except carbon dioxide) and qualifying gas mixtures
4	Non-flammable, toxic, and corrosive (or corrosive by hydrolysis) gases and qualifying gas mixtures
5 <sup>a</sup>	Air
6	Flammable and non-toxic gases and qualifying gas mixtures
7	Flammable, toxic, and corrosive (basic) gases and qualifying gas mixtures
8	Flammable, toxic, and corrosive (acidic) or non-corrosive gases and qualifying gas mixtures
9	Spontaneously flammable gases and qualifying gas mixtures
10 <sup>a</sup>	Oxygen
11 <sup>a</sup>	Nitrous oxide
12	Oxidizing, toxic, and/or corrosive gases and qualifying gas mixtures
13	Flammable gases and qualifying gas mixtures subject to decomposition or polymerization
14 <sup>a</sup>	Acetylene
15	Oxidizing, non-toxic, and non-corrosive gas mixtures

<sup>a</sup> Groups 2, 5, 10, 11, and 14 only contain one single gas and are assigned to individual named gases from which mixtures and other gases are excluded.

## 5.2 Assignment of a gas mixture to a group

For the purposes of this document, a gas mixture is defined as an intentional combination of two or more gases, which might be either in the gaseous phase or liquefied under pressure when in a gas cylinder.

NOTE This document does not attempt to identify gas mixtures which can be safely and satisfactorily prepared; this is the responsibility of the gas manufacturer. It does not describe any methods or techniques for preparing gas mixtures.

The principle of allocation of a four-digit numerical code (FTSC) to gas mixtures is the same as that for single gases. The allocation of the FTSC code to a gas mixture, which allows the assignment of this mixture to one of the group of gases and gas mixtures (see [Table 1](#)), depends on the flammability, oxidizing power, toxicity, and corrosiveness of the final mixture. The determination of flammability and oxidizing power is given in ISO 10156, that of toxicity in ISO 10298, and that for corrosiveness in ISO 13338.

Mixtures containing spontaneously flammable gases (i.e. pyrophoric gases such as silane in [Table 10](#)) shall be considered as spontaneously flammable gas mixtures if the content of the pyrophoric gas(es) is more than 1 % (by volume).

[Table 16](#) gives the complete list of gases in alphabetical order.

## 5.3 Tables of compatible groups of gases and liquids

**Table 2 — Gases and gas/liquid mixtures belonging to group 1 (non-flammable, non-toxic gases and gas mixtures, less stable thermally than group 3)**

Gas	FTSC code	Synonym	CAS Number
Bromochlorodifluoromethane	0100	R12B 1	353-59-3
Bromochloromethane <sup>a</sup>	0100	Halon 1011	74-97-5
Bromotrifluoromethane	0100	Trifluorobromomethane R13B1	75-63-8
Chlorodifluoromethane	0100	Monochlorodifluoromethane R22	75-45-6
Chlorodifluoromethane and Chloropentafluoroethane	0100	R502	azeotropic mixture
Chloroheptafluorocyclobutane <sup>a</sup>	0100	C317	377-41-3
Chloropentafluoroethane	0100	Monochloropentafluoroethane R115	76-15-3
1-Chloro-1,2,2,2-tetrafluoroethane	0100	R124	2837-89-0
1-Chloro-2,2,2-trifluoroethane	0100	R133a	75-88-7
Chlorotrifluoromethane	0100	Monochlorotrifluoromethane R13	75-72-9
Chlorotrifluoromethane and Trifluoromethane	0100	R503	azeotropic mixture
1,2 - dibromo-1,1-difluoroethane <sup>a</sup>	0100		75-82-1
1, 2-Dibromotetrafluoroethane <sup>a</sup>	0100	R114B2	124-73-2
1, 2-Dichlorodifluoroethylene	0100	R1112a	79-35-6
Dichlorodifluoromethane	0100	R12	75-71-8
Dichlorodifluoromethane and 1,1-Difluoroethane	0100	R500	azeotropic mixture
Dichlorofluoromethane	0100	R21	75-43-4
1,2-Dichlorohexafluorocyclobutane <sup>a</sup>	0100	C316	356-18-3
1,1-Dichlorotetrafluoroethane	0100	R114a	374-07-2

<sup>a</sup> Some products, being liquid at normal ambient conditions, are included since they might be supplied in non-pressurized containers. They are included in this grouping because valve outlets are necessary when these products are supplied together with a propellant in a pressurized container.

## ISO/DIS 14456:2022(E)

Table 2 (continued)

Gas	FTSC code	Synonym	CAS Number
1,2-Dichlorotetrafluoroethane	0100	R114	76-14-2
2,2-Dichloro-1,1,1-trifluoro ethane <sup>a</sup>	0100	R123	306-83-2
Difluoromethane, Pentafluoroethane, and 1,1,1,2-Tetrafluoroethane	0100	R407A, R407B, R407C	zeotropic mixture
Heptafluoropropane	0100	R227	431-89-0
Hexafluoroethane	0100	Perfluoroethane R116	76-16-4
Hexafluoropropylene	0100	Hexafluoropropene R1216	116-15-4
Methylene bromide <sup>a</sup>	0100	Dibromomethane	74-95-3
Octafluorobut-2-ene	0100	R1318	360-89-4
Octafluorocyclobutane	0100	Perfluorocyclobutane RC318	115-25-3
Octafluoropropane	0100	Perfluoropropane R218	76-19-7
Pentachlorofluoroethane <sup>a</sup>	0100		29756-45-4
Pentafluoroethane	0100	R125	354-33-6
Pentafluoroethane, 1,1,1-Trifluoroethane, and 1,1,1,2-Tetrafluoroethane	0100	R404A	zeotropic mixture
Pentafluoroethyl iodide <sup>a</sup>	0100		354-64-3
Perfluorobutane	0100	R610	355-25-9
Sulfur hexafluoride	0100		2551-62-4
1,1,1,2-Tetrachlorodifluoroethane (solid)	0100	R112a	76-11-9
1,1,2,2-Tetrachlorodifluoroethane <sup>a</sup>	0100	R112	76-12-0
Tetrachloromethane <sup>a</sup>	0100	Carbon tetrachloride	56-23-5
1,1,2,2-Tetrafluoro-1-chloroethane	0100	R124a	354-25-6
1,1,1,2-Tetrafluoroethane	0100	R134a	811-97-2
1,1,2-Trichloroethene <sup>a</sup>	0100	Trichloroethylene	79-01-6
Trichlorofluoromethane <sup>a</sup>	0100	Trichloromonofluoromethane, R11	75-69-4
1,1,1-Trichlorotrifluoroethane <sup>a</sup>	0100	R113a	354-58-5
1,1,2-Trichlorotrifluoroethane <sup>a</sup>	0100	R113	76-13-1
Trifluoromethane	0100	Fluoroform, R23	75-46-7

<sup>a</sup> Some products, being liquid at normal ambient conditions, are included since they might be supplied in non-pressurized containers. They are included in this grouping because valve outlets are necessary when these products are supplied together with a propellant in a pressurized container.

Table 3 — Gases belonging to group 2 (carbon dioxide)

Gas	FTSC code	Synonym	CAS Number
Carbon dioxide	0110	Carbonic acid anhydride, R744	124-38-9

Table 4 — Gases and gas mixtures belonging to group 3 (non-flammable, non-toxic, and thermally stable gases and gas mixtures)

Gas	FTSC code	Synonym	CAS Number
Argon	0150		7440-37-1
Helium	0150		7440-59-7
Krypton	0150		7439-90-9
Neon	0150		7440-01-9

<sup>a</sup> FTSC code due to the gas having a critical temperature above 15 °C.



Table 4 (continued)

Gas	FTSC code	Synonym	CAS Number
Nitrogen	0150		7727-37-9
Xenon	0110 <sup>a</sup>		7440-63-3
Tetrafluoromethane	0150	Carbon tetrafluoride, R14	75-73-0

<sup>a</sup> FTSC code due to the gas having a critical temperature above 15 °C.

Table 5 — Gases and gas mixtures belonging to group 4 (non-flammable, toxic, and corrosive (or corrosive by hydrolysis) gases and gas mixtures)

Gas	FTSC code <sup>c</sup>	Synonym	CAS Number
Antimony pentafluoride <sup>a</sup>	0303		7783-70-2
Arsenic pentafluoride	0303		7784-36-3
Boron trichloride	0203	Boron chloride	10294-34-5
Boron trifluoride	0253	Boron fluoride	7637-07-2
Bromoacetone <sup>a</sup>	(0303)- <b>2203<sup>b</sup></b>		598-31-2
Bromodifluoromethane	0100		1511-62-2
Carbonyl fluoride	0213	Fluorophosgene	353-50-4
Cyanogen chloride	0303		506-77-4
Deuterium chloride	0213		7698-05-7
Deuterium fluoride	0203		14333-26-7
Dibromodifluoromethane <sup>a</sup>	0100	R12B2	75-61-6
Dichloro-2-chlorovinyl arsine <sup>a</sup>	0303	Lewisite	541-25-3
Diphosgene <sup>a</sup>	0303		503-38-8
Ethylchloroarsine <sup>a</sup>	0303		598-14-1
Germanium tetrachloride <sup>a</sup>	0203	Germanium chloride	10038-98-9
Germanium tetrafluoride	0203	Germanium fluoride	7783-58-6
Hexafluoroacetone	0203	1,1,1,3,3,3,-hexafluoro-2-propanone	684-16-2
Hydrogen bromide	0203	Hydrobromic acid (anhydrous)	10035-10-6
Hydrogen chloride	0213	Hydrochloric acid (anhydrous)	7647-01-0
Hydrogen fluoride <sup>a</sup>	0203	Hydrofluoric acid (anhydrous)	7664-39-3
Hydrogen iodide	0203	Hydroiodic acid (anhydrous)	10034-85-2
Iodotrifluoromethane	(0200)- <b>0100<sup>b</sup></b>	Trifluoromethyl iodide	2314-97-8
Methyl bromide	(0300)- <b>2200<sup>b</sup></b>	Bromomethane	74-83-9
Methyldichloroarsine <sup>a</sup>	0303		593-89-5
Methyl iodide <sup>a</sup>	0223	Iodomethane	74-88-4
Nitrosyl chloride	0303		2696-92-6
Octafluorocyclopentene <sup>a</sup>	0220		559-40-0
Perfluoro-2-butene	(0200)- <b>0100<sup>b</sup></b>	Octafluorobutene; R1318	360-89-4
Phenylcarbylamine Chloride <sup>a</sup>	(0303)- <b>2303<sup>b</sup></b>		622-44-6

<sup>a</sup> Some products, being liquid at normal ambient conditions, are included since they might be supplied in non-pressurized containers. They are included in this grouping because valve outlets are necessary when these products are supplied together with a propellant in a pressurized container.

<sup>b</sup> To be consistent with ISO 10298, the former FTSC code is completed by the new one in bold figures corresponding to the new toxicity level.

<sup>c</sup> Some gases with an FTSC code of 0100 are listed in [table 5](#) because they historically have been assigned valve outlet connections specified for this group, see ISO 5145:2017.