

ISO/TC 94/SC 15

Secretariat: DIN

Voting begins on:  
2020-10-06

Voting terminates on:  
2020-12-01

---

---

## Respiratory protective devices — Performance requirements —

### Part 4: Requirements for supplied breathable gas RPD

*Appareils de protection respiratoire — Exigences de performances —*

*Partie 4: Exigences pour les équipements de protection respiratoire  
alimentés en gaz respirable*

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



---

---

Reference number  
ISO/FDIS 17420-4:2020(E)

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/645e5d2c-0e62-4a08-b5e4-13bffc7104/iso-fdis-17420-4>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>vi</b>
<b>Introduction</b> .....	<b>vii</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms, definitions, abbreviations and symbols</b> .....	<b>2</b>
3.1 Terms and definitions.....	2
3.2 Abbreviated terms.....	3
3.3 Symbols.....	4
<b>4 Classification overview</b> .....	<b>4</b>
<b>5 General requirements</b> .....	<b>5</b>
5.1 General.....	5
5.2 Field of vision.....	5
5.3 Resistance to flame – Single burner dynamic.....	5
5.4 Compatibility with additional equipment.....	5
5.5 Monitor performance.....	5
5.6 Warning and checking device(s).....	5
5.6.1 Performance of warning device(s).....	5
5.6.2 Type Sxxxx RPD.....	6
5.6.3 Type Sxxxx RPD using generated breathable gas.....	6
5.6.4 Type SY RPD.....	6
5.6.5 Performance of checking device.....	6
5.7 Protection class determination.....	6
5.7.1 General.....	6
5.7.2 Total inward leakage (TIL).....	6
5.8 Validation by practical performance.....	6
5.8.1 General.....	6
5.8.2 Donning/doffing.....	7
5.8.3 Communication performance - hearing and speech.....	7
5.8.4 Eye irritation caused by the RPD.....	7
5.8.5 Fogging of visor.....	7
5.8.6 Ergonomic requirements.....	7
5.8.7 Restriction and mobility of low pressure hose(s).....	7
5.9 Requirements for elements/components.....	7
<b>6 Requirements for supplied breathable gas RPD</b> .....	<b>8</b>
6.1 Temperature of operation.....	8
6.2 RPD performance.....	8
6.2.1 General.....	8
6.2.2 Setting for RPD using compressed breathable air or gas mixtures for respiration only.....	10
6.2.3 Setting for RPD using regenerated breathable gas or RPD using enriched oxygen.....	10
6.3 Work of breathing (WoB), breathing resistance and elastance.....	11
6.4 Determination of capacity of type Sxxxx RPD.....	11
6.4.1 General.....	11
6.4.2 Type Sxxxx RPD having class T (tight fitting) RIs and using compressed breathable air or gas mixtures for respiration only.....	11
6.4.3 Type Sxxxx RPD having class L (loose fitting) RIs using compressed breathable gas.....	12
6.4.4 Type Sxxxx RPD - using generated breathable gas or using enriched oxygen.....	13
6.5 CO <sub>2</sub> concentration limits.....	14
6.6 Temperature and humidity of inhaled breathable gas for regenerated breathable gas RPD and oxygen enriched breathable gas RPD.....	15

6.7	Contact with skin by hot and cold surface generated by the RPD .....	15
6.8	Oxygen content .....	16
6.8.1	Oxygen content of RPD using regenerated breathable gas .....	16
6.8.2	Oxygen content of RPD using oxygen enriched breathable gas .....	16
6.9	Noise limit .....	16
6.10	Assesment of reliability .....	16
6.11	Pre-conditioning (Sequential/Non-sequential) .....	17
6.11.1	General .....	17
6.12	Flexibility and resistance to deformation of hoses .....	19
6.12.1	General .....	19
6.12.2	Low pressure hose up to 2 m in length .....	19
6.12.3	Low pressure hose of 2 m or greater in length .....	19
6.12.4	Medium and high pressure hose greater than 2 m and up to 10 m in length .....	19
6.12.5	Medium and high pressure hose greater than 10 m in length .....	19
6.12.6	Flexibility of medium pressure hose .....	20
6.12.7	Flexibility of high pressure hose .....	20
6.12.8	Resistance to kinking of low, medium and high pressure hoses for use in a RPD with a hose length greater than 2 m .....	20
6.13	Compressed breathable gas cylinder and cylinder valve assemblies .....	21
6.13.1	General .....	21
6.13.2	Gas cylinder(s) .....	21
6.13.3	Cylinder valve(s) .....	21
6.13.4	Control means (other than cylinder valve) .....	22
6.14	Connections .....	23
6.14.1	General .....	23
6.14.2	Operation of connections .....	23
6.14.3	Strength of connections .....	23
6.15	Combined and multi-functional RPD .....	26
6.15.1	Combined RPD .....	26
6.15.2	Multi-functional RPD .....	27
6.16	Requirements for optional features .....	27
6.16.1	General .....	27
6.16.2	Connectors .....	27
6.16.3	Second high pressure outlet/inlet coupling requirements .....	28
6.16.4	Ambient air bypass performance .....	28
6.16.5	Extreme cold temperature requirements .....	29
6.16.6	Extreme high temperature requirements .....	31
6.16.7	Hydration .....	31
6.16.8	Submersion .....	32
6.16.9	Use of RPD in potentially explosive atmospheres .....	32
6.16.10	Electromagnetic compatibility of RPD .....	32
6.16.11	Permeation of medium pressure hoses for Class SY RPD, longer than 10 m including couplings .....	32
<b>7</b>	<b>Testing .....</b>	<b>33</b>
7.1	General .....	33
7.2	Inspection .....	33
7.3	Testing of leak tightness .....	33
7.3.1	Using positive pressure .....	33
7.3.2	Using negative pressure .....	33
7.4	High pressure leak-tightness test .....	34
7.5	Resistance to impact of cylinder valve .....	34
7.6	Testing permeation of medium pressure hoses .....	35
<b>8</b>	<b>Marking .....</b>	<b>37</b>
8.1	General .....	37
8.2	Marking of RPD without separable components .....	37
8.3	Marking of RPD replacement parts .....	37
8.4	Marking of RPD components as part of a system .....	38

8.4.1	RI.....	38
8.4.2	Other separable components.....	38
<b>9</b>	<b>Information supplied by the RPD manufacturer.....</b>	<b>38</b>
9.1	General.....	38
9.2	RPD.....	39
9.2.1	Minimum information.....	39
9.2.2	Additional information.....	39
9.2.3	Second high or medium pressure outlet/inlet.....	39
9.2.4	Ambient air bypass.....	40
9.2.5	Hydration facility.....	40
9.3	RPD components and replacement parts.....	40
9.3.1	RI.....	40
9.3.2	Other components or replacement parts.....	41
<b>Annex A (informative) Reliability.....</b>		<b>42</b>
<b>Annex B (informative) Example of failure modes and effect analysis (FMEA).....</b>		<b>44</b>
<b>Annex C (normative) Test schedules.....</b>		<b>48</b>
<b>Annex D (normative) Normalisation of test results.....</b>		<b>71</b>
<b>Bibliography.....</b>		<b>73</b>

**iTeh STANDARD PREVIEW**  
 (standards.iteh.ai)  
 Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/645e5d2c-0e62-4a08-b5e4-13bffc7104/iso-fdis-17420-4>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 94, *Personal safety - Personal protective equipment*, Subcommittee SC 15, *Respiratory protective devices*.

A list of all parts in the ISO 17420 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

This document describes basic requirements for supplied breathable gas respiratory protective devices (RPD) and its elements and components.

Requirements for RPD used in environments for special applications are given in the relevant parts of the ISO 17420 series.

Some test methods are described. For other test methods references are given to the ISO 16900 series "Methods of test and test equipment" or other test methods not developed by ISO/TC 94/SC 15.

[Annex A](#) gives information about reliability.

[Annex B](#) features an example of a FMEA (Failure Mode and Effects Analysis).

[Annex C](#) gives the test schedules including any pre-conditioning and number of samples.

[Annex D](#) provides information for normalisation of test results.

The sequence of testing follows the principle to minimize the necessary number of samples by carrying out destructive tests at the end. It also includes for safety reason that tests with test subjects are only carried out after the test samples have shown their safe performance in other tests.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/645e5d2c-0e62-4a08-b5e4-13bffc7104/iso-fdis-17420-4>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/645e5d2c-0e62-4a08-b5e4-13bffc7104/iso-fdis-17420-4>



# Respiratory protective devices — Performance requirements —

## Part 4: Requirements for supplied breathable gas RPD

### 1 Scope

This document specifies requirements for the performance and testing of supplied breathable gas respiratory protective devices (RPD) in accordance with their classification and for use in the workplace to protect the wearer from hazardous atmospheres and/or environments.

### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9227, *Corrosion tests in artificial atmospheres — Salt spray tests*

ISO 10297:2014, *Gas cylinders — Cylinder valves — Specification and type testing*

ISO 10297:2014/Amd 1:2017, *Gas cylinders — Cylinder valves — Specification and type testing — Amendment 1: Pressure drums and tubes*

ISO 12209, *Gas cylinders — Outlet connections for gas cylinder valves for compressed breathable air*

ISO 13341, *Gas cylinders — Fitting of valves to gas cylinders*

ISO 16900-1:2019, *Respiratory protective devices — Methods of test and test equipment — Part 1: Determination of inward leakage*

ISO 16900-2, *Respiratory protective devices — Methods of test and test equipment — Part 2: Determination of breathing resistance*

ISO 16900-5, *Respiratory protective devices — Methods of test and test equipment — Part 5: Breathing machine, metabolic simulator, RPD headforms and torso, tools and verification tools*

ISO 16900-6:—, *Respiratory protective devices — Methods of test and test equipment — Part 6: Mechanical resistance/strength of components and connections*

ISO 16900-7:2020, *Respiratory protective devices — Methods of test and test equipment — Part 7: Practical performance test methods*

ISO 16900-9, *Respiratory protective devices — Methods of test and test equipment — Part 9: Determination of carbon dioxide content of the inhaled gas*

ISO 16900-12, *Respiratory protective devices — Methods of test and test equipment — Part 12: Determination of volume-averaged work of breathing and peak respiratory pressures*

ISO 16900-13, *Respiratory protective devices — Methods of test and test equipment — Part 13: RPD using regenerated breathable gas and special application mining escape RPD: Consolidated test for gas concentration, temperature, humidity, work of breathing, breathing resistance, elastance and duration*

## ISO/FDIS 17420-4:2020(E)

ISO 16900-14, *Respiratory protective devices — Methods of test and test equipment — Part 14: Measurement of sound pressure level*

ISO 16972, *Respiratory protective devices — Vocabulary and graphical symbols*

ISO 17420-1:—, *Respiratory protective devices — Performance requirements — Part 1: General*

EN 144, *Respiratory protective devices — Gas cylinder valves — Part 2: Outlet connections*

EN 388:2016, *Protective gloves against mechanical risks*

CGA V-1, *Compressed Gas Cylinder Valve Outlet and Inlet Connections*

JIS B 8246, *Valves for high pressure gas cylinders*

IEC 60068-2-27:2010, *Environmental testing — Part 2-27: Tests — Test Ea and guidance: Shock*

IEC 60068-2-64, *Environmental testing — Part 2-64: Tests — Test Fh: Vibration, broadband random and guidance*

IEC 60721-1:2002, *Classification of environmental conditions — Part 1: Environmental parameters and their severities*

IEC 60721-3-2:2018, *Classification of environmental conditions — Part 3-2: Classification of groups of environmental parameters and their severities — Transportation and Handling*

IEC 61000-6-2, *Electromagnetic compatibility (EMC) — Part 6-2: Generic standards — Immunity standard for industrial environments*

## 3 Terms, definitions, abbreviations and symbols

### 3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 16972 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

#### 3.1.1

##### **RPD in as worn state**

RPD where all components are connected and assembled in the way that it is intended to be used (e.g. worn by the wearer, adapted to an RPD headform or RPD headform and torso or suitable holder)

Note 1 to entry: All of the various components (e.g. for an SCBA: gas cylinder, respiratory interface, demand valve, harness etc.) have been completely assembled and then connected (RI connected to the demand valve) together in accordance with the information supplied by the manufacturer.

#### 3.1.2

##### **RPD in ready for use state**

RPD ready to be donned as described by the manufacturer

Note 1 to entry: In line with the information supplied by the manufacturer for donning the RPD, further actions can be necessary, such as connections of components as part of the donning process.

**3.1.3****ready for assembly state**

RPD or components with seals, plugs or other environmental protective means, still in place ready to be assembled and/or donned

Note 1 to entry: RPD or components can remain sealed and plugged until donning if so stated in the information supplied by the manufacturer.

**3.1.4****integrated RPD**

RPD designed so that components in the breathable gas supply chain are non separable

**3.1.5****replacement part**

identical to the one originally supplied with the RPD by the manufacturer, and declared interchangeable by the manufacturer

**3.2 Abbreviated terms**

BTPS	Body Temperature Pressure Saturated
STPD	Standard Temperature Pressure Dry
FMEA	Failure Mode and Effects Analysis
RI	Respiratory Interface
$V_T$	Tidal volume
WoB	Work of Breathing

### 3.3 Symbols

#### 3.3.1



Product information; information point (ISO 7000-2760).

Indication for the RI that it is a part of a RPD system with multiple configurations.


#### 3.3.2



Operator's manual; operating instructions (ISO 7000-1641).

Booklet: "See information supplied by the RPD manufacturer"

#### 3.3.3




yyyy/mm

Use by date (ISO 7000-2607)

Hourglass: "End of shelf life"

Key: yyyy year, mm month

#### 3.3.4



RPD headform number allocation for size designation

## 4 Classification overview

ISO 17420-1:—, 4.1 applies with the following addition:

The classification of a supplied breathable gas RPD is determined by the appropriate combination of the classes:

Example for supplied breathable gas RPD with protection class (PC5), work rate class (W3), RI class (cT), supplied breathable gas capacity class (S1800).

Marking for the given example PC5 W3 cT S1800

Multifunctional supplied breathable gas RPD have separate classifications for each function, e.g. one classification as an airline RPD and one classification as an non-airline RPD.

Combined RPD work in both filtering and supplied breathable gas modes and are classified separately for each mode.

Additionally supplied breathable gas RPD may be classified for one or more special applications, as given in ISO 17420-5 to ISO 17420-9.

## 5 General requirements

### 5.1 General

ISO 17420-1:—, 5.1, applies.

### 5.2 Field of vision

ISO 17420-1:—, 5.2, applies.

### 5.3 Resistance to flame – Single burner dynamic

ISO 17420-1:—, 5.3, applies.

### 5.4 Compatibility with additional equipment

ISO 17420-1:—, 5.4, applies.

### 5.5 Monitor performance

ISO 17420-1:—, [5.5](#), applies with the following addition:

If the performance of the RPD is dependent on high pressure it shall be equipped with a pressure monitor, such as a pressure gauge, that continuously monitors that pressure. The accuracy of the pressure monitor shall be within  $\pm 2,5\%$  of the full scale with the exception of the redundant cylinder valve pressure gauge.

Check in accordance with [7.2](#) and [Clause 9](#).

### 5.6 Warning and checking device(s)

#### 5.6.1 Performance of warning device(s)

RPD shall be checked after sequential pre-conditioning in accordance with [6.11.1.1](#).

RPD powered by an energy source shall be equipped with a low energy warning device to warn the wearer at least 5 min prior to the performance of the RPD falling below the manufacturer's minimum design conditions. From the activation of the warning the RPD shall be tested in accordance with [6.2](#) for a period of 5 min but with a fixed setting of 35 l/min, see [Table 1](#).

Check in accordance with [7.2](#) and [Clause 9](#).

Any warning shall be detectable by the wearer without any intervention by the wearer. Any warning shall be detectable by the wearer within 15 s.

Testing shall be performed in accordance with ISO 16900-7:2020, Annex B, k).

Any warnings which require different reactions by the wearer shall be distinguishable from one another.