FINAL DRAFT

INTERNATIONAL STANDARD

ISO/FDIS 17420-6

ISO/TC 94/SC 15

Secretariat: DIN

Voting begins on: **2020-11-16**

Voting terminates on:

2021-01-11

Respiratory protective devices — Performance requirements —

Part 6:

Special application escape - Filtering RPD and supplied breathable gas RPD

iTeh STAppareils de protection respiratoire → Exigences de performances —
Partie 6: Application particulière d'évacuation - APR filtrants et APR
alimentés en gaz respirable

ISO/FDIS 17420-6 https://standards.iteh.ai/catalog/standards/sist/204023d2-144e-46cd-96b4-1c3947d3b313/iso-fdis-17420-6

Member bodies are requested to consult relevant national interests in ISO/TC 94/SC 14 before casting their ballot to the e-Balloting application.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number ISO/FDIS 17420-6:2020(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 17420-6 https://standards.iteh.ai/catalog/standards/sist/204023d2-144e-46cd-96b4-1c3947d3b313/iso-fdis-17420-6



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Coi	ntent	S		Page		
Fore	word			iv		
Intro	oductio	n		v		
1	Scop	e		1		
2	Norn	native ref	erences	1		
3						
3	3.1		and definitions			
	3.2	Abbrevi	ated terms	3		
4	Class		overview			
	4.1					
	4.2		d breathable gas RPD for escape			
_	4.3	`	g RPD for escape			
5		-	rements for RPD			
6	Basic	requirer	nents for supplied breathable gas RPD and filtering RPD	4		
7	_		ation for supplied breathable gas escape RPD and filtering escape RPD			
	7.1	-	application escape RPD - Requirement matrices			
		7.1.1 7.1.2	General Supplied breathable gas RPD — Escape			
	7.2	Require	Filtering escape RPD ments for special application escape RPD	8		
		7.2.1	Exposure to dust	8		
		7.2.2	Contact with hot or cold surfaces generated by the RPD	8		
		7.2.3	Avoidance of frictional sparks - Filtering escape RPD and supplied	Ω		
		7.2.4http:	breathable gas escape RPD 7420-6 Resistance to flame/standards/sist/204023d2-144e-46cd-96b4-	9		
		7.2.5	Mechanical Requirement iso-fdis-17420-6	10		
		7.2.6	Requirements for escape RPD used in explosive atmospheres and			
		7.7.7	electromagnetic compatibility	10		
		7.2.7	Antistatic properties - Filtering escape RPD and supplied breathable gas escape RPD	11		
		7.2.8	Eye irritation (external) - Filtering escape RPD and supplied breathable	11		
			gas escape RPD			
		7.2.9	Determination of duration			
	7.3	7.2.10	Validation of escape RPD performance requirements ditioning			
	7.3	7.3.1	Exposure to impact from drop — Filtering escape RPD and supplied	20		
		7.10.12	breathable gas escape RPD	28		
		7.3.2	Resistance to changes in atmospheric pressure			
		7.3.3	Intermittent exposure to salt spray			
		7.3.4 7.3.5	Exposure to vibration and shock for supplied breathable gas escape RPD Exposure to vibration and shock - marine			
		7.3.5	Exposure to vibration and shock - marine Exposure to vibration and shock - mining			
		7.3.7	Filtering escape RPD			
8	Inspe	ection		31		
-	8.1					
	8.2		ion			
	8.3		of leak tightness using positive pressure			
9	Mark	ing		32		
10	Infor	mation s	upplied by the manufacturer	32		

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. (Standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 94, *Personal safety – Personal protective equipment*, Subcommittee SC 15, *Respiratory protective devices*:

https://standards.iteh.au/catalog/standards/sist/204023d2-144e-46cd-96b4-

A list of all parts in the ISO 17420 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document describes requirements for RPD including its elements and components used for special applications for escape devices.

Some test methods are described. For other test methods references are given to the ISO 16900 series "Methods of test and test equipment" or other test methods not developed by ISO/TC 94/SC 15.

The sequence of testing follows the principle to minimize the necessary number of samples by carrying out destructive tests at the end. It also includes for safety reason that tests with test subjects are only carried out after the test samples have shown their safe performance in other tests.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 17420-6 https://standards.iteh.ai/catalog/standards/sist/204023d2-144e-46cd-96b4-1c3947d3b313/iso-fdis-17420-6

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 17420-6 https://standards.iteh.ai/catalog/standards/sist/204023d2-144e-46cd-96b4-1c3947d3b313/iso-fdis-17420-6

Respiratory protective devices — Performance requirements —

Part 6:

Special application escape - Filtering RPD and supplied breathable gas RPD

1 Scope

This document specifies the requirements for supplied breathable gas RPD and for filtering RPD to be used for special application escape for use in the workplace to protect the wearer.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8031, Rubber and plastics hoses and hose assemblies — Determination of electrical resistance and conductivity (standards.iteh.ai)

ISO 9227, Corrosion tests in artificial atmospheres — Salt spray tests

ISO 16900-1:2014, Respiratory protective devices sixt/2 Methods 4 of test and test equipment — Part 1: Determination of inward leakage 1c3947d3b313/iso-fdis-17420-6

ISO 16900-4, Respiratory protective devices — Methods of test and test equipment — Part 4: Determination of gas filter capacity and migration, desorption and carbon monoxide dynamic testing

ISO 16900-5, Respiratory protective devices — Methods of test and test equipment — Part 5: Breathing machine, metabolic simulator, RPD headforms and torso, tools and verification tools

ISO 16900-6, Respiratory protective devices — Methods of test and test equipment — Part 6: Mechanical resistance/strength of components and connections

ISO 16900-8, Respiratory protective devices — Methods of test and test equipment — Part 8: Measurement of RPD air flow rates of assisted filtering RPD

ISO 16900-9, Respiratory protective devices — Methods of test and test equipment — Part 9: Determination of carbon dioxide content of the inhaled gas

ISO 16900-10, Respiratory protective devices — Methods of test and test equipment — Part 10: Resistance to ignition, flame, radiant heat and heat

ISO 16900-12, Respiratory protective devices — Methods of test and test equipment — Part 12: Determination of volume-averaged work of breathing and peak respiratory pressures

ISO 16972, Respiratory protective devices — Vocabulary and graphical symbols

ISO 17420-1:—, Respiratory protective devices — Performance requirements — Part 1: General

ISO 17420-2:—, Respiratory protective devices — Performance requirements — Part 2: Requirements for filtering RPD

ISO/FDIS 17420-6:2020(E)

ISO 17420-4:—, Respiratory protective devices — Performance requirements — Part 4: Requirements for supplied breathable gas RPD

ISO 23269-2:2011, Ships and marine technology — Breathing apparatus for ships — Part 2: Self-contained breathing apparatus for shipboard firefighters

IEC 60068-2-27:2010, Environmental testing — Part 2-27: Tests — Test Ea and guidance: Shock

IEC 60068-2-64:2009, Environmental testing — Part 2-64: Tests — Test Fh: Vibration, broadband random and guidance

IEC 60079-0, Explosive atmospheres — Part 0: Equipment — General requirements

IEC 60079-11, Explosive atmospheres — Part 11: Equipment protection by intrinsic safety "i"

IEC 60079-32-1:2013, Explosive atmospheres — Part 32-1: Electrostatics hazards — Guidance

IEC 60079-32-2:2015, Explosive atmospheres — Part 32-2: Electrostatics hazards — Tests

IEC 60721-1:2003, Classification of environmental conditions — Part 1: Environmental parameters and their severities

IEC 60721-3-2:2018, Classification of environmental conditions — Part 3-2: Classification of groups of environmental parameters and their severities — Transportation and Handling

EN 50303, Group 1, category M1 equipment intended to remain functional in atmospheres endangered by firedamp and/or coal dust

ISO/FDIS 17420-6

3 Terms, definitions and abbreviations tandards/sist/204023d2-144e-46cd-96b4-1c3947d3b313/iso-fdis-17420-6

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 16972 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1.1

non pre-conditioned state

without pre-conditioning but possibly modified to carry out tests or already used in non-destructive tests

Note 1 to entry: This includes e.g. cleaning and disinfection.

3.1.2

RPD in as worn state

RPD where all components are connected and assembled in the way that it is intended to be used (e.g. worn by the wearer, adapted to an RPD headform or RPD headform and torso or suitable holder).

Note 1 to entry: All of the various components (e.g. for an assisted filtering RPD: blower unit, battery, RI, filters, etc.) have been completely assembled and then connected (RI connected to the hose of the blower unit) together in accordance with the information supplied by the manufacturer.

3.1.3

component in ready for assembly state

component with seals, plugs, packaging or other environmental protective means, still in place

3.1.4

RPD in ready for assembly state

RPD with seals, plug, or other environmental protective means, still in place

Note 1 to entry: In line with the information supplied by the manufacturer for donning the RPD, further actions can be necessary.

3.1.5

RPD in ready for use state

RPD ready to be donned as described by the manufacturer, but seals, plug, or other environmental protective means are already removed

Note 1 to entry: In line with the information supplied by the manufacturer for donning the RPD, further actions can be necessary.

Note 2 to entry: For escape devices this includes also the RPD in its container unopened.

3.2 Abbreviated terms

RI	Respiratory Interface	
RPD	Respiratory Protective Devices	
V_{T}	Tidal volume	
WoB	Work of Breathing	

iTeh STANDARD PREVIEW

4 Classification overview

(standards.iteh.ai)

ISO 17420-2:—, Clause 4 or ISO 17420-4:—, Clause 4 applies.

ISO/FDIS 17420-6

4.1 General

https://standards.iteh.ai/catalog/standards/sist/204023d2-144e-46cd-96b4-1c3947d3b313/iso-fdis-17420-6

ISO 17420-1:—, 4.1 applies.

The following subclause applies in addition to ISO 17420-2:—, Clause 4:

4.2 Supplied breathable gas RPD for escape

In addition, supplied breathable gas RPD may be classified for one or more special applications, as given in Table 1.

Table 1 — Special application classification supplied breathable gas RPD

Special application	Classes		
	ES MN ta (Underground mining escape)		
Eggana	ES MA t ^a (Marine escape)		
Escape	ES FF t ^a (Escape from fire)		
	ES t^a (Escape general supplied breathable gas)		
a Nominal service life in <i>t</i> minutes, e.g. ES	15.		

Example for a special application escape with Protection class (PC4), RI class (dL) and special application class (ES 15).

EXAMPLE PC4 dL ES 15.

The following subclause applies in addition to ISO 17420-2:—, Clause 4.

4.3 Filtering RPD for escape

In addition, filtering RPD may be classified for one or more special applications, as given in Table 2.

Table 2 — Special application classification of filtering RPD

Special application		Classes		
		ES MN t ^a (Underground Mining Escape)		
	Escape	ES FF t ^a (Escape from fire)		
		ES XX ^b t ^a (Escape general filtering)		
а	Nominal service life in "t" minutes, e.g. E	ES 10.		
b	Gas type.			

Example for a special application escape general with Protection class (PC3), RI class (bT) and special application escape (ES), particle filter performance class (F3) and gas filter class (AC) and class t (10).

EXAMPLE PC3 bT ES F3 AC10.

Multi-functional filtering RPD have separate classifications for each function, i.e. one classification for the unassisted mode and one classification for the assisted mode.

5 General requirements for RPD

ISO 17420-1: —, Clause 5 and ISO 17420-2: —, Clause 5 or ISO 17420-4: —, Clause 5 apply.

(standards.iteh.ai)

6 Basic requirements for supplied breathable gas RPD and filtering RPD

All requirements of ISO 17420-2: — Clause 6 or ISO 17420-6. Clause 6 apply unless superseded by this document and indicated in the relevant clauses. 13/iso-fdis-17420-6

NOTE 1 Optional features are also given in ISO 17420-2 or ISO 17420-4.

NOTE 2 Where requirements are superseded by those in <u>Clause 7</u> of this document test schedules given in ISO 17420-2: —, Annex C or ISO 17420-4: —, Annex C can be used as a guideline.

7 Special application for supplied breathable gas escape RPD and filtering escape RPD

7.1 Special application escape RPD - Requirement matrices

7.1.1 General

Supplied breathable gas escape RPD shall fulfil all requirements given in Table 3

Filtering escape RPD shall fulfil all requirements given in Table 4.

7.1.2 Supplied breathable gas RPD — Escape

<u>Table 3</u> gives an overview about requirements and preconditioning of special application supplied breathable gas RPD — Escape.

For each line in the table, at least one RPD shall be tested after the required preconditioning or set of pre-conditionings where combined by "&". Combined preconditioning shall be completed in the order specified.

Table 3 shall be read as follows:

In the first column the requirements are given. In the third to sixth column the required preconditioning for different escape classes are given.

For each pre-conditioning within one line of the cell different sample(s) shall be used.

For the requirement <u>7.2.10.1.1</u> and class marine escape the following applies:

At least one sample shall be preconditioned TH&VSS&IE (Exposure to temperature and humidity, exposure to vibration and shock – marine and intermittend exposure).

At least one further sample shall be preconditioned DR (Exposure to impact from drop)

For the total number of samples see ISO 17420-1: —, 5.1.

Table 3 — Special application requirement overview — Supplied breathable gas RPD — Escape

		Supplied breathable gas escape general	Escape from fire	Marine escape	Underground mining escape
Requirement	Title	ES t ^a	ES FF ta	ES MA ta	ES MN t ^a
	Title	Protection class	Protection class	Protection class	Protection class
		≥PC3	≥PC3	≥PC3	≥PC3
	iTeh STAND	ARD PE	Pre-co	nditioning	
7.2.1	Exposure to dust	X^{b}	X^{b}	Xb	Xp
7.2.2.1 ^c	Contact with hot and cold surfaces – Supplied breathable gas escape RPD ISO/F	r ds.1teh. TH&VS&IE DIS 17420-6	al) TH&VSF&IE	TH&VSS&IE	TH&VSM&PR&IE
<u>7.2.3</u> h	Avoidance of frictional sparks	'		96b4AR/NP	AR/NP
7.2.4.1	Six burner dynamic 947d3b3	3/iso-fdist 17420	-6 AR	AR	AR
7.2.6.2	Intrinsic Safety – Firefighting	d	AR/NP	d	d
7.2.6.3	Intrinsic Safety - Mining	d	d	d	AR/NP
7.2.6.4	Intrinsic Safety - Marine	d	d	AR/NP	_
7.2.7.1	Antistatic properties - General	<u></u> d	AR/NP	AR/NP	AR/NP
7.2.7.2	Antistatic properties – Fire-fighting	d	AR/NP	d	d
7.2.7.3	Antistatic properties - Mining	<u></u> d	<u></u> d	d	AR/NP

a Nominal service life in "t" min, see also 7.2.9.1.

AR as received.

AR/NP as received or in non pre-conditioned state.

TH&VS&IE Exposure to temperature and humidity (ISO 17420-4:—, 6.11.1.1.2), exposure to vibration and shock (ISO 17420-4:—, 6.11.1.1.3) and intermittent exposure (7.3.3).

TH&VSF&IE Exposure to temperature and humidity (ISO 17420-4:—, 6.11.1.1.2), exposure to vibration and shock-fire fighting (ISO 17420-5:201x, 7.2.2) and intermittent exposure (7.3.3).

TH&VSS&IE Exposure to temperature and humidity (ISO 17420-4:—, 6.11.1.1.2), exposure to vibration and shock marine (7.3.5) and intermittent exposure (7.3.3).

TH&VSM&PR&IE Exposure to temperature and humidity (ISO 17420-4:—, 6.11.1.1.2), exposure to vibration and shock mining (7.3.6), resistance to changes in atmospheric pressure (7.3.2) and intermittent exposure (7.3.3).

DR Exposure to impact from drop (7.3.1).

b X means exposure to dust has to be addressed by the FMEA (see 7.2.1).

c Will be determined during the validation of escape RPD performance regime specified in 7.2.10.

d — means that a test is not required for this combination of requirement and special application class.

Table 3 (co	ontinued)
--------------------	-----------

7.2.7.4	Antistatic properties - Exposed RPD hoses	d	AR/NP	AR/NP	AR/NP
<u>7.2.8</u>	Eye irritation (external)	AR/NP	AR/NP	AR/NP	AR/NP
7202	Determination of duration (t) of Escape RPD	TH&VS&IE	TH&VSF&IE	TH&VSS&IE	TH&VSM&PR&IE
<u>7.2.9.2</u>		DR	DR	DR	DR
721011	Validation of escape RPD performance requirements	TH&VS&IE	TH&VSF&IE	TH&VSS&IE	TH&VSM&PR&IE
<u>7.2.10.1.1</u>		DR	DR	DR	DR
<u>7.2.10.4</u>	Donning and doffing	AR/NP	AR/NP	AR/NP	AR/NP

Nominal service life in "t" min, see also <u>7.2.9.1</u>.

AR as received.

AR/NP as received or in non pre-conditioned state.

TH&VS&IE Exposure to temperature and humidity (ISO 17420-4:—, 6.11.1.1.2), exposure to vibration and shock (ISO 17420-4:—, 6.11.1.1.3) and intermittent exposure (7.3.3).

TH&VSF&IE Exposure to temperature and humidity (ISO 17420-4:—, 6.11.1.1.2), exposure to vibration and shock-fire fighting (ISO 17420-5:201x, 7.2.2) and intermittent exposure (7.3.3).

TH&VSS&IE Exposure to temperature and humidity (ISO 17420-4:—, 6.11.1.1.2), exposure to vibration and shock marine (7.3.5) and intermittent exposure (7.3.3). 1 STANDARD PROVIDED TO STANDARD PROVIDED

TH&VSM&PR&IE Exposure to temperature and humidity (ISO 17420-4:—, 6.11.1.1.2), exposure to vibration and shock mining (7.3.6), resistance to changes in atmospheric pressure (7.3.2) and intermittent exposure (7.3.3).

DR Exposure to impact from drop (7.3.1).

ISO/FDIS 17420-6

7.1.3 Filtering escape RPD //standards.iteh.ai/catalog/standards/sist/204023d2-144e-46cd-96b4-1c3947d3b313/iso-fdis-17420-6

Table 4 gives an overview about requirements and preconditioning of filtering RPD.

At least one RPD shall be tested after each required preconditioning. Pre-conditionings shall not be combined.

Table 4 shall be read as follows:

In the first column the requirements are given. In the third to sixth column the required preconditioning for different escape classes are given.

For each pre-conditioning within one line of the cell different sample(s) shall be used.

For the requirement <u>7.2.10.6.3</u> and class mining escape the following applies:

At least one sample shall be preconditioned VSM&PR&IE (Vibration and shock –mining, exposure to positive pressure and intermittent exposure)

At least one further sample shall be preconditioned DR (Exposure to impact from drop)

For the total number of samples see ISO 17420-1:—, 5.1.

b X means exposure to dust has to be addressed by the FMEA (see 7.2.1).

^c Will be determined during the validation of escape RPD performance regime specified in <u>7.2.10</u>.

[—] means that a test is not required for this combination of requirement and special application class.

Table 4 — Special application requirement overview — Filtering RPD — Escape

		Filtering es- cape general	Escape from fire	Underground mining escape	
		ES XX ^a t ^b	ES FF tb	ES MN tb	
Requirement	Title	Protection class	Protection class	Protection class	
		≥PC3	≥PC3	≥PC3	
			Pre-conditioning		
<u>7.2.1</u>	Exposure to dust	Xc	Xc	Xc	
7.2.2.2 ^d	Contact with hot surfaces - Filtering	TH&MR	TH&VSF	THOMODDOIE	
<u>1.2.2.2</u> *	escape RPD	DR	Πανστ	TH&VSM&PR&IE	
<u>7.2.3</u>	Avoidance of frictional sparks	е	AR	AR	
<u>7.2.4.1</u>	Six burner dynamic	е	AR	AR	
<u>7.2.6.2</u>	Intrinsic Safety – Firefighting	е	AR	е	
<u>7.2.6.3</u>	Intrinsic Safety – Mining	е	е	AR	
<u>7.2.7.1</u>	Antistatic properties - General	AR	AR	AR	
<u>7.2.7.2</u>	Antistatic properties Firefighting	е	AR	е	
<u>7.2.7.3</u>	Antistatic properties - Mining	е	е	AR	
<u>7.2.7.4</u>	Antistatic properties - Exposed RPD hoses	е	AR	AR	
<u>7.2.8</u>	Eye irritation (external)	REARIE	V AR	AR	
<u>7.2.9.3</u>	Determination of duration (t) of filtering	TH&MR	TH&VSF	TH&VSM&PR	
<u>7.2.7.3</u>	escape RPD (Standards.Ite)	1.al _{DR}	DR	DR	
7.2.10.2.1	Performance of work of breathing /	TH&MR&IE	TH&VSF&IE	TH&VSM&PR&IE	
<u>/.2.10.2.1</u>	breathing resistance/ elastance for in-	DR 123d2-144e-46cd-	96b4- DR	DR	
7.2.10.2.2	Performance of work of breathing/breath-	₂₀ TH&MR&IE	TH&VSF	TH&VSM&PR&IE	
<u>/.2.1U.2.2</u>	ing resistance/elastance for assisted	DR	DR	DR	
<u>7.2.10.3</u>	CO ₂ concentration limits	AR	AR	AR	
<u>7.2.10.4</u>	Donning and doffing	AR/NP	AR/NP	AR/NP	

a Gas type.

AR as received (or in non pre-conditioned state).

DR Exposure to impact from drop- escape RPD (7.3.1).

TH&MR Exposure to temperature and humidity (ISO 17420-2:—, 6.11.1.1.2), Mechanical resistance test (ISO 17420-2:201x, 6.9.2.3).

TH&MR&IE Exposure to temperature and humidity (ISO 17420-2:—, 6.11.1.1.2), Mechanical resistance test (ISO 17420-2:201x, 6.9.2.3) and intermittent exposure (7.3.3).

TH&VSF Exposure to temperature and humidity (ISO 17420-2:—, 6.11.1.1.2), Vibration and shock –fire-fighting (ISO 17420-5:201x, 7.2.2).

TH&VSF&IE Exposure to temperature and humidity (ISO 17420-2:—, 6.11.1.1.2), Vibration and shock –fire-fighting (ISO 17420-5:201x, 7.2.2) and intermittent exposure (7.3.3).

TH&VSM&PR Exposure to temperature and humidity (ISO 17420-2:—, 6.11.1.1.2), Vibration and shock –mining (7.3.6), resistance to changes in atmospheric pressure (7.3.2).

TH&VSM&PR&IE Exposure to temperature and humidity (ISO 17420-2:—, 6.11.1.1.2), Vibration and shock –mining (7.3.6), resistance to changes in atmospheric pressure (7.3.2) and intermittent exposure (7.3.3).

b nominal service life in "t" min, see also <u>7.2.9.1</u>.

 $^{^{}c}$ X means exposure to dust has to be addressed by the FMEA (7.2.1).

d Will be determined during the performance of work of breathing/breathing resistance/elastance for unassisted (7.2.10.2.1) or assisted escape RPD (7.2.10.2.2).

means that a test is not required for this combination of requirement and special application class.