
Specification of liquefied natural gas as a fuel for marine applications

*Spécification du gaz naturel liquéfié comme carburant pour les
applications maritimes*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 23306:2020](https://standards.iteh.ai/catalog/standards/sist/af54888c-2a45-44b7-b710-a8e8649b74c4/iso-23306-2020)

[https://standards.iteh.ai/catalog/standards/sist/af54888c-2a45-44b7-b710-
a8e8649b74c4/iso-23306-2020](https://standards.iteh.ai/catalog/standards/sist/af54888c-2a45-44b7-b710-a8e8649b74c4/iso-23306-2020)



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 23306:2020

<https://standards.iteh.ai/catalog/standards/sist/af54888c-2a45-44b7-b710-a8e8649b74c4/iso-23306-2020>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General requirements	2
5 Sampling	3
6 Requirements, limit values and related test methods	3
7 Main compounds removed by liquefaction process	4
Annex A (normative) Propane knock index: Methane number calculation method	6
Annex B (informative) Examples of LNG composition	12
Annex C (informative) Methane number (knock resistance) and Wobbe index (thermal input through a restriction)	15
Annex D (informative) LNG ageing along the bunkering chain	17
Annex E (informative) Particles	18
Annex F (informative) Melting and boiling points of pure components and impurities that can be present in different LNG	19
Bibliography	21

[ISO 23306:2020](https://standards.iteh.ai/catalog/standards/sist/af54888c-2a45-44b7-b710-a8e8649b74c4/iso-23306-2020)

<https://standards.iteh.ai/catalog/standards/sist/af54888c-2a45-44b7-b710-a8e8649b74c4/iso-23306-2020>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 28, *Petroleum and related products, fuels and lubricants from natural or synthetic sources*, Subcommittee SC 4, *Classifications and specifications*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 408, *Natural gas and biomethane for use in transport and biomethane for injection in the natural gas grid*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Due to numerous economic and environmental factors, the use of liquefied natural gas (LNG) as fuel for marine applications has increased. The 0,10 % sulfur limit, in the sulfur emission controlled areas in Europe and the US, which entered into force on 1 January 2015 has been one of the major driving forces for using LNG as fuel for marine applications. The decision for the 0,50 % global sulfur limit from 1 January 2020 by the International Maritime Organization (IMO) might further increase the interest in LNG. The International Code of Safety for Ships using Gases or other Low-flashpoint Fuels (IGF Code) was a response to the need of guidance in this emerging market. Since LNG-fueled vessels are likely to bunker LNG in different parts of the world, a common specification is needed for ship owners, ship operators and LNG suppliers. It would help engine manufacturers and ship designers and it is beneficial for the development of this new alternative marine fuel market.

In 2018, IMO adopted an initial strategy on reduction of greenhouse gas (GHG) emissions from ships. The strategy includes the objective to peak GHG emissions from international shipping as soon as possible, whilst pursuing efforts towards decarbonizing the sector as soon as possible in this century. It also includes the objectives to reduce the CO₂ emissions per transport work and total annual GHG emissions from international shipping by 2050, with an interim target in 2030. Thus, LNG produced from renewable sources as biomethane that can reduce CO₂ emissions when used as marine fuel is also addressed in this document.

LNG is produced in different locations in the world in liquefaction plants. Large scale production facilities are often dedicated to specific markets such as natural gas grids and large power plants that use their own standards. This document takes into consideration this major constraint for any adaptation to marine applications specificities/requirements.

(standards.iteh.ai)

ISO 23306:2020

<https://standards.iteh.ai/catalog/standards/sist/af54888c-2a45-44b7-b710-a8e8649b74c4/iso-23306-2020>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 23306:2020

<https://standards.iteh.ai/catalog/standards/sist/af54888c-2a45-44b7-b710-a8e8649b74c4/iso-23306-2020>

Specification of liquefied natural gas as a fuel for marine applications

1 Scope

This document specifies the quality requirements for Liquefied Natural Gas (LNG) used as a fuel for marine applications. It defines the relevant parameters to measure as well as the required values and the test reference methods for all those parameters.

This document applies to LNG from any source, e.g. gas from conventional reservoirs, shale gas, coalbed methane, biomethane, synthetic methane. LNG described in this document can come from synthesis process out of fossil fuels or renewable sources.

This document identifies the required specifications for fuels delivered at the time and place of custody transfer (at the delivery point).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6578, *Refrigerated hydrocarbon liquids — Static measurement — Calculation procedure*

ISO 6974 (all parts), *Natural gas — Determination of composition and associated uncertainty by gas chromatography* <https://standards.iteh.ai/catalog/standards/sist/a54888c-2a45-44b7-b710-a8e8649b74c4/iso-23306-2020>

ISO 6976, *Natural gas — Calculation of calorific values, density, relative density and Wobbe indices from composition*

ISO 8943, *Refrigerated light hydrocarbon fluids — Sampling of liquefied natural gas — Continuous and intermittent methods*

EN 16726, *Gas infrastructure — Quality of gas — Group H*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

biomethane

methane rich gas derived from biogas or from gasification of biomass by upgrading with the properties similar to natural gas

[SOURCE: ISO 14532:2014, 2.1.1.15]

3.2
liquefied natural gas
LNG

natural gas that has been liquefied after processing

[SOURCE: ISO 14532:2014, 2.1.1.12, modified — Definition has been shortened, note to entry has been deleted.]

3.3
methane number
MN

rating indicating the knocking characteristics of a fuel gas

Note 1 to entry: It is comparable to the octane number for petrol. One expression of the methane number is the volume percentage of methane in a methane-hydrogen mixture, that in a test engine under standard conditions has the same tendency to knock as the fuel gas to be examined.

[SOURCE: ISO 14532:2014, 2.6.6.1]

3.4
natural gas

complex gaseous mixture of hydrocarbons, primarily methane, but generally includes ethane, propane and higher hydrocarbons, and some non-combustible gases such as nitrogen and carbon dioxide

Note 1 to entry: Natural gas can also contain components or contaminants such as sulfur compounds and/or other chemical species.

[SOURCE: ISO 14532:2014, 2.1.1.1]

3.5
Wobbe index

calorific value on a volumetric basis at specified reference conditions, divided by the square root of the relative density at the same specified metering reference conditions

[SOURCE: ISO 14532:2014, 2.6.4.3, modified — Note to entry has been deleted.]

4 General requirements

4.1 The LNG at the delivery point shall conform with the characteristics and limits given in [Table 1](#) when tested in accordance with the specified methods.

The components listed in [Table 1](#) and [Table 2](#) shall be measured to enable the calculation of the physical properties of the LNG at the delivery point.

4.2 The LNG delivered shall be free from any material at a concentration that causes the LNG to be unacceptable for use, i.e. material not at a concentration that is harmful to personnel, jeopardizes the safety of the ship, or adversely affects the performance of the machinery.

4.3 Physicochemical characteristics not requiring measurement are listed in [Table 3](#).

It is not practical to require detailed chemical analysis for each delivery of fuels beyond the requirements listed in [Table 1](#) or [Table 2](#). Instead, a liquefaction plant, LNG terminal or any other supply facility, including supply barges and truck deliveries, shall have in place adequate quality assurance and management of change procedures to ensure that the resultant LNG is in conformance with the requirements of this document.

Examples of LNG compositions are given in [Annex B](#).

Information on ageing of LNG can be found in [Annex D](#) and information on particles can be found in [Annex E](#).

4.4 The reference conditions shall be 288,15 K, 101,325 kPa (see ISO 13443:1996, Clause 3) in the gaseous phase.

5 Sampling

Samples for quality verification are not mandatory but can be taken at various locations as agreed among the parties concerned. Samples, if any, can also be taken at multiple moments in time, as LNG has distinct different ageing characteristics than traditional hydrocarbon maritime fuels (with regards to ageing reference is made to [Annex D](#)). In order to ensure a representative sample, proper sampling procedures should be followed.

When sampling of LNG for analysis is carried out, it shall be in accordance with the procedures provided in ISO 8943 or an equivalent national standard agreed between the parties concerned. Where specific sampling requirements are documented, the relevant parties should agree on the reference test methods. The LNG collected in liquid state shall be instantly conditioned to gaseous state without any partial vaporization or loss of molecular components to ensure a representative sample.

There are two methods for sampling LNG as defined in ISO 8943, continuous and intermittent. Both methods obtain LNG from the LNG cargo/bunker line and then it is gasified in a vaporizer. The continuous method collects the gasified LNG in a sample holder at a constant flow rate for offline analysis. The intermittent method collects gasified LNG and directs it to an on-line analyzer at predetermined intervals. Please refer to ISO 8943 for more details on these methods.

The requirements for sampling LNG for marine applications can vary throughout the industry, depending on availability and equipment. Load port samples can be used for quality determination if the sampling equipment is not available and if it is agreed between the parties.

6 Requirements, limit values and related test methods

The components and physicochemical characteristics that shall be measured or calculated using the related test methods are given in [Table 1](#) and [Table 2](#).

NOTE Information can be found in ISO 6975^[1].

Information on MN and Wobbe index can be found in [Annex C](#).

Table 1 — Physicochemical characteristics requiring measurement/calculation with limit values

Characteristic	Unit	Limit	Value	Test method
Net Calorific Value (NCV)	MJ/m ³ (s)	Min	33,6 ^a	ISO 6976
Nitrogen	% (mol)	Max	1,0	ISO 6974 (all parts)
Methane Number (MN)	no unit	Min	b	Annex A (Propane knock index) or EN 16726
^a Calculated for a theoretical mixture of 99 % (mol) methane and 1 % (mol) nitrogen in liquid phase. The Gross Calorific Value can be calculated from the Net Calorific Value (see ISO 13443:1996).				
^b Both the method used for determining the MN and the minimum value shall be agreed between supplier and user.				

The fuel supplier shall calculate the actual MN at the delivery point and provide this information to the user (see [Clause 5](#) for sampling location). This information shall be given as MN_(PKI) or MN_(EN 16726). For guidance on the MN applicability to a specific application, Original Equipment Manufacturer (OEM) specifications should be considered.

Table 2 — Physicochemical characteristics requiring measurement without limit values

Characteristic	Unit	Test method	Value
Density ^a	kg/m ³	ISO 6578	Report
Methane (CH ₄)	% (mol)	ISO 6974 (all parts)	Report
Ethane (C ₂ H ₆)	% (mol)	ISO 6974 (all parts)	Report
Propane (C ₃ H ₈)	% (mol)	ISO 6974 (all parts)	Report
n-Butane (C ₄ H ₁₀) i-Butane	% (mol)	ISO 6974 (all parts)	Report
Pentane (C ₅ H ₁₂)	% (mol)	ISO 6974 (all parts)	Report

^a Density at temperature of the liquid phase.

7 Main compounds removed by liquefaction process

Natural gas is liquid at around -160 °C under atmospheric pressure and becomes Liquefied Natural Gas (LNG). To avoid freezing and plugging in the liquefaction plant's cryogenic heat exchangers, usual impurities or compounds that are present in the natural gas from various sources are removed upstream from the liquefaction process below their solubility level. Some LNG components (e.g. ethane, propane, butane and pentane) are possibly removed for commercial reasons or to achieve a targeted calorific value range.

LNG composition is therefore within more narrow limits compared to natural gas. The compounds that can be considered as harmful for marine applications are removed or reduced to very low levels (trace) so that they are no more a concern. They shall comply with 4.2. The main compounds removed by liquefaction are listed in Table 3 and below for information and reference. The measurement of these species is not required. However, if the parties concerned agree to measure them, they should be measured according to the referenced methods listed in Table 3.

The melting and boiling points for a range of compounds, including those possibly present in biomethane, are available in Table F.1.

Table 3 — Main compounds removed by liquefaction and not requiring measurement

Characteristic	Unit	Test method	Solubility limit in LNG (around -160 °C, atm. Pressure)	Typical value out of LNG plant	Remarks
Hexane and higher hydrocarbons	% (mol)	ISO 6974 (all parts)	n.a.	n.a.	n.a.
Total sulfur	mg(S)/m ³	ISO 19739 ^[5] ISO 20729 ^[6]	(n.a.)	Max 30 mg(S)/m ³ (gas)	Depends on LNG contracts. Actual value very often much lower.
Hydrogen sulfide	mg/m ³	ISO 19739	n.a.	4,29 mg/m ³ (N)	Removed in Acid Gas Removal Unit (AGRU) in liquefaction plant for safety purposes.
Mercaptan	mg/m ³	ISO 19739	Depends on size of molecule	n.a.	Removed in AGRU or in heavy hydrocarbon removal unit in liquefaction plant.
Carbon dioxide	% (mol)	ISO 6974 (all parts)	Around 0,02 % (mol)	0,005 % (mol)	Removed in AGRU in liquefaction plant.
Oxygen	% (mol)	ISO 6974 (all parts)	n.a.	n.a.	Removed in liquefaction plant
Water	mg/m ³	ISO 10101 ^[3]	Below 0,74 mg/m ³	0,74 mg/m ³ or below	Removed in dehydration unit in liquefaction plant
Mercury	µg/m ³	ISO 6978-2 ^[2]	n.a.	0,01 µg/m ³	Removed in liquefaction plant

NOTE See Annex F for components in low concentration or absent, e.g. siloxanes.
n.a. Not available.