

INTERNATIONAL STANDARD

ISO
2568

Second edition
1988-12-01



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION
ORGANISATION INTERNATIONALE DE NORMALISATION
МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

Hand- and machine-operated circular screwing dies and hand-operated die stocks

Filières rondes de filetage, à main et à machine, et porte-filière à main

ITEH STANDARD PREVIEW
(standards.iteh.ai)

ISO 2568:1988

<https://standards.iteh.ai/catalog/standards/sist/91bf5a90-c029-4fa6-9e98-9382125b6f83/iso-2568-1988>

Reference number
ISO 2568 : 1988 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 2568 was prepared by Technical Committee ISO/TC 29, *Small tools*.

This second edition cancels and replaces the first edition (ISO 2568 : 1973), of which it constitutes a minor revision. It incorporates amendments 1 and 2, published in 1977 and 1983 respectively, and a new clause 5 "Marking" has been added.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

Hand- and machine-operated circular screwing dies and hand-operated die stocks

1 Scope and field of application

This International Standard specifies the general dimensions of hand-operated and machine-operated screwing dies. These dimensions, established as a function of the thread diameter and pitch, are the following:

- outside diameter;
 - thickness;
 - cutting portion length;
 - general dimensions of attachment.
- iTeh STANDARD PREVIEW**
(standards.iteh.ai)
ISO 2568:1988
<https://standards.iteh.ai/catalog/standards/sist/91b5a90-c029-4fa6-9e98-9382125b6f83/iso-2568-1988>

It also gives the interchangeability dimensions of hand-operated die stocks.

This International Standard is applicable to screwing dies intended for the manufacture of the following threads:

- ISO metric threads:
 - coarse thread, from M1 to M68;
 - fine thread, from M1 to M56.
- ISO inch threads:
 - “Unified coarse” series (UNC), from No. 1 — 64 to 2 3/4 — 4;
 - “Unified fine” series (UNF), from No. 0 — 80 to 1 1/2 — 12.

The dimensional characteristics of circular screwing dies, as a function of thread diameters and pitches, are given in annex A.

The general dimensions of screwing dies for threads which are not dealt with in this International Standard, and therefore are not recommended, are given for guidance only in annex B. Annex B is applicable to screwing dies for inch threads of the following types:

- B.1 — “British Standard Whitworth” (BSW).
- B.2 — “British Standard Fine” (BSF).
- B.3 — “British Association” (BA).

All screwing dies are available in two classes, namely

- non-precision screwing dies;
- precision screwing dies.

2 ISO metric threads

Screwing dies with:

$D = 16$ and 20 mm

$D > 25$ mm




Figure 1 — Metric screwing dies

2.1 Coarse thread

Table 1

Dimensions in millimetres

Designation	d nom.	Pitch	D	D_1	E	E_1	C	b	a					
M1	1	0,25	16	11	5	2,5	0,5	3	0,2					
M1,1	1,1													
M1,2	1,2													
M1,4	1,4	0,3												
M1,6	1,6	0,35												
M1,8	1,8													
M2	2					0,4								
M2,2	2,2	0,45												
M2,5	2,5													
M3	3					0,5								
M3,5	3,5	0,6				20				13	6	0,6	4	0,5
M4	4	0,7												
M4,5	4,5	0,75												
M5	5	0,8												
M6	6	1												
M7	7													
M8	8													
M9	9	1,25	25	16	8		0,8	5	1					
M10	10													
M11	11	1,5												

Designation	d nom.	Pitch	D	E	C	b	a
M12	12	1,75	38	14	1,2	6	1
M14	14	2					
M16	16						
M18	18	2,5	45	18*	1,5	8	2
M20	20						
M22	22						
M24	24	3	55	22	1,8	10	2
M27	27						
M30	30						
M33	33	3,5	65	25	2	10	2
M36	36	4					
M39	39						
M42	42	4,5	75	30	2	10	2
M45	45						
M48	48	5	90	36	2,5	10	2
M52	52						
M56	56	5,5	105	36	2,5	10	2
M60	60						
M64	64	6	120	36	2,5	10	2
M68	68						

* For an M16 die, this dimension is an exception to the general table (table 6) given in annex A.

NOTES

1 The shape of the V-groove is left to the discretion of the manufacturer. Screwing dies are generally supplied with two chamfers at the thread entrance, according to the material to be threaded and at the discretion of the manufacturer.

2 Tolerances:

- for precision screwing dies:
 - on D : f10
 - on E : js12
- for non-precision screwing dies:
 - on D and E : the tolerances are left to the discretion of the manufacturer.

2.2 Fine thread

Table 2

Dimensions in millimetres

Designation	d nom.	Pitch	D	D_1	E	E_1	C	b	a						
M1 × 0,2	1	0,2	16	11	5	2	0,5	3	0,2						
M1,1 × 0,2	1,1														
M1,2 × 0,2	1,2														
M1,4 × 0,2	1,4														
M1,6 × 0,2	1,6														
M1,8 × 0,2	1,8														
M2 × 0,25	2	0,25	20		5		4								
M2,2 × 0,25	2,2														
M2,5 × 0,35	2,5	0,35													
M3 × 0,35	3	15		3											
M3,5 × 0,35	3,5														
M4 × 0,5	4	0,5			7	0,6									
M4,5 × 0,5	4,5														
M5 × 0,5	5														
M5,5 × 0,5	5,5														
M6 × 0,75	6	0,75								0,8					
M7 × 0,75	7														
M8 × 1	8	1	25		9		5	0,5							
M9 × 1	9														
M10 × 1	10	1,25	30		11	1									
M10 × 1,25	1,25														
M12 × 1,25	12	1,5	38		10										
M12 × 1,5	1,5														
M14 × 1,25	14	1,5													
M14 × 1,5	1,5														
M15 × 1,5	15	1,5					1,2		6						
M16 × 1,5	16														
M17 × 1,5	17	1,5	45		14										
M18 × 1,5	18														
M18 × 2	2	2													
M20 × 1,5	20														
M20 × 2	2	2													
M22 × 1,5	22														
M22 × 2	2	2													
M24 × 1,5	24														
M24 × 2	2	55		16		1,5									
M25 × 1,5	25														
M25 × 2	2						8								
M27 × 1,5	27														
M27 × 2	2														
M28 × 1,5	28														
M28 × 2	2	65		18		1,8									

For the shape of the V-groove and the tolerances, see notes 1 and 2 in 2.1.

Designation	d nom.	Pitch	D	E	C	b	a
M30 × 1,5	30	1,5	65	18	1,8		1
M30 × 2		2		25			
M30 × 3		3					
M32 × 1,5	32	1,5	65	18	1,8		
M32 × 2		2		25			
M33 × 1,5	33	1,5		18			
M33 × 2		2		25			
M33 × 3	35	3		25			
M35 × 1,5		1,5	65	18	1,8		
M36 × 1,5	36	1,5		25			
M36 × 2		2		25			
M36 × 3	39	3		25			
M39 × 1,5		1,5	75	20	2		
M39 × 2	40	2		30			
M39 × 3		3		30			
M40 × 1,5	40	1,5	75	20	2		
M40 × 2		2		30			
M40 × 3	42	3		30			
M42 × 1,5		1,5	90	20	2		
M42 × 2	42	2		30			
M42 × 3		3		30			
M42 × 4	45	4		30			
M45 × 1,5		1,5	90	22	2		
M45 × 2	45	2		36			
M45 × 3		3		36			
M45 × 4	48	4		36			
M48 × 1,5		1,5	90	22	2		
M48 × 2	48	2		36			
M48 × 3		3		36			
M48 × 4	50	4		36			
M50 × 1,5		1,5	90	22	2		
M50 × 2	50	2		36			
M50 × 3		3		36			
M52 × 1,5	52	1,5	90	22	2		
M52 × 2		2		36			
M52 × 3	52	3		36			
M52 × 4		4		36			
M55 × 1,5	55	1,5	105	22	2,5	10	
M55 × 2		2		36			
M55 × 3	55	3		36			
M55 × 4		4		36			
M56 × 1,5	56	1,5	105	22	2,5	10	
M56 × 2		2		36			
M56 × 3	56	3		36			
M56 × 4		4		36			

3 ISO inch threads

Screwing dies with:


 $D = 16$ and 20 mm $D > 25$ mm

Figure 2 — Screwing dies UNC and UNF

3.1 "Unified coarse" series (UNC)

Table 3

Dimensions in millimetres

Designation			d nom.	Pitch \approx	D	D_1	E	E_1	C	b	a
No. 1	— 64	— UNC	1,854	0,397	16	11	5	3	0,5	3	0,2
No. 2	— 56	— UNC	2,184	0,454							
No. 3	— 48	— UNC	2,515	0,529							
No. 4	— 40	— UNC	2,845	0,635	20	14	7	0,6	4	0,5	
No. 5	— 40	— UNC	3,175	0,794							
No. 6	— 32	— UNC	3,505	1,058							
No. 8	— 32	— UNC	4,166	1,27							
No. 10	— 24	— UNC	4,826	1,411							
No. 12	— 24	— UNC	5,486	1,588							
1/4	— 20	— UNC	6,35	1,814	25	17	9	0,8	5	1	
5/16	— 18	— UNC	7,938	1,954							
3/8	— 16	— UNC	9,525	2,117	30	20	11	1	6	2	
7/16	— 14	— UNC	11,112	2,309							
1/2	— 13	— UNC	12,7	2,54	38	25	14	1,2	8	2	
9/16	— 12	— UNC	14,288	2,822							
5/8	— 11	— UNC	15,875	3,175	45	30	18	1,5	10	2	
3/4	— 10	— UNC	19,05	3,629							
7/8	— 9	— UNC	22,225	4,233	55	36	22	1,8	10	2	
1	— 8	— UNC	25,4	5,08							
1 1/8	— 7	— UNC	28,575	5,644	65	42	25	2	10	2	
1 1/4	— 7	— UNC	31,75	6,35							
1 3/8	— 6	— UNC	34,925		75	48	30	2,5	10	2	
1 1/2	— 6	— UNC	38,1								
1 3/4	— 5	— UNC	44,45		90	57	36	2,5	10	2	
2	— 4 1/2	— UNC	50,8								
2 1/4	— 4 1/2	— UNC	57,15		105	66	36	2,5	10	2	
2 1/2	— 4	— UNC	63,5								
2 3/4	— 4	— UNC	69,85		120	76	36				

3.2 "Unified fine" series (UNF)

Table 4

Dimensions in millimetres

Designation	d nom.	Pitch \approx	D	D_1	E	E_1	C	b	a	
No. 0 — 80 — UNF	1,524	0,318	16	11	5	2,5	0,5	3	0,2	
No. 1 — 72 — UNF	1,854	0,353								
No. 2 — 64 — UNF	2,184	0,397								
No. 3 — 56 — UNF	2,515	0,454				3				
No. 4 — 48 — UNF	2,845	0,529	20			5		4	0,5	
No. 5 — 44 — UNF	3,175	0,577								
No. 6 — 40 — UNF	3,505	0,635								
No. 8 — 36 — UNF	4,166	0,706								
No. 10 — 32 — UNF	4,826	0,794	25		7		0,6	5	0,5	
No. 12 — 28 — UNF	5,486	0,907								
1/4 — 28 — UNF	6,35	0,907								
5/16 — 24 — UNF	7,938	0,907								
3/8 — 24 — UNF	9,525	1,058	30		11		0,8	5	1	
7/16 — 20 — UNF	11,112	1,27								
1/2 — 20 — UNF	12,7	1,27								
9/16 — 18 — UNF	14,288	1,411	38							
5/8 — 18 — UNF	15,875	1,411	45		10		1,2	6	1	
3/4 — 16 — UNF	19,05	1,588								
7/8 — 14 — UNF	22,225	1,814	55		14		1,5	8	2	
1 — 12 — UNF	25,4	2,117								
1 1/8 — 12 — UNF	28,575	2,117	65		16		1,8	8	2	
1 1/4 — 12 — UNF	31,75	2,117								
1 3/8 — 12 — UNF	34,925	2,117								
1 1/2 — 12 — UNF	38,1	2,117								
			75		20					

NOTES

1 The shape of the V-groove is left to the discretion of the manufacturer. Screwing dies are generally supplied with two chamfers at the thread entrance, according to the material to be threaded and at the discretion of the manufacturer.

2 Tolerances:

- for precision screwing dies:
 - on D : f10
 - on E : js12
- for non-precision screwing dies:
 - on D and E : the tolerances are left to the discretion of the manufacturer.

4 Die stocks — Interchangeability dimensions

(For metric and inch threads)




Table 5

ISO 2568:1988

Dimensions in millimetres

D	E_2	E_3	E_4	D_3	d_1
D10			0 -0,2		
16	5	4,8	2,4	11	M3
20	5	4,8	2,4	15	M4
	7	6,5	3,4		
25	9	8,5	4,4	20	M5
30	11	10	5,3	25	
38	10	9	4,8	32	M6
	14	13	6,8		
45	14	13	6,8	38	M6
	18	17	8,8		
55	16	15	7,8	48	M8
	22	20	10,7		
65	18	17	8,8	58	M8
	25	23	12,2		
75	20	18	9,7	68	M8
	30	28	14,7		
90	22	20	10,7	82	M8
	36	34	17,7		
105	22	20	10,7	95	M10
	36	34	17,7		
120	22	20	10,7	107	M10
	36	34	17,7		

5 Marking

5.1 Screwing dies for ISO metric threads, the dimensions of which conform with those given in tables 1 and 2, shall be marked with the thread designation.

Examples:

A circular screwing die for coarse ISO metric threads (for example M1) shall be marked as follows:

M1

A circular screwing die for fine ISO metric threads (for example M12 × 1,25) shall be marked as follows:

M12 × 1,25

5.2 Screwing dies for ISO inch threads, UNC and UNF series and types BSW, BSF and BA, the dimensions of which conform with those given in tables 3, 4, 7, 8 and 9, shall be marked with the thread designation.

Examples:

A screwing die for ISO inch threads, UNC series (for example 1/4 — 20), shall be marked as follows:

1/4 — 20 — UNC

A screwing die for ISO inch threads, UNF series (for example No. 12 — 28), shall be marked as follows:

No. 12 — 28 — UNF

A screwing die for ISO inch threads, type BSW (for example 1/2 — 12), shall be marked as follows:

1/2 — 12 — BSW

A screwing die for ISO inch threads, type BSF (for example 1/4 — 26), shall be marked as follows:

1/4 — 26 — BSF

A screwing die for ISO inch threads, type BA (for example No. 4), shall be marked as follows:

BA No. 4

5.3 Where tools comply in all respects with the relevant International Standards, the symbol ISO may be appended to the mark at the discretion of the manufacturer.