



SLOVENSKI STANDARD
oSIST prEN IEC 62680-1-3:2022

01-marec-2022

**Vmesniki univerzalnega serijskega vodila za prenos podatkov in napajanje - 1-3.
del: Skupne komponente - Specifikacija za kable in priključke univerzalnega
serijskega vodila tipa C®**

Universal serial bus interfaces for data and power - Part 1-3: Common components -
USB Type-C® Cable and Connector Specification

Schnittstellen des Universellen Seriellen Busses für Daten und Energie – Teil 1-3:
Gemeinsame Bauteile – Festlegung für USB-Typ-CTM-Kabel und -Steckverbinder

Interfaces de bus universel en série pour les données et l'alimentation électrique - Partie
1-3: Composants communs - Spécification des câbles et des connecteurs USB Type-C®

Ta slovenski standard je istoveten z: IEC prEN IEC 62680-1-3:2022

<https://standards.iteh.ai/catalog/standards/sist/7a97b682-04b1-4a94-91f6-9ba3b9710012/sist-en-iec-62680-1-3-2023>

ICS:

35.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment
--------	------------------------------------	--

oSIST prEN IEC 62680-1-3:2022

en,fr,de



100/3715/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER:

IEC 62680-1-3 ED5

DATE OF CIRCULATION:

2022-01-28

CLOSING DATE FOR VOTING:

2022-04-22

SUPERSEDES DOCUMENTS:

100/3707/RR

IEC TA 18 : MULTIMEDIA HOME SYSTEMS AND APPLICATIONS FOR END-USER NETWORKS	
SECRETARIAT: Japan	SECRETARY: Mr Keisuke Koide
OF INTEREST TO THE FOLLOWING COMMITTEES:	PROPOSED HORIZONTAL STANDARD: <input type="checkbox"/> Other TC/SCs are requested to indicate their interest, if any, in this CDV to the secretary.
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING Attention IEC-CENELEC parallel voting The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting. The CENELEC members are invited to vote through the CENELEC online voting system.	<input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

Universal serial bus interfaces for data and power - Part 1-3: Common components - USB Type-C® Cable and Connector Specification

PROPOSED STABILITY DATE: 2026

NOTE FROM TC/SC OFFICERS:

Copyright © 2021 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

Only the cover page was created by TA18.

For the main body, the document (USB Type-C Spec R2.1 - May 2021.docx) supplied from USB-IF was uploaded as "CDV additional file (s)".

Please have the IEC Central Office convert it to the IEC prescribed format.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[SIST EN IEC 62680-1-3:2023](https://standards.iteh.ai/catalog/standards/sist/7a97b682-04b1-4a94-91f6-9ba3b9710012/sist-en-iec-62680-1-3-2023)

<https://standards.iteh.ai/catalog/standards/sist/7a97b682-04b1-4a94-91f6-9ba3b9710012/sist-en-iec-62680-1-3-2023>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19

Universal Serial Bus Type-C Cable and Connector Specification

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

Release 2.1
May 2021

[SIST EN IEC 62680-1-3:2023](https://standards.iteh.ai/catalog/standards/sist/7a97b682-04b1-4a94-91f6-9ba3b9710012/sist-en-iec-62680-1-3-2023)

<https://standards.iteh.ai/catalog/standards/sist/7a97b682-04b1-4a94-91f6-9ba3b9710012/sist-en-iec-62680-1-3-2023>

20 **Copyright © 2014-2021, USB 3.0 Promoter Group:**
21 **Apple Inc., HP Inc., Intel Corporation, Microsoft**
22 **Corporation, Renesas, STMicroelectronics, and Texas Instruments**
23 **All rights reserved.**
24
25

26 NOTE: Adopters may only use the USB Type-C® cable and connector to implement USB or third-
27 party functionality as expressly described in this Specification; all other uses are prohibited.

28 LIMITED COPYRIGHT LICENSE: The USB 3.0 Promoters grant a conditional copyright license under
29 the copyrights embodied in the USB Type-C Cable and Connector Specification to use and reproduce
30 the Specification for the sole purpose of, and solely to the extent necessary for, evaluating whether to
31 implement the Specification in products that would comply with the specification. Without limiting
32 the foregoing, use of the Specification for the purpose of filing or modifying any patent application to
33 target the Specification or USB compliant products is not authorized. Except for this express
34 copyright license, no other rights or licenses are granted, including without limitation any patent
35 licenses. In order to obtain any additional intellectual property licenses or licensing commitments
36 associated with the Specification a party must execute the USB 3.0 Adopters Agreement. NOTE: By
37 using the Specification, you accept these license terms on your own behalf and, in the case where you
38 are doing this as an employee, on behalf of your employer.

39
40
41 **INTELLECTUAL PROPERTY DISCLAIMER**

42 THIS SPECIFICATION IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER,
43 INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS
44 FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL
45 LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS,
46 RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE
47 PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE,
48 EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY
49 RIGHTS.

50 All implementation examples and reference designs contained within this Specification are
51 included as part of the limited patent license for those companies that execute the USB 3.0
52 Adopters Agreement.

53
54
55 USB Type-C®, USB-C® and USB4™ are trademarks of the Universal Serial Bus Implementers
56 Forum (USB-IF). DisplayPort™ is a trademark of VESA. All product names are trademarks,
57 registered trademarks, or service marks of their respective owners.

58 Thunderbolt™ is a trademark of Intel Corporation. You may only use the Thunderbolt™
59 trademark or logo in conjunction with products designed to this specification that complete
60 proper certification and executing a Thunderbolt™ trademark license – see
61 usb.org/compliance for further information.

62

CONTENTS

63	Specification Work Group Chairs / Specification Editors	18
64	Specification Work Group Contributors	18
65	Pre-Release Draft Industry Reviewing Companies That Provided Feedback.....	25
66	Revision History.....	25
67	1 Introduction	26
68	1.1 Purpose.....	26
69	1.2 Scope.....	26
70	1.3 Related Documents.....	27
71	1.4 Conventions.....	27
72	1.4.1 Precedence	27
73	1.4.2 Keywords	27
74	1.4.3 Numbering.....	28
75	1.5 Terms and Abbreviations.....	28
76	2 Overview	33
77	2.1 Introduction	33
78	2.2 USB Type-C Receptacles, Plugs and Cables.....	34
79	2.3 Configuration Process	35
80	2.3.1 Source-to-Sink Attach/Detach Detection.....	36
81	2.3.2 Plug Orientation/Cable Twist Detection.....	36
82	2.3.3 Initial Power (Source-to-Sink) Detection and Establishing the Data	
83	(Host-to-Device) Relationship.....	36
84	2.3.4 USB Type-C VBUS Current Detection and Usage	37
85	2.3.5 USB PD Communication.....	38
86	2.3.6 Functional Extensions.....	38
87	2.4 VBUS.....	38
88	2.5 VCONN.....	39
89	2.6 Hubs.....	40
90	3 Mechanical.....	41
91	3.1 Overview	41
92	3.1.1 Compliant Connectors.....	41
93	3.1.2 Compliant Cable Assemblies.....	41
94	3.1.3 Compliant USB Type-C to Legacy Cable Assemblies	42
95	3.1.4 Compliant USB Type-C to Legacy Adapter Assemblies	43
96	3.2 USB Type-C Connector Mating Interfaces	43
97	3.2.1 Interface Definition.....	43
98	3.2.2 Reference Designs.....	66
99	3.2.3 Pin Assignments and Descriptions.....	73
100	3.3 Cable Construction and Wire Assignments.....	74
101	3.3.1 Cable Construction (Informative)	74
102	3.3.2 Wire Assignments	76
103	3.3.3 Wire Gauges and Cable Diameters (Informative).....	77

104	3.4	Standard USB Type-C Cable Assemblies	79
105	3.4.1	USB Full-Featured Type-C Cable Assembly	79
106	3.4.2	USB 2.0 Type-C Cable Assembly.....	80
107	3.4.3	USB Type-C Captive Cable Assemblies.....	81
108	3.4.4	USB Type-C Thumb Drive Assemblies.....	81
109	3.5	Legacy Cable Assemblies	82
110	3.5.1	USB Type-C to <i>USB 3.1</i> Standard-A Cable Assembly	82
111	3.5.2	USB Type-C to <i>USB 2.0</i> Standard-A Cable Assembly	84
112	3.5.3	USB Type-C to <i>USB 3.1</i> Standard-B Cable Assembly	85
113	3.5.4	USB Type-C to <i>USB 2.0</i> Standard-B Cable Assembly	86
114	3.5.5	USB Type-C to <i>USB 2.0</i> Mini-B Cable Assembly	87
115	3.5.6	USB Type-C to <i>USB 3.1</i> Micro-B Cable Assembly.....	88
116	3.5.7	USB Type-C to <i>USB 2.0</i> Micro-B Cable Assembly.....	90
117	3.6	Legacy Adapter Assemblies	91
118	3.6.1	USB Type-C to <i>USB 3.1</i> Standard-A Receptacle Adapter Assembly	91
119	3.6.2	USB Type-C to <i>USB 2.0</i> Micro-B Receptacle Adapter Assembly.....	93
120	3.7	Electrical Characteristics	94
121	3.7.1	Raw Cable (Informative)	94
122	3.7.2	USB Type-C to Type-C Passive Cable Assemblies (Normative)	95
123	3.7.3	Mated Connector (Informative – USB 3.2 Gen2 and USB4 Gen2)	117
124	3.7.4	Receptacle Connector SI Requirements and Testing (Normative –	
125		USB4 Gen3).....	120
126	3.7.5	USB Type-C to Legacy Cable Assemblies (Normative)	121
127	3.7.6	USB Type-C to USB Legacy Adapter Assemblies (Normative)	125
128	3.7.7	Shielding Effectiveness Requirements (Normative).....	127
129	3.7.8	DC Electrical Requirements (Normative)	130
130	3.8	Mechanical and Environmental Requirements (Normative).....	133
131	3.8.1	Mechanical Requirements.....	134
132	3.8.2	Environmental Requirements.....	139
133	3.9	Docking Applications (Informative)	140
134	3.10	Implementation Notes and Design Guides	141
135	3.10.1	EMC Management (Informative).....	141
136	3.10.2	Stacked and Side-by-Side Connector Physical Spacing (Informative)	
137		144
138	3.10.3	Cable Mating Considerations (Informative).....	144
139	3.11	Extended Power Range (EPR) Cables	145
140	3.11.1	Electrical Requirements	145
141	3.11.2	EPR Cable Identification Requirements	145
142	4	Functional	146
143	4.1	Signal Summary.....	146
144	4.2	Signal Pin Descriptions	146
145	4.2.1	SuperSpeed USB Pins	146
146	4.2.2	USB 2.0 Pins	147
147	4.2.3	Auxiliary Signal Pins.....	147

148	4.2.4	Power and Ground Pins	147
149	4.2.5	Configuration Pins	147
150	4.3	Sideband Use (SBU).....	147
151	4.4	Power and Ground.....	148
152	4.4.1	IR Drop.....	148
153	4.4.2	VBUS.....	149
154	4.4.3	VCONN.....	151
155	4.5	Configuration Channel (CC)	157
156	4.5.1	Architectural Overview	157
157	4.5.2	CC Functional and Behavioral Requirements	170
158	4.5.3	USB Port Interoperability Behavior.....	208
159	4.6	Power.....	227
160	4.6.1	Power Requirements during USB Suspend.....	228
161	4.6.2	VBUS Power Provided Over a USB Type-C Cable	229
162	4.7	USB Hubs	235
163	4.8	Power Sourcing and Charging.....	236
164	4.8.1	DFP as a Power Source	236
165	4.8.2	Non-USB Charging Methods	239
166	4.8.3	Sinking Host	239
167	4.8.4	Sourcing Device.....	239
168	4.8.5	Charging a System with a Dead Battery	239
169	4.8.6	USB Type-C Multi-Port Chargers	239
170	4.9	Electronically Marked Cables.....	242
171	4.9.1	Parameter Values	244
172	4.9.2	Active Cables.....	244
173	4.10	VCONN-Powered Accessories (VPAs) and VCONN-Powered USB Devices	
174		(VPDs)	244
175	4.10.1	VCONN-Powered Accessories (VPAs).....	244
176	4.10.2	VCONN-Powered USB Devices (VPDs)	245
177	4.11	Parameter Values.....	247
178	4.11.1	Termination Parameters	247
179	4.11.2	Timing Parameters.....	249
180	4.11.3	Voltage Parameters.....	252
181	5	USB4 Discovery and Entry	254
182	5.1	Overview of the Discovery and Entry Process.....	254
183	5.2	USB4 Functional Requirements.....	255
184	5.2.1	USB4 Host Functional Requirements	255
185	5.2.2	USB4 Device Functional Requirements	255
186	5.2.3	USB4 Alternate Mode Support.....	255
187	5.2.3.1	USB4 Alternate Mode Support on Hosts.....	255
188	5.2.3.2	USB4 Alternate Mode Support on Hubs and USB4-based Docks..	255
189	5.3	USB4 Power Requirements.....	256
190	5.3.1	Source Power Requirements.....	256
191	5.3.2	Sink Power Requirements	256

192	5.3.3	Device Power Management Requirements	257
193	5.4	USB4 Discovery and Entry Flow Requirements	257
194	5.4.1	USB Type-C Initial Connection	257
195	5.4.2	USB Power Delivery Contract	257
196	5.4.3	USB4 Discovery and Entry Flow	258
197	5.4.3.1	USB4 Device Discovery (SOP)	259
198	5.4.3.2	USB4 Cable Discovery (SOP')	259
199	5.4.3.3	USB4 Operational Entry	262
200	5.4.4	USB4 Post-Entry Operation	262
201	5.4.4.1	During USB4 Operation	262
202	5.4.4.2	Exiting USB4 Operation	262
203	5.5	USB4 Hub Connection Requirements	263
204	5.5.1	USB4 Hub Port Initial Connection Requirements	263
205	5.5.2	USB4 Hub UFP and Host Capabilities Discovery	263
206	5.5.3	Hub DFP Connection Requirements	264
207	5.5.3.1	Speculative Connections	264
208	5.5.3.2	Operational Connections	264
209	5.5.4	Hub Ports Connection Behavior Flow Examples	265
210	5.5.5	Connecting to Downstream USB4 Hubs	270
211	5.5.6	Fallback Functional Requirements for USB4 Hubs	270
212	5.6	USB4 Device Connection Requirements	271
213	5.6.1	Fallback Mapping of USB4 Peripheral Functions to USB Device	
214		Class Types	271
215	5.7	Parameter Values	272
216	5.7.1	Timing Parameters	272
217	6	Active Cables	273
218	6.1	USB Type-C State Machine	275
219	6.2	USB PD Requirements	275
220	6.2.1	Active Cable USB PD Requirements	277
221	6.2.2	USB PD Messages for OIAC	278
222	6.2.3	Short Active Cable Behaviors in Response to Power Delivery	
223		Events	290
224	6.3	OIAC Connection Flow and State Diagrams	290
225	6.3.1	OIAC Connection Flow – Discovery – Phase 1	291
226	6.3.2	OIAC Connection Flow – Reboot – Phase 2	292
227	6.3.3	OIAC Connection Flow – Configuration – Phase 3	293
228	6.3.4	OIAC Connection State Diagram Plug-A	296
229	6.3.5	OIAC Connection State Diagram Plug-B	304
230	6.4	Active Cable Power Requirements	309
231	6.4.1	VBUS Requirements	309
232	6.4.2	OIAC VBUS Requirements	309
233	6.4.3	USB PD Rules in Active State	311
234	6.4.4	VCONN Requirements	312
235	6.5	Mechanical	312

236	6.5.1	Thermal	312
237	6.5.2	Plug Spacing	313
238	6.6	Electrical Requirements	313
239	6.6.1	Shielding Effectiveness Requirement.....	313
240	6.6.2	Low Speed Signal Requirement.....	313
241	6.6.3	USB 2.0.....	314
242	6.6.4	USB 3.2.....	315
243	6.6.5	USB4	322
244	6.6.6	Return Loss	336
245	6.7	Active Cables That Support Alternate Modes.....	336
246	6.7.1	Discover SVIDs	336
247	6.7.2	Discover Modes	336
248	6.7.3	Enter/Exit Modes	336
249	6.7.4	Power in Alternate Modes	336
250	A	Audio Adapter Accessory Mode	337
251	A.1	Overview	337
252	A.2	Detail	337
253	A.3	Electrical Requirements	338
254	A.4	Example Implementations	340
255	A.4.1	Passive 3.5 mm to USB Type-C Adapter – Single Pole Detection	
256		Switch.....	340
257	A.4.2	3.5 mm to USB Type-C Adapter Supporting 500 mA Charge-	
258		Through	340
259	B	Debug Accessory Mode	342
260	B.1	Overview	342
261	B.2	Functional	342
262	B.2.1	Signal Summary	343
263	B.2.2	Port Interoperability	343
264	B.2.3	Debug Accessory Mode Entry	343
265	B.2.4	Connection State Diagrams	344
266	B.2.5	DTS Port Interoperability Behavior.....	353
267	B.2.6	Orientation Detection	362
268	B.3	Security/Privacy Requirements:.....	363
269	C	USB Type-C Digital Audio.....	364
270	C.1	Overview	364
271	C.2	USB Type-C Digital Audio Specifications.....	364
272	D	Thermal Design Considerations for Active Cables	366
273	D.1	Introduction	366
274	D.2	Model	366
275	D.2.1	Assumptions.....	366
276	D.2.2	Model Architecture	367
277	D.2.3	Heat Sources	368
278	D.2.4	Heat Flow	368
279	D.3	USB 3.2 Single Lane Active Cable	369

280	D.3.1	USB 3.2 Single-Lane Active Cable Design Considerations.....	369
281	D.4	Dual-Lane Active Cables	372
282	D.4.1	USB 3.2 Dual-Lane Active Cable Design Considerations	372
283	D.4.2	USB 3.2 Dual-Lane Active Cable in a Multi-Port Configuration....	374
284	D.5	USB 3.2 Host and Device Design Considerations	376
285	D.5.1	Heat Spreading or Heat Sinking from Host or Device	376
286	D.5.2	Motherboard Temperature Control	377
287	D.5.3	Wider Port Spacing for Multi-Port Applications.....	377
288	D.5.4	Power Policies	377
289	E	Alternate Modes.....	378
290	E.1	Alternate Mode Architecture.....	378
291	E.2	Alternate Mode Requirements.....	378
292	E.2.1	Alternate Mode Pin Reassignment	379
293	E.2.2	Alternate Mode Electrical Requirements	380
294	E.3	Parameter Values.....	382
295	E.4	Example Alternate Mode – USB DisplayPort™ Dock	383
296	E.4.1	USB DisplayPort™ Dock Example	383
297	E.4.2	Functional Overview	384
298	E.4.3	Operational Summary	385
299	F	Thunderbolt 3 Compatibility Discovery and Entry.....	387
300	F.1	TBT3 Compatibility Mode Functional Requirements	387
301	F.1.1	TBT3-Compatible Power Requirements.....	387
302	F.1.2	TBT3-Compatible Host Requirements	387
303	F.1.3	TBT3-Compatible Device Upstream Requirements	387
304	F.1.4	TBT3-Compatible Device Downstream Requirements.....	387
305	F.1.5	TBT3-Compatible Self-Powered Device Without Predefined	
306		Upstream Port Rules.....	388
307	F.1.6	TBT3-Compatible Devices with a Captive Cable	388
308	F.2	TBT3 Discovery and Entry Flow	388
309	F.2.1	TBT3 Passive Cable Discover Identity Responses.....	390
310	F.2.2	TBT3 Active Cable Discover Identity Responses	392
311	F.2.3	TBT3 Device Discover Identity Responses	395
312	F.2.4	TBT3 Discover SVID Responses	396
313	F.2.5	TBT3 Device Discover Mode Responses.....	397
314	F.2.6	TBT3 Cable Discover Mode Responses	398
315	F.2.7	TBT3 Cable Enter Mode Command	399
316	F.2.8	TBT3 Device Enter Mode Command	400
317	F.2.9	TBT3 Cable Functional Difference Summary	402
318	G	Extracting Pulse Response from Sampled Data and Calculating Non-Linearity	
319		Noise.....	403
320	H	USB PD High-Voltage Design Considerations.....	405
321	H.1	Potential for Arcing Damage During Cable Withdrawal	405
322	H.2	USB Type-C Cable Withdrawal Arcing Due to Sink Discharge	405
323	H.3	Mitigating Arcing Damage During Cable Withdrawal.....	407

324	H.3.1	Limiting Sink Discharge Rate.....	408
325	H.3.2	Load Removal	410
326	H.3.3	Limiting Source Current Capability	412

327

328 FIGURES

329

330	Figure 2-1	USB Type-C Receptacle Interface (Front View)	33
331	Figure 2-2	USB Full-Featured Type-C Plug Interface (Front View)	34
332	Figure 3-1	USB Type-C Receptacle Interface Dimensions.....	47
333	Figure 3-2	Reference Design USB Type-C Plug External EMC Spring Contact Zones	50
334	Figure 3-3	USB Full-Featured Type-C Plug Interface Dimensions	51
335	Figure 3-4	Reference Footprint for a USB Type-C Vertical Mount Receptacle (Informative).....	54
336	Figure 3-5	Reference Footprint for a USB Type-C Dual-Row SMT Right Angle Receptacle (Informative).....	55
338	Figure 3-6	Reference Footprint for a USB Type-C Hybrid Right-Angle Receptacle (Informative)	56
339	Figure 3-7	Reference Footprint for a USB Type-C Mid-Mount Dual-Row SMT Receptacle (Informative).....	57
341	Figure 3-8	Reference Footprint for a USB Type-C Mid-Mount Hybrid Receptacle (Informative).....	58
342	Figure 3-9	Reference Footprint for a USB 2.0 Type-C Through Hole Right Angle Receptacle (Informative).....	59
344	Figure 3-10	Reference Footprint for a USB 2.0 Type-C Single Row Right Angle Receptacle (Informative).....	60
346	Figure 3-11	USB 2.0 Type-C Plug Interface Dimensions	62
347	Figure 3-12	USB Type-C Plug EMC Shielding Spring Tip Requirements	65
348	Figure 3-13	Reference Design of Receptacle Mid-Plate	66
349	Figure 3-14	Reference Design of the Retention Latch	67
350	Figure 3-15	Illustration of the Latch Soldered to the Paddle Card Ground.....	67
351	Figure 3-16	Reference Design of the USB Full-Featured Type-C Plug Internal EMC Spring	68
352	Figure 3-17	Reference Design of the USB 2.0 Type-C Plug Internal EMC Spring	69
353	Figure 3-18	Reference Design of Internal EMC Pad.....	70
354	Figure 3-19	Reference Design of a USB Type-C Receptacle with External EMC Springs.....	71
355	Figure 3-20	Reference Design for a USB Full-Featured Type-C Plug Paddle Card.....	72
356	Figure 3-21	Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example with VCONN.....	75
358	Figure 3-22	Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example without VCONN.....	75
360	Figure 3-23	USB Full-Featured Type-C Standard Cable Assembly.....	79
361	Figure 3-24	USB Type-C to USB 3.1 Standard-A Cable Assembly	82
362	Figure 3-25	USB Type-C to USB 2.0 Standard-A Cable Assembly	84
363	Figure 3-26	USB Type-C to USB 3.1 Standard-B Cable Assembly.....	85
364	Figure 3-27	USB Type-C to USB 2.0 Standard-B Cable Assembly.....	86
365	Figure 3-28	USB Type-C to USB 2.0 Mini-B Cable Assembly	87
366	Figure 3-29	USB Type-C to USB 3.1 Micro-B Cable Assembly	88
367	Figure 3-30	USB Type-C to USB 2.0 Micro-B Cable Assembly	90
368	Figure 3-31	USB Type-C to USB 3.1 Standard-A Receptacle Adapter Assembly	91
369	Figure 3-32	USB Type-C to USB 2.0 Micro-B Receptacle Adapter Assembly	93
370	Figure 3-33	Illustration of Test Points for a Mated Cable Assembly.....	95
371	Figure 3-34	Recommended Differential Insertion Loss Requirement (USB 3.2 Gen2 and USB4 Gen2)	96
372			
373	Figure 3-35	Recommended Differential Return Loss Requirement.....	97
374	Figure 3-36	Recommended Differential Crosstalk Requirement	97

375	Figure 3-37 Recommended Differential Near-End and Far-End Crosstalk Requirement between USB	
376	D+/D- Pair and TX/RX Pair	98
377	Figure 3-38 Recommended Differential Insertion Loss Requirement (USB4 Gen3)	98
378	Figure 3-39 Illustration of Insertion Loss Fit at Nyquist Frequency	100
379	Figure 3-40 Input Pulse Spectrum	101
380	Figure 3-41 IMR Limit as Function of ILfitatNq	101
381	Figure 3-42 IRL Limit as Function of ILfitatNq	103
382	Figure 3-43 Differential-to-Common-Mode Conversion Requirement	104
383	Figure 3-44 IMR Limit as Function of ILfit at 10 GHz (USB4 Gen3)	107
384	Figure 3-45 Definition of Port, Victim, and Aggressor	108
385	Figure 3-46 IXT_DP and IXT_USB Limit as Function of ILfit at 10 GHz (USB4 Gen3)	108
386	Figure 3-47 IRL Limit as Function of ILfitatNq (USB4 Gen3)	109
387	Figure 3-48 Differential-to-Common-Mode Conversion Requirement (USB4 Gen3)	109
388	Figure 3-49 Cable Assembly in System	110
389	Figure 3-50 Requirement for Differential Coupling between CC and D+/D-	112
390	Figure 3-51 Requirement for Single-Ended Coupling between CC and D- in USB 2.0 Type-C Cables	
391	113
392	Figure 3-52 Requirement for Single-Ended Coupling between CC and D- in USB Full-Featured Type-	
393	C Cables	113
394	Figure 3-53 Requirement for Differential Coupling between VBUS and D+/D-	114
395	Figure 3-54 Requirement for Single-Ended Coupling between SBU_A and SBU_B	115
396	Figure 3-55 Requirement for Single-Ended Coupling between SBU_A/SBU_B and CC	115
397	Figure 3-56 Requirement for Coupling between SBU_A and differential D+/D-, and SBU_B and	
398	differential D+/D-	116
399	Figure 3-57 Illustration of USB Type-C Mated Connector	117
400	Figure 3-58 Recommended Impedance Limits of a USB Type-C Mated Connector	117
401	Figure 3-59 Recommended Ground Void Dimensions for USB Type-C Receptacle	118
402	Figure 3-60 Recommended Differential Near-End and Far-End Crosstalk Limits between D+/D- Pair	
403	and TX/RX Pairs	120
404	Figure 3-61 Recommended Limits for Differential-to-Common-Mode Conversion	120
405	Figure 3-62 IMR Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly	124
406	Figure 3-63 IRL Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly	124
407	Figure 3-64 Cable Assembly Shielding Effectiveness Testing	128
408	Figure 3-65 Shielding Effectiveness Pass/Fail Criteria	129
409	Figure 3-66 LLCR Measurement Diagram	130
410	Figure 3-67 Temperature Measurement Point	132
411	Figure 3-68 Example Current Rating Test Fixture Trace Configuration	133
412	Figure 3-69 Example of 4-Axis Continuity Test Fixture	135
413	Figure 3-70 Example Wrenching Strength Test Fixture for Plugs without Overmold	137
414	Figure 3-71 Reference Wrenching Strength Continuity Test Fixture	138
415	Figure 3-72 Example of Wrenching Strength Test Mechanical Failure Point	138
416	Figure 3-73 Wrenching Strength Test with Cable in Fixture	139
417	Figure 3-74 USB Type-C Cable Receptacle Flange Example	141
418	Figure 3-75 EMC Guidelines for Side Latch and Mid-plate	142
419	Figure 3-76 EMC Finger Connections to Plug Shell	142
420	Figure 3-77 EMC Pad Connections to Receptacle Shell	143
421	Figure 3-78 Examples of Connector Apertures	143
422	Figure 3-79 Recommended Minimum Spacing between Connectors	144
423	Figure 3-80 Recommended Minimum Plug Overmold Clearance	144
424	Figure 3-81 Cable Plug Overmold and an Angled Surface	145
425	Figure 4-1 Cable IR Drop	148
426	Figure 4-2 Cable IR Drop for powered cables	148
427	Figure 4-3 Logical Model for Single-Lane Data Bus Routing across USB Type-C-based Ports	158
428	Figure 4-4 Logical Model for USB Type-C-based Ports for a Single-Lane Direct Connect Device	158
429	Figure 4-5 Pull-Up/Pull-Down CC Model	160