



**SLOVENSKI STANDARD**  
**oSIST prEN IEC 62680-1-3:2022**  
**01-marec-2022**

---

**Vmesniki univerzalnega serijskega vodila za prenos podatkov in napajanje - 1-3. del: Skupne komponente - Specifikacija za kable in priključke univerzalnega serijskega vodila tipa C®**

Universal serial bus interfaces for data and power - Part 1-3: Common components - USB Type-C® Cable and Connector Specification

Schnittstellen des Universellen Seriellen Busses für Daten und Energie – Teil 1-3: Gemeinsame Bauteile – Festlegung für USB-Typ-CTM-Kabel und -Steckverbinder

Interfaces de bus universel en série pour les données et l'alimentation électrique - Partie 1-3: Composants communs - Spécification des câbles et des connecteurs USB Type-C®

[oSIST prEN IEC 62680-1-3:2022](https://standards.iteh.ai/catalog/standards/sist/7a97b682-0401-4a24-9116-9ba3b9711012/osist-pr-en-iec-62680-1-3-2022)

**Ta slovenski standard je istoveten z: prEN IEC 62680-1-3:2022**

---

**ICS:**

35.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment
--------	---------------------------------	---

**oSIST prEN IEC 62680-1-3:2022**      **en,fr,de**

**iTeh STANDARD  
PREVIEW  
(standards.iteh.ai)**

[oSIST prEN IEC 62680-1-3:2022](https://standards.iteh.ai/catalog/standards/sist/7a97b682-04b1-4a94-91f6-9ba3b9710012/osist-pren-iec-62680-1-3-2022)

<https://standards.iteh.ai/catalog/standards/sist/7a97b682-04b1-4a94-91f6-9ba3b9710012/osist-pren-iec-62680-1-3-2022>



# 100/3715/CDV

## COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER:

**IEC 62680-1-3 ED5**

DATE OF CIRCULATION:

**2022-01-28**

CLOSING DATE FOR VOTING:

**2022-04-22**

SUPERSEDES DOCUMENTS:

**100/3707/RR**

IEC TA 18 : MULTIMEDIA HOME SYSTEMS AND APPLICATIONS FOR END-USER NETWORKS	
SECRETARIAT: Japan	SECRETARY: Mr Keisuke Koide
OF INTEREST TO THE FOLLOWING COMMITTEES:	PROPOSED HORIZONTAL STANDARD: <input type="checkbox"/> Other TC/SCs are requested to indicate their interest, if any, in this CDV to the secretary.
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING <b>Attention IEC-CENELEC parallel voting</b> The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting. The CENELEC members are invited to vote through the CENELEC online voting system.	<input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

**Universal serial bus interfaces for data and power - Part 1-3: Common components - USB Type-C® Cable and Connector Specification**

PROPOSED STABILITY DATE: 2026

NOTE FROM TC/SC OFFICERS:

**Copyright © 2021 International Electrotechnical Commission, IEC.** All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

Only the cover page was created by TA18.

For the main body, the document (USB Type-C Spec R2.1 - May 2021.docx) supplied from USB-IF was uploaded as "CDV additional file (s)".

Please have the IEC Central Office convert it to the IEC prescribed format.

**iTeh STANDARD  
PREVIEW  
(standards.iteh.ai)**

[oSIST prEN IEC 62680-1-3:2022](https://standards.iteh.ai/catalog/standards/sist/7a97b682-04b1-4a94-91f6-9ba3b9710012/osist-pren-iec-62680-1-3-2022)

<https://standards.iteh.ai/catalog/standards/sist/7a97b682-04b1-4a94-91f6-9ba3b9710012/osist-pren-iec-62680-1-3-2022>

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19

# Universal Serial Bus Type-C Cable and Connector Specification

**iTeh STANDARD  
PREVIEW  
(standards.iteh.ai)**

**Release 2.1  
May 2021**

[oSIST prEN IEC 62680-1-3:2022](https://standards.iteh.ai/catalog/standards/sist/7a97b682-04b1-4a94-91f6-9ba3b9710012/osist-pren-iec-62680-1-3-2022)  
<https://standards.iteh.ai/catalog/standards/sist/7a97b682-04b1-4a94-91f6-9ba3b9710012/osist-pren-iec-62680-1-3-2022>

20 **Copyright © 2014-2021, USB 3.0 Promoter Group:**  
21 **Apple Inc., HP Inc., Intel Corporation, Microsoft**  
22 **Corporation, Renesas, STMicroelectronics, and Texas Instruments**  
23 **All rights reserved.**

26 NOTE: Adopters may only use the USB Type-C® cable and connector to implement USB or third-  
27 party functionality as expressly described in this Specification; all other uses are prohibited.

28 LIMITED COPYRIGHT LICENSE: The USB 3.0 Promoters grant a conditional copyright license under  
29 the copyrights embodied in the USB Type-C Cable and Connector Specification to use and reproduce  
30 the Specification for the sole purpose of, and solely to the extent necessary for, evaluating whether to  
31 implement the Specification in products that would comply with the specification. Without limiting  
32 the foregoing, use of the Specification for the purpose of filing or modifying any patent application to  
33 target the Specification or USB compliant products is not authorized. Except for this express  
34 copyright license, no other rights or licenses are granted, including without limitation any patent  
35 licenses. In order to obtain any additional intellectual property licenses or licensing commitments  
36 associated with the Specification a party must execute the USB 3.0 Adopters Agreement. NOTE: By  
37 using the Specification, you accept these license terms on your own behalf and, in the case where you  
38 are doing this as an employee, on behalf of your employer.

39 **iTeh STANDARD**  
40 **PREVIEW**

41 INTELLECTUAL PROPERTY DISCLAIMER

42 THIS SPECIFICATION IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER,  
43 INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS  
44 FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL  
45 LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS,  
46 RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE  
47 PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE,  
48 EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY  
49 RIGHTS.

50 All implementation examples and reference designs contained within this Specification are  
51 included as part of the limited patent license for those companies that execute the USB 3.0  
52 Adopters Agreement.

53  
54  
55 USB Type-C®, USB-C® and USB4™ are trademarks of the Universal Serial Bus Implementers  
56 Forum (USB-IF). DisplayPort™ is a trademark of VESA. All product names are trademarks,  
57 registered trademarks, or service marks of their respective owners.

58 Thunderbolt™ is a trademark of Intel Corporation. You may only use the Thunderbolt™  
59 trademark or logo in conjunction with products designed to this specification that complete  
60 proper certification and executing a Thunderbolt™ trademark license – see  
61 [usb.org/compliance](https://usb.org/compliance) for further information.

62

## CONTENTS

63	Specification Work Group Chairs / Specification Editors .....	18
64	Specification Work Group Contributors .....	18
65	Pre-Release Draft Industry Reviewing Companies That Provided Feedback.....	25
66	Revision History.....	25
67	1 Introduction .....	26
68	1.1 Purpose.....	26
69	1.2 Scope.....	26
70	1.3 Related Documents.....	27
71	1.4 Conventions.....	27
72	1.4.1 Precedence .....	27
73	1.4.2 Keywords .....	27
74	1.4.3 Numbering.....	28
75	1.5 Terms and Abbreviations.....	28
76	2 Overview .....	33
77	2.1 Introduction .....	33
78	2.2 USB Type-C Receptacles, Plugs and Cables .....	34
79	2.3 Configuration Process .....	35
80	2.3.1 Source-to-Sink Attach/Detach Detection.....	36
81	2.3.2 Plug Orientation/Cable Twist Detection.....	36
82	2.3.3 Initial Power (Source-to-Sink) Detection and Establishing the Data	
83	(Host-to-Device) Relationship.....	36
84	2.3.4 USB Type-C VBUS Current Detection and Usage .....	37
85	2.3.5 USB PD Communication.....	38
86	2.3.6 Functional Extensions.....	38
87	2.4 VBUS.....	38
88	2.5 VCONN.....	39
89	2.6 Hubs.....	40
90	3 Mechanical.....	41
91	3.1 Overview .....	41
92	3.1.1 Compliant Connectors.....	41
93	3.1.2 Compliant Cable Assemblies.....	41
94	3.1.3 Compliant USB Type-C to Legacy Cable Assemblies .....	42
95	3.1.4 Compliant USB Type-C to Legacy Adapter Assemblies .....	43
96	3.2 USB Type-C Connector Mating Interfaces .....	43
97	3.2.1 Interface Definition.....	43
98	3.2.2 Reference Designs.....	66
99	3.2.3 Pin Assignments and Descriptions.....	73
100	3.3 Cable Construction and Wire Assignments.....	74
101	3.3.1 Cable Construction (Informative) .....	74
102	3.3.2 Wire Assignments .....	76
103	3.3.3 Wire Gauges and Cable Diameters (Informative).....	77

104	3.4	Standard USB Type-C Cable Assemblies .....	79
105	3.4.1	USB Full-Featured Type-C Cable Assembly .....	79
106	3.4.2	USB 2.0 Type-C Cable Assembly.....	80
107	3.4.3	USB Type-C Captive Cable Assemblies.....	81
108	3.4.4	USB Type-C Thumb Drive Assemblies.....	81
109	3.5	Legacy Cable Assemblies .....	82
110	3.5.1	USB Type-C to <i>USB 3.1</i> Standard-A Cable Assembly .....	82
111	3.5.2	USB Type-C to <i>USB 2.0</i> Standard-A Cable Assembly .....	84
112	3.5.3	USB Type-C to <i>USB 3.1</i> Standard-B Cable Assembly .....	85
113	3.5.4	USB Type-C to <i>USB 2.0</i> Standard-B Cable Assembly .....	86
114	3.5.5	USB Type-C to <i>USB 2.0</i> Mini-B Cable Assembly.....	87
115	3.5.6	USB Type-C to <i>USB 3.1</i> Micro-B Cable Assembly.....	88
116	3.5.7	USB Type-C to <i>USB 2.0</i> Micro-B Cable Assembly.....	90
117	3.6	Legacy Adapter Assemblies .....	91
118	3.6.1	USB Type-C to <i>USB 3.1</i> Standard-A Receptacle Adapter Assembly	91
119	3.6.2	USB Type-C to <i>USB 2.0</i> Micro-B Receptacle Adapter Assembly.....	93
120	3.7	Electrical Characteristics .....	94
121	3.7.1	Raw Cable (Informative) .....	94
122	3.7.2	USB Type-C to Type-C Passive Cable Assemblies (Normative) .....	95
123	3.7.3	Mated Connector (Informative - <i>USB 3.2</i> Gen2 and <i>USB4</i> Gen2)	117
124	3.7.4	Receptacle Connector SI Requirements and Testing (Normative -	
125		<i>USB4</i> Gen3).....	120
126	3.7.5	USB Type-C to Legacy Cable Assemblies (Normative) .....	121
127	3.7.6	USB Type-C to USB Legacy Adapter Assemblies (Normative) .....	125
128	3.7.7	Shielding Effectiveness Requirements (Normative).....	127
129	3.7.8	DC Electrical Requirements (Normative) .....	130
130	3.8	Mechanical and Environmental Requirements (Normative).....	133
131	3.8.1	Mechanical Requirements.....	134
132	3.8.2	Environmental Requirements.....	139
133	3.9	Docking Applications (Informative) .....	140
134	3.10	Implementation Notes and Design Guides.....	141
135	3.10.1	EMC Management (Informative).....	141
136	3.10.2	Stacked and Side-by-Side Connector Physical Spacing (Informative)	
137		.....	144
138	3.10.3	Cable Mating Considerations (Informative).....	144
139	3.11	Extended Power Range (EPR) Cables .....	145
140	3.11.1	Electrical Requirements .....	145
141	3.11.2	EPR Cable Identification Requirements .....	145
142	4	Functional .....	146
143	4.1	Signal Summary.....	146
144	4.2	Signal Pin Descriptions .....	146
145	4.2.1	SuperSpeed USB Pins .....	146
146	4.2.2	USB 2.0 Pins .....	147
147	4.2.3	Auxiliary Signal Pins.....	147



148	4.2.4	Power and Ground Pins .....	147
149	4.2.5	Configuration Pins .....	147
150	4.3	Sideband Use (SBU).....	147
151	4.4	Power and Ground.....	148
152	4.4.1	IR Drop.....	148
153	4.4.2	VBUS.....	149
154	4.4.3	VCONN.....	151
155	4.5	Configuration Channel (CC) .....	157
156	4.5.1	Architectural Overview .....	157
157	4.5.2	CC Functional and Behavioral Requirements .....	170
158	4.5.3	USB Port Interoperability Behavior.....	208
159	4.6	Power.....	227
160	4.6.1	Power Requirements during USB Suspend.....	228
161	4.6.2	VBUS Power Provided Over a USB Type-C Cable .....	229
162	4.7	USB Hubs .....	235
163	4.8	Power Sourcing and Charging.....	236
164	4.8.1	DFP as a Power Source .....	236
165	4.8.2	Non-USB Charging Methods .....	239
166	4.8.3	Sinking Host .....	239
167	4.8.4	Sourcing Device.....	239
168	4.8.5	Charging a System with a Dead Battery .....	239
169	4.8.6	USB Type-C Multi-Port Chargers .....	239
170	4.9	Electronically Marked Cables.....	242
171	4.9.1	Parameter Values .....	244
172	4.9.2	Active Cables.....	244
173	4.10	VCONN-Powered Accessories (VPAs) and VCONN-Powered USB Devices	
174		(VPDs) .....	244
175	4.10.1	VCONN-Powered Accessories (VPAs).....	244
176	4.10.2	VCONN-Powered USB Devices (VPDs) .....	245
177	4.11	Parameter Values.....	247
178	4.11.1	Termination Parameters .....	247
179	4.11.2	Timing Parameters.....	249
180	4.11.3	Voltage Parameters.....	252
181	5	USB4 Discovery and Entry .....	254
182	5.1	Overview of the Discovery and Entry Process.....	254
183	5.2	USB4 Functional Requirements.....	255
184	5.2.1	USB4 Host Functional Requirements .....	255
185	5.2.2	USB4 Device Functional Requirements .....	255
186	5.2.3	USB4 Alternate Mode Support.....	255
187	5.2.3.1	USB4 Alternate Mode Support on Hosts.....	255
188	5.2.3.2	USB4 Alternate Mode Support on Hubs and USB4-based Docks..	255
189	5.3	USB4 Power Requirements.....	256
190	5.3.1	Source Power Requirements.....	256
191	5.3.2	Sink Power Requirements .....	256

192	5.3.3	Device Power Management Requirements .....	257
193	5.4	USB4 Discovery and Entry Flow Requirements .....	257
194	5.4.1	USB Type-C Initial Connection .....	257
195	5.4.2	USB Power Delivery Contract .....	257
196	5.4.3	USB4 Discovery and Entry Flow .....	258
197	5.4.3.1	USB4 Device Discovery (SOP) .....	259
198	5.4.3.2	USB4 Cable Discovery (SOP') .....	259
199	5.4.3.3	USB4 Operational Entry .....	262
200	5.4.4	USB4 Post-Entry Operation .....	262
201	5.4.4.1	During USB4 Operation .....	262
202	5.4.4.2	Exiting USB4 Operation .....	262
203	5.5	USB4 Hub Connection Requirements .....	263
204	5.5.1	USB4 Hub Port Initial Connection Requirements .....	263
205	5.5.2	USB4 Hub UFP and Host Capabilities Discovery .....	263
206	5.5.3	Hub DFP Connection Requirements .....	264
207	5.5.3.1	Speculative Connections .....	264
208	5.5.3.2	Operational Connections .....	264
209	5.5.4	Hub Ports Connection Behavior Flow Examples .....	265
210	5.5.5	Connecting to Downstream USB4 Hubs .....	270
211	5.5.6	Fallback Functional Requirements for USB4 Hubs .....	270
212	5.6	USB4 Device Connection Requirements .....	271
213	5.6.1	Fallback Mapping of USB4 Peripheral Functions to USB Device	
214		Class Types .....	271
215	5.7	Parameter Values .....	272
216	5.7.1	Timing Parameters .....	272
217	6	Active Cables .....	273
218	6.1	USB Type-C State Machine .....	275
219	6.2	USB PD Requirements .....	275
220	6.2.1	Active Cable USB PD Requirements .....	277
221	6.2.2	USB PD Messages for OIAC .....	278
222	6.2.3	Short Active Cable Behaviors in Response to Power Delivery	
223		Events .....	290
224	6.3	OIAC Connection Flow and State Diagrams .....	290
225	6.3.1	OIAC Connection Flow – Discovery – Phase 1 .....	291
226	6.3.2	OIAC Connection Flow – Reboot – Phase 2 .....	292
227	6.3.3	OIAC Connection Flow – Configuration – Phase 3 .....	293
228	6.3.4	OIAC Connection State Diagram Plug-A .....	296
229	6.3.5	OIAC Connection State Diagram Plug-B .....	304
230	6.4	Active Cable Power Requirements .....	309
231	6.4.1	VBUS Requirements .....	309
232	6.4.2	OIAC VBUS Requirements .....	309
233	6.4.3	USB PD Rules in Active State .....	311
234	6.4.4	VCONN Requirements .....	312
235	6.5	Mechanical .....	312

236	6.5.1	Thermal .....	312
237	6.5.2	Plug Spacing .....	313
238	6.6	Electrical Requirements .....	313
239	6.6.1	Shielding Effectiveness Requirement.....	313
240	6.6.2	Low Speed Signal Requirement.....	313
241	6.6.3	USB 2.0.....	314
242	6.6.4	USB 3.2.....	315
243	6.6.5	USB4 .....	322
244	6.6.6	Return Loss .....	336
245	6.7	Active Cables That Support Alternate Modes.....	336
246	6.7.1	Discover SVIDs .....	336
247	6.7.2	Discover Modes .....	336
248	6.7.3	Enter/Exit Modes .....	336
249	6.7.4	Power in Alternate Modes .....	336
250	A	Audio Adapter Accessory Mode .....	337
251	A.1	Overview .....	337
252	A.2	Detail .....	337
253	A.3	Electrical Requirements .....	338
254	A.4	Example Implementations .....	340
255	A.4.1	Passive 3.5 mm to USB Type-C Adapter – Single Pole Detection	
256		Switch.....	340
257	A.4.2	3.5 mm to USB Type-C Adapter Supporting 500 mA Charge-	
258		Through.....	340
259	B	Debug Accessory Mode .....	342
260	B.1	Overview .....	342
261	B.2	Functional .....	342
262	B.2.1	Signal Summary .....	343
263	B.2.2	Port Interoperability .....	343
264	B.2.3	Debug Accessory Mode Entry .....	343
265	B.2.4	Connection State Diagrams .....	344
266	B.2.5	DTS Port Interoperability Behavior.....	353
267	B.2.6	Orientation Detection .....	362
268	B.3	Security/Privacy Requirements:.....	363
269	C	USB Type-C Digital Audio.....	364
270	C.1	Overview .....	364
271	C.2	USB Type-C Digital Audio Specifications.....	364
272	D	Thermal Design Considerations for Active Cables .....	366
273	D.1	Introduction .....	366
274	D.2	Model.....	366
275	D.2.1	Assumptions.....	366
276	D.2.2	Model Architecture .....	367
277	D.2.3	Heat Sources .....	368
278	D.2.4	Heat Flow.....	368
279	D.3	USB 3.2 Single Lane Active Cable.....	369

280	D.3.1	USB 3.2 Single-Lane Active Cable Design Considerations.....	369
281	D.4	Dual-Lane Active Cables .....	372
282	D.4.1	USB 3.2 Dual-Lane Active Cable Design Considerations .....	372
283	D.4.2	USB 3.2 Dual-Lane Active Cable in a Multi-Port Configuration....	374
284	D.5	USB 3.2 Host and Device Design Considerations .....	376
285	D.5.1	Heat Spreading or Heat Sinking from Host or Device .....	376
286	D.5.2	Motherboard Temperature Control .....	377
287	D.5.3	Wider Port Spacing for Multi-Port Applications.....	377
288	D.5.4	Power Policies .....	377
289	E	Alternate Modes.....	378
290	E.1	Alternate Mode Architecture.....	378
291	E.2	Alternate Mode Requirements.....	378
292	E.2.1	Alternate Mode Pin Reassignment .....	379
293	E.2.2	Alternate Mode Electrical Requirements .....	380
294	E.3	Parameter Values.....	382
295	E.4	Example Alternate Mode – USB DisplayPort™ Dock .....	383
296	E.4.1	USB DisplayPort™ Dock Example .....	383
297	E.4.2	Functional Overview .....	384
298	E.4.3	Operational Summary .....	385
299	F	Thunderbolt 3 Compatibility Discovery and Entry.....	387
300	F.1	TBT3 Compatibility Mode Functional Requirements .....	387
301	F.1.1	TBT3-Compatible Power Requirements .....	387
302	F.1.2	TBT3-Compatible Host Requirements .....	387
303	F.1.3	TBT3-Compatible Device Upstream Requirements .....	387
304	F.1.4	TBT3-Compatible Device Downstream Requirements.....	387
305	F.1.5	TBT3-Compatible Self-Powered Device Without Predefined	
306		Upstream Port Rules.....	388
307	F.1.6	TBT3-Compatible Devices with a Captive Cable .....	388
308	F.2	TBT3 Discovery and Entry Flow .....	388
309	F.2.1	TBT3 Passive Cable Discover Identity Responses.....	390
310	F.2.2	TBT3 Active Cable Discover Identity Responses .....	392
311	F.2.3	TBT3 Device Discover Identity Responses .....	395
312	F.2.4	TBT3 Discover SVID Responses .....	396
313	F.2.5	TBT3 Device Discover Mode Responses .....	397
314	F.2.6	TBT3 Cable Discover Mode Responses .....	398
315	F.2.7	TBT3 Cable Enter Mode Command .....	399
316	F.2.8	TBT3 Device Enter Mode Command .....	400
317	F.2.9	TBT3 Cable Functional Difference Summary .....	402
318	G	Extracting Pulse Response from Sampled Data and Calculating Non-Linearity	
319		Noise.....	403
320	H	USB PD High-Voltage Design Considerations.....	405
321	H.1	Potential for Arcing Damage During Cable Withdrawal .....	405
322	H.2	USB Type-C Cable Withdrawal Arcing Due to Sink Discharge .....	405
323	H.3	Mitigating Arcing Damage During Cable Withdrawal.....	407

324	H.3.1	Limiting Sink Discharge Rate.....	408
325	H.3.2	Load Removal .....	410
326	H.3.3	Limiting Source Current Capability .....	412

327

328 **FIGURES**

329

330	Figure 2-1	USB Type-C Receptacle Interface (Front View) .....	33
331	Figure 2-2	USB Full-Featured Type-C Plug Interface (Front View) .....	34
332	Figure 3-1	USB Type-C Receptacle Interface Dimensions.....	47
333	Figure 3-2	Reference Design USB Type-C Plug External EMC Spring Contact Zones .....	50
334	Figure 3-3	USB Full-Featured Type-C Plug Interface Dimensions .....	51
335	Figure 3-4	Reference Footprint for a USB Type-C Vertical Mount Receptacle (Informative).....	54
336	Figure 3-5	Reference Footprint for a USB Type-C Dual-Row SMT Right Angle Receptacle (Informative).....	55
338	Figure 3-6	Reference Footprint for a USB Type-C Hybrid Right-Angle Receptacle (Informative) .....	56
339	Figure 3-7	Reference Footprint for a USB Type-C Mid-Mount Dual-Row SMT Receptacle (Informative).....	57
341	Figure 3-8	Reference Footprint for a USB Type-C Mid-Mount Hybrid Receptacle (Informative).....	58
342	Figure 3-9	Reference Footprint for a USB 2.0 Type-C Through Hole Right Angle Receptacle (Informative).....	59
344	Figure 3-10	Reference Footprint for a USB 2.0 Type-C Single Row Right Angle Receptacle (Informative).....	60
346	Figure 3-11	USB 2.0 Type-C Plug Interface Dimensions .....	62
347	Figure 3-12	USB Type-C Plug EMC Shielding Spring Tip Requirements .....	65
348	Figure 3-13	Reference Design of Receptacle Mid-Plate .....	66
349	Figure 3-14	Reference Design of the Retention Latch .....	67
350	Figure 3-15	Illustration of the Latch Soldered to the Paddle Card Ground.....	67
351	Figure 3-16	Reference Design of the USB Full-Featured Type-C Plug Internal EMC Spring .....	68
352	Figure 3-17	Reference Design of the USB 2.0 Type-C Plug Internal EMC Spring .....	69
353	Figure 3-18	Reference Design of Internal EMC Pad .....	70
354	Figure 3-19	Reference Design of a USB Type-C Receptacle with External EMC Springs.....	71
355	Figure 3-20	Reference Design for a USB Full-Featured Type-C Plug Paddle Card .....	72
356	Figure 3-21	Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example with VCONN.....	75
358	Figure 3-22	Illustration of a USB Full-Featured Type-C Cable Cross Section, a Coaxial Wire Example without VCONN.....	75
360	Figure 3-23	USB Full-Featured Type-C Standard Cable Assembly.....	79
361	Figure 3-24	USB Type-C to USB 3.1 Standard-A Cable Assembly .....	82
362	Figure 3-25	USB Type-C to USB 2.0 Standard-A Cable Assembly .....	84
363	Figure 3-26	USB Type-C to USB 3.1 Standard-B Cable Assembly.....	85
364	Figure 3-27	USB Type-C to USB 2.0 Standard-B Cable Assembly.....	86
365	Figure 3-28	USB Type-C to USB 2.0 Mini-B Cable Assembly .....	87
366	Figure 3-29	USB Type-C to USB 3.1 Micro-B Cable Assembly .....	88
367	Figure 3-30	USB Type-C to USB 2.0 Micro-B Cable Assembly .....	90
368	Figure 3-31	USB Type-C to USB 3.1 Standard-A Receptacle Adapter Assembly .....	91
369	Figure 3-32	USB Type-C to USB 2.0 Micro-B Receptacle Adapter Assembly .....	93
370	Figure 3-33	Illustration of Test Points for a Mated Cable Assembly.....	95
371	Figure 3-34	Recommended Differential Insertion Loss Requirement (USB 3.2 Gen2 and USB4 Gen2) .....	96
373	Figure 3-35	Recommended Differential Return Loss Requirement.....	97
374	Figure 3-36	Recommended Differential Crosstalk Requirement .....	97

375	Figure 3-37 Recommended Differential Near-End and Far-End Crosstalk Requirement between USB	
376	D+/D- Pair and TX/RX Pair .....	98
377	Figure 3-38 Recommended Differential Insertion Loss Requirement (USB4 Gen3) .....	98
378	Figure 3-39 Illustration of Insertion Loss Fit at Nyquist Frequency .....	100
379	Figure 3-40 Input Pulse Spectrum .....	101
380	Figure 3-41 IMR Limit as Function of ILfitatNq .....	101
381	Figure 3-42 IRL Limit as Function of ILfitatNq .....	103
382	Figure 3-43 Differential-to-Common-Mode Conversion Requirement .....	104
383	Figure 3-44 IMR Limit as Function of ILfit at 10 GHz (USB4 Gen3) .....	107
384	Figure 3-45 Definition of Port, Victim, and Aggressor .....	108
385	Figure 3-46 IXT_DP and IXT_USB Limit as Function of ILfit at 10 GHz (USB4 Gen3) .....	108
386	Figure 3-47 IRL Limit as Function of ILfitatNq (USB4 Gen3) .....	109
387	Figure 3-48 Differential-to-Common-Mode Conversion Requirement (USB4 Gen3) .....	109
388	Figure 3-49 Cable Assembly in System .....	110
389	Figure 3-50 Requirement for Differential Coupling between CC and D+/D- .....	112
390	Figure 3-51 Requirement for Single-Ended Coupling between CC and D- in USB 2.0 Type-C Cables	
391	.....	113
392	Figure 3-52 Requirement for Single-Ended Coupling between CC and D- in USB Full-Featured Type-	
393	C Cables .....	113
394	Figure 3-53 Requirement for Differential Coupling between VBUS and D+/D- .....	114
395	Figure 3-54 Requirement for Single-Ended Coupling between SBU_A and SBU_B .....	115
396	Figure 3-55 Requirement for Single-Ended Coupling between SBU_A/SBU_B and CC .....	115
397	Figure 3-56 Requirement for Coupling between SBU_A and differential D+/D-, and SBU_B and	
398	differential D+/D- .....	116
399	Figure 3-57 Illustration of USB Type-C Mated Connector .....	117
400	Figure 3-58 Recommended Impedance Limits of a USB Type-C Mated Connector .....	117
401	Figure 3-59 Recommended Ground Void Dimensions for USB Type-C Receptacle .....	118
402	Figure 3-60 Recommended Differential Near-End and Far-End Crosstalk Limits between D+/D- Pair	
403	and TX/RX Pairs .....	120
404	Figure 3-61 Recommended Limits for Differential-to-Common-Mode Conversion .....	120
405	Figure 3-62 IMR Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly .....	124
406	Figure 3-63 IRL Limit as Function of ILfitatNq for USB Type-C to Legacy Cable Assembly .....	124
407	Figure 3-64 Cable Assembly Shielding Effectiveness Testing .....	128
408	Figure 3-65 Shielding Effectiveness Pass/Fail Criteria .....	129
409	Figure 3-66 LLCR Measurement Diagram .....	130
410	Figure 3-67 Temperature Measurement Point .....	132
411	Figure 3-68 Example Current Rating Test Fixture Trace Configuration .....	133
412	Figure 3-69 Example of 4-Axis Continuity Test Fixture .....	135
413	Figure 3-70 Example Wrenching Strength Test Fixture for Plugs without Overmold .....	137
414	Figure 3-71 Reference Wrenching Strength Continuity Test Fixture .....	138
415	Figure 3-72 Example of Wrenching Strength Test Mechanical Failure Point .....	138
416	Figure 3-73 Wrenching Strength Test with Cable in Fixture .....	139
417	Figure 3-74 USB Type-C Cable Receptacle Flange Example .....	141
418	Figure 3-75 EMC Guidelines for Side Latch and Mid-plate .....	142
419	Figure 3-76 EMC Finger Connections to Plug Shell .....	142
420	Figure 3-77 EMC Pad Connections to Receptacle Shell .....	143
421	Figure 3-78 Examples of Connector Apertures .....	143
422	Figure 3-79 Recommended Minimum Spacing between Connectors .....	144
423	Figure 3-80 Recommended Minimum Plug Overmold Clearance .....	144
424	Figure 3-81 Cable Plug Overmold and an Angled Surface .....	145
425	Figure 4-1 Cable IR Drop .....	148
426	Figure 4-2 Cable IR Drop for powered cables .....	148
427	Figure 4-3 Logical Model for Single-Lane Data Bus Routing across USB Type-C-based Ports .....	158
428	Figure 4-4 Logical Model for USB Type-C-based Ports for a Single-Lane Direct Connect Device .....	158
429	Figure 4-5 Pull-Up/Pull-Down CC Model .....	160

430	Figure 4-6 Current Source/Pull-Down CC Model.....	160
431	Figure 4-7 Source Functional Model for CC1 and CC2.....	163
432	Figure 4-8 Source Functional Model Supporting USB PD PR_Swap .....	164
433	Figure 4-9 Sink Functional Model for CC1 and CC2 .....	165
434	Figure 4-10 Sink Functional Model Supporting USB PD PR_Swap and VCONN_Swap.....	166
435	Figure 4-11 DRP Functional Model for CC1 and CC2.....	166
436	Figure 4-12 Connection State Diagram: Source.....	171
437	Figure 4-13 Connection State Diagram: Sink.....	172
438	Figure 4-14 Connection State Diagram: Sink with Accessory Support .....	173
439	Figure 4-15 Connection State Diagram: DRP.....	174
440	Figure 4-16 Connection State Diagram: DRP with Accessory and Try.SRC Support.....	175
441	Figure 4-17 Connection State Diagram: DRP with Accessory and Try.SNK Support.....	176
442	Figure 4-18 Connection State Diagram: Charge-Through VPD.....	177
443	Figure 4-19 Sink Power Sub-States.....	201
444	Figure 4-20 Passive Cable eMarker State Diagram .....	203
445	Figure 4-21 Active Cable eMarker State Diagram.....	203
446	Figure 4-22 Cable Ra Management State Diagram .....	205
447	Figure 4-23 Source to Sink Functional Model .....	208
448	Figure 4-24 Source to DRP Functional Model.....	209
449	Figure 4-25 DRP to Sink Functional Model.....	210
450	Figure 4-26 DRP to DRP Functional Model – CASE 1 .....	211
451	Figure 4-27 DRP to DRP Functional Model – CASE 2 & 3.....	212
452	Figure 4-28 Source to Source Functional Model .....	214
453	Figure 4-29 Sink to Sink Functional Model.....	215
454	Figure 4-30 DRP to VPD Model .....	215
455	Figure 4-31 Example DRP to Charge-Through VCONN-Powered USB Device Model.....	216
456	Figure 4-32 Source to Legacy Device Port Functional Model.....	224
457	Figure 4-33 Legacy Host Port to Sink Functional Model.....	225
458	Figure 4-34 DRP to Legacy Device Port Functional Model.....	226
459	Figure 4-35 Legacy Host Port to DRP Functional Model.....	227
460	Figure 4-36 Sink Monitoring for Current in Pull-Up/Pull-Down CC Model .....	231
461	Figure 4-37 Sink Monitoring for Current in Current Source/Pull-Down CC Model.....	231
462	Figure 4-38 USB PD over CC Pins.....	232
463	Figure 4-39 USB PD BMC Signaling over CC.....	232
464	Figure 4-40 USB Type-C Cable’s Output as a Function of Load for Non-PD-based USB Type-C Charging.....	237
466	Figure 4-41 0 – 3 A USB PD-based Charger USB Type-C Cable’s Output as a Function of Load.....	238
467	Figure 4-42 3 – 5 A USB PD-based Charger USB Type-C Cable’s Output as a Function of Load.....	238
468	Figure 4-43 Electronically Marked Cable with VCONN connected through the cable .....	243
469	Figure 4-44 Electronically Marked Cable with SOP’ at both ends .....	244
470	Figure 4-45 Example Charge-Through VCONN-Power USB Device Use Case.....	246
471	Figure 4-46 DRP Timing.....	250
472	Figure 5-1 USB4 Discovery and Entry Flow Model.....	258
473	Figure 5-2 USB4 Hub with USB4 Host and Device Connection Flow Alignment .....	265
474	Figure 5-3 USB4 Hub with USB 3.2 Host and USB4 Device Host Connection Flow .....	266
475	Figure 5-4 USB4 Hub with USB4 Host and USB 3.2 Device Connection Flow .....	267
476	Figure 5-5 USB4 Hub with USB 3.2 Host and Device Connection Flow.....	268
477	Figure 5-6 USB4 Hub with USB4 Host and DP Alt Mode Device Connection Flow .....	269
478	Figure 5-7 USB4 Hub with USB 3.2 Host and DP Alt Mode Device Connection Flow.....	270
479	Figure 6-1 Electronically Marked Short Active Cable with SOP’ Only .....	276
480	Figure 6-2 Electronically Marked Short Active Cable with SOP’ and SOP” .....	276
481	Figure 6-3 Electronically Marked Optically Isolated Active Cable .....	277
482	Figure 6-4 OIAC USB PD Message Forwarding .....	284
483	Figure 6-5 OIAC Successful Data Role Swap.....	287
484	Figure 6-6 OIAC Rejected Data Role Swap .....	288