



Designation: D6975 – 04 (Reapproved 2010)

Standard Test Method for Cummins M11 EGR Test¹

This standard is issued under the fixed designation D6975; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method is commonly referred to as the Cummins M11 Exhaust Gas Recirculation Test (EGR). The test method defines a heavy-duty diesel engine test procedure conducted under high soot conditions to evaluate oil performance with regard to valve train wear, sludge deposits, and oil filter plugging² in an EGR environment.

1.2 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use. See Annex A1 for general safety precautions.*

1.4 Table of Contents:

Scope	1
Referenced Documents	2
Terminology	3
Summary of Test Method	4
Significance and Use	5
Apparatus	6
Test Engine Configuration	6.1
Test Engine	6.1.1

Oil Heat Exchanger, Adapter Blocks, and Block Off Plate	6.1.2
Oil Filter Head Modification	6.1.3
Oil Pan Modification	6.1.4
Engine Control Module	6.1.5
Engine Position Sensor	6.1.6
Air Compressor and Fuel Pump	6.1.7
Test Stand Configuration	6.2
Engine Mounting	6.2.1
Intake Air System	6.2.2
Aftercooler	6.2.3
Exhaust System	6.2.4
Exhaust Gas Recirculation System	6.2.5
Fuel Supply	6.2.6
Coolant System	6.2.7
Pressurized Oil Fill System	6.2.8
External Oil System	6.2.9
Crankcase Aspiration	6.2.10
Blowby Rate	6.2.11
System Time Responses	6.3
Oil Sample Containers	6.4
Mass Balance	6.5
Engine and Cleaning Fluids	7
Test Oil	7.1
Test Fuel	7.2
Engine Coolant	7.3
Solvent	7.4
Preparation of Apparatus	8
Cleaning of Parts	8.1
General	8.1.1
Engine Block	8.1.2
Cylinder Head	8.1.3
Rocker Cover and Oil Pan	8.1.4
External Oil System	8.1.5
Crosshead Cleaning and Measurement	8.1.6
Rod Bearing Cleaning and Measurement	8.1.7
Ring Cleaning and Measurement	8.1.8
Injector Adjusting Screw Cleaning and Measurement	8.1.9
Engine Assembly	8.2
General	8.2.1
Parts Reuse and Replacement	8.2.2
Build-Up Oil	8.2.3
Coolant Thermostat	8.2.4
Oil Thermostat	8.2.5
Fuel Injectors	8.2.6
New Parts	8.2.7

¹ This test method is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.B0.02 on Heavy Duty Engine Oils.

Current edition approved Oct. 1, 2010. Published November 2010. Originally approved in 2003. Last previous edition approved in 2004 as D6975-04. DOI: 10.1520/D6975-04R10.

² The ASTM Test Monitoring Center will update changes in this test method by means of Information Letters. Information letters may be obtained from the ASTM Test Monitoring Center, 6555 Penn Avenue, Pittsburgh, PA 15206-4489, Attention: Administrator. This edition incorporates revisions contained in all information letters through 03-1.

Operational Measurements	8.3
Units and Formats	8.3.1
Instrumentation Calibration	8.3.2
Temperatures	8.3.3
Pressures	8.3.4
Flow Rates	8.3.5
Intake and Exhaust CO ₂ Measurement	8.3.6
Engine/Stand Calibration and Non-Reference Oil Tests	9
General	9.1
New Test Stand	9.2
New Test Stand Calibration	9.2.1
Stand Calibration Period	9.3
Stand Modification and Calibration Status	9.4
Test Numbering System	9.5
General	9.5.1
Reference Oil Tests	9.5.2
Non-Reference Oil Tests	9.5.3
Reference Oil Test Acceptance	9.6
Unacceptable Reference Oil Test	9.7
Reference Oil Accountability	9.8
Non-Reference Oil Tests	9.9
Last Start Date	9.9.2
Test Procedure	10
Engine Installation and Stand Connections	10.1
Coolant System Fill	10.2
Oil Fill for Break-in	10.3
Engine Build Committed	10.3.3
Fuel Samples	10.4
Engine Warm-up	10.5
Shutdown During Warm-up	10.5.1
Engine Break-in	10.6
Shutdown and Maintenance	10.7
Normal Shutdown	10.7.1
Emergency Shutdown	10.7.2
Maintenance	10.7.3
Downtime	10.7.4
300-h Test Procedure	10.8
Oil Fill for Test	10.8.2
Operating Conditions	10.8.4
Injection Timing Change	10.8.5
Mass % Soot Validity	10.8.6
Test Timer	10.8.7
Operational Data Acquisition	10.8.8
Oil Purge, Sample and Addition	10.8.9
End of Test (EOT)	10.9
Engine Disassembly	10.9.4
Calculations, Ratings, and Test Validity	11
Crosshead Mass Loss	11.1
Injector Adjusting Screw Mass Loss	11.2
Rod Bearing Mass Loss	11.3
Ring Mass Loss	11.4
Sludge Ratings	11.5
Piston Ratings	11.6
Oil Filter Plugging	11.7
Oil Analyses	11.8
Oil Consumption	11.9
Fuel Analyses	11.10
Assessment of Operational Validity	11.11
Assessment of Test Interpretability	11.12
Test Report	12
Precision and Bias	13
Keywords	14
Annexes	
Safety Precautions	Annex A1
Intake Air Aftercooler	Annex A2
Engine Build Parts Kit	Annex A3
Sensor Locations and Special Hardware	Annex A4
External Oil System	Annex A5
Fuel Specification	Annex A6
Cummins Service Publications	Annex A7
Specified Units and Formats	Annex A8
Report Forms and Data Dictionary	Annex A9
Sludge Rating Worksheets	Annex A10
Piston Rating Locations	Annex A11
Oil Analyses	Annex A12
Oil Filter Plugging	Annex A13
Determination of Operational Validity	Annex A14

Exhaust CO ₂ Sampling Probe	Annex A15
Appendix	
Typical System Configurations	Appendix X1

2. Referenced Documents

2.1 ASTM Standards:³

- D86 Test Method for Distillation of Petroleum Products and Liquid Fuels at Atmospheric Pressure
- D92 Test Method for Flash and Fire Points by Cleveland Open Cup Tester
- D97 Test Method for Pour Point of Petroleum Products
- D129 Test Method for Sulfur in Petroleum Products (General High Pressure Decomposition Device Method)
- D130 Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test
- D287 Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)
- D445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)
- D482 Test Method for Ash from Petroleum Products
- D524 Test Method for Ramsbottom Carbon Residue of Petroleum Products
- D613 Test Method for Cetane Number of Diesel Fuel Oil
- D664 Test Method for Acid Number of Petroleum Products by Potentiometric Titration
- D976 Test Method for Calculated Cetane Index of Distillate Fuels
- D1319 Test Method for Hydrocarbon Types in Liquid Petroleum Products by Fluorescent Indicator Adsorption
- D2274 Test Method for Oxidation Stability of Distillate Fuel Oil (Accelerated Method)
- D2500 Test Method for Cloud Point of Petroleum Products
- D2622 Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-ray Fluorescence Spectrometry
- D2709 Test Method for Water and Sediment in Middle Distillate Fuels by Centrifuge
- D2896 Test Method for Base Number of Petroleum Products by Potentiometric Perchloric Acid Titration
- D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter
- D4485 Specification for Performance of Active API Service Category Engine Oils
- D4737 Test Method for Calculated Cetane Index by Four Variable Equation
- D4739 Test Method for Base Number Determination by Potentiometric Hydrochloric Acid Titration
- D5185 Test Method for Multielement Determination of Used and Unused Lubricating Oils and Base Oils by Inductively Coupled Plasma Atomic Emission Spectrometry (ICP-AES)
- D5302 Test Method for Evaluation of Automotive Engine Oils for Inhibition of Deposit Formation and Wear in a

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

Spark-Ignition Internal Combustion Engine Fueled with Gasoline and Operated Under Low-Temperature, Light-Duty Conditions (Withdrawn 2003)⁴

D5844 Test Method for Evaluation of Automotive Engine Oils for Inhibition of Rusting (Sequence IID) (Withdrawn 2003)⁴

D5967 Test Method for Evaluation of Diesel Engine Oils in T-8 Diesel Engine

D6483 Test Method for Evaluation of Diesel Engine Oils in T-9 Diesel Engine (Withdrawn 2009)⁴

D6557 Test Method for Evaluation of Rust Preventive Characteristics of Automotive Engine Oils

E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

E344 Terminology Relating to Thermometry and Hydrometry

2.2 *Coordinating Research Council (CRC)*:⁵

CRC Manual No. 20

2.3 *National Archives and Records Administration*:⁶

Code of Federal Regulations Title 40 Part 86.310-79

3. Terminology

3.1 Definitions:

3.1.1 *blind reference oil*, *n*—a reference oil, the identity of which is unknown by the test facility. **D5844**

3.1.2 *blowby*, *n*—in internal combustion engines, the combustion products and unburned air-and-fuel mixture that enter the crankcase. **D5302**

3.1.3 *calibrate*, *v*—to determine the indication or output of a measuring device with respect to that of a standard. **E344**

3.1.4 *heavy-duty*, *adj*— in internal combustion engine operation, characterized by average speeds, power output, and internal temperatures that are close to the potential maximum. **D4485**

3.1.5 *heavy-duty engine*, *adj*—in internal combustion engines, one that is designed to allow operation continuously at or close to its peak output. **D4485**

3.1.6 *non-reference oil*, *n*—any oil other than a reference oil, such as a research formulation, commercial oil, or candidate oil. **D5844**

3.1.7 *non-standard test*, *n*—a test that is not conducted in conformance with the requirements in the standard test method; such as running in a non-calibrated test stand or using different test equipment, applying different equipment assembly procedures, or using modified operating conditions. **D5844**

3.1.8 *reference oil*, *n*—an oil of known performance characteristics used as a basis for comparison. **D4485**

3.1.9 *sludge*, *n*—in internal combustion engines, a deposit, principally composed of insoluble resins and oxidation products from fuel combustion and the lubricant, that does not drain

from engine parts but can be removed by wiping with a cloth. **D5302**

3.1.10 *test oil*, *n*—any oil subjected to evaluation in an established procedure. **D6557**

3.1.11 *wear*, *n*—the loss of material from, or relocation of material on, a surface. **D5302**

3.1.11.1 *Discussion*—Wear generally occurs between two surfaces moving relative to each other, and is the result of mechanical or chemical action or by a combination of mechanical and chemical actions.

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *crosshead*, *n*—an overhead component, located between the rocker arm and each intake valve and exhaust valve pair, that transfers rocker arm travel to the opening and closing of each valve pair.

3.2.1.1 *Discussion*—Each cylinder has two crossheads, one for each pair of intake valves and exhaust valves.

3.2.2 *de-rate protocols*, *n*—protocols in the engine control module that cause the engine to reduce power output when certain operating parameters are exceeded.

3.2.3 *exhaust gas recirculation (EGR)*, *n*—a method by which a portion of the engine exhaust is returned to the combustion chambers through the intake system.

3.2.4 *overhead*, *n*—in internal combustion engines, the components of the valve train located in or above the cylinder head.

3.2.5 *overfuel*, *v*—to cause the fuel flow to exceed the standard production setting.

3.2.6 *valve train*, *n*— in internal combustion engines, the series of components, such as valves, crossheads, rocker arms, push rods, and camshaft, that open and close the intake and exhaust valves.

4. Summary of Test Method

4.1 This test method uses a Cummins M11 400 diesel engine with a specially modified engine block. Test operation includes a 25-min warm-up, a 2-h break-in, and 300 h in six 50-h stages. During stages A, C, and E, the engine is operated with retarded fuel injection timing and is overfueled to generate excess soot. During stages B, D, and F, the engine is operated at conditions to induce valve train wear.

4.2 Prior to each test, the engine is cleaned and assembled with new cylinder liners, pistons, piston rings, and overhead valve train components. All aspects of the assembly are specified.

4.3 A forced oil drain, an oil sample, and an oil addition, equivalent to an oil consumption of 0.23 g/kW-h, is performed at the end of each 25-h period.

4.4 The test stand is equipped with the appropriate instrumentation to control engine speed, fuel flow, and other operating parameters.

4.5 Oil performance is determined by assessing crosshead wear at 8.5 mass % soot, sludge deposits, and oil filter plugging.

⁴ The last approved version of this historical standard is referenced on www.astm.org.

⁵ Available from the Coordinating Research Council, Inc., 219 Perimeter Parkway, Atlanta, GA 30346.

⁶ Available from Superintendent of Documents, Attn: New Orders, P.O. Box 371954, Pittsburgh, PA 15250-7954.

TABLE 1 Maximum Allowable System Time Responses

Measurement	Time Response (s)
Speed	2.0
Temperature	3.0
Pressure	3.0
Flow	To be determined

5. Significance and Use

5.1 This test method was developed to assess the performance of an engine oil to control engine wear and deposits under heavy-duty operating conditions selected to accelerate soot generation, valve train wear, and deposit formation in a turbocharged, aftercooled four-stroke-cycle diesel engine equipped with exhaust gas recirculation hardware.

5.2 This test method may be used for engine oil specification acceptance when all details of this test method are in compliance. Applicable engine oil service categories are included in Specification D4485.

5.3 The design of the engine used in this test method is representative of many, but not all, modern diesel engines. This factor, along with the accelerated operating conditions, needs to be considered when extrapolating test results.

6. Apparatus

6.1 Test Engine Configuration:

6.1.1 *Test Engine*—The Cummins M11 400 is an in-line six-cylinder heavy-duty diesel engine with 11 L of displacement and is turbocharged and aftercooled. The engine has an overhead valve configuration and EGR hardware. It features a 1994 emissions configuration with electronic control of fuel metering and fuel injection timing. Obtain the test engine, the engine build parts kit, and non-kit parts from the central parts distributor (CPD).^{7,8} The components of the engine build parts kit are shown in Table A3.1. Non-kit parts are shown in Table A3.2.

6.1.2 *Oil Heat Exchanger, Adapter Blocks, and Block-Off Plate*—The oil heat exchanger is relocated from the stock position with the use of adapter blocks as shown in Fig. A4.1.^{8,9} Install an oil cooler block-off plate on the back of the coolant thermostat housing (Fig. A4.1). Control the oil temperature by directing engine coolant through the oil heat exchanger (Fig. A4.2).

6.1.3 *Oil Filter Head Modification*—Modify the oil filter head by plugging the filter bypass return to sump line and the engine oil thermostat (Fig. A4.8). Block the thermostat passage to route all of the engine oil into the oil cooler.

6.1.4 *Oil Pan Modification*—Modify the oil pan as shown in Fig. A4.3.^{8,9}

⁷ The sole source of supply of the parts known to the committee at this time is Test Engineering Inc., 12758 Cimmaron Path, Suite 102, San Antonio, TX 78249-3417.

⁸ If you are aware of alternative suppliers, please provide this information to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee,¹ which you may attend.

⁹ The sole source of supply of the apparatus known to the committee at this time is Southwest Research Institute, P.O. Drawer 28510, San Antonio, TX 78228.

TABLE 2 Warm-up Conditions

Parameter	Unit	Stage				
		A	B	C	D	E
Stage Length	min	5	5	5	5	5
Speed	r/min	700	1200	1600	1600	1600
Torque	Nom	135	270	540	1085	1470
Coolant Out Temperature ^A	°C	105	105	105	105	105
Oil Gallery Temperature ^A	°C	130	130	130	130	130
Intake Manifold Temperature ^A	°C	70	70	70	70	70

^A Maximum.

TABLE 3 Break-in Conditions

Parameter	Unit	Specification
Stage Length	min	120
Speed	r/min	1600 ± 5 (target)
Torque ^A	Nom	1930
Fuel Flow	kg/h	64.4 ± 0.9 (target)
Coolant Out Temperature	°C	65.5
Fuel In Temperature	°C	40 ± 2
Oil Gallery Temperature	°C	115.5
Turbo Inlet Air Temperature	°C	record
Intake Manifold Temperature	°C	65.5 (target)
Oil Gallery Pressure	kPa	record
Oil Filter Delta Pressure	kPa	record
Intake Manifold Pressure	kPa abs.	≤ 320
Exhaust Pressure	kPa abs.	107 ± 1
Crankcase Pressure	kPa	record
Inlet Air Pressure	kPa abs.	record
Coolant System Pressure	kPa	103 ± 4

^A At standard atmospheric temperature and pressure.

TABLE 4 Normal Shutdown Conditions

Parameter	Unit	Stage		
		B	A	Idle
Stage Length	min	5	5	5
Speed	r/min	1200	700	700
Torque	N·m	270	135	<40
Coolant Out Temperature	°C	105 max	105 max	105 max
Intake Manifold Temperature	°C	70 max	70 max	70 max
Oil Gallery Temperature	°C	130 max	130 max	30 max

6.1.5 *Engine Control Module (ECM)*—Obtain the ECM from the CPD.^{7,8} The ECM programming has been modified to provide overfueling and retarded injection timing to increase soot generation and overhead wear. The de-rate protocols have been disabled. However the de-rate messages will still be displayed when using Cummins electronic service tools.

6.1.6 *Engine Position Sensor*—The engine position sensor has two measurement coils. Disable the secondary coil by cutting the two outside wires colored red and black. The red and black wires are labeled A and D, respectively, on the engine position sensor plug (Fig. A4.15).

6.1.7 *Air Compressor and Fuel Pump*—The engine-mounted air compressor is not used for this test method. Remove the air compressor and install the fuel injection pump in its place (Fig. A4.4). The fuel injection pump is driven with Cummins coupling P/N 208755.^{8,10}

¹⁰ Available from a Cummins parts distributor.