

Designation: A891/A891M - 10

StandardSpecification for Precipitation Hardening Iron Base Superalloy Forgings for Turbine Rotor Disks and Wheels¹

This standard is issued under the fixed designation A891/A891M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope*

- 1.1 This specification covers precipitation hardening iron base superalloy forgings which are primarily intended for use as turbine rotor disks and wheels.
- 1.2 Two heat treatments are covered. Selection will depend upon design, service conditions, mechanical properties, and elevated temperature characteristics.
- 1.3 All of the provisions of Specification A788/A788M, apply, except as amended herein.
- 1.4 The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

2. Referenced Documents

- 2.1 ASTM Standards:²
- A788/A788M Specification for Steel Forgings, General Requirements

 ASTM A891/
- E112 Test Methods for Determining Average Grain Size
- E139 Test Methods for Conducting Creep, Creep-Rupture, and Stress-Rupture Tests of Metallic Materials
- E165 Practice for Liquid Penetrant Examination for General Industry
- E292 Test Methods for Conducting Time-for-Rupture Notch Tension Tests of Materials

3. Ordering Information

- 3.1 Orders for material under this specification shall include the following:
 - 3.1.1 *Condition*—See Section 4.
- ¹ This specification is under the jurisdiction of Committee A01 on Steel, Stainless Steel and Related Alloysand is the direct responsibility of Subcommittee A01.06 on Steel Forgings and Billets.
- Current edition approved Nov. 1, 2010. Published December 2010. Originally approved in 1988. Last previous edition approved in 2008 as A891/A891M 08. DOI: 10.1520/A0891_A0891M-10.
- ² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

- 3.1.2 Stress Rupture Test—Parameters for material furnished in condition 2 of 7.3.3.
- 3.1.3 Forging Drawing—Each forging shall be manufactured in accordance with a drawing furnished by the purchaser showing the dimensions of the forging and the location of mechanical test specimens.
- 3.1.4 Include the information specified in Specification A788/A788M.

4. Condition and Heat Treatment

- 4.1 The forgings covered in this specification may be ordered in two different solution treated and aged conditions:
 - 4.1.1 *Type 1:*
- 4.1.1.1 Solution anneal at $1650 \pm 25^{\circ}$ F [$900 \pm 14^{\circ}$ C] for 2 to 5 h at temperature liquid quench.
- 4.1.1.2 Precipitation harden at $1420 \pm 15^{\circ}F$ [770 $\pm 8^{\circ}C$] for 16 h at temperature air cool; $1200 \pm 15^{\circ}F$ [650 $\pm 8^{\circ}C$] for 16 h at temperature air cool.
 - 4.1.2 *Type 2:*
- 4.1.2.1 Solution anneal at $1800 \pm 25^{\circ}$ F [$980 \pm 14^{\circ}$ C] for 2 to 5 h at temperature liquid quench.
- 4.1.2.2 Precipitation harden at $1420 \pm 15^{\circ}F$ [770 $\pm 8^{\circ}C$] for 16 h at temperature air cool; $1200 \pm 15^{\circ}F$ [650 $\pm 8^{\circ}C$] for 16 h at temperature air cool.

5. Manufacture

- 5.1 The material shall be made by vacuum melting followed by consumable electrode vacuum arc or electroslag remelting as agreed upon between producer and user.
- 5.2 The forgings shall be upset forged so that the axis of the disk corresponds with that of the ingot.

6. Chemical Requirements

- 6.1 *Heat Analysis*—Each heat shall be analyzed by the manufacturer in accordance with Specification A788/A788M. The chemical composition shall conform to the requirements specified in Table 1.
- 6.2 *Product Analysis*—The purchaser may obtain a product analysis, representing each heat or multiple heat, in accordance with the provisions of Specification A788/A788M.