
Gumene cevi in cevni priključki - S spiralnimi žicami ojačene hidravlične cevi za tekočine na oljni ali vodni osnovi - Specifikacija

Rubber hoses and hose assemblies - Rubber-covered spiral-wire-reinforced hydraulic types for oil-based or water-based fluids - Specification

iTeh STANDARD PREVIEW

Tuyaux et flexibles en caoutchouc - Types hydrauliques avec armature hélicoïdale de fils métalliques pour fluides à base d'huile ou à base d'eau - Spécifications

[SIST ISO 3862:2020](https://standards.iteh.ai/catalog/standards/sist/3862-2020/3862-2020)

Ta slovenski standard je istoveten z: ISO 3862:2020

ICS:

23.100.40	Cevna napeljava in sklopke	Piping and couplings
83.140.40	Gumene cevi	Hoses

SIST ISO 3862:2020**en,fr,de**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 3862:2020

<https://standards.iteh.ai/catalog/standards/sist/e7c732eb-1ad6-4256-9eb0-0fad368416a9/sist-iso-3862-2020>

INTERNATIONAL
STANDARD

ISO
3862

Fifth edition
2020-02

**Rubber hoses and hose assemblies —
Rubber-covered spiral-wire-
reinforced hydraulic types for
oil-based or water-based fluids —
Specification**

*Tuyaux et flexibles en caoutchouc — Types hydrauliques avec
armature hélicoïdale de fils métalliques pour fluides à base d'huile ou
à base d'eau — Spécifications*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 3862:2020](https://standards.iteh.ai/catalog/standards/sist/e7c732eb-1ad6-4256-9eb0-0fad368416a9/sist-iso-3862-2020)

<https://standards.iteh.ai/catalog/standards/sist/e7c732eb-1ad6-4256-9eb0-0fad368416a9/sist-iso-3862-2020>



Reference number
ISO 3862:2020(E)

© ISO 2020

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 3862:2020

<https://standards.iteh.ai/catalog/standards/sist/e7c732eb-1ad6-4256-9eb0-0fad368416a9/sist-iso-3862-2020>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Classification	2
5 Materials and construction	2
5.1 Hoses.....	2
5.2 Hose assemblies.....	2
6 Dimensions	2
6.1 Hose diameters and hose concentricity.....	2
6.2 Length.....	5
7 Performance requirements	5
7.1 General.....	5
7.2 Hydrostatic requirements.....	5
7.3 Minimum bend radius.....	6
7.4 Resistance to impulse.....	6
7.4.1 Oil-based fluid impulse test.....	6
7.4.2 Water-based fluid impulse test.....	7
7.5 Leakage of hose assemblies.....	7
7.6 Low temperature flexibility.....	7
7.7 Adhesion between components.....	7
7.8 Abrasion resistance.....	8
7.9 Fluid resistance.....	8
7.9.1 General.....	8
7.9.2 Oil resistance.....	8
7.9.3 Water resistance.....	8
7.10 Ozone resistance.....	8
7.11 Visual examination.....	8
8 Frequency of testing	8
9 Marking	9
9.1 Hoses.....	9
9.2 Hose assemblies.....	9
Annex A (normative) Test frequency for type tests and routine tests	10
Annex B (informative) Production acceptance tests	11
Annex C (informative) Recommendations for lengths of supplied hoses and tolerances on length of hose assemblies	12
Bibliography	13

ISO 3862:2020(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 1, *Rubber and plastics hoses and hose assemblies*.

This fifth edition cancels and replaces the fourth edition (ISO 3862:2017), which has been technically revised.

The main changes compared to the previous edition are as follows:

- in [Clause 1](#), the temperature of water and water-based fluids has been increased from +60 °C to +70 °C;
- in [6.1](#), definitions of [Table 1](#), [Table 2](#), [Table 3](#) and [Table 4](#) have been updated;
- [Table 1](#) has been split into [Table 1](#), [Table 2](#) and [Table 3](#); subsequent tables and references have been renumbered;
- dimensions in [Table 1](#), [Table 2](#) and [Table 3](#) have been updated;
- in [Table 5](#), [Table 6](#) and [Table 7](#), maximum working pressure, proof pressure and minimum burst pressure have been updated;
- in [7.4.2](#) and [7.9.3](#), the temperature of water and water-based fluids has been increased from +60 °C to +70 °C;
- in [Clause 9](#), some of the marking requirements have been revised.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Rubber hoses and hose assemblies — Rubber-covered spiral-wire-reinforced hydraulic types for oil-based or water-based fluids — Specification

1 Scope

This document specifies requirements for five types of spiral-wire-reinforced hydraulic hoses and hose assemblies of nominal size from 6,3 to 51.

They are suitable for use with:

- oil-based hydraulic fluids HH, HL, HM, HR and HV as defined in ISO 6743-4 at temperatures ranging from -40 °C to $+100\text{ °C}$ for types 4SP and 4SH hoses and from -40 °C to $+120\text{ °C}$ for types R12, R13 and R15 hoses;
- water-based fluids HFC, HFAE, HFAS and HFB as defined in ISO 6743-4 at temperatures ranging from -40 °C to $+70\text{ °C}$;
- water at temperatures ranging from 0 °C to $+70\text{ °C}$.

This document does not include requirements for end fittings. It is limited to requirements for hoses and hose assemblies.

NOTE It is the responsibility of the user, in consultation with the hose manufacturer, to establish the compatibility of the hose with the fluid to be used.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1402, *Rubber and plastics hoses and hose assemblies — Hydrostatic testing*

ISO 1817, *Rubber, vulcanized or thermoplastic — Determination of the effect of liquids*

ISO 4671, *Rubber and plastics hoses and hose assemblies — Methods of measurement of the dimensions of hoses and the lengths of hose assemblies*

ISO 6605, *Hydraulic fluid power — Test methods for hoses and hose assemblies*

ISO 6743-4, *Lubricants, industrial oils and related products (class L) — Classification — Part 4: Family H (Hydraulic systems)*

ISO 6803, *Rubber or plastics hoses and hose assemblies — Hydraulic-pressure impulse test without flexing*

ISO 7326:2016, *Rubber and plastics hoses — Assessment of ozone resistance under static conditions*

ISO 8033:2016, *Rubber and plastics hoses — Determination of adhesion between components*

ISO 8330, *Rubber and plastics hoses and hose assemblies — Vocabulary*

ISO 10619-1:2017, *Rubber and plastics hoses and tubing — Measurement of flexibility and stiffness — Part 1: Bending tests at ambient temperature*

ISO 3862:2020(E)

ISO 10619-2:2017, *Rubber and plastics hoses and tubing — Measurement of flexibility and stiffness — Part 2: Bending tests at sub-ambient temperatures*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8330 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Classification

Five types of hoses are specified, distinguished by their construction, working pressure and oil resistance:

- Type 4SP: medium-pressure hoses with four plies of steel wire spiral.
- Type 4SH: high-pressure hoses with four plies of steel wire spiral.
- Type R12: heavy-duty high-temperature hoses with a medium-pressure rating having four plies of steel wire spiral.
- Type R13: heavy-duty high-temperature hoses with a high-pressure rating having a multiple-steel-wire spiral.
- Type R15: heavy-duty high-temperature hoses with an extra-high-pressure rating having a multiple-steel-wire spiral.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST ISO 3862:2020
<https://standards.iteh.ai/catalog/standards/sist/e7c732eb-1ad6-4256-9eb0-0fad368416a9/sist-iso-3862-2020>

5 Materials and construction

5.1 Hoses

Hoses shall consist of a rubber lining resistant to oil- or water-based hydraulic fluids or water, spiral plies of steel wire wrapped in alternating directions, and an oil- and weather-resistant rubber cover. Each spiral wire ply shall be separated by an insulating layer.

5.2 Hose assemblies

Hose assemblies shall be manufactured using hoses conforming to the requirements of this document.

Hose assemblies shall be manufactured only with those hose fittings whose correct functioning has been verified in accordance with [7.2](#), [7.4](#), [7.5](#) and [7.6](#). The manufacturer's instructions shall be followed for the preparation and fabrication of hose assemblies.

6 Dimensions

6.1 Hose diameters and hose concentricity

When measured in accordance with ISO 4671, the inside diameter of hoses shall conform to the values given in [Table 1](#).

When measured in accordance with ISO 4671, the diameter over reinforcement of hoses shall conform to the values given in [Table 2](#).

When measured in accordance with ISO 4671, the outside diameter of hoses shall conform to the values given in [Table 3](#).

When measured in accordance with ISO 4671, the concentricity of hoses shall conform to the values given in [Table 4](#).

Table 1 — Inside diameters of hoses

Nominal size ^a	Inside diameter mm									
	Type 4SP		Type 4SH		Type R12		Type R13		Type R15	
	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.
6,3	6,2	7,0	—	—	—	—	—	—	—	—
10	9,4	10,1	—	—	9,3	10,1	—	—	9,3	10,1
12,5	12,6	13,5	—	—	12,3	13,5	—	—	12,3	13,5
16	15,8	16,7	—	—	15,5	16,7	—	—	—	—
19	18,8	19,8	19,1	19,8	18,6	19,8	18,6	19,8	18,6	19,8
25	25,4	26,4	25,5	26,4	25,0	26,4	25,0	26,4	25,0	26,4
31,5	31,8	33,0	32,0	33,0	31,4	33,0	31,4	33,0	31,4	33,0
38	38,0	39,3	38,2	39,3	37,7	39,3	37,7	39,3	37,7	39,3
51	50,6	52,0	50,6	52,0	50,4	52,0	50,4	52,0	50,4	52,0

^a The nominal sizes correspond to those given in ISO 1307.

SIST ISO 3862:2020
<https://standards.iteh.ai/catalog/standards/sist/e7c732eb-1ad6-4256-9eb0-0fad368416a9/sist-iso-3862-2020>