INTERNATIONAL STANDARD

ISO 4079

Sixth edition 2020-06

Rubber hoses and hose assemblies — Textile-reinforced hydraulic types for oil-based or water-based fluids — Specification

Tuyaux et flexibles en caoutchouc — Types hydrauliques avec armature de textile pour fluides à base d'huile ou à base d'eau — Spécifications

(https://standards.iteh.ai) **Document Preview**

ISO 4079:2020

https://standards.iteh.ai/catalog/standards/iso/3550832f-7b91-4084-adf0-12204ce81c21/iso-4079-2020



iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 4079:2020

https://standards.iteh.ai/catalog/standards/iso/3550832f-7b91-4084-adf0-12204ce81c21/iso-4079-2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents			Page
Fore	word		iv
1	Scope		1
2	Norm	ative references	1
3		s and definitions	
4		ification	
5		rials and construction	
J	5.1 Hoses		
	5.2	Hose assemblies	
6	Dimensions		2
	6.1	Hose diameters and hose concentricity	
	6.2	Length	3
7	Performance requirements		
	7.1	General	
	7.2 7.3	Hydrostatic requirements Minimum bend radius	
	7.3 7.4	Resistance to impulse	
	7.1	7.4.1 Oil-based fluid impulse test	
		7.4.2 Water-based fluid impulse test	
	7.5	Leakage of hose assemblies	7
	7.6	Low temperature flexibility	7
	7.7	Adhesion between components	7
	7.8	Vacuum resistance	7
	7.9	Abrasion resistance	
	7.10	Fluid resistance WC 11 12 11 1	
		7.10.1 General	
		7.10.2 Oil resistance 150 4079:2020	
	an dands.	7.10.3 Water resistance Ozone resistance	
	7.11 7.12	Visual examination	
8		iency of testing	
9	Marking		
	9.1	Hoses	
	9.2	Hose assemblies	
Ann	ex A (no	rmative) Test frequency for type tests and routine tests	10
Ann	ex B (inf	ormative) Production acceptance tests	11
	ex C (info	ormative) Recommendations for lengths of supplied hoses and tolerances ngth of hose assemblies	
D:L1	iography		13
DIDL	เบยเสมกา	v .	1.5

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 1, *Rubber and plastics hoses and hose assemblies*.

This sixth edition cancels and replaces the fifth edition (ISO 4079:2017), which has been technically revised. 150.4079:2020

The main changes compared to the previous edition are as follows:

- the temperature of water and water-based fluids has been increased from +60 °C to +70 °C in <u>Clause 1</u>;
- definitions of <u>Table 1</u>, <u>Table 2</u> and <u>Table 3</u> have been updated;
- Table 1 has been split into <u>Table 1</u> and <u>Table 2</u>; all following tables and references have been renumbered;
- <u>Table 1</u> and <u>Table 2</u> have been updated with dimensions from EN 853;
- the proof pressure, the minimum burst pressure and the maximum working pressure have been updated in <u>Tables 3</u>, <u>4</u> and <u>5</u>;
- the temperature of water and water-based fluids has been changed from +60 °C to +70 °C in $\frac{7.4.2}{10.3}$;
- "oil No. 3" has been changed to" IRM 903 oil" in 7.10.2;
- some of the marking requirements have been revised in <u>Clause 9</u>.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Rubber hoses and hose assemblies — Textile-reinforced hydraulic types for oil-based or water-based fluids — Specification

1 Scope

This document specifies requirements for five types of textile-reinforced hydraulic hoses and hose assemblies of nominal size from 5 to 100.

They are suitable for use with:

- oil-based hydraulic fluids HH, HL, HM, HR and HV as defined in ISO 6743-4 at temperatures ranging from -40 °C to +100 °C;
- water-based fluids HFC, HFAE, HFAS and HFB as defined in ISO 6743-4 at temperatures ranging from -40 °C to +70 °C;
- water at temperatures ranging from 0 °C to +70 °C.

This document does not include requirements for end fittings. It is limited to requirements for hoses and hose assemblies.

NOTE It is the responsibility of the user, in consultation with the hose manufacturer, to establish the compatibility of the hose with the fluid to be used.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1402, Rubber and plastics hoses and hose assemblies — Hydrostatic testing

ISO 1817, Rubber, vulcanized or thermoplastic — Determination of the effect of liquids

ISO 4671, Rubber and plastics hoses and hose assemblies — Methods of measurement of the dimensions of hoses and the lengths of hose assemblies

ISO 6605, Hydraulic fluid power — Test methods for hoses and hose assemblies

ISO 6743-4, Lubricants, industrial oils and related products (class L) — Classification — Part 4: Family H (Hydraulic systems)

ISO 6803, Rubber or plastics hoses and hose assemblies — Hydraulic-pressure impulse test without flexing

ISO 7233, Rubber and plastics hoses and hose assemblies — Determination of resistance to vacuum

ISO 7326:2016, Rubber and plastics hoses — Assessment of ozone resistance under static conditions

ISO 8033:2016, Rubber and plastics hoses — Determination of adhesion between components

ISO 8330, Rubber and plastics hoses and hose assemblies — Vocabulary

ISO 10619-1:2017, Rubber and plastics hoses and tubing — Measurement of flexibility and stiffness — Part 1: Bending tests at ambient temperature

ISO 10619-2:2017, Rubber and plastics hoses and tubing — Measurement of flexibility and stiffness — Part 2: Bending tests at sub-ambient temperatures

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8330 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

4 Classification

Five types of hose are specified, distinguished by their construction, working pressure and minimum bend radius.

- Type 1TE: hoses with a single braid of textile reinforcement.
- Type 2TE: hoses with one or more braid(s) of textile reinforcement.
- Type 3TE: hoses with one or more braid(s) of textile reinforcement (higher working pressure).
- Type R3: hoses with two braids of textile reinforcement.
- Type R6: hoses with a single braid of textile reinforcement.

NOTE Type 1TE is not subjected to the impulse or vacuum resistance test. Type R3 is not subjected to the vacuum resistance test. Type R6 is not subjected to the impulse or vacuum resistance test.

5 Materials and construction

ISO 4079:2020

5.1 https://atandards.iteh.ai/catalog/standards/iso/3550832f-7b91-4084-adf0-12204ce81c21/iso-4079-2020

Hoses shall consist of a rubber lining that is resistant to oil- or water-based hydraulic fluids or water, one or more layers of suitable textile yarn and a weather- and oil-resistant rubber cover.

Hoses shall be designed to enable end fittings to be assembled without removal of the cover.

5.2 Hose assemblies

Hose assemblies shall be manufactured using hoses conforming to the requirements of this document.

Hose assemblies shall be manufactured only with those hose fittings whose correct functioning has been verified in accordance with 7.2, 7.4, 7.5 and 7.6. The manufacturer's instructions shall be followed for the preparation and fabrication of hose assemblies.

6 Dimensions

6.1 Hose diameters and hose concentricity

When measured in accordance with ISO 4671, the inside and outside diameters of hoses shall conform to the values given in Table 1.

When measured in accordance with ISO 4671, the concentricity of hoses shall conform to the values given in <u>Table 2</u>.