FINAL DRAFT

INTERNATIONAL STANDARD

ISO/FDIS 11806-2

ISO/TC 23/SC 17

Secretariat: SIS

Voting begins on: **2021-05-28**

Voting terminates on: **2021-07-23**

Agricultural and forestry machinery — Safety requirements and testing for portable, hand-held, powered brush-cutters and grasstrimmers —

iTeh ST^{Part 2}: Machines for use with back-pack (stpower uniteh.ai)

Materiel agricole et forestier — Exigences de sécurité et essais pour https://standards.itel et course and standards/star 2005 portatifs à moteur — 9d63-5e287319db44/iso-idis-11806-2

Partie 2: Machines pour utilisation avec source motrice portée à dos

ISO/CEN PARALLEL PROCESSING

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNO-LOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STAN-DARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number ISO/FDIS 11806-2:2021(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/FDIS 11806-2</u> https://standards.iteh.ai/catalog/standards/sist/49582728-9097-482a-9d63-5e287319db44/iso-fdis-11806-2



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents

Foreword			iv
Intro	oductio	n	v
1	Scop	е	
2	Norr	native references	
3	Tern	is and definitions	2
4	Safety requirements and/or protective measures		
	4.1	General	
	4.2	Distance to cutting attachment	
		4.2.1 Requirements	
		4.2.2 Verification	
	4.3	Handgrip on backpack power unit	
		4.3.1 Requirement	
		4.3.2 Verification	
	4.4	Harness for backpack power unit	4
		4.4.1 Requirements	
		4.4.2 Verification	
	4.5	Hydraulic and pneumatic pipes and hoses	5
		4.5.1 Requirements	5
		4.5.2 Verification	5
	4.6	Throttle control SLANDARD PREVIEW	5
		4.6.1 Position	5
		4.6.2 Operation Standards. Iten.al)	5
		4.6.3 Throttle control latch	6
	4.7	Fuel tank structural integrity/FDIS-11806-2	7
		4.7.1 htRequirements.ai/catalog/standards/sist/49582728-9097-482a-	7
		4.7.2 Verification63-5e287319db44/iso-fdis-11806-2	7
5	Info	mation for use	7
Anne	ex A (in	formative) List of significant hazards	
Anne	ex B (in	formative) Fuel tank structural integrity	
Anne	ex ZA (i	nformative) Relationship between this European Standard and the essential	
	requ	irements of Directive 2006/42/EC aimed to be covered	
Bibliography			

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 17, *Manually portable forest machinery*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 144, *Tractors and machinery for agriculture and forestry*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 11806-2:2011), which has been technically revised.

The main changes compared to the previous edition are as follows:

- the reference to ISO 11806-1:2021 has been updated to the latest edition;
- the requirements for the harness for the backpack power unit have been reworded and amended;
- the throttle control requirements for the backpack power unit have been added;
- the fuel tank structural integrity for the backpack power unit has been added by including a new <u>Annex B</u>.

A list of all parts in the ISO 11806 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

Introduction

This document is a type-C standard as stated in ISO 12100.

This document is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (regulators, accident prevention organisations, market surveillance, etc.)

Others can be affected by the level of machinery safety achieved with the means of the document by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, e.g. for maintenance (small, medium and large enterprises);
- consumers (in case of machinery intended for use by consumers).

The above-mentioned stakeholder groups have been given the possibility to participate at the drafting process of this document.

The machinery concerned and the extent to which hazards, hazardous situations or hazardous events are covered are indicated in the scope of this document.

When requirements of this type-**C** standard are different from those which are stated in type-A or type-B standards, the requirements of this type-C standard take precedence over the requirements of the other standards for machines that <u>have been designed</u> and built according to the requirements of this type-C standard.<u>https://standards.iteh.ai/catalog/standards/sist/49582728-9097-482a-9d63-5e287319db44/iso-fdis-11806-2</u>

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/FDIS 11806-2</u> https://standards.iteh.ai/catalog/standards/sist/49582728-9097-482a-9d63-5e287319db44/iso-fdis-11806-2

Agricultural and forestry machinery — Safety requirements and testing for portable, hand-held, powered brush-cutters and grass-trimmers —

Part 2: Machines for use with back-pack power unit

1 Scope

This document specifies safety requirements, and measures for their verification, for the design and construction of portable, hand-held, powered brush-cutters and grass-trimmers with a backpack-mounted combustion engine power source and mechanical power transmission between the power source and the cutting attachment (hereafter referred to as "machine"). Methods for the elimination or reduction of hazards arising from the use of these machines and the type of information on safe working practices to be provided by the manufacturer are specified.

This document, taken together with the relevant clauses of ISO 11806-1:2021 (see <u>4.1</u>), deals with all significant hazards, hazardous situations and hazardous events, with the exception of whole-body vibration from the backpack power unit, relevant to these machines when they are used as intended and under conditions of misuse which are reasonably foreseeable by the manufacturer.

NOTE 1 A standardized test procedure for measuring whole-body vibration from the backpack power unit is not available at the time of publication. ISO/FDIS 11806-2

NOTE 2 See <u>Annex A</u>, together with ISO 11806-1:2021, Annex A, for a list of significant hazards.

This document is applicable to portable, hand-held, powered brush-cutters and grass-trimmers manufactured after its date of publication.

This document is not applicable to machines equipped with metallic cutting attachments consisting of more than one piece, such as pivoting chains or flail blades.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4413:2010, Hydraulic fluid power — General rules and safety requirements for systems and their components

ISO 4414:2010, Pneumatic fluid power — General rules and safety requirements for systems and their components

ISO 11806-1:2021, Agricultural and forestry machinery — Safety requirements and testing for portable, hand- held, powered brush-cutters and grass-trimmers — Part 1: Machines fitted with an integral combustion engine

ISO 12100:2010, Safety of machinery — General principles for design — Risk assessment and risk reduction

ISO 13857:2019, Safety of machinery — Safety distances to prevent hazard zones being reached by upper and lower limbs

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11806-1:2021 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at http://www.electropedia.org/

3.1

machine

complete brush-cutter, brush saw or grass-trimmer, including backpack power unit and assembly of drive shaft tube and mechanical power transmission including cutting attachment, guard, handles and if applicable, barrier

Note 1 to entry: Figure 1 provides an example of a brush-cutter with a backpack power unit (machine) falling within the scope of this document.



Key

- 1 harness
- 2 backpack power unit
- 3 barrier
- 4 blade
- 5 cutting attachment guard
- 6 drive-shaft tube
- 7 front handle
- 8 rear handle

Figure 1 — Machine (brush-cutter) with backpack power unit

4 Safety requirements and/or protective measures

4.1 General

Machines shall comply with the safety requirements and/or protective measures of this clause. In addition, the machine shall be designed according to the principles of ISO 12100:2021 for relevant but not significant hazards which are not dealt with by this document.

Machines shall comply with ISO 11806-1:2021, Clause 4, except for 4.4, 4.5, 4.13 and 4.15.2.

The safe operation of a brush-cutter and a grass-trimmer also depends on the safe environment associated with the use of personal protective equipment (PPE), such as gloves, slip-resistance footwear, and leg, eye and hearing protective equipment, as well as safe working procedures (see ISO 11806-1:2021, 5.1).

If a grass-trimmer can be converted to a brush-cutter then the converted machine shall in accordance with requirements for a brush-cutter and vice versa.

Except where otherwise specified in this document, the safety distances specified in ISO 13857:2019, 4.2.4.1 and 4.2.4.3, shall be met.

4.2 Distance to cutting attachment

4.2.1 Requirements

Machines with front and rear handles shall have a minimum straight-line distance of 1 200 mm from the mid- point of the rear handle to the nearest unguarded point of the cutting attachment (point A in Figure 2). Point A is the intersection between the plane perpendicular to the cutting path and the side-edge of the cutting attachment guard. ISO/FDIS 11806-2

This minimum distance shall apply to all recommended cutting attachments.

9d63-5e287319db44/iso-fdis-11806-2

4.2.2 Verification

The distance shall be verified by measurement.

Dimensions in millimetres



Key

- 1 cutting attachment
- 2 guard
- 3 front handle
- 4 rear handle
- 5 mechanical power transmission
- 6 barrier
- A intersection point

Figure 2 — Distance to cutting attachment

4.3 Handgrip on backpack power unit

4.3.1 Requirement

A handgrip shall be available which may be a part of the frame and which shall allow an operator to grasp the backpack power unit for handling and transport.

The handgrip shall be designed such that

- it can be fully gripped by an operator when wearing gloves,
- it provides the necessary sureness of grip by its shaping and surface, and
- its length is at least 100 mm and where, for a bail or closed handgrip, this length is straight or curved at a radius greater than 100 mm together with any blend radius, but not more than 10 mm at one or both ends of the gripping surface.

4.3.2 Verification

The handgrip design shall be verified by inspection, measurement and functional testing.

4.4 Harness for backpack power unit

4.4.1 Requirements

All machines shall be equipped with a double shoulder harness. The harness shall be adjustable to the size of the operator and shall be: (standards.iteh.ai)

- designed in a way for easy removal; or
- ISO/FDIS 11806-2
 equipped with a quick-release mechanism that ensures that the machine/can be removed or released quickly from the operator.
 9d63-5e287319db44/iso-fdis-11806-2

A double shoulder harness is considered to be designed in a way for easy removal, if the left and right shoulder straps are not connected to each other in front of the operator's body.

If a waist belt and/or supplementary straps to connect the left and right shoulder straps are provided, the double shoulder harness is also considered to be designed in a way for easy removal if they can be released under the load of the machine by using one hand, and there are no more than two release points.

NOTE An example of a release point is a buckle that requires squeezing between a thumb and finger before releasing, such as side release buckles.

A quick release mechanism, if provided, shall be positioned either at the connection between the machine and the harness or between the harness and the operator. The quick release mechanism shall only function by deliberate action of the operator.

It shall be possible to open the quick release mechanism while under load using only one hand and it shall have no more than two release points.

4.4.2 Verification

The harness, its functionality and its adjustment shall be verified by inspection. The quick-release mechanism shall be verified by a functional test, carried out by a person wearing the harness with a vertical load of three times the dry weight of the backpack power unit acting on the suspension point.

4.5 Hydraulic and pneumatic pipes and hoses

4.5.1 Requirements

Hydraulic systems shall be in accordance with the safety requirements of ISO 4413:2010. Pneumatic systems shall be in accordance with the safety requirements of ISO 4414:2010.

Hydraulic and pneumatic pipes and hoses subject to internal pressures in excess of 500 kPa shall be shielded so that in the event of rupture during operation of the machine, the fluid cannot be discharged directly onto the operator.

4.5.2 Verification

The shielding of pipes and hoses shall be verified by inspection.

4.6 Throttle control

4.6.1 Position

4.6.1.1 Requirements

The throttle trigger shall be positioned so that it can be pressed and released with a gloved hand while holding the handle to which the throttle trigger is mounted.

4.6.1.2 Verification

iTeh STANDARD PREVIEW

(standards.iteh.ai) The position shall be verified by inspection and functional testing.

4.6.2 Operation https://standards.iteh.ai/catalog/standards/sist/49582728-9097-482a-9d63-5e287319db44/jso-fdis-11806-2

4.6.2.1 Requirements

The machine shall be provided with a throttle trigger that, when released, automatically reverts to the idling position. The throttle trigger, except for grass-trimmers with a cutting attachment where each filament or pivoting non-metallic blade has a kinetic energy of less than 10 J, shall be retained in the idling position by the automatic engagement of a throttle trigger lock-out.

NOTE When fitted to assist starting, a throttle control latch maintains an engine speed higher than the idling speed until the throttle trigger is activated and released.

For brush-cutters and grass-trimmers with a cutting attachment where each filament or pivoting nonmetallic blade has a kinetic energy of 10 J or more, after the starting procedure has been finished, activation of the throttle trigger to increase the engine speed to a point where the cutting attachment starts to move, shall only be possible after the throttle trigger lock-out has been disengaged.

The starting procedure is finished when the operator disengages the throttle control latch and the engine returns to idling speed.

For the calculation of kinetic energy, see <u>4.6.2.2</u>.

When a force is applied to the throttle trigger, while the throttle trigger lockout is engaged, engine speed shall not increase to a point where the clutch engages and cutting attachment movement begins, see 4.6.2.3.