INTERNATIONAL STANDARD

First edition 2020-03

Petroleum and natural gas industries — Arctic operations — Escape, evacuation and rescue from offshore installations

Industries du pétrole et du gaz naturel — Opérations en Arctique — Échappement, évacuation et sauvetage depuis les installations en mer

(https://standards.iteh.ai) Document Preview

<u>ISO 35102:2020</u>

https://standards.iteh.ai/catalog/standards/iso/7cd2f80d-d25d-45a7-b70f-1b6d452d1db5/iso-35102-2020



Reference number ISO 35102:2020(E)

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 35102:2020

https://standards.iteh.ai/catalog/standards/iso/7cd2f80d-d25d-45a7-b70f-1b6d452d1db5/iso-35102-2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents

Page

Forev	vord	v		
Intro	duction	vi		
1	Scope	1		
2	Normative references			
3	Terms and definitions			
4	Abbreviated terms	9		
5	General requirements and conditions for EER systems	9		
	5.1 Fundamental requirements	9		
	5.2 Methods — Design			
	5.2.1 General5.2.2 Structural configuration — Design			
	5.3 Methods — Operations			
	5.3.1 General			
	5.3.2 Structural configuration — Operations			
6	Escape, evacuation and rescue strategy			
	6.1 General EER strategy			
	6.2 Human and hardware performance in EER			
7	Physical environment			
	7.1 General physical environment			
	7.2 Physical environmental conditions — Design			
	7.3 Physical environmental conditions — Operations	14		
8	Escape, evacuation and rescue hazard identification and risk analysis — Design and			
	operations Document Preview			
	8.1 General			
	 8.2 General HAZID and risk analysis 8.3 EER HAZID 			
	8.4 EER risk analysis)2016		
9	Continuous assessment			
,	9.1 Continuous assessment — Design			
	9.2 Continuous assessment — Operations			
10	Escape, evacuation and rescue system capabilities			
	10.1 EER system capabilities — Design			
	10.2 EER system capabilities — Operations			
11	Emergency response organization			
	11.1 ERO — Design			
	11.2 ERO — Operations			
12	Competency assurance			
	12.1 Competency assurance — Design			
	12.2 Competency assurance — Operations			
13	Communications and alarms			
	13.1 Communications and alarms — Design			
	13.2 Communications and alarms — Operations			
14	Personal protective equipment (PPE)			
	14.1 PPE — Design			
. –	14.2 PPE — Operations			
15	Man overboard recovery			
	 15.1 MOB recovery — Design 15.2 MOB recovery — Operations 			
	15.2 $inod recovery = operations$	2J		

16	Escap	е	
	16.1	Escape — Design	
		16.1.1 General escape — Design	24
		16.1.2 Escape routes — Design	24
		16.1.3 TR — Design	
		16.1.4 MS — Design	
	16.2	Escape operations	
		16.2.1 General escape — Operations	
		16.2.2 Escape routes — Operations	
		16.2.3 TR — Operations	
		16.2.4 MS — Operations	
17	Evacu	ation	
	17.1	Evacuation — Design	
		17.1.1 General evacuation — Design	
		17.1.2 Evacuation method — Design	
	17.2	Evacuation — Operations	
		17.2.1 General evacuation — Operations	
		17.2.2 Evacuation method — Operations	
18	Rescu	e	
	18.1	Rescue — Design	
	18.2	Rescue — Operations	
Anne	x A (info	ormative) Additional information and guidance	
Anne	x B (info	ormative) Examples of Arctic EER risk analysis and operational EER systems	70
Biblid	ogranhy	/	103
21011	-9P-1	(https://standards.iteh.ai)	100

Document Preview

ISO 35102:2020

https://standards.iteh.ai/catalog/standards/iso/7cd2f80d-d25d-45a7-b70f-1b6d452d1db5/iso-35102-2020

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 8, *Arctic operations*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

https://standards.iteh.ai/catalog/standards/iso/7cd2f80d-d25d-45a7-b70f-1b6d452d1db5/iso-35102-2020

Introduction

The International Standards on arctic operations (ISO 35101, ISO 35102, ISO 35103, ISO 35104, ISO/TS 35105 and ISO 35106) address design and operational requirements and provide guidance on their use by the petroleum and natural gas industries in offshore arctic and cold regions. These documents promote internationally agreed approaches for oil and gas operations in arctic and cold region offshore environments. They were developed in response to the offshore oil and gas industry's demand for a coherent and consistent definition of methodologies to design, analyze, assess and operate arctic and cold region offshore structures. Through their proper application, the intention is to help ensure the safety of life and to minimize damage to the arctic environment. These documents are intended to provide wide latitude in the selection of design and operational solutions without hindering innovation. Even so, sound engineering judgement is expected in the application of these documents.

Personnel working in petroleum and natural gas industries in the arctic offshore face a number of risks from the physical and work environments. These include prolonged periods of darkness (in the winter) and light (in the summer), remoteness, cold ambient air temperatures, wind chill, dense fog, cold water temperatures, sea ice in varying concentrations and thickness and potentially, icebergs. These environmental factors can affect worker safety, should the installation's integrity be compromised. Additionally, these harsh environmental factors can have a negative impact on equipment.

The escape, evacuation and rescue (EER) system facilitates the successful escape from an incident, subsequent precautionary or emergency evacuation from the installation, and the ultimate rescue of installation personnel. The EER provisions are the compensating measures mitigating risks which facilitate the safety of personnel working in arctic and cold region offshore environments.

This document specifies requirements and recommendations applicable to design and operational aspects of EER from oil and gas installations deployed in arctic and cold region offshore environments. Through their application, the intention is to achieve reliability levels appropriate for manned and normally unmanned offshore installations, regardless of the type of structure/facility and the nature or combination of the materials used and the severity of the environment to which the installation is subjected.

The EER provisions are largely performance-based stipulations which include verifiable attributes or benchmarks that provide qualitative levels or quantitative measures of performance. The key characteristic of a performance-based standard is that it is focused on what needs to be achieved rather than on how it should be done. One of the performance targets is that use of the EER minimizes the possibility of casualties in the process. The performance target is developed in the context of a design HSE case.

The main body of this document considers the overall EER system design and operational aspects. <u>Annex A</u> provides EER system design and operational background information and guidance intended to assist the user of this document in understanding the requirements and how they can be met. The clause numbering in <u>Annex A</u> is the same as in the main body text to facilitate cross-referencing. <u>Annex B</u> provides a risk analysis example and information pertaining to operational EER systems.

In this document, the following verbal forms are used:

- "shall" indicates a requirement;
- "should" indicates a recommendation;
- "may" indicates a permission;
- "can" indicates a possibility or a capability.

Users of this document are expected to be familiar with ISO 15544, ISO 17776 and ISO 31000.

Petroleum and natural gas industries — Arctic operations — Escape, evacuation and rescue from offshore installations

1 Scope

This document establishes the principles, specifies the requirements and provides guidance for the development and implementation of an escape, evacuation and rescue (EER) plan. It is applicable to offshore installation design, construction, transportation, installation, offshore production/exploration drilling operation service life inspection/repair, decommissioning and removal activities related to petroleum and natural gas industries in the arctic and cold regions.

Reference to arctic and cold regions in this document is deemed to include both the Arctic and other locations characterized by low ambient temperatures and the presence or possibility of sea ice, icebergs, icing conditions, persistent snow cover and/or permafrost.

This document contains requirements for the design, operation, maintenance, and service-life inspection or repair of new installations and structures, and to modification of existing installations for operation in the offshore Arctic and cold regions, where ice can be present for at least a portion of the year. This includes offshore exploration, production and accommodation units utilized for such activities. To a limited extent, this document also addresses the vessels that support ER, if part of the overall EER plan.

While this document does not apply specifically to mobile offshore drilling units (MODUs, see ISO 19905-1) many of the EER provisions contained herein are applicable to the assessment of such units in situations when the MODU is operated in arctic and cold regions.

The provisions of this document are intended to be used by stakeholders including designers, operators and duty holders. In some cases, floating platforms (as a type of offshore installations) can be classified as vessels (ships) by national law and the EER for these units are stipulated by international maritime law. However, many of the EER provisions contained in this document are applicable to such floating platforms.

This document applies to mechanical, process and electrical equipment or any specialized process equipment associated with offshore arctic and cold region operations that impacts the performance of the EER system. This includes periodic training and drills, EER system maintenance and precautionary down-manning as well as emergency situations.

EER associated with onshore arctic oil and gas facilities are not addressed in this document, except where relevant to an offshore development.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15544, Petroleum and natural gas industries — Offshore production installations — Requirements and guidelines for emergency response

ISO 17776, Petroleum and natural gas industries — Offshore production installations — Major accident hazard management during the design of new installations

ISO 35102:2020(E)

ISO 19901-6, Petroleum and natural gas industries — Specific requirements for offshore structures — Part 6: Marine operations

ISO 19906, Petroleum and natural gas industries — Offshore production installations — Arctic offshore structures

ISO 31000, Risk management — Guidelines

ISO 35104, Petroleum and natural gas industries — Arctic operations — Ice management

ISO 35106, Petroleum and natural gas industries — Arctic operations — Metocean, ice, and seabed data

IMO International Convention for the Safety of Life at Sea (SOLAS), 1974

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>

— IEC Electropedia: available at http://www.electropedia.org/

3.1

abandonment

act of personnel on-board leaving an installation in an emergency

3.2

accommodation

place where personnel on-board sleep and spend their off-duty time

Note 1 to entry: It can include dining rooms, recreation rooms, lavatories, cabins, offices, sickbay, living quarters, galley, pantries and similar permanently enclosed spaces.

3.3 ttps://standards.iteh.ai/catalog/standards/iso/7cd2f80d-d25d-45a7-b70f-1b6d452d1db5/iso-35102-2020 annual risk tolerability criterion

ARTC

value of the individual and collective *risks* (3.50) per year of a fatality for persons, considering the amount of time spent in the operation and considering all risk sources, including workplace accidents, other incidents and *EER* (3.18) risks

3.4

anti-icing

measures to prevent ice from forming on surfaces, structures or equipment

Note 1 to entry: The intent of anti-icing is to make the surfaces, structures or equipment immediately available for use.

3.5

as low as reasonably practicable

ALARP

implementation of *risk* (3.50) reducing measures until the cost (including time, capital costs or other resources/assets) of further risk reduction is grossly disproportional to the potential risk reducing effect achieved by implementing any additional measure

3.6

casualty

serious injury or fatality resulting from an accident that occurs during the EER (3.18) process

cold-climate conditions

potential presence of combinations of low air temperatures, low seawater temperatures, wind, snow, ice, freezing fog, etc.

3.8

action

measure to limit the extent and/or duration of a hazardous event to prevent *escalation* (3.16)

3.9

direct evacuation

dry evacuation

movement of personnel from the installation directly to a *safe haven* (3.52) or to a vessel in the vicinity with the capability of safely reaching the platform without having to enter the sea or the ice cover

3.10

drills and exercises

activities undertaken to ensure verification of performance criteria, targets or requirements

3.11

duty holder

individual, legal entity or organization holding legal title to the equipment or process and accountable for the safety and welfare of all associated personnel

3.12

embarkation area

place from which personnel abandon the installation during *evacuation* (3.20)

3.13

emergency breathing system

EBS Document Preview

compressed air emergency breathing system

CA-EBS

form of personal protective equipment that provides the user with a means to breathe underwater for at least one minute, overcoming the need to make a single breath last for the complete duration of an underwater *escape* (3.17) from a helicopter

Note 1 to entry: If used correctly, EBS can mitigate the *risk* (3.50) of drowning. EBSs are categorized as follows:

- Category A: capable of deployment in air and underwater within 12 s;
- Category B: capable of deployment in air within 20 s.

3.14

emergency

hazardous event which cannot be handled by normal measures and requires immediate *action* (3.8) to limit its extent, duration or consequences

3.15

emergency response

ER

action (3.8) taken by personnel on or off the installation to control or mitigate a hazardous event or initiate and execute *abandonment* (3.1)

3.16

escalation

increase in the consequences of a hazardous event

escape

act of personnel moving away from a hazardous event to a place on the installation where its effects are reduced or removed

3.18

escape, evacuation and rescue

EER

range of possible *actions* (3.8) in an *emergency* (3.14)

EXAMPLE *Escape* (3.17), *muster* (3.38), refuge, emergency or *precautionary evacuation* (3.44) and *rescue* (3.48).

3.19

escape route

normally available and unobstructed route from locations where personnel can be present on the installation to the *temporary refuge* (3.61) or alternative protected muster point

3.20

evacuation

planned method of abandoning the installation in an *emergency* (3.14)

3.21

evacuation craft

survival craft

marine or amphibious craft used by installation personnel to evacuate to the sea or ice cover

Note 1 to entry: An evacuation or survival craft provides evacuees with protection from the incident and the physical environment.

Note 2 to entry: This is a generic term that can cover lifeboats, life rafts, personnel basket or similar.

3.22

immersion suit

protective suit made of materials which reduce loss of body heat of a person wearing it in cold water or on the ice

https://standards.iteh.ai/catalog/standards/iso/7cd2f80d-d25d-45a7-b70f-1b6d452d1db5/iso-35102-2020 3.23

first-year ice

FYI

sea ice of not more than one winter's growth

3.24

floe

relatively flat piece of sea ice greater than 20 m across

Note 1 to entry: Typical subcategories are: small (20 m to 100 m across), medium (100 m to 500 m across), big (500 m to 2 000 m across), vast (2 km to 10 km across) and giant (greater than 10 km across).

3.25

freeboard

ice freeboard vertical distance from the mean sea surface to the ice surface

3.26

hazard

potential source of harm

3.27

hazard zone

largest possible area within which personnel safety is at risk (3.50) due to the installation hazard (3.26)

iceberg

glacial or shelf ice of greater than 5 m freeboard (3.25) that has broken (calved) away from its source

Note 1 to entry: Icebergs can be freely floating or grounded, and their shapes are sometimes defined as tabular, dome, pinnacle, wedge or block. Smaller pieces of ice are called bergy bits or growlers

3.29

ice detection

discrimination of ice features from the surrounding environment

3.30

ice island

large tabular-shaped ice feature that has calved from an ice shelf or glacier

3.31

ice management

active processes used to alter the ice environment with the intent of reducing the frequency, severity or uncertainty of ice actions

3.32

ice management plan

detailed plan outlining the objectives, active procedures involved and individual responsibilities for the implementation of the ice management strategy

3.33

indirect evacuation

iTeh Standards

movement of personnel from the installation to an intermediate *safe haven* (3.52) off the installation, such as an *evacuation* (3.20) craft

3.34

indirect evacuation system

system by which evacuees move from the *temporary refuge* (3.61) or muster point on the installation to a location outside the *hazard zone* (3.27) if they are able to do so

https://35ndards.iteh.ai/catalog/standards/iso/7cd2f80d-d25d-45a7-b70f-1b6d452d1db5/iso-35102-2020

landfast ice

fast ice

ice that remains attached to a shoreline, island or a grounded ice feature

3.36

major incident

major accident

event with potential for multiple personnel casualties, significant environmental damage, installation failure, or any combination of these consequences

3.37

multi-year ice

sea ice that has survived at least one summer melt season

Note 1 to entry: When the term "multi-year ice" is used in conjunction with the term "second-year ice", the former should be interpreted as ice that has survived at least two summer melt seasons.

3.38

muster

movement of people to a designated area(s) so that the person in overall charge can account for all people and thereby facilitate *emergency response* (3.15) *actions* (3.8)

muster station

MS

muster area

assembly station designated area(s) to which personnel report when required to do so in an *emergency* (3.14)

3.40

offshore installation manager

OIM

person legally responsible for the installation and all operations on and around an offshore platform

3.41

pack ice

sea ice consisting of discrete floes (3.24) that are not landfast ice (3.35)

3.42

performance-based standard

standard that specifies in qualitative and quantitative terms the requirements of safety-critical systems and their elements

3.43

personnel on board POB

total number of personnel on board the installation

Note 1 to entry: This includes visitors, vessel crews, cross-shift personnel on the installation transferring to vessel, helicopter or other means, etc.

3.44

precautionary evacuation **Document**

controlled means of removing personnel from the installation prior to an uncontrolled or escalating incident that can otherwise dictate an emergency *evacuation* (3.20)

3.45

3.45 ps://standards.iteh.ai/catalog/standards/iso/7cd2f80d-d25d-45a7-b70f-1b6d452d1db5/iso-35102-2020 preferred means of evacuation

method of choice for evacuating personnel based on the lowest *risk* (3.50) and on the familiarity, frequency of use, availability and suitability under prevailing conditions

Note 1 to entry: This is the method normally used to transfer personnel to and from the offshore location and could possibly not be available in an emergency.

3.46

primary means of evacuation

method of evacuating personnel that can be carried out in a controlled manner under the direction of the person in charge

Note 1 to entry: This is the *preferred means of evacuation* (3.45) of the installation in an emergency.

3.47

recovery

retrieval

transfer of evacuees to a rescue vessel, helicopter, safe installation or other safe haven (3.52)

3.48

rescue

process by which those who have evacuated, survived until a *safe haven* (3.52) is available and are retrieved to a place where medical assistance is generally available

ridge

ice ridge

linear ice feature, formed of ice blocks created by the relative motion between ice sheets

Note 1 to entry: A pressure ice ridge is formed when ice sheets are pushed together, and a shear ice ridge is formed when ice sheets slide along a common boundary.

3.50

risk

probability that a specified undesirable event will occur combined with the severity of the consequences of that event

3.51

rubble field

region of broken ice blocks floating together as a continuous body

3.52

safe haven

area outside the *hazard zone* (3.27) in which personnel safety is no longer at *risk* (3.50) due to the installation *hazard* (3.26) or physical environmental risks, and where medical attention is normally available

EXAMPLE A safe haven can be a rescue helicopter or a *standby vessel* (3.58).

3.53

iTeh Standards

safety-critical element SCE

item of equipment, procedure or structure whose failure can lead to a *major incident* (3.36) or whose purpose is to prevent or limit the consequences of a major incident

3.54

scenario risk tolerability criterion

SRTC

upper limit of the individual and collective *risk* (3.50) for any *EER* (3.18) scenario

3.55

secondary means of evacuation

method of evacuating personnel in an *emergency* (3.14) when the primary *means of evacuation* (3.46) cannot be used, which can be carried out in a fully controlled manner under the direction of the person in charge, independent of external support

Note 1 to entry: This means of *evacuation* (3.20) does not provide as much protection from *hazards* (3.26) and the elements as does the *primary means of evacuation* (3.46) but it can avoid immersion in the sea/ice.

3.56

second-year ice

sea ice that has survived one summer's melt season

Note 1 to entry: Second-year ice is sometimes referred to as *multi-year ice* (3.37).

3.57

stamukha

grounded ice feature composed of broken ice pieces or rubble

Note 1 to entry: The plural form of "stamukha" is " stamukhi".

standby vessel

SBV

vessel stationed near the installation at all times that provides *rescue* (3.48) assistance if needed within defined performance times and can accommodate installation *personnel on board* (3.43) and typically can offer medical assistance to survivors

3.59

standby ice management vessel SIMV

icebreaker standby vessel

standby vessel (3.58) used during the ice season that is capable of clearing ice and ice rubble away from the installation to create a clear route in the event of an *emergency* (3.14)

3.60

station bill

posted list showing the duties and duty stations of designated personnel on the installation with *emergency response* (3.15) organization roles and responsibilities

3.61

success

conduct of an EER (3.18) operation with zero casualties

Note 1 to entry: See also definition of *casualty* (<u>3.6</u>).

3.62

temporary refuge

TR

place provided where personnel can take refuge for a predetermined period whilst investigations, *emergency response* (3.15) and *evacuation* (3.20) preparations are undertaken

Note 1 to entry: Where provided, a TR might not necessarily be useable under all incident scenarios.

Note 2 to entry: The specified period that a TR is deemed to provide a *safe haven* (3.52) is called the TR impairment time. ds.iteh.al/catalog/standards/iso/7cd2180d-d25d-45a7-b70f-1b6d452d1db5/iso-35102-2020

3.63

tertiary means of evacuation

method of evacuating personnel in an *emergency* (3.14) that relies heavily on an individual's own *actions* (3.8), is used when the primary and secondary means are not available, and that has an inherently higher *risk* (3.50)

3.64

training

activities undertaken to ensure that competence is increased or maintained on an individual and team level

3.65

winterization

measures taken in the design and preparation of a facility or installation to facilitate operations in cold climates

Note 1 to entry: Winterization is primarily focused on the adverse effects and control of freezing, icing, wind chill, snow, falling ice and material properties in cold temperatures.