



**Designation: ~~C139-05~~ Designation: C139 – 10**

# Standard Specification for Concrete Masonry Units for Construction of Catch Basins and Manholes<sup>1</sup>

This standard is issued under the fixed designation C139; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the Department of Defense.*

## 1. Scope\*

1.1 This specification covers solid precast segmental concrete masonry units made from hydraulic cement, water, and suitable mineral aggregates, with or without the inclusion of other materials. The units are intended for use in the construction of catch basins and manholes.

1.2 The text of this standard referenced notes and footnotes which provide explanatory material. These notes and footnotes (excluding those in tables and figures) shall not be considered as requirements of the standard.

1.3 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

## 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

C33 [Specification for Concrete Aggregates](#)

C140 [Test Methods for Sampling and Testing Concrete Masonry Units and Related Units](#)

C150 [Specification for Portland Cement](#)

C207 [Specification for Hydrated Lime for Masonry Purposes](#)

C595 [Specification for Blended Hydraulic Cements](#)

C618 [Specification for Coal Fly Ash and Raw or Calcined Natural Pozzolan for Use in Concrete](#)

C989 [Specification for Slag Cement for Use in Concrete and Mortars](#)

C1157 [Performance Specification for Hydraulic Cement](#) ~~C1209 Terminology of Concrete Masonry Units and Related Units~~

C1232 [Terminology of Masonry](#)

## 3. Terminology

~~3.1 Terminology defined in Terminology C1209 and Terminology C1209~~ [ASTM C139-10](#) [9862-412-91fd-c4e77afa2227/astm-c139-10](#)

3.1 Terminology defined in Terminology C1232 shall apply for this specification.

## 4. Materials

4.1 Cementitious materials shall conform to the following ASTM specifications:

4.1.1 *Portland Cement*— Specification C150.

4.1.2 *Blended Hydraulic Cements*—Specification C595.

4.1.3 *Hydraulic Cement*—Specification C1157.

4.1.4 *Ground Blast-Furnace Slag*—Specification C989.

4.1.5 *Hydrated Lime*— Type S of Specification C207.

4.1.6 *Fly Ash*—Specification C618.

4.1.7 *Siliceous and Pozzolanic Materials*—Siliceous and pozzolanic materials shall conform to applicable ASTM standards, or shall be shown by test or experience to be not detrimental to the durability of the concrete.

4.2 *Aggregates*—Aggregates shall conform to Specification C33, except grading requirements shall not apply.

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee C15 on Manufactured Masonry Units and is the direct responsibility of Subcommittee C15.03 on Concrete Masonry Units and Related Units.

Current edition approved May 15, 2005. Published June 2005. Originally approved in 1938. Last previous edition approved in 2003 as C139 – 03. DOI: 10.1520/C0139-05.

Current edition approved Dec. 1, 2010. Published December 2010. Originally approved in 1938. Last previous edition approved in 2005 as C139 – 05. DOI: 10.1520/C0139-10.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

\*A Summary of Changes section appears at the end of this standard.