

ISO/TC 22/SC 41

Secretariat: UNI

Voting begins on:
2020-06-16

Voting terminates on:
2020-08-11

Road vehicles — Compressed natural gas (CNG) fuel system components —

Part 14: Excess flow valve

Véhicules routiers — Composants des systèmes de combustible gaz naturel comprimé (GNC) —

Partie 14: Valve de limitation de débit

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number
ISO/FDIS 15500-14:2020(E)

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/eb7add2f-e736-479f-9d2a-998a19612405/iso-fdis-15500-14>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Marking	2
5 Construction and assembly	2
6 Tests	2
6.1 Applicability	2
6.2 Hydrostatic strength	3
6.3 Leakage	3
6.4 Excess torque resistance	4
6.5 Bending moment	4
6.6 Continued operation	4
6.7 Operation	4
6.8 Pressure impulse	4
Bibliography	5

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/eb7add2f-e736-479f-9d2a-998a19612405/iso-fdis-15500-14>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 41, *Specific aspects for gaseous fuels*.

This third edition cancels and replaces the second edition (ISO 15500-14:2012), which has been technically revised. It also incorporates the Amendment ISO 15500-14:2012/Amd.1:2016. The main changes compared to the previous edition are as follows:

- update of [Clause 4](#) (Marking);
- update of [6.3](#) (Leakage test).

A list of all parts in the ISO 15500 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

For the purposes of this document, all fuel system components in contact with natural gas have been considered suitable for natural gas as defined in the ISO 15403 series. However, it is recognized that miscellaneous components not specifically covered herein can be examined to meet the criteria of this document and tested according to the appropriate functional tests.

All references to pressure in this document are considered to be gauge pressures unless otherwise specified.

This document is based on a service pressure for natural gas used as fuel of 20 MPa [200 bar¹⁾] settled at 15 °C. Other service pressures can be accommodated by adjusting the pressure by the appropriate factor (ratio). For example, a 25 MPa (250 bar) service pressure system will require pressures to be multiplied by 1,25.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/eb7add2f-e736-479f-9d2a-998a19612405/iso-fdis-15500-14>

1) 1 bar = 0,1 MPa = 10⁵ Pa 1 MPa = 1 N/mm².

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/eb7add2f-e736-479f-9d2a-998a19612405/iso-fdis-15500-14>

Road vehicles — Compressed natural gas (CNG) fuel system components —

Part 14: Excess flow valve

1 Scope

This document specifies tests and requirements for the excess flow valve, a compressed natural gas (CNG) fuel system component intended for use on the types of motor vehicles defined in ISO 3833.

This document is applicable to vehicles (mono-fuel, bi-fuel or dual-fuel applications) using natural gas in accordance with the ISO 15403 series.

It is not applicable to the following:

- a) liquefied natural gas (LNG) fuel system components located upstream of, and including, the vaporizer;
- b) fuel containers;
- c) stationary gas engines;
- d) container-mounting hardware;
- e) electronic fuel management;
- f) refuelling receptacles.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15500-1, *Road vehicles — Compressed natural gas (CNG) fuel system components — Part 1: General requirements and definitions*

ISO 15500-2, *Road vehicles — Compressed natural gas (CNG) fuel system components — Part 2: Performance and general test methods*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 15500-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

internal excess flow valve

excess flow valve installed inside the cylinder or cylinder valve

3.2

external excess flow valve

excess flow valve installed outside the cylinder or cylinder valve

3.3

shut-off type excess flow valve

excess flow valve that stops flow when in the closed position

3.4

flow-limiter type excess flow valve

excess flow valve that limits flow when activated

Note 1 to entry: The device resets automatically when the excess flow condition is no longer present.

3.5

activation flow

differential pressure flow or other condition specified by the manufacturer at which the excess flow valve is activated

4 Marking

Marking of the component shall provide sufficient information to allow the following to be traced:

- a) the manufacturer's or agent's name, trademark or symbol;
- b) the model designation (part number);
- c) the operating specifications (working pressure, temperature range, excess flow valve type, activation flow or ΔP , maximum flow when activated);
- d) the serial number or data code.

The following additional markings are recommended:

- the direction of flow (when necessary for correct installation);
- the type of fuel;
- the electrical ratings (if applicable);
- the symbol of the certification agency;
- the type approval number;
- a reference to this document.

NOTE This information can be provided by a suitable identification code on at least one part of the component when it consists of more than one part.

5 Construction and assembly

The excess flow valve shall comply with the applicable provisions of ISO 15500-1 and ISO 15500-2, and with the tests specified in [Clause 6](#). Tolerances should follow the specifications of ISO 15500-2.

6 Tests

6.1 Applicability

There are many types of excess flow valves available. This document provides requirements for two different designs: internal and external excess flow valves. A valve of either design could be one of

two different types: shut-off or flow-limiter. A shut-off valve should have a means of resetting after activation. As excess flow valve designs vary, so will the tests required.

The function of an excess flow valve can be achieved in other ways. For example, instead of using a mechanical device, an electronic system can be adopted to ensure the closing or limiting of the gas flow from the cylinder in an accident.

The tests required to be carried out are indicated in [Table 1](#).

Table 1 — Applicable tests

Test method	Applicable	Test procedure as required by ISO 15500-2	Specific test requirements of this document
Hydrostatic strength	X	X	X (see 6.2)
Leakage	X	X	X (see 6.3)
Excess torque resistance	X	X	X (see 6.4)
Bending moment	X	X	X (see 6.5)
Continued operation	X	X	X (see 6.6)
Corrosion resistance	X	X	
Oxygen ageing	X	X	
Ozone ageing	X	X	
Heat ageing	X	X	
Automotive fluids	X	X	
Non-metallic material immersion	X	X	
Vibration resistance	X	X	
Brass material compatibility	X	X	
Operation	X		X (see 6.7)
Pressure impulse	X		X (see 6.8)

6.2 Hydrostatic strength

The purpose of the hydrostatic strength test is to establish the strength of the housing.

Test the excess flow valve according to the procedure for testing hydrostatic strength specified in ISO 15500-2. For internal or external excess flow valves, the test pressure shall be 2,5 times the working pressure.

6.3 Leakage

The internal leakage test shall be conducted on an activated shut-off type excess flow valves. Test the excess flow valve according to the procedure for leakage test as specified in ISO 15500-2 at the temperatures and pressures given in [Table 2](#).

Table 2 — Test temperatures and pressures

Temperature °C	Pressure Factor × working pressure (WP)	
	First test	Second test
-40 or -20	0,75 × WP	0,025 × WP
20	0,025 × WP	1,5 × WP
85 or 120	0,05 × WP	