

ISO/TC 22/SC 41

Secretariat: UNI

Voting begins on:  
2020-05-04

Voting terminates on:  
2020-06-29

---

---

## Road vehicles — Compressed natural gas (CNG) fuel system components —

### Part 18: Filter

*Véhicules routiers — Composants des systèmes de combustible gaz naturel comprimé (GNC) —*

*Partie 18: Filtre*

**ITeH STANDARD IN REVIEW**  
(standard.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/29d431f-015f-438a-a42b-98037f248017/iso-fdis-15500-18>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



---

---

Reference number  
ISO/FDIS 15500-18:2020(E)

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/e29d431f-015f-438a-a42b-98037f248017/iso-fdis-15500-18>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword.....	iv
Introduction.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
<b>4 Marking.....</b>	<b>2</b>
<b>5 Construction and assembly.....</b>	<b>2</b>
<b>6 Tests.....</b>	<b>2</b>
6.1 Applicability.....	2
6.2 Hydrostatic strength.....	3
6.3 Continued operation.....	3
<b>Bibliography.....</b>	<b>4</b>

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/e29d431f-015f-438a-a42b-98037f248017/iso-fdis-15500-18>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 41, *Specific aspects for gaseous fuels*.

This third edition cancels and replaces the second edition (ISO 15500-18:2012), which has been technically revised. It also incorporates the Amendment ISO 15500-18:2012/Amd.1:2016. The main changes compared to the previous edition are as follows:

- serial number or data code became mandatory in marking;
- removed vibration resistance test clause and added reference to ISO 15500-2.

A list of all parts in the ISO 15500 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

For the purpose of this document, all fuel system components in contact with natural gas have been considered suitable for natural gas as defined in the ISO 15403 series. However, it is recognized that miscellaneous components not specifically covered herein can be examined to meet the criteria of this document and tested according to the appropriate functional tests.

All references to pressure in this document are considered to be gauge pressures unless otherwise specified.

This document is based on a service pressure for natural gas used as fuel of 20 MPa [200 bar<sup>1)</sup>] settled at 15 °C. Other service pressures can be accommodated by adjusting the pressure by the appropriate factor (ratio). For example, a 25 MPa (250 bar) service pressure system will require pressures to be multiplied by 1,25.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/e9d431f-015f-438a-a42b-98037f248017/iso-fdis-15500-18>

---

1) 1 bar = 0,1 MPa = 10<sup>5</sup> Pa 1 MPa = 1 N/mm<sup>2</sup>.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/e9d431f-015f-438a-a42b-98037e248017/iso-fdis-15500-18>

# Road vehicles — Compressed natural gas (CNG) fuel system components —

## Part 18: Filter

### 1 Scope

This document specifies tests and requirements for the filter, a compressed natural gas (CNG) fuel system component intended for use on the types of motor vehicles defined in ISO 3833.

This document is applicable to vehicles (mono-fuel, bi-fuel or dual-fuel applications) using natural gas in accordance with the ISO 15403 series. It is not applicable to the following:

- a) liquefied natural gas (LNG) fuel system components located upstream of, and including, the vaporizer;
- b) fuel containers;
- c) stationary gas engines;
- d) container-mounting hardware;
- e) electronic fuel management;
- f) refuelling receptacles.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15500-1, *Road vehicles — Compressed natural gas (CNG) fuel system components — Part 1: General requirements and definitions*

ISO 15500-2, *Road vehicles — Compressed natural gas (CNG) fuel system components — Part 2: Performance and general test methods*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 15500-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

## 4 Marking

Marking of the component shall provide sufficient information to allow the following to be traced:

- a) the manufacturer's or agent's name, trademark or symbol;
- b) the model designation (part number);
- c) the working pressure or pressure and temperature range;
- d) the direction of flow (when necessary for correct installation);
- e) the serial number or date code.

The following additional markings are recommended:

- the type of fuel;
- the electrical ratings (if applicable);
- the symbol of the certification agency;
- the type approval number;
- a reference to this document.

NOTE This information can be provided by a suitable identification code on at least one part of the component when it consists of more than one part.

## 5 Construction and assembly

The filter shall comply with the applicable provisions of ISO 15500-1 and ISO 15500-2, and with the tests specified in [Clause 6](#). Tolerances should follow the specifications of ISO 15500-2.

If non-conductive materials are used, the filter shall be designed to take its conductivity into account.

## 6 Tests

### 6.1 Applicability

The tests required to be carried out are indicated in [Table 1](#).



Table 1 — Applicable tests

Test	Applicable	Test procedure as required by ISO 15500-2	Specific test requirements of this document
Hydrostatic strength	X	X	X (see <a href="#">6.2</a> )
Leakage	X	X	
Excess torque resistance	X	X	
Bending moment	X	X	
Continued operation	X	X	X (see <a href="#">6.3</a> )
Corrosion resistance	X	X	
Oxygen ageing	X	X	
Ozone ageing	X	X	
Heat ageing	X	X	
Automotive fluids	X	X	
Electrical over-voltages			
Non-metallic material immersion	X	X	
Vibration resistance	X	X	
Brass material compatibility	X	X	

## 6.2 Hydrostatic strength

Test the filter according to the procedure for testing hydrostatic strength specified in ISO 15500-2. The test pressure shall be 2,5 times the working pressure.

## 6.3 Continued operation

Test the filter in accordance with the procedure for testing continued operation given in ISO 15500-2 for a total of 20 000 cycles.

Following cycling testing, perform the hydrostatic strength test in accordance with [6.2](#).