This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.



Designation: D7018-04 Designation: D7018/D7018M - 11

Standard Terminology Relating to Glass Fiber and Its Products¹

This standard is issued under the fixed designation D7018/D7018M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This standard is a compilation of terminology developed by Committee D13.18 on Glass Fiber and its Products.

1.2 This terminology is unique to glass fibers, strands, yarns, fabrics, etc. in the glass textile industry. Terms that are generally understood or adequately defined in other readily available sources are not included.

1.3Subcommittee D13.18 has jurisdictional responsibility for standards and terminology in this standard. Any change in wording requires the approval of D13.18 subcommittee. Any changes approved by the subcommittee and main committee are then directed to subcommittee D13.92 on Terminology for inclusion in Terminology D123.

<u>1.3</u> The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

<u>1.4</u> Subcommittee D13.18 has jurisdictional responsibility for standards and terminology in this standard. Any change in wording requires the approval of D13.18 subcommittee. Any changes approved by the subcommittee and main committee are then directed to subcommittee D13.92 on Terminology for inclusion in Terminology D123.

2. Referenced Documents

2.1 ASTM Standards:²

- D578 Specification for Glass Fiber Strands
- D579 Specification for Greige Woven Glass Fabrics
- D580 Specification for Greige Woven Glass Tables
- D581 Specification for Glass Fiber Greige Braided Tubular Sleeving
- D3374 Specification for Vinyl-Coated Glass Yarns
- D3656 Specification for Insect Screening and Louver Cloth Woven from Vinyl-Coated Glass Yarns
- D4028 Specification for Solar Screening Woven from Vinyl-Coated Fiber Glass Yarn
- D4029 Specification for Finished Woven Glass Fabrics 7018/D7018M-
- D4030 Specification for Glass Fiber Cord and Sewing Thread

D4389 Specification for Finished Glass Fabrics Woven From Rovings D4912 Test Method for Fabric Stability of Vinyl-Coated Glass Yarn Insect Screening and Louver Cloth D4963 Test Method for Ignition Loss of Glass Strands and Fabrics

3. Terminology

3.1 Alphabetical listing of terms for which Subcommittee D13.18 has jurisdiction:

atmosphere for testing textiles, *n*—for glass, air maintained at a relative humidity of at least 48 % and no greater than 67 %, and at a temperature of at least 20°C ($\frac{(68^{\circ}F)}{(68^{\circ}F)}$ and no greater than 25°C ($\frac{77^{\circ}F}{(77^{\circ}F)}$.

DISCUSSION—(as related to all D13.18 standards)—Glass textiles are used in various products such as reinforced plastics, mat-like material, tire cords, electrical insulation, etc. Each of these materials require different testing atmospheres. It is the intent of this wide spread in testing atmosphere to allow testing of glass textiles in respective laboratories where end product test atmosphere requirements differ. The test atmospheres for respective products should be controlled as specified in Specification E171. It is the opinion of Subcommittee D13.18 that the physical properties cited in respective specifications would not be affected by the range selected. In any event, the test atmosphere should be stated in the report.

blocking, n-of coated fiber glass yarn solar screening, an undesired adhesion between touching layers of a material. Such as

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.

¹ This terminology is under the jurisdiction of ASTM Committee D13 on Textiles and is the direct responsibility of Subcommittee D13.18 on Glass Fiber and its Products. Current edition approved March 1, 2004. Published April 2004. DOI: 10.1520/D7018-04.

Current edition approved Jan. 1, 2011. Published January 2011. Originally approved in 2004. Last previous edition approved in 2004 as D7018-04. DOI: 10.1520/D7018_D7018M-11.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.