INTERNATIONAL STANDARD



Third edition 2021-09

Information security — Encryption algorithms —

Part 1: **General**

Sécurité de l'information — Algorithmes de chiffrement —

iTeh STPartie DGeneralitesPREVIEW (standards.iteh.ai)

<u>ISO/IEC 18033-1:2021</u> https://standards.iteh.ai/catalog/standards/sist/3c31efea-3403-4e5c-ae60-301a4befd3fe/iso-iec-18033-1-2021



Reference number ISO/IEC 18033-1:2021(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 18033-1:2021 https://standards.iteh.ai/catalog/standards/sist/3c31efea-3403-4e5c-ae60-301a4befd3fe/iso-iec-18033-1-2021



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Page

Forew	ord	iv
Introd	uction	v
1	Scope	
2	Normative references	1
- 2	Terms and definitions	1
3 4	Symbols and abbreviated terms	
5	Nature of encryption 5.1 Purpose of encryption	5
	5.2 Symmetric and asymmetric encryption systems5.3 Key management	6 6
6	Use and properties of encryption 6.1 General 6.2 Asymmetric encryption systems 6.3 Block ciphers 6.3.1 General 6.3.2 Modes of operation 6.3.3 Message authentication codes (MACs) 6.4 Stream ciphers 6.5 Identity based encryption systems 6.6 Homomorphic encryption systems	6 6 7 7 7 7 7 7 8 8 8 8 8
7	Object identifiers (Standar us.iten.ar)	8
Annex	A (informative) Criteria for submission of encryption systems for possible inclusion in the ISO/IEC 18033 series i/catalog/standards/sist/3c31efea=3403-4e5c-ac60-	9
Annex	B (informative) Criteria for the deletion of encryption systems from the ISO/IEC 18033 series	14
Annex	C (informative) Attacks on encryption algorithms	
Biblio	graphy	

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iso.org/directiv

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <u>www.iso.org/patents</u>) or the IEC list of patent declarations received (see <u>patents.iec.ch</u>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC⁰JTC⁵1, *Information technology*, Subcommittee SC 27, *Information security, cybersecurity and privacy protection*.

This third edition cancels and replaces the second edition (ISO/IEC 18033-1:2015), which has been technically revised. The main changes compared with the previous edition are as follows:

- <u>Clause 3</u> has been refined;
- criteria for submission of encryption systems have been refined for possible inclusion in the ISO/IEC 18033 series; and
- the use and security properties of encryption algorithms have been clarified.

A list of all parts in the ISO/IEC 18033 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u> and <u>www.iec.ch/national</u> <u>-committees</u>.

Introduction

The ISO/IEC 18033 series specifies encryption systems for the purpose of data confidentiality. The inclusion of encryption systems in this document is intended to promote their use as reflecting the current state of the art in encryption systems.

The primary purpose of encryption systems is to protect the confidentiality of stored or transmitted data. An encryption algorithm is applied to data (often called plaintext) to yield encrypted data (or ciphertext). This process is known as encryption. The encryption algorithm should be designed so that the ciphertext yields no information about the plaintext except, perhaps, its length. Associated with every encryption algorithm is a corresponding decryption algorithm, which transforms ciphertext back into its original plaintext.

Encryption systems work in association with a key. In a symmetric encryption system, the same key is used in both the encryption and decryption algorithms. In an asymmetric encryption system, different but related keys are used for encryption and decryption. ISO/IEC 18033-2 and ISO/IEC 18033-5 focus on two different classes of asymmetric encryption systems, known as conventional asymmetric encryption systems (or just asymmetric encryption systems), and identity-based encryption systems. ISO/IEC 18033-3 and ISO/IEC 18033-4 focus on two different classes of symmetric encryption systems, known as block ciphers and stream ciphers. ISO/IEC 18033-6 focuses on a specific class of encryption systems called homomorphic.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/IEC 18033-1:2021</u> https://standards.iteh.ai/catalog/standards/sist/3c31efea-3403-4e5c-ae60-301a4befd3fe/iso-iec-18033-1-2021

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 18033-1:2021 https://standards.iteh.ai/catalog/standards/sist/3c31efea-3403-4e5c-ae60-301a4befd3fe/iso-iec-18033-1-2021

Information security — Encryption algorithms —

Part 1: **General**

1 Scope

This document is general in nature and provides definitions that apply in subsequent parts of the ISO/IEC 18033 series.

It introduces the nature of encryption and describes certain general aspects of its use and properties.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 18033-2, Information technology Security techniques Encryption algorithms — Part 2: Asymmetric ciphers

ISO/IEC 18033-3, Information technology Security techniques – Encryption algorithms – Part 3: Block ciphers

ISO/IEC 18033-1:2021 ISO/IEC 18033-4, Information dechnology gistar Security stechniques 3-4-5 Encryption algorithms — Part 4: Stream ciphers 301a4befd3fe/iso-iec-18033-1-2021

ISO/IEC 18033-5, Information technology — Security techniques — Encryption algorithms — Part 5: Identity-based ciphers

ISO/IEC 18033-6, IT Security techniques — Encryption algorithms — Part 6: Homomorphic encryption

ISO/IEC 18033-7, Information technology — Security techniques — Encryption algorithms — Part 7: Tweakable block ciphers

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>
- IEC Electropedia: available at <u>http://www.electropedia.org/</u>

3.1

asymmetric cryptographic technique

cryptographic technique that uses two related transformations, a public transformation [defined by the *public key* (3.22)] and a private transformation [defined by the *private key* (3.21)]

Note 1 to entry: The two transformations have the property that, given the public transformation, it is computationally infeasible to derive the private transformation. Computational feasibility depends on the specific security requirements and environment.

[SOURCE: ISO/IEC 11770-1:2010, 2.1, modified — The last sentence in note 1 to entry has been added.]

3.2

asymmetric encryption system

asymmetric cipher

asymmetric encipherment system

system based on *asymmetric cryptographic techniques* (3.1) whose public transformation is used for *encryption* (3.11) and whose private transformation is used for *decryption* (3.9)

Note 1 to entry: A method for key (3.17) pair generation is assumed.

[SOURCE: ISO/IEC 9798-1:2010, 3.2, modified — The admitted terms "asymmetric cipher" and "asymmetric encipherment system" and note 1 to entry have been added.]

3.3

attack

algorithm that performs computations and that can request the *encryption* (3.11) and/or *decryption* (3.9) of adaptively chosen texts under a single *secret key* (3.25)/*private key* (3.21), with the purpose of recovering either the unknown *plaintext* (3.20) for a given *ciphertext* (3.7), which may be adaptively chosen but for which a request to decrypt the ciphertext is not issued, or a secret key/private key

Note 1 to entry: Attacks are discussed in detail in <u>Annex C</u>.

3.4

attack cost

ratio of the average workload of the *attack* (3.3) to an equivalent number of calls to the *encryption algorithm* (3.12) under attack multiplied by the success probability of the attack

Note 1 to entry: Using the notation defined in <u>Clause 4</u>, the attack cost is equal to the ratio *W/P*.

Note 2 to entry: Other attack cost metrics and properties, such as memory complexity, data complexity, the ability to be accelerated by specialized hardware or parallelizability may also be important in judging the impact of a cryptographic attack. ISO/IEC 18033-1:2021

3.5

https://standards.iteh.ai/catalog/standards/sist/3c31efea-3403-4e5c-ae60-301a4befd3fe/iso-iec-18033-1-2021

block

string of bits of a defined length

3.6

block cipher

symmetric encryption system (3.29) with the property that the encryption algorithm (3.12) operates on a block (3.5) of plaintext (3.20) to yield a block of ciphertext (3.7)

Note 1 to entry: The block ciphers standardized in ISO/IEC 18033-3 have the property that plaintext and ciphertext blocks are of the same length.

3.7

ciphertext

data which has been transformed to hide its information content

3.8

cryptanalytic attack

attack (3.3) against a *cipher* (3.13) that makes use of properties of the cipher

Note 1 to entry: Every cryptanalytic attack has its own attack model, some of which may or may not be applicable to specific implementations. Since the application of a cipher is generally unknown to the cipher designer, all possible models in the single *key* (3.17) setting need to be considered when assessing the security of an algorithm. Several existing application examples also show the need to consider multi-key settings.

Note 2 to entry: Cryptanalytic attacks do not include implementation-specific attacks, e.g. involving side channel analysis.

3.9 decryption decipherment reversal of a corresponding *encryption* (3.11)

[SOURCE: ISO/IEC 11770-1:2010, 2.6, modified — The admitted term "decipherment" has been added; note 1 to entry has been removed.]

3.10

decryption algorithm

decipherment algorithm

process which transforms *ciphertext* (3.7) into *plaintext* (3.20)

3.11

encryption

encipherment

(reversible) transformation of data by an *encryption algorithm* (3.12) to produce *ciphertext* (3.7), i.e. to hide the information content of the data

3.12

encryption algorithm

encipherment algorithm process which transforms *plaintext* (3.20) into *ciphertext* (3.7)

3.13

encryption system iTeh STANDARD PREVIEW

cipher

(standards.iteh.ai)

cryptographic technique used to protect the confidentiality of data, and which consists of three component processes: an *encryption algorithm* (3.12), a *decryption algorithm* (3.10), and a method for component processes (2.17)

generating keys (3.1.7) generating keys (3.1.7) ittps://standards.iteh.ai/catalog/standards/sist/3c31efea-3403-4e5c-ae60-301a4befd3fe/iso-iec-18033-1-2021

3.14

generic attack

attack (3.3) against an *encryption system* (3.13) which does not rely on the encryption system design and can be used to recover a *secret key* (3.25)/*private key* (3.21) or *plaintext* (3.20)

Note 1 to entry: Generic attacks depend on models and goals, see <u>Clause A.2</u> for details.

3.15

homomorphic encryption system

homomorphic cipher

homomorphic encipherment system

encryption system (3.13) with the property that if certain computations are performed on the *ciphertext* (3.7), the *plaintext* (3.20) obtained after *decryption* (3.9) will have had the same computations applied to it

3.16

identity-based encryption system

identity-based cipher

asymmetric encryption system (3.2) in which the *encryption algorithm* (3.12) takes an arbitrary string as a *public key* (3.22)

[SOURCE: ISO/IEC 18033-5:2015, 3.6, modified — The preferred term has been changed to "identity-based encryption system"; "identity-based cipher" has been changed to an admitted term; "asymmetric cipher" has been changed to "asymmetric encryption system".]

3.17

key

sequence of symbols that controls the operation of a cryptographic transformation [e.g. *encryption* (3.11), *decryption* (3.9)]

[SOURCE: ISO/IEC 11770-1:2010, 2.12, modified — The list of cryptographic mechanisms has been removed.]

3.18

keystream

pseudorandom sequence of symbols, intended to be secret, used by the *encryption* (3.11) and *decryption algorithms* (3.10) of a *stream cipher* (3.27)

Note 1 to entry: If a portion of the keystream is known by an attacker, then it shall be computationally infeasible for the attacker to deduce more than a negligible amount of information about the remainder of the keystream. Computational feasibility depends on the specific security requirements and environment.

3.19

n-bit block cipher

block cipher (3.6) with the property that *plaintext* (3.20) *blocks* (3.5) and *ciphertext* (3.7) blocks are *n* bits in length

3.20

plaintext

cleartext unencrypted information

3.21

iTeh STANDARD PREVIEW (standards.iteh.ai)

key (3.17) of an entity's key pair which is known only by that entity

ISO/IEC 18033-1:2021 [SOURCE: ISO/IEC 9594-8:2020, 3.5.50, modified <u>state</u> The parenthesis 3"(In a public-key cryptosystem)", "That" at the beginning of the definition and the period at the end have been deleted.]

3.22

public key

key (3.17) of an entity's key pair which is publicly known

[SOURCE: ISO/IEC 9594-8:2020, 3.5.57, modified — "That" at the beginning of the definition and the period at the end have been deleted.]

3.23

public-key certificate

public key (3.22) of an entity, together with some other information, rendered unforgeable by digital signature with the *private key* (3.21) of the certification authority that issued it

[SOURCE: ISO/IEC 9594-8:2020, 3.5.58, modified — "The" at the beginning of the definition, the parenthesis "(CA)" and the period at the end have been deleted.]

3.24 public-key infrastructure

PKI

infrastructure able to support the management of *public keys* (3.22) able to support authentication, *encryption* (3.11), integrity or non-repudiation services

[SOURCE: ISO/IEC 9594-8:2020, 3.5.60, modified — "The" at the beginning of the definition and the period at the end have been deleted.]

3.25

secret key

key (3.17) used with symmetric cryptographic techniques (3.28) by a specified set of entities

[SOURCE: ISO/IEC 11770-3:2015, 3.36]

3.26

security strength

number associated with the amount of work (e.g. the number of operations) that is required to break a cryptographic algorithm

Note 1 to entry: For key (3.17) recovery, a security strength of k bits implies that the workload required to break the *cipher* (3.13) is equivalent to 2^k executions of the cipher. For further information on the application of security strength to selecting cryptographic algorithms for this document, see <u>C.1.4</u>.

3.27

stream cipher

symmetric encryption system (3.29) with the property that the encryption algorithm (3.12) involves combining a sequence of *plaintext* (3.20) symbols with a sequence of *keystream* (3.18) symbols one symbol at a time, using an invertible function

Note 1 to entry: Two types of stream cipher can be identified: synchronous stream ciphers and self-synchronous stream ciphers, distinguished by the method used to obtain the keystream.

3.28

symmetric cryptographic technique

cryptographic technique for which all transformations use the same key (3.17)

3.29

(standards.iteh.ai)

symmetric encryption system symmetric encipherment system ISO/IEC 18033-1:2021 symmetric cipher https://standards.iteh.ai/catalog/standards/sist/3c31efea-3403-4e5c-ae60encryption system (3.13) based on symmetric cryptographic techniques (3.28)

Symbols and abbreviated terms 4

- ECB electronic code book
- k key length
- MAC message authentication code
- plaintext/ciphertext block length for a block cipher n
- Р probability that a cryptanalytic attack will succeed
- W workload or complexity of an attack, measured in terms of the number of calls to the cryptographic algorithm

Nature of encryption 5

5.1 Purpose of encryption

The primary purpose of encryption systems is to protect the confidentiality of stored or transmitted data. Encryption algorithms achieve this by transforming plaintext into ciphertext, from which it is computationally infeasible to find any information about the content of the plaintext unless the secret/ private key is also known. However, in many cases, the length of the ciphertext is not concealed by encryption, since the length of the ciphertext is typically the same as, or a little larger than, the length of the corresponding plaintext.