



Designation: E 868 – 82 (Reapproved 1999)

Standard Test Methods for Conducting Performance Tests on Mechanical Conveying Equipment Used in Resource Recovery Systems¹

This standard is issued under the fixed designation E 868; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 These test methods include descriptions for conducting and reporting throughput and electrical power tests on mechanical conveying equipment for municipal solid waste and recovered products from resource recovery systems. Other aspects of performance testing such as spillage, conveyor tracking, dusting, slippage, transfer points, etc., should be considered in the interpretation of the results. These test methods can be used on equipment handling raw refuse, processed refuse, magnetic scrap metals, nonferrous scrap metals, mixed glass, and residues or tailings. These test methods may also be used for materials in other industries.

1.2 These test methods cover mechanical conveying equipment including apron, belt, drag, flight, screw, slat, and vibrating conveyors and bucket elevators.

1.3 These test methods are applicable specifically to the resource recovery industry since municipal solid wastes are heterogeneous mixtures and the composition and bulk densities vary considerably depending on many factors. Because of the varying composition of municipal solid waste, a number of samples must be taken to determine accurately the performance of the mechanical conveying equipment.

1.4 Test Methods for determining the approximate as-conveyed bulk density of the material and for determining the electrical horsepower input of the equipment motors are also included.

1.5 It is intended that the tests be made and reported by personnel trained in the proper application and use of the various instruments and methods involved.

1.6 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.7 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* For hazard statement, see Section 7.

¹ These test methods are under the jurisdiction of ASTM Committee D34 on Waste Management and are the direct responsibility of Subcommittee D34.03.02 on Municipal Recovery and Reuse.

Current edition approved March 26, 1982. Published December 1982.

2. Referenced Documents

2.1 *ASTM Standards:*²

E 380 Practice for Use of the International System of Units (SI) (the Modernized Metric System)

E 856 Definitions of Terms and Abbreviations Relating to Physical and Chemical Characteristics of Refuse-Derived Fuel

2.2 *Other Standard:*

No. 550 Classification and Definitions of Bulk Materials³

3. Terminology

3.1 *Definitions:*

3.1.1 *oversize bulky waste (OBW)*—items whose large size precludes or complicates processing or sampling.

3.1.2 *performance test*—a test devised to permit observation and measurement of the performance of a system or unit of equipment operating under prescribed load conditions.

3.2 For definitions of other terms used in these test methods, refer to Definitions **E 856**. For an explanation of the metric system including symbols and conversion factors, refer to Practice **E 380**.

4. Summary of Test Methods

4.1 The conveying equipment performance can be calculated by determining the volume or weight of a representative sample of material on the conveying equipment and measuring its speed. Another method for calculating the conveying equipment performance is to measure the infeed or discharge weight or volume in a given length of time. The minimum recommended number of test runs and size of samples are provided for various types of materials (see **Table 1**).

4.2 The material flow rate may be reported in any unit; sample calculations are given only for selected (common) units.

4.3 Motor wattage (or amperage and voltage) may be measured and used to calculate the electrical power consumption.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from Conveyor Equipment Manufacturers Association, 1000 Vermont Ave., N.W., Washington, DC 20005.



5. Significance and Use

5.1 These test methods may be used to measure the equipment performance.

5.2 These test methods are applicable when the conveying equipment is of sufficient length and is accessible for taking the samples and measuring the speed, or when the discharge is accessible to collect a sample in a given length of time. Not all pieces of equipment in a processing plant may be accessible; therefore, the input or total of inputs to adjacent upstream equipment/output or total of outputs of adjacent downstream equipment may be used to determine the throughput of the conveying equipment in question. Judgement must be used to determine any loss of material or changes in bulk density.

6. Apparatus

6.1 *Ammeter/Voltmeter*—Multimeter or individual meters to permit reading the maximum current and voltage anticipated. Meters may be the snap-on type with analog or digital readout.

6.2 *Bulk Density-Measuring Container*—An open-top container constructed of suitable materials such as plywood or plastic and having the following internal dimensions: 300 mm wide by 300 mm long (1 by 1 ft) and 600 mm (2 ft) high may be used for material normally smaller than 150 mm (6 in.) in size. Suitable handles may be attached to the exterior of the container to aid in subsequent handling.

NOTE 1—Alternatively, containers of other dimensions may be employed provided the base area is known and sides are perpendicular. Dimensions of the container shall be a minimum of two times the largest particle size.

6.3 *Bulk Density Measuring Rod*—A round or square rod, approximately 50 mm (2 in.) in diameter or square by 600 mm (2 ft) long, calibrated in 5-mm (0.1-in.) intervals starting from one end. The end should be cut off square to prevent sinking into sample.

6.4 *Tachometer or Speed Indicator*—A tachometer with linear speed indicator or surface speed indicator. Indicator may be hand type with digital readout.

6.5 *Wattmeter*—Industrial analyzer or individual wattmeter to provide two wattmeter indications for three-phase power. Meters may be analog or digital type.

7. Safety Hazards

7.1 These test methods may involve the use of hazardous materials, operations, and equipment. It is the responsibility of whomever uses this standard to establish appropriate safety practices and to determine the applicability of regulatory limitations prior to use.

7.2 Due to the origins of municipal solid waste, common sense dictates that some precautions should be observed when conducting tests. Recommended hygienic practices include use of gloves when handling the waste, wearing dust masks (NIOSH-approved type), and washing hands before eating or smoking.

7.3 Safety precautions should be taken when measuring conveyor speeds or collecting samples near open, moving equipment and taking electrical measurements.

NOTE 2—**Precaution:** Include use of eye protection and hard hats, avoidance of loose-fitting clothing that could become entangled in

machinery, and adopt the use of a “buddy system” in which the person conducting the test is always within sight and hearing of a coworker.

8. Sampling

8.1 *Minimum Number of Tests and Size of Sample*—The minimum recommended number of tests and minimum size of samples to be collected are shown in Table 1, based on the type of material and particle sizes.

NOTE 3—The quantity and size of samples have to be statistically verified. ASTM is conducting additional sampling experiments to verify this information.

8.2 *Frequency of Sample Collection*—No more than one sample shall be taken at a time. After collecting a representative sample, a minimum of 15 min processing time shall elapse before taking the next sample.

9. Procedures

9.1 *General*—Install, lubricate, and align the equipment to be tested in accordance with the manufacturer’s recommendations. It is advisable to make one or more preliminary tests for the purpose of determining the adequacy of the instruments and apparatus, and the training of the personnel, if required. Before the tests are begun, run the equipment under stable conditions for sufficient length of time to bring about equilibrium and steady readings.

9.2 *Recording Data*—Keep complete records of all information relevant to the tests. A suggested form for recording the data and calculating the results is given in Fig. 1. Additional observations such as material wetness, particle size variations, unusual constituents in the waste or unusually high concentrations of a particular constituent, and conveying equipment spillage, rollback of material, dusting, etc., should be recorded on the back of Fig. 1 or on a separate sheet. Before removing test equipment, compute the results to determine if they are reasonable. If so, the test can be considered terminated and the test equipment removed.

9.3 *Calibration of Instruments*—Properly calibrate all instruments in accordance with the manufacturer’s instructions. Confirm that the instruments are in good condition and are being used under conditions corresponding to those existing at the time of their calibration.

9.4 *Sample Collection on Open Conveyors*—On open conveyors such as apron, belt, drag, and flight conveyors that can be stopped, cut two bulkheads from plywood or similar material to fit the contour of the conveying surface to prevent material rollback. Place these contoured bulkheads on the conveyor to establish sample (gathering) boundary. Stop the conveyor. Place one bulkhead, perpendicular to the length of the conveyor and perpendicular to the conveying surface, making sure the material is separated uniformly. Place the second bulkhead in a similar manner either upstream or downstream from the first, a sufficient distance to obtain one of the recommended size samples from the conveyor. Measure the length between the bulkheads (L_s) to the nearest 10 mm (0.25 in.) and record. Carefully remove all of the material, including the fine, particulate materials, from between the two bulkheads. Place the sample in adequate container(s) or plastic bag(s) for material where moisture is a factor. If the length of time before measuring the bulk density is to be more than 2 h, it is