



SLOVENSKI STANDARD
oSIST prEN ISO 20567-2:2023
01-januar-2023

**Barve in laki - Ugotavljanje odpornosti premazov proti udarcem kamenja - 2. del:
Preskus z enim udarcem vodenega telesa (ISO/DIS 20567-2:2022)**

Paints and varnishes - Determination of stone-chip resistance of coatings - Part 2:
Single-impact test with a guided impact body (ISO/DIS 20567-2:2022)

Beschichtungsstoffe - Prüfung der Steinschlagfestigkeit von Beschichtungen - Teil 2:
Einzelschlagprüfung mit geführtem Schlagkörper (ISO/DIS 20567-2:2022)

Peintures et vernis - Détermination de la résistance des revêtements aux impacts de
cailloux - Partie 2: Essai de choc simple par corps percutant guidé (ISO/DIS 20567-
2:2022)

Ta slovenski standard je istoveten z: prEN ISO 20567-2 rev

ICS:

87.040

Barve in laki

Paints and varnishes

oSIST prEN ISO 20567-2:2023

en,fr,de

DRAFT INTERNATIONAL STANDARD

ISO/DIS 20567-2

ISO/TC 35/SC 9

Secretariat: BSI

Voting begins on:
2022-12-07Voting terminates on:
2023-03-01

Paints and varnishes — Determination of stone-chip resistance of coatings —

Part 2: Single-impact test with a guided impact body

*Peintures et vernis — Détermination de la résistance des revêtements aux impacts de cailloux —
Partie 2: Essai de choc simple par corps percutant guidé*

ICS: 87.040

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN ISO 20567-2:2023](https://standards.iteh.ai/catalog/standards/sist/8a892238-3811-4a27-ad6d-00cc785507a3/osist-pren-iso-20567-2-2023)

<https://standards.iteh.ai/catalog/standards/sist/8a892238-3811-4a27-ad6d-00cc785507a3/osist-pren-iso-20567-2-2023>

This document is circulated as received from the committee secretariat.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

ISO/CEN PARALLEL PROCESSING



Reference number
ISO/DIS 20567-2:2022(E)

© ISO 2022

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 20567-2:2023](https://standards.iteh.ai/catalog/standards/sist/8a892238-3811-4a27-ad6d-00cc785507a3/osist-pren-iso-20567-2-2023)

<https://standards.iteh.ai/catalog/standards/sist/8a892238-3811-4a27-ad6d-00cc785507a3/osist-pren-iso-20567-2-2023>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Principle.....	1
5 Apparatus and materials.....	2
5.1 Single-impact tester.....	2
6 Test panels.....	2
6.1 Substrate.....	2
6.2 Preparation and coating.....	2
6.3 Thickness of the coating.....	2
7 Procedure.....	4
7.1 Calibration.....	4
7.2 Conditioning of the test panels.....	4
7.3 Test conditions.....	4
7.4 Number of test runs.....	4
7.5 Determination.....	4
8 Evaluation.....	5
9 Precision.....	6
9.1 Repeatability limit, r	6
9.2 Reproducibility limit, R	6
10 Test report.....	7
Annex A (informative) Examples of suitable procedures for removing loose paint.....	8
Annex B (normative) Calibration of the test apparatus.....	9

ISO/DIS 20567-2:2022(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 35, *Paints and varnishes*, Subcommittee SC 9, *General test methods for paints and varnishes*.

This third edition cancels and replaces the second edition (ISO 20567-2:2017), which has been technically revised.

The main changes are as follows:

- **A.4** has been re-worded so that the use of a knife or similar instrument can be carried out without using another method before;
- in **B.3** the requirement has been deleted how often the instrument shall be calibrated;
- the document has been revised editorially and the normative references have been updated.

A list of all parts in the ISO 20567 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

In the automobile industry, multi-layer paint coatings are applied to car bodies for protection. Grit, road-metal and other materials can damage these coatings in such a way that individual layers come off or the whole coating delaminates from the substrate.

Stone chipping can be simulated by means of single- and/or multi-impact tests. ISO 20567-1 describes multi-impact testing; ISO 20567-2 and ISO 20567-3 describe single-impact tests

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN ISO 20567-2:2023](https://standards.iteh.ai/catalog/standards/sist/8a892238-3811-4a27-ad6d-00cc785507a3/osist-pren-iso-20567-2-2023)

<https://standards.iteh.ai/catalog/standards/sist/8a892238-3811-4a27-ad6d-00cc785507a3/osist-pren-iso-20567-2-2023>

Paints and varnishes — Determination of stone-chip resistance of coatings —

Part 2: Single-impact test with a guided impact body

1 Scope

This document specifies a method for the evaluation of the resistance of automobile finishes and other coatings to the impact of a wedge-shaped body projected onto the surface under test to simulate the impact of stones.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1514, *Paints and varnishes — Standard panels for testing*

ISO 2808, *Paints and varnishes — Determination of film thickness*

ISO 3270, *Paints and varnishes and their raw materials — Temperatures and humidities for conditioning and testing*

EN 573-3, *Aluminium and aluminium alloys — Chemical composition and form of wrought products — Part 3: Chemical composition and form of products*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 Principle

The stone-chip resistance of the coating under test is checked by projecting a defined impact body onto it. The impact body used in the test has a wedge-shaped cutting edge to obtain a damage pattern equivalent to that produced in a multi-impact test. The wedge-shaped impact body is pushed onto the coating under test by the transmission of a pulse of energy from a steel ball accelerated using compressed air.

Loose fragments of coating material are removed.

The stone-chip resistance is evaluated by measuring the total width of the delaminated coating, including the mark left by the wedge.

ISO/DIS 20567-2:2022(E)

5 Apparatus and materials

Use ordinary laboratory apparatus, together with the following.

5.1 Single-impact tester.

[Figure 1](#) shows the upper part of the test apparatus.

[Figure 2](#) shows the shape of the impact body and its dimensions. The impact body shall be made of hardened steel (hardness 60 HRC to 66 HRC).

The test panel is inserted on the tester with the wedge-shaped end of the impact body touching the coated test panel and the spring exerting a slight pressure on the body. A steel ball of mass inferior to that of the impact body is accelerated by a compressed-air blast ($p = 300$ kPa) and transmits part of its energy to the impact body, which then strikes the test panel.

NOTE 100 kPa = 1 bar.

The impact body shall be checked, and replaced if necessary, after a maximum of 500 test runs (i.e. after 500 impacts) or at the end of the series of tests during which the impact body passes the point at which it has been used for a total of 500 test runs.

6 Test panels

6.1 Substrate

Use test panels of at least 100 mm × 100 mm in size that are at least 0,7 mm thick.

6.2 Preparation and coating

Prepare each test panel in accordance with ISO 1514 before coating and drying or stoving it. Use the application method specified by the paint manufacturer.

6.3 Thickness of the coating

Determine the thickness, in micrometres, of the dry coating by one of the procedures specified in ISO 2808.