



SLOVENSKI STANDARD SIST ISO 19162:2024

01-september-2024

Nadomešča:
SIST ISO 19162:2017

Geografske informacije - Koordinatni referenčni sistemi, podani kot tekst

Geographic information — Well-known text representation of coordinate reference systems

Information géographique — Représentation textuelle bien lisible de systèmes de référence par coordonnées

Ta slovenski standard je istoveten z: **ISO 19162:2019**

SIST ISO 19162:2024

<https://standards.iteh.ai/catalog/standards/sist/9f42c8bd-dafb-4e94-8fe2-12bd290bc2b6/sist-iso-19162-2024>

ICS:

07.040	Astronomija. Geodezija. Geografija	Astronomy. Geodesy. Geography
35.240.70	Uporabniške rešitve IT v znanosti	IT applications in science

SIST ISO 19162:2024

en

INTERNATIONAL STANDARD

ISO
19162

Second edition
2019-07

Geographic information — Well-known text representation of coordinate reference systems

Information géographique — Représentation textuelle bien lisible de systèmes de référence par coordonnées

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[SIST ISO 19162:2024](https://standards.itih.ai/catalog/standards/sist/9f42c8bd-dafb-4e94-8fe2-12bd290bc2b6/sist-iso-19162-2024)

<https://standards.itih.ai/catalog/standards/sist/9f42c8bd-dafb-4e94-8fe2-12bd290bc2b6/sist-iso-19162-2024>



Reference number
ISO 19162:2019(E)

© ISO 2019

ISO 19162:2019(E)

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[SIST ISO 19162:2024](https://standards.iteh.ai/catalog/standards/sist/9f42c8bd-dafb-4e94-8fe2-12bd290bc2b6/sist-iso-19162-2024)

<https://standards.iteh.ai/catalog/standards/sist/9f42c8bd-dafb-4e94-8fe2-12bd290bc2b6/sist-iso-19162-2024>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms, definitions and abbreviated terms	1
3.1 Terms and definitions.....	1
3.2 Abbreviated terms.....	10
4 Conformance requirements	10
5 Backus-Naur Form notation and syntax	11
6 WKT string form	12
6.1 Overview.....	12
6.2 Encoding.....	12
6.3 Characters used in WKT.....	12
6.3.1 Basic characters.....	12
6.3.2 Numbers.....	13
6.3.3 Date and time.....	14
6.3.4 CRS WKT characters.....	15
6.3.5 Double quote.....	15
6.4 Delimiter.....	15
6.5 Case sensitivity.....	16
6.6 Reserved keywords.....	16
6.7 Backward compatibility.....	18
7 WKT representation of common attributes	18
7.1 General.....	18
7.2 Name.....	18
7.3 Scope, extent, identifier and remark.....	19
7.3.1 General.....	19
7.3.2 Usage (scope and extent).....	19
7.3.3 Identifier.....	22
7.3.4 Remark.....	23
7.4 Unit and unit conversion factor.....	24
7.4.1 Unit description.....	24
7.4.2 Conversion factor — Spatial and parametric units.....	25
7.4.3 Conversion factor — Temporal quantities.....	25
7.4.4 Default unit.....	26
7.5 Coordinate system.....	26
7.5.1 Syntax.....	26
7.5.2 Coordinate system type, dimension and coordinate data type.....	29
7.5.3 Axis name and abbreviation.....	29
7.5.4 Axis direction.....	30
7.5.5 Axis order.....	31
7.5.6 Axis unit and coordinate system unit.....	32
7.5.7 Examples of WKT describing coordinate systems.....	33
7.6 Datum ensemble.....	34
7.7 Dynamic coordinate reference systems.....	36
8 WKT representation of geodetic and geographic coordinate reference systems	37
8.1 Overview.....	37
8.2 Geodetic reference frame (geodetic datum).....	38
8.2.1 Ellipsoid.....	38
8.2.2 Prime meridian.....	39
8.2.3 Geodetic reference frame (datum).....	40

ISO 19162:2019(E)

8.3	Coordinate systems for geodetic and geographic CRSs	41
8.4	Examples of WKT describing a geodetic or geographic CRS	42
9	WKT representation of projected CRSs	43
9.1	Overview	43
9.2	Base CRS	43
9.2.1	General	43
9.2.2	Ellipsoidal CS unit	44
9.3	Map projection	45
9.3.1	Introduction	45
9.3.2	Map projection name and identifier	46
9.3.3	Map projection method	46
9.3.4	Map projection parameter	47
9.4	Coordinate systems for projected CRSs	47
9.5	Examples of WKT describing a projected CRS	47
10	WKT representation of vertical CRSs	49
10.1	Overview	49
10.2	Vertical reference frame (vertical datum)	50
10.3	Vertical coordinate system	50
10.4	Example of WKT describing a vertical CRS	51
11	WKT representation of engineering CRSs	51
11.1	Overview	51
11.2	Engineering datum	51
11.3	Coordinate systems for engineering CRSs	52
11.4	Examples of WKT describing an engineering CRS	52
12	WKT representation of parametric CRSs	53
12.1	Overview	53
12.2	Parametric datum	53
12.3	Parametric coordinate system	53
12.4	Example of WKT describing a parametric CRS	53
13	WKT representation of temporal CRSs	54
13.1	Temporal CRS	54
13.2	Temporal datum	54
13.3	Temporal coordinate system	55
13.3.1	General	55
13.3.2	Axis unit for temporalDateTime coordinate systems	55
13.3.3	Axis unit for temporalCount and temporalMeasure coordinate systems	55
13.4	Examples of WKT describing a temporal CRS	55
14	WKT representation of derived CRSs	56
14.1	Overview	56
14.2	Deriving conversion	57
14.2.1	General	57
14.2.2	Derived CRS conversion method	57
14.2.3	Derived CRS conversion parameter	58
14.2.4	Derived CRS conversion parameter file	58
14.2.5	Derived CRS conversion example	59
14.3	Derived geodetic CRS and derived geographic CRS	59
14.3.1	Representation	59
14.3.2	Example of WKT describing a derived geographic CRS	61
14.4	Derived projected CRS	61
14.4.1	Representation	61
14.4.2	Example of WKT describing a derived projected CRS	62
14.5	Derived vertical CRS	63
14.6	Derived engineering CRS	63
14.7	Derived parametric CRS	64
14.8	Derived temporal CRS	64

15	WKT representation of compound coordinate reference systems	65
15.1	Overview.....	65
15.2	Examples of WKT describing a compound CRS.....	65
16	WKT representation of coordinate epoch and coordinate metadata	66
16.1	Coordinate epoch.....	66
16.2	Coordinate metadata.....	67
17	WKT representation of coordinate transformations and coordinate conversions excluding map projections	68
17.1	Coordinate operations.....	68
17.2	Transformation and conversion components.....	68
17.2.1	Operation name and version.....	68
17.2.2	Source and target CRS.....	68
17.2.3	Transformation and conversion name and identifier.....	69
17.2.4	Coordinate operation method.....	69
17.2.5	Coordinate operation parameter.....	69
17.2.6	Coordinate operation parameter file.....	70
17.2.7	Interpolation CRS.....	70
17.2.8	Coordinate operation accuracy.....	70
17.2.9	Other coordinate operation attributes.....	71
17.3	Examples of WKT describing a coordinate transformation.....	71
18	WKT representation of point motion operations	72
19	WKT representation of concatenated coordinate operations	73
19.1	General.....	73
19.2	Examples of WKT describing a concatenated coordinate operation.....	75
20	WKT representation of CRS and coordinate operation couplets	76
20.1	Bound CRS.....	76
20.2	Bound CRS components.....	77
20.2.1	Abridged coordinate transformation.....	77
20.2.2	Coordinate operation method in abridged coordinate transformations.....	77
20.2.3	Abridged coordinate transformation parameter.....	77
20.2.4	Coordinate operation parameter file.....	78
20.3	Examples of WKT describing a bound CRS.....	78
	Annex A (normative) Abstract test suite	80
	Annex B (informative) Recommended practice for implementation	89
	Annex C (informative) Mapping of concepts from previous versions of CRS WKT	92
	Annex D (informative) Backward compatibility with ISO 19162:2015	103
	Annex E (normative) Triaxial ellipsoid	107
	Annex F (informative) Identifiers for coordinate operation methods and parameters	108
	Bibliography	113

ISO 19162:2019(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 211, *Geographic information/Geomatics* in close collaboration with the Open Geospatial Consortium (OGC).

This second edition cancels and replaces the first edition (ISO 19162:2015), which has been technically revised.

The main changes compared to the previous edition are as follows:

- updates to reflect the changes made in ISO 19111:2019 from its previous edition ISO 19111:2007 to describe dynamic geodetic reference frames, three-dimensional projected coordinate reference systems, datum ensembles and coordinate metadata;
- remodelling of the descriptions of temporal coordinate reference systems, to reflect the changes made in ISO 19111:2019;
- the correction of minor errors.

Further details are given in [Annex D](#).

In accordance with the ISO/IEC Directives, Part 2, 2018, *Rules for the structure and drafting of International Standards*, in International Standards the decimal sign is a comma on the line. However, the General Conference on Weights and Measures (*Conférence Générale des Poids et Mesures*) at its meeting in 2003 passed unanimously the following resolution:

“The decimal marker shall be either a point on the line or a comma on the line.”

In practice, the choice between these alternatives depends on customary use in the language concerned. In the technical areas of geodesy and geographic information it is customary for the decimal point always to be used, for all languages. That practice is used throughout this document.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Well-known text (WKT) offers a compact machine- and human-readable representation of geometric objects. WKT may also be used for succinctly describing the critical elements of coordinate reference system (CRS) definitions.

WKT was described in the Open Geospatial Consortium implementation specifications 99-036 through 06-103r4 and ISO 19125-1:2004. The WKT representation of coordinate reference systems was subsequently extended in Open Geospatial Consortium implementation specification 01-009 "Coordinate Transformation Services" and this extension was later adopted in the Open Geospatial Consortium GeoAPI 3.0 implementation standard 09-083r3 and GeoPackage 1.0 implementation standard 12-128r10. The WKT representation of coordinate reference systems as defined in ISO 19125-1:2004 and OGC specification 01-009 is inconsistent with the terminology and technical provisions of ISO 19111:2007 and OGC Abstract Specification topic 2 (08-015r2), "Geographic information — Spatial referencing by coordinates".

The 2015 version of this document provided an updated version of WKT representation of coordinate reference systems that follows the provisions of ISO 19111:2007 and ISO 19111-2:2009. It extended earlier WKT to allow for the description of coordinate operations.

This document updates WKT for the extensions to ISO 19111 made through its 2019 revision:

- the description of dynamic geodetic and vertical coordinate reference systems;
- the change of coordinate values within a coordinate reference system due to point motion caused by tectonic deformation;
- the description of geoid-based vertical coordinate reference systems;
- the description of datum ensembles, groups of realizations of one terrestrial or vertical reference system that for low accuracy purposes may be merged ignoring coordinate transformation;
- a rigorous description of temporal coordinate reference systems;
- the removal (deprecation) of image coordinate reference systems; and
- the remodelling of scope and extent information.

This document defines the structure and content of well-known text strings. It does not prescribe how implementations should read or write these strings.

Geographic information — Well-known text representation of coordinate reference systems

1 Scope

This document defines the structure and content of a text string implementation of the abstract model for coordinate reference systems described in ISO 19111. The string defines frequently needed types of coordinate reference systems and coordinate operations in a self-contained form that is easily readable by machines and by humans. The essence is its simplicity; as a consequence there are some constraints upon the more open content allowed in ISO 19111. To retain simplicity in the well-known text (WKT) description of coordinate reference systems and coordinate operations, the scope of this document excludes parameter grouping and pass-through coordinate operations. The text string provides a means for humans and machines to correctly and unambiguously interpret and utilise a coordinate reference system definition with look-ups or cross references only to define coordinate operation mathematics. A WKT string is not suitable for the storage of definitions of coordinate reference systems or coordinate operations because it omits metadata about the source of the data and may omit metadata about the applicability of the information.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8601-1, *Date and time — Representations for information interchange — Part 1: Basic rules*

ISO/IEC 10646, *Information technology — Universal Coded Character Set (UCS)*

<https://www.iso.org/standard/62906.html> ISO 19111:2019, *Geographic information — Referencing by coordinates*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1.1

affine coordinate system

coordinate system in Euclidean space with straight axes that are not necessarily mutually perpendicular

[SOURCE: ISO 19111:2019, 3.1.1]

ISO 19162:2019(E)

3.1.2

bearing

<geodesy> horizontal angle at a point relative to a specified direction

Note 1 to entry: The direction is usually specified to be north. In some communities the term bearing refers specifically to grid north and directions relative to true north are then termed 'azimuth'; in other communities a bearing refers specifically to true north. In this document bearing is used for any specified reference direction. The angle may be reckoned positive clockwise or positive counter-clockwise depending upon the application.

3.1.3

Cartesian coordinate system

coordinate system in Euclidean space which gives the position of points relative to n mutually perpendicular straight axes all having the same unit of measure

Note 1 to entry: n is 2 or 3 for the purposes of this document.

Note 2 to entry: A Cartesian coordinate system is a specialisation of an affine coordinate system.

[SOURCE: ISO 19111:2019, 3.1.2]

3.1.4

compound coordinate reference system

coordinate reference system using at least two independent coordinate reference systems

Note 1 to entry: Coordinate reference systems are independent of each other if coordinate values in one cannot be converted or transformed into coordinate values in the other.

[SOURCE: ISO 19111:2019, 3.1.3]

3.1.5

coordinate conversion

coordinate operation that changes coordinates in a source coordinate reference system to coordinates in a target coordinate reference system in which both coordinate reference systems are based on the same datum

Note 1 to entry: A coordinate conversion uses parameters which have specified values.

EXAMPLE 1 A mapping of ellipsoidal coordinates to Cartesian coordinates using a map projection.

EXAMPLE 2 Change of units such as from radians to degrees or from feet to metres.

[SOURCE: ISO 19111:2019, 3.1.6]

3.1.6

coordinate epoch

epoch to which coordinates in a dynamic coordinate reference system are referenced

[SOURCE: ISO 19111:2019, 3.1.7]

3.1.7

coordinate operation

process using a mathematical model, based on a one-to-one relationship, that changes coordinates in a source coordinate reference system to coordinates in a target coordinate reference system, or that changes coordinates at a source coordinate epoch to coordinates at a target coordinate epoch within the same coordinate reference system

[SOURCE: ISO 19111:2019, 3.1.8]

3.1.8

coordinate reference system

coordinate system that is related to an object by a datum

Note 1 to entry: Geodetic and vertical datums are referred to as reference frames.

Note 2 to entry: For geodetic and vertical reference frames, the object will be the Earth. In planetary applications, geodetic and vertical reference frames may be applied to other celestial bodies.

[SOURCE: ISO 19111:2019, 3.1.9]

3.1.9

coordinate system

set of mathematical rules for specifying how coordinates are to be assigned to points

[SOURCE: ISO 19111:2019, 3.1.11]

3.1.10

coordinate transformation

coordinate operation that changes coordinates in a source coordinate reference system to coordinates in a target coordinate reference system in which the source and target coordinate reference systems are based on different datums

Note 1 to entry: A coordinate transformation uses parameters which are derived empirically. Any error in those coordinates will be embedded in the coordinate transformation and when the coordinate transformation is applied the embedded errors are transmitted to output coordinates.

Note 2 to entry: A coordinate transformation is colloquially sometimes referred to as a 'datum transformation'. This is erroneous. A coordinate transformation changes coordinate values. It does not change the definition of the datum. In this document coordinates are referenced to a coordinate reference system. A coordinate transformation operates between two coordinate reference systems, not between two datums.

[SOURCE: ISO 19111:2019, 3.1.12]

3.1.11

cylindrical coordinate system

three-dimensional coordinate system in Euclidean space in which position is specified by two linear coordinates and one angular coordinate

[SOURCE: ISO 19111:2019, 3.1.14]

3.1.12

datum

reference frame

parameter or set of parameters that realize the position of the origin, the scale, and the orientation of a coordinate system

[SOURCE: ISO 19111:2019, 3.1.15]

3.1.13

datum ensemble

group of multiple realizations of the same terrestrial or vertical reference system that, for approximate spatial referencing purposes, are not significantly different

Note 1 to entry: Datasets referenced to the different realizations within a datum ensemble may be merged without coordinate transformation.

Note 2 to entry: 'Approximate' is for users to define but typically is in the order of under 1 decimetre but may be up to 2 metres.

EXAMPLE "WGS 84" as an undifferentiated group of realizations including WGS 84 (TRANSIT), WGS 84 (G730), WGS 84 (G873), WGS 84 (G1150), WGS 84 (G1674) and WGS 84 (G1762). At the surface of the Earth these have changed on average by 0.7 m between the TRANSIT and G730 realizations, a further 0.2 m between G730 and G873, 0.06 m between G873 and G1150, 0.2 m between G1150 and G1674 and 0.02 m between G1674 and G1762.

[SOURCE: ISO 19111:2019, 3.1.16]

ISO 19162:2019(E)**3.1.14****derived coordinate reference system**

coordinate reference system that is defined through the application of a specified coordinate conversion to the coordinates within a previously established coordinate reference system

Note 1 to entry: The previously established coordinate reference system is referred to as the base coordinate reference system.

Note 2 to entry: A derived coordinate reference system inherits its datum or reference frame from its base coordinate reference system.

Note 3 to entry: The coordinate conversion between the base and derived coordinate reference system is implemented using the parameters and formula(s) specified in the definition of the coordinate conversion.

[SOURCE: ISO 19111:2019, 3.1.8]

3.1.15**dynamic coordinate reference system**

coordinate reference system that has a dynamic reference frame

Note 1 to entry: Coordinates of points on or near the crust of the Earth that are referenced to a dynamic coordinate reference system may change with time, usually due to crustal deformations such as tectonic motion and glacial isostatic adjustment.

Note 2 to entry: Metadata for a dataset referenced to a dynamic coordinate reference system should include coordinate epoch information.

[SOURCE: ISO 19111:2019, 3.1.9]

3.1.16**dynamic reference frame**

dynamic datumreference frame in which the defining parameters include time evolution

Note 1 to entry: The defining parameters that have time evolution are usually a coordinate set.

[SOURCE: ISO 19111:2019, 3.1.20]

[SIST ISO 19162:2024](https://standards.iteh.ai/catalog/standards/sist/9f42c8bd-dafb-4e94-8fe2-12bd290bc2b6/sist-iso-19162-2024)

<https://standards.iteh.ai/catalog/standards/sist/9f42c8bd-dafb-4e94-8fe2-12bd290bc2b6/sist-iso-19162-2024>

3.1.17**ellipsoid**

reference ellipsoid

<geodesy> geometric reference surface embedded in 3D Euclidean space formed by an ellipse that is rotated about a main axis

Note 1 to entry: For the Earth the ellipsoid is bi-axial with rotation about the polar axis. This results in an oblate ellipsoid with the midpoint of the foci located at the nominal centre of the Earth.

[SOURCE: ISO 19111:2019, 3.1.22]

3.1.18**ellipsoidal coordinate system**

geodetic coordinate system

coordinate system in which position is specified by geodetic latitude, geodetic longitude and (in the three-dimensional case) ellipsoidal height

[SOURCE: ISO 19111:2019, 3.1.23]