INTERNATIONAL STANDARD

ISO/IEC 23001-7

Third edition 2016-02-15 **AMENDMENT 1** 2019-09

Information technology — MPEG systems technologies —

Part 7:

Common encryption in ISO base media file format files

iTeh STAMENDMENTRE AES CBC-128 and key (stations.iteh.ai)

Technologies de l'information — Technologies des systèmes MPEG — https://standards.iteh.@artie/JstCryptage/commun des fichiers du format de fichier de médias aa89c6f5(de1a/base150)1-7-2016-amd-1-2019

AMENDEMENT 1: AES-CBC-128 et rotation des clés



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 23001-7:2016/Amd 1:2019 https://standards.iteh.ai/catalog/standards/sist/a2d4d937-1195-49fb-921b-aa89c6f56e03/iso-iec-23001-7-2016-amd-1-2019



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <u>www.iso.org/patents</u>) or the IEC list of patent declarations received (see <u>http://patents.iec.ch</u>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, Information technology, Subcommittee SC 29, Coding of audio, picture, multimedia and hypermedia information.

A list of all parts in the ISO/IEC 23001 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 23001-7:2016/Amd 1:2019 https://standards.iteh.ai/catalog/standards/sist/a2d4d937-1195-49fb-921b-aa89c6f56e03/iso-iec-23001-7-2016-amd-1-2019

Information technology — MPEG systems technologies —

Part 7:

Common encryption in ISO base media file format files

AMENDMENT 1: AES-CBC-128 and key rotation

Clause 2

Add the following new normative references:

ISO/IEC 23008-2, Information technology — High efficiency coding and media delivery in heterogeneous environments — Part 2: High efficiency video coding

ISO/IEC 23008-12, Information technology — High efficiency coding and media delivery in heterogeneous environments — Part 12: Image File Format (HEIF)

iTeh STANDARD PREVIEW

3.1

Insert a new 3.1.8 and renumber current 3.1.8 as 3.1.9:

3.1.8

ISO/IEC 23001-7:2016/Amd 1:2019

https://standards.iteh.ai/catalog/standards/sist/a2d4d937-1195-49fb-921bsample

media sample when the protection applies to media tracks, or payload of an item when the protection applies to items

Note 1 to entry: Media sample as defined in 14496-12.

Note 2 to entry: Payload of an item as defined in 14496-12.

4.2

Add the following item to the list:

e) 'sve1' - AES-CTR content sensitive encryption, as defined in Annex A.

```
Clause 6
```

In paragraph 4, replace:

```
unsigned int(8)
                        reserved = 0;
   unsigned int(4)
                        crypt_byte_block;
   unsigned int(4)
                        skip byte block;
   unsigned int(8)
                        isProtected;
   unsigned int(8)
                        Per Sample IV Size;
   unsigned int(8)[16] KID;
   if (Per_Sample_IV_Size == 0) {
      unsigned int(8) constant IV size;
      unsigned int(8)[constant_IV_size] constant_IV;
                          iTeh STANDARD PREVIEW
}
                                   (standards.iteh.ai)
with
                                    ISO/IEC 23001-7:2016/Amd 1:2019
                       https://standards.iteh.ai/catalog/standards/sist/a2d4d937-1195-49fb-921b-
   unsigned int(1)
                        multi_kexoftlgge03/iso-iec-23001-7-2016-amd-1-2019
   unsigned int(7)
                       reserved = 0;
   unsigned int(4)
                        crypt_byte_block;
   unsigned int(4)
                        skip byte block;
   unsigned int(8)
                        isProtected;
   if (multi_key_flag == 1) {
      unsigned int(16)
                          key_count;
   } else {
      key count = 1;
   for (i=1; i <= key_count; i++) {
      unsigned int(8)
                           Per_Sample_IV_Size;
      unsigned int(8)[16] KID;
      if (Per Sample IV Size == 0) {
         unsigned int(8) constant IV size;
         unsigned int(8) [constant IV size] constant IV;
```

```
}
```

Clause 6

Add a new item to the list in paragraph 5 (insert before semantics of isProtected):

— multi_key_flag indicates that the multiple key version of the sample group description is used. If this flag is set, multiple keys will be described for this sample group description entry; otherwise, a single key is described for this sample group description entry.

Add a new item to the list in paragraph 5 (insert after semantics of isProtected):

 key_count indicates the number of keys that may apply to a sample associated to this sample group description entry. It is not required that a sample associated with this sample group description entry uses all the keys described.

7.1

Replace the sample auxiliary information in paragraph 3 with:

```
aligned(8) class CencSampleAuxiliaryDataFormat (Standards.iteh.ai)
   unsigned int (Per_sample_fivesize *8)23fhit7a112atronvector;
     if (sample info size > Per Sample IV Size ) {
        unsigned int(16) subsample count;
         {
           unsigned int(16) BytesOfClearData;
           unsigned int (32) BytesOfProtectedData;
        } [subsample count ]
     }
   } else if (aux info type parameter == 1) {
     unsigned int(16) multi IV count;
     for (i=1; i <= multi _IV_count; i++) {</pre>
        unsigned int(8) multi subindex IV;
        unsigned int (Per Sample IV Size*8) IV;
     unsigned int (32) subsample count;
     {
```

```
unsigned int(16) multi_subindex;
unsigned int(16) BytesOfClearData;
unsigned int(32) BytesOfProtectedData;
} [subsample_count]
}
```

Following the sample auxiliary information, add the following at the end of the 'where' list (after semantics of BytesOfProtectedData):

multi IV count indicates the number of entries in the initialization vector loop;

multi_subindex_IV indicates the index of the associated key entry, where value one is the first entry, in the associated list; if this data is read for the processing of a track sample, the associated list is the 'seig' sample group description entry associated with this sample; otherwise (this data is read for the processing of an item), the associated list is the list of key definitions in the 'ienc' item property of this item. The associated key entry shall have a Per_Sample_IV_Size different from 0, i.e. key entries using constant IV shall not be present in this loop. If this data is read for the processing of a track sample and aux_info_type_parameter is set to 1, the associated 'seig' sample group description entry shall have the multi key flag set to 1;

indicates the initialization vector to be used for the first block of protected data for the associated key entry;

multi_subindex indicates the index of the associated key entry, where value one is the first entry, in the associated list (see multi_subindex_IV) for the following run of encrypted data.

https://standards.iteh.ai/catalog/standards/sist/a2d4d937-1195-49fb-921b-aa89c6f56e03/iso-iec-23001-7-2016-amd-1-2019

7.2.2

Replace the content of 7.2.2 with the following:

```
aligned(8) class SampleEncryptionBox extends FullBox('senc', version, flags)
{
   unsigned int(32)    sample_count;
   {
      if (version==0) {
        unsigned int(Per_Sample_IV_Size*8) InitializationVector;
      if (flags & 0x000002) {
        unsigned int(16) subsample_count;
        {
            unsigned int(16) BytesOfClearData;
            unsigned int(32) BytesOfProtectedData;
        } [subsample_count]
    }
}
```

```
} else if (version==1) {
         unsigned int(16) multi IV count;
         for (i=1; i <= multi _IV_count; i++) {</pre>
             unsigned int(8) multi_subindex_IV;
             unsigned int (Per Sample IV Size*8) IV;
         unsigned int(32) subsample count;
             unsigned int(16) multi subindex;
             unsigned int(16) BytesOfClearData;
             unsigned int (32) BytesOfProtectedData;
         } [subsample count]
      }
   }[ sample count ]
                    iTeh STANDARD PREVIEW
}
                              (standards.iteh.ai)
7.2.3
                               ISO/IEC 23001-7:2016/Amd 1:2019
                  https://standards.iteh.ai/catalog/standards/sist/a2d4d937-1195-49fb-921b-
Add the following to the list of semantics: -iec-23001-7-2016-amd-1-2019
— multi IV count, multi subindex IV, IV and multi subindex SHALL conform to the definition
    specified in Clause 7.
8.1.1
Replace
Container: Movie ('moov') or Movie Fragment ('moof')
with
Container: Movie ('moov') or Movie Fragment ('moof') or 'meta' if no Movie ('moov')
```

8.2

Add the following new subclauses after 8.2:

8.3 Item encryption box

8.3.1 Definition

Box Type: `ienc'

Container: Item Properties Box

Mandatory (per item): Yes for protected items using schemes defined in this document

Quantity (per item): At most one associated with any item

Quantity: Zero or one

Items as defined in ISO/IEC 14496-12 may be protected using the schemes defined in this document. In this case, such items shall have an associated ItemEncryptionBox property and an associated auxiliary item with an aux_info_type matching the protection scheme used, as defined in 8.4. The payload of that auxiliary item shall be exactly one CencSampleAuxiliaryDataFormat as defined in 7.1.

The ItemEncryptionBox contains default values for the isProtected flag, Per_Sample_IV_Size, and KID for the item. In the case where pattern-based encryption is in effect, it supplies the pattern and when Constant IVs are in use, it supplies the Constant IV. These values are used as the encryption parameters for the item in this meta box. For files with only one key for all items, this property box allows the basic encryption parameters to be specified once for all items instead of being repeated per item.

Items sharing this property are always protected; consequently, the default value for isProtected field (see 9.1) is 1.

If the value Per_Sample_IV_Size is 0, then the constant_IV_size for all items that use these settings SHALL be present. A Constant IV SHALL NOT be used with counter-mode encryption.

ItemEncryptionBox properties shall be marked as essential in ItemPropertyAssociation.

NOTE The version field of the ItemEncryptionBox is set to a value greater than zero when the pattern encryption defined in 9.6 is used and to zero otherwise.

8.3.2 Syntax iTeh STANDARD PREVIEW

```
aligned(8) class ItemEncryptionBox extends [ItemFullFropenty()]enc', version, flags=0)
                                      ISO/IEC 23001-7:2016/Amd 1:2019
      unsigned int (8) reserve aderdo iteh.ai/catalog/standards/sist/a2d4d937-1195-49fb-921b-
                                 aa89c6f56e03/iso-iec-23001-7-2016-amd-1-2019
      if (version==0) {
             unsigned int(8) reserved = 0;
      } else { // version is 1 or greater
             unsigned int(4) crypt byte block;
             unsigned int(4) skip byte block;
      unsigned int(8) num keys;
      for (i=1; i<= num keys; i++) {
         unsigned int(8) Per Sample IV Size;
         unsigned int(8)[16] KID;
          if (Per Sample IV Size == 0) {
             unsigned int(8) constant IV size;
             unsigned int(8)[ constant IV size] constant IV;
```

8.3.3 Semantics

version SHALL be zero unless pattern-based encryption is in use, whereupon it SHALL be 1.

<code>crypt_byte_block</code> specifies the count of the encrypted blocks in the protection pattern, where each block is of size 16-bytes, for items associated with this key entry. See 9.1 for further details.

skip_byte_block specifies the count of the unencrypted blocks in the protection pattern for items associated with this key entry. See the skip byte block field in 9.1 for further details.

num keys indicates the number of key definition entries.

Per_Sample_IV_Size is the initialization vector size in bytes for items associated with this key entry. See the Per_Sample_IV_Size field in 9.1 for further details.

kid is the key identifier used for items associated with this key entry. See the kid field in 9.1 for further details.

constant IV size is the size of a initialization vector for items associated with this key entry.

 $constant_{IV}$, if present, is the initialization vector for items associated with this key entry. See the $constant_{IV}$ field in 9.1 for further details.

8.4 Item auxiliary information box

8.4.1 Definition

Box Type: `iaux' iTeh STANDARD PREVIEW

Container: Item Properties Box (standards.iteh.ai)

Mandatory (per item): Yes for protected items using schemes defined in this document

Quantity (per item): At most one associated with any item 1 2010

Quantity: Zero or one

An item may have some auxiliary information associated, similarly to sample of a track having auxiliary sample information. This information is usually declared through item properties and associations; it can also be declared through auxiliary information items, to allow sharing the auxiliary info between items and samples through the extent construction method of the item.

Auxiliary information items shall be declared with an <code>item_type</code> value of <code>`auxi'</code>. Items shall indicate their auxiliary information items through an item reference of type <code>`auxr'</code> from the item to the auxiliary information item(s).

Auxiliary information item may have an ItemAuxiliaryInformationBox property associated, indicating the type of auxiliary information and its parameter type (aux_info_type and aux_info_type_parameter).

If no ItemAuxiliaryInformationBox is present for an auxiliary information item, then the implied value of aux_info_type is either (a) in the case of protected content, the scheme_type included in the ProtectionSchemeInfoBox of the referring item or otherwise (b) the item_type of the referring item. The default value of the aux_info_type_parameter is 0. The ItemAuxiliaryInformationBox shall be present when the referring item is not protected and is not defined using version 2 or higher of ItemInfoEntry.

There shall be at most one auxiliary information item with a given <code>aux_info_type</code> and <code>aux_info_type_parameter</code> associated with an item.

When present, the ItemAuxiliaryInformationBox property shall be marked as essential in ItemPropertyAssociation.

8.4.2 Syntax