



SLOVENSKI STANDARD
SIST EN 301 087 V7.1.1:2003

01-december-2003

8 [[]HJb]`WV] b]`hY`_ca i b]_UW`g_]`g]ghYa `fZUuU&]b`ZUuU&ZL`E`GdYVWZ_ UW`UnU
cdfYa c`g]ghYa UVUhb]`dcghU`f6 GGL`E`FUX]`g_]`j]X]_]`f] GA `%%&`zfUh`]]WU+`%`%`z
]nXUU`%`- , Ł

Digital cellular telecommunications system (Phase 2 and Phase 2+) (GSM); Base Station System (BSS) equipment specification; Radio aspects (GSM 11.21 version 7.1.1 Release 1998)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 087 V7.1.1:2003
https://standards.iteh.ai/catalog/standards/sist/68f29901-9676-4943-8094-0fe7a3e2889c/sist-en-301-087-v7-1-1-2003](https://standards.iteh.ai/catalog/standards/sist/68f29901-9676-4943-8094-0fe7a3e2889c/sist-en-301-087-v7-1-1-2003)

Ta slovenski standard je istoveten z: EN 301 087 Version 7.1.1

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---	--

SIST EN 301 087 V7.1.1:2003 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 087 V7.1.1:2003](https://standards.iteh.ai/catalog/standards/sist/68f29901-9676-4943-8094-0fe7a3e2889c/sist-en-301-087-v7-1-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/68f29901-9676-4943-8094-0fe7a3e2889c/sist-en-301-087-v7-1-1-2003>

ETSI EN 301 087 V7.1.1 (1999-11)

European Standard (Telecommunications series)

**Digital cellular telecommunications system (Phase 2 & Phase 2+);
Base Station System (BSS) equipment specification;
Radio aspects
(GSM 11.21 version 7.1.1 Release 1998)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

GSM®

GLOBAL SYSTEM FOR
MOBILE COMMUNICATIONS

[SIST EN 301 087 V7.1.1:2003](https://standards.iteh.ai/catalog/standards/sist/68f29901-9676-4943-8094-0fe7a3e2889c/sist-en-301-087-v7-1-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/68f29901-9676-4943-8094-0fe7a3e2889c/sist-en-301-087-v7-1-1-2003>



Reference

REN/SMG-081121Q7 (a2c03ico.PDF)

Keywords

Digital cellular telecommunications system,
Global System for Mobile communications (GSM)**ETSI**

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la
Sous-Prefecture de Grasse (06) N° 7803/88

<https://standards.etsi.org/standards-search/>
0fe7a3e2889c/sist-en-301-087-v7-1-1-2003

Internet

secretariat@etsi.frIndividual copies of this ETSI deliverable
can be downloaded from<http://www.etsi.org>If you find errors in the present document, send your
comment to: editor@etsi.fr

Important notice

This ETSI deliverable may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference should be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.
All rights reserved.

Contents

Intellectual Property Rights	8
Foreword	8
1 Scope.....	9
2 References.....	10
3 Definitions, abbreviations, frequency bands and channels	11
3.1 Definitions	11
3.2 Abbreviations.....	12
3.3 Frequency bands and channels.....	12
3.3.1 Frequency bands.....	12
3.3.2 Channels and channel numbering.....	12
4 General test conditions and declarations	13
4.1 Output power and determination of power class.....	13
4.2 Specified frequency range.....	13
4.3 Frequency hopping.....	14
4.4 RF power control	14
4.5 Downlink discontinuous transmission (DTX).....	14
4.6 Test environments.....	14
4.6.1 Normal test environment	14
4.6.2 Extreme test environment.....	15
4.6.2.1 Extreme temperature.....	15
4.6.3 Vibration	15
4.6.4 Power supply.....	16
4.7 Acceptable uncertainty of measurement equipment.....	16
4.8 Interpretation of measurement results.....	19
4.9 Selection of configurations for testing.....	20
4.10 BTS Configurations	20
4.10.1 Receiver diversity.....	21
4.10.2 Duplexers	21
4.10.3 Power supply options	21
4.10.4 Ancillary RF amplifiers.....	21
4.10.5 BSS using antenna arrays	22
5 Format and interpretation of tests.....	23
6 Transmitter.....	24
6.1 Static Layer 1 functions	24
6.1.1 Test purpose	24
6.1.2 Test case.....	25
6.1.3 Essential conformance.....	25
6.1.4 Complete conformance.....	25
6.1.5 Requirement reference	25
6.2 Phase error and mean frequency error	25
6.2.1 Test purpose	25
6.2.2 Test case.....	25
6.2.3 Essential conformance.....	26
6.2.4 Complete conformance.....	26
6.2.5 Requirement reference	27
6.3 Mean transmitted RF carrier power	27
6.3.1 Test purpose	27
6.3.2 Test case.....	27
6.3.3 Essential conformance.....	28
6.3.4 Complete conformance.....	28
6.3.5 Requirement reference	28

6.4	Transmitted RF carrier power versus time	28
6.4.1	Test purpose	28
6.4.2	Test case	29
6.4.3	Essential conformance	29
6.4.4	Complete conformance	29
6.4.5	Requirement reference	30
6.5	Adjacent channel power	30
6.5.1	Spectrum due to modulation and wideband noise	30
6.5.1.1	Test purpose	30
6.5.1.2	Test case	30
6.5.1.3	Essential Conformance	31
6.5.1.4	Complete conformance	33
6.5.1.5	Requirement reference	33
6.5.2	Switching transients spectrum	33
6.5.2.1	Test purpose	33
6.5.2.2	Test case	33
6.5.2.3	Essential conformance	35
6.5.2.4	Complete conformance	35
6.5.2.5	Requirement reference	35
6.6	Spurious emissions from the transmitter antenna connector	35
6.6.1	Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band	36
6.6.1.1	Test Purpose	36
6.6.1.2	Test Case	36
6.6.1.3	Essential conformance	36
6.6.1.4	Complete conformance	36
6.6.1.5	Requirement Reference	36
6.6.2	Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band	36
6.6.2.1	Applicability (Phase 2)	36
6.6.2.1.1	Test Purpose	37
6.6.2.1.2	Test Case	37
6.6.2.1.3	Essential conformance	38
6.6.2.1.4	Complete conformance	38
6.6.2.1.5	Requirement Reference	38
6.6.2.2	Applicability (Phase 2+)	38
6.6.2.2.1	Test Purpose	38
6.6.2.2.2	Test Case	39
6.6.2.2.3	Essential conformance	39
6.6.2.2.4	Complete conformance	40
6.6.2.2.5	Requirement Reference	40
6.7	Intermodulation attenuation	40
6.7.1	Test purpose	40
6.7.2	Test case	41
6.7.3	Essential Conformance	42
6.7.4	Complete conformance	42
6.7.5	Requirement reference	43
6.8	Intra Base Station System intermodulation attenuation	43
6.8.1	Test purpose	43
6.8.2	Test case	43
6.8.3	Essential conformance	44
6.8.4	Complete conformance	44
6.8.5	Requirement reference	44
7	Receivers	45
7.1	Static Layer 1 receiver functions (nominal error ratios)	45
7.1.1	Test Purpose	45
7.1.2	Test Case	45
7.1.3	Essential conformance	46
7.1.4	Complete conformance	46
7.1.5	Requirement Reference	47
7.2	Erroneous Frame Indication Performance	47

7.2.1	Test Purpose	47
7.2.2	Test Case	47
7.2.3	Essential conformance	48
7.2.4	Complete conformance	48
7.2.5	Requirement reference	48
7.3	Static Reference Sensitivity Level	48
7.3.1	Test Purpose	48
7.3.2	Test Case	48
7.3.3	Essential conformance	49
7.3.4	Complete conformance	49
7.3.5	Requirements Reference	50
7.4	Multipath Reference Sensitivity Level	50
7.4.1	Test Purpose	50
7.4.2	Test Case	50
7.4.3	Essential conformance	52
7.4.4	Complete conformance	53
7.4.5	Requirement Reference	55
7.5	Reference interference level	55
7.5.1	Test Purpose	55
7.5.2	Test Case	55
7.5.3	Essential conformance	57
7.5.4	Complete conformance	59
7.5.5	Requirements Reference	62
7.6	Blocking Characteristics	62
7.6.1	Test Purpose	62
7.6.2	Test Case	62
7.6.3	Essential conformance	64
7.6.4	Complete conformance	65
7.6.5	Requirements reference	65
7.7	Intermodulation characteristics	65
7.7.1	Test Purpose	65
7.7.2	Test Case	65
7.7.3	Essential conformance	66
7.7.4	Complete conformance	67
7.7.5	Requirement Reference	67
7.8	AM suppression	67
7.8.1	Test Purpose	67
7.8.2	Test Case	67
7.8.3	Essential conformance	68
7.8.4	Complete conformance	68
7.8.5	Requirement Reference	68
7.9	Spurious emissions from the receiver antenna connector	68
7.9.1	Test Purpose	68
7.9.2	Test Case	68
7.9.3	Essential conformance	69
7.9.4	Complete conformance	69
7.9.5	Requirement Reference	69
8	Radiated spurious emissions	69
8.1	Test Purpose	69
8.2	Test Case	70
8.3	Essential conformance	71
8.4	Complete conformance	71
8.5	Requirement reference	71
9	Radio link management	71
9.1	General	71
9.2	Synchronization	72
9.2.1	Timing Tolerance	72
9.2.1.1	Test purpose	72
9.2.1.2	Test case	72

9.2.1.3	Essential conformance	72
9.2.1.4	Complete conformance	73
9.2.1.5	Requirement reference	73
9.3	Frame structure	73
9.3.1	BCCH Multiframe	73
9.3.1.1	Test purpose	73
9.3.1.2	Test case	73
9.3.1.3	Essential conformance	73
9.3.1.4	Complete conformance	73
9.3.1.5	Requirement reference	74
9.3.2	TDMA-frame structure	74
9.3.2.1	Test purpose	74
9.3.2.2	Test case	74
9.3.2.3	Essential conformance	74
9.3.2.4	Complete conformance	74
9.3.2.5	Requirement reference	74
9.4	Radio link measurements	74
9.4.1	Signal Strength	75
9.4.1.1	Measurement Accuracy	75
9.4.1.1.1	Test purpose	75
9.4.1.1.2	Test case	75
9.4.1.1.3	Essential conformance	75
9.4.1.1.4	Complete conformance	75
9.4.1.2	Selectivity of signal strength measurements	76
9.4.1.2.1	Test purpose	76
9.4.1.2.2	Test case	77
9.4.1.2.3	Essential conformance	77
9.4.1.2.4	Complete conformance	77
9.4.1.2.5	Requirement reference	78
9.4.2	Signal quality	78
9.4.2.1	Test purpose	78
9.4.2.2	Test case	78
9.4.2.3	Essential conformance	78
9.4.2.4	Complete conformance	79
9.4.2.5	Requirement reference	79
9.4.3	Idle channel signal level	80
9.4.3.1	Test purpose	80
9.4.3.2	Test case	80
9.4.3.3	Essential conformance	80
9.4.3.4	Complete conformance	80
9.4.3.5	Requirement reference	81
9.5	Adaptive frame alignment	81
9.5.1	Test purpose	81
9.5.2	Test case	81
9.5.3	Essential conformance	82
9.5.4	Complete conformance	82
9.5.5	Requirement reference	82
Annex A (informative): Testing of statistical parameters		83
A.1	General theoretical methodology	83
A.2	Detailed theoretical methodology	84
A.3	Limitations and corrections to the theoretical methodology	85
A.3.1	Independent errors	86
A.3.2	Gaussian distribution	86
A.3.3	Stationary random processes	86
A.3.4	Low error ratios	87
A.3.5	Total corrections	87

A.4	Alternative experimental methodology	87
A.5	Detailed definition of error events.....	88
Annex B (informative): Description of special test equipment.....		89
B.1	Base Station System Test Equipment (BSSTE)	89
B.1.1	Fading and multipath propagation simulator.....	89
B.2	Measurement set ups for TX intermodulation.....	89
B.2.1	Test set-up for Intermodulation Attenuation (6.7.)	90
B.2.1.1	RX-Band	90
B.2.1.2	Outside RX Band	90
B.2.2	Test set-up for Intra BSS Intermodulation Attenuation (6.8.).....	91
B.2.2.1	RX-Band	91
B.2.2.2	TX-Band	91
Annex C (informative): Number of samples needed for statistical testing.....		92
C.1	GSM 900; Number of samples for testing	92
C.2	DCS 1800; Number of Samples for Testing.....	99
Annex D (informative): Change history.....		109
History.....		111

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 087 V7.1.1:2003](https://standards.iteh.ai/catalog/standards/sist/68f29901-9676-4943-8094-0fe7a3e2889c/sist-en-301-087-v7-1-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/68f29901-9676-4943-8094-0fe7a3e2889c/sist-en-301-087-v7-1-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by the Special Mobile Group (SMG).

The present document specifies the Radio Frequency (RF) test methods and conformance requirements for GSM 900 and DCS 1800 Base Station Systems (BSS)s. within the Digital cellular telecommunications system (Phase 2+).

The contents of the present document may be subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of the present document, it will be resubmitted for formal approval procedure by ETSI with an identifying change of release date and an increase in version number as follows:

Version 7.x.y

where:

- x the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- y the third digit is incremented when editorial only changes have been incorporated in the specification.

NOTE: The present document contains both essential conformance requirements and complete conformance requirements. Essential conformance requirements are those requirements which may be deemed sufficient for radio type approval purposes, complete conformance requirements cover all conformance aspects.

National transposition dates

Date of adoption of this EN:	19 November 1999
Date of latest announcement of this EN (doa):	29 February 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 2000
Date of withdrawal of any conflicting National Standard (dow):	31 August 2000

1 Scope

The present document specifies the Radio Frequency (RF) test methods and conformance requirements for GSM 900 and DCS 1800 Base Station Systems (BSS)s. These have been derived from, and are consistent with, the core GSM specifications specified in the requirements reference subclause of each test.

The present document is applicable to BSS meeting the requirements of either GSM Phase 2 or GSM Phase 2+. Unless otherwise stated, all tests are applicable to BSS meeting Phase 2 and/or Phase 2+ GSM requirements, because the requirements of the Phase 2 and Phase 2+ core GSM specifications which are referenced in the test are consistent. Most differences between Phase 2 and Phase 2+ requirements represent Phase 2+ features which are optional for the BSS to support.

For each test, two conformance requirements are specified:

- essential conformance requirements;
- complete conformance requirements.

Essential conformance requirements are those which are required:

- a) to ensure compatibility between the radio channels in the same cell;
- b) to ensure compatibility between cells, both co-ordinated and unco-ordinated;
- c) to ensure compatibility with existing systems in the same or adjacent frequency bands;
- d) to verify the important aspects of the transmission quality of the system.

Essential conformance requirements are sufficient to verify the performance of the equipment for radio type approval purposes, in countries where this is applicable.

Complete conformance requirements may be tested to verify all aspects of the performance of a BSS. These requirements are intended to be used by manufacturers and operators to allow conformance and acceptance testing to be performed in a consistent manner; the tests to be performed should be agreed between the parties.

In some tests there are separate requirements for micro-BTS and BTS. If there is no separate requirement for a micro-BTS, the requirements for the BTS apply to a micro-BTS.

In the present document, the reference point for RF connections (except for the measurement of mean transmitted RF carrier power) is the antenna connector, as defined by the manufacturer. The present document does not apply to repeaters or RF devices which may be connected to an antenna connector of a BSS, except as specified in subclause 4.10.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.
- For this Release 1998 document, references to GSM documents are for Release 1998 versions (version 7.x.y).

- [1] GSM 01.04 (ETR 350): "Digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms".
- [2] GSM 04.22 (ETS 300 946): "Digital cellular telecommunications system (Phase 2+); Radio Link Protocol (RLP) for data and telematic services on the Mobile Station - Base Station System (MS - BSS) interface and the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [3] GSM 05.01: "Digital cellular telecommunications system (Phase 2); Physical layer on the radio path; General description".
- [4] GSM 05.02 (ETS 300 574): "Digital cellular telecommunications system (Phase 2); Multiplexing and multiple access on the radio path".
- [5] GSM 05.03 (ETS 300 575): "Digital cellular telecommunications system (Phase 2); Channel coding".
- [6] GSM 05.04 (ETS 300 576): "Digital cellular telecommunications system (Phase 2); Modulation".
- [7] GSM 05.05 (ETS 300 577): "Digital cellular telecommunications system (Phase 2); Radio transmission and reception".
- [8] GSM 05.08 (ETS 300 578): "Digital cellular telecommunications system (Phase 2); Radio subsystem link control".
- [9] GSM 05.10 (ETS 300 579): "Digital cellular telecommunications system (Phase 2); Radio subsystem synchronization".
- [10] GSM 08.20: "Digital cellular telecommunications system (Phase 2); Rate adaption on the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [11] ETS 300 019-1: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment Part 1-0: Classification of environmental conditions Introduction".
- [12] IEC 68-2: "Basic environmental testing procedures; Part 2: Tests".
- [13] IEC 721: "Classification of environmental conditions".
- [14] ETR 027: "Radio and Equipment Systems; methods of measurement for mobile radio equipment".
- [15] ETR 028: "Radio and Equipment Systems; Uncertainties in the measurement of mobile radio equipment characteristics".
- [16] ETS 300 113: "Radio Equipment and Systems; Land mobile service; Technical characteristics and test conditions for radio equipment intended for transmission of data (and speech) and having an antenna connector".

- [17] GSM 04.22 (ETS 300 563): "Digital cellular telecommunications system (Phase 2); Radio Link Protocol (RLP) for data and telematic services on the Mobile Station - Base Station System (MS - BSS) interface and the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [18] GSM 05.01: "Digital cellular telecommunications system (Phase 2+); Physical layer on the radio path; General description".
- [19] GSM 05.02 (ETS 300 908): "Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path".
- [20] GSM 05.03 (ETS 300 909): "Digital cellular telecommunications system (Phase 2+); Channel coding".
- [21] GSM 05.04 (ETS 300 959): "Digital cellular telecommunications system (Phase 2+); Modulation".
- [22] GSM 05.05 (ETS 300 910): "Digital cellular telecommunications system (Phase 2+); Radio transmission and reception".
- [23] GSM 05.08 (ETS 300 911): "Digital cellular telecommunications system (Phase 2+); Radio subsystem link control".
- [24] GSM 05.10 (ETS 300 912): "Digital cellular telecommunications system (Phase 2+); Radio subsystem synchronization".

3 Definitions, abbreviations, frequency bands and channels

3.1 Definitions

[SIST EN 301 087 V7.1.1:2003](https://standards.iteh.ai/catalog/standards/sist/68f29901-9676-4943-8094-01e7a5c2889c/sist-en-301-087-v7-1-1-2003)

For the purposes of the present document, the following terms and definitions apply.

Carrier Frequency: The centre of the ARFCN under test.

GSM: Unless otherwise specified, references to GSM include both GSM 900 and DCS1800.

BSS: In the present document, the term BSS (or base station subsystem) applies to both a BTS and integrated BSS. If a separate BSC is required to perform tests on a BTS, the BSC may be regarded as test equipment and the environmental conditions of the BSC need not be controlled.

pico-BTS: As defined in GSM 05.05 (Ref: TBD). In the present document, this also includes a BSS which incorporates a pico-BTS.

micro-BTS: As defined in GSM 05.05 (ETS 300 577 [7] and ETS300 910 [22]). In the present document, this also includes a BSS which incorporates a micro-BTS.

normal BTS: Any BTS or BSS as defined by GSM 05.05 (ETS 300 910) [7] which is not a micro-BTS.

BSSTE: Base Station System Test Equipment; see annex B.

manufacturer: In the present document, a reference to a manufacturer shall also apply to an agent of the manufacturer.

P-GSM: The primary GSM 900 band.

E-GSM: The extended GSM 900 band (includes P-GSM band).

R-GSM: The Railways GSM 900 band (includes P-GSM band and E-GSM band).

Relevant TX band (or relevant transmit band): The transmit band defined in subclause 3.3.1 for the frequency band of BTS declared by the manufacturer

Relevant RX band (or relevant receive band): The receive band defined in subclause 3.3.1 for the frequency band of BTS declared by the manufacturer

Operating band: The transmit and receive operating bands together comprise the frequency band supported by the BSS; (see subclause 4.2)

Circuit switched logical channels: All the standard GSM logical channels, including traffic channels (TCH), common control channels (RACH) and dedicated control channels (SDCCH, SACCH).

Packet switched logical channels: All the General Packet Radio Services (GPRS) packet data logical channels, including packet traffic channels (PDTCH and PACCH) and packet common control channels (PRACH).

3.2 Abbreviations

Unless otherwise stated, abbreviations used in the present document shall have the meaning given in GSM 01.04 (ETR 350) [1].

B	"Bottom"; the lowest frequency on which a test is performed.
M	"Middle"; a frequency in the middle portion of the operating band of the BSS on which a test is performed.
T	"Top"; the highest frequency on which a test is performed.

3.3 Frequency bands and channels

iTeh STANDARD PREVIEW

3.3.1 Frequency bands (standards.iteh.ai)

The frequency bands for the Base Station System are given in table 1.

Table 1: Frequency bands for GSM900 and DCS1800 Base Station Systems

	TX:	RX:
P-GSM900	935-960 MHz	890-915 MHz
DCS1800	1805-1880 MHz	1710-1785 MHz
E-GSM900	925-960 MHz	880-915 MHz
R-GSM900	921-960 MHz	876-915 MHz

NOTE: It is up to the operator to choose any subset of these bands (or the complete band) on a location basis within a frequency band assigned to the operator by the authority responsible for frequency management issues.

3.3.2 Channels and channel numbering

The channel numbers (ARFCN) for the carrier frequencies (RF channels) within the frequency bands defined above (as defined in GSM 05.05 (ETS 300 910) [7]), are given in table 2. $F_l(n)$ is the frequency of the centre of the RF channel n in the lower band (=RX) and $F_u(n)$ the corresponding frequency in the upper band (=TX).

Table 2: Channel Numbering: Frequencies are in MHz

P-GSM900	$F_l(n)=890+0.2*n$	$1 \leq n \leq 124$	$F_u(n)=F_l(n)+45$
E-GSM900	$F_l(n)=890+0.2*n$ $F_l(n)=890+0.2*(n-1024)$	$0 \leq n \leq 124$ $975 \leq n \leq 1023$	$F_u(n)=F_l(n)+45$
R-GSM900	$F_l(n)=890+0.2*n$ $F_l(n)=890+0.2*(n-1024)$	$0 \leq n \leq 124$ $955 \leq n \leq 1023$	$F_u(n)=F_l(n)+45$
DCS1800	$F_l(n)=1710.2+0.2*(n-512)$	$512 \leq n \leq 885$	$F_u(n)=F_l(n)+95$

4 General test conditions and declarations

The requirements of this clause apply to all tests in the present document, when applicable.

The general conditions during the tests should be according to the relevant parts of ETR 027 [14] (methods of measurement for mobile radio equipment) with the exceptions and additions defined in the individual tests.

Many of the tests in the present document measure a parameter relative to a value which is not fully specified in the GSM specifications. For these tests, the conformance requirement is determined relative to a nominal value specified by the manufacturer.

Certain functions of a BTS are optional in the GSM specifications.

When specified in a test, the manufacturer shall declare the nominal value of a parameter, or whether an option is supported.

4.1 Output power and determination of power class

The manufacturer shall declare the rated maximum power per TRX. For a micro or pico-BTS, this shall be specified at the antenna connector. For a normal BTS, it shall be stated whether this is specified at the input to the combiner or at the antenna connector of the BSS.

For a micro-BTS, the class of the micro-BTS shall be determined from the declared maximum power, according to table 3. Where applicable, the manufacturer shall declare whether the BTS meets the requirements of a micro or pico-BTS.

Table 3: Micro and pico-BTS Power Classes

TRX power class	GSM 900 micro and pico-BTS Maximum output power	DCS1800 micro and pico-BTS Maximum output power
M1	(>19)-24 dBm	(>27)-32 dBm
M2	(>14)-19 dBm	(>22)-27 dBm
M3	(>9)-14 dBm	(>17)-22 dBm
P1	(>13)-20 dBm	(>16)-23 dBm

NOTE: For a normal BTS, the TRX power class can be determined from the manufacturers declared output power per TRX measured at the input to the combiner, according to the tables of TRX power classes in ETS 300 910 [22]. The test requirements for a normal BTS do not vary in this [EN] with TRX power classes. The definition of TRX power class only relates to the declared power per TRX and does not impose any requirement on the measured output power of the BTS.

4.2 Specified frequency range

The manufacturer shall declare:

- which of the frequency bands defined in subclause 3.3.1 is supported by the BSS; a BSS may support the DCS 1800 band and one of the GSM 900 bands, but shall not be defined as supporting more than one of the GSM 900 bands.
- the frequency range within the above frequency band(s) supported by the BSS; This frequency range comprises the transmit and receive operating bands