
**Meat and meat products —
Determination of L-(+)-glutamic acid
content — Reference method**

*Viande et produits à base de viande — Détermination de la teneur en
acide L-(+)-glutamique — Méthode de référence*

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 4134:2021

<https://standards.iteh.ai/catalog/standards/iso/fa1946fc-a311-4798-b899-68cfd69da41f/iso-4134-2021>



Reference number
ISO 4134:2021(E)

© ISO 2021

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 4134:2021

<https://standards.iteh.ai/catalog/standards/iso/fa1946fc-a311-4798-b899-68cfd69da41f/iso-4134-2021>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	1
5 Sampling	2
6 Preparation of test sample	2
7 Test method of spectrophotometer	2
7.1 Reagents	2
7.2 Apparatus	4
7.3 Procedure	5
7.3.1 General	5
7.3.2 Test portion	5
7.3.3 Preparation of extract	5
7.3.4 Determination	5
7.4 Calculation and results	6
7.4.1 Absorbance difference of L-(+)-glutamic acid standard solution	6
7.4.2 Absorbance difference of L-(+)-glutamic acid test solution	7
7.4.3 Formula of linear regression of L-(+)-glutamic acid standard curve	7
7.4.4 L-(+)-glutamic acid concentration of the test solution	7
7.4.5 L-(+)-glutamic acid content of test sample	8
7.5 Precision	8
7.5.1 Interlaboratory test	8
7.5.2 Repeatability	8
7.5.3 Reproducibility	8
7.6 Detection limit	8
8 Test method of light absorption microplate reader	9
8.1 Reagents	9
8.2 Apparatus	9
8.3 Procedure	9
8.3.1 General	9
8.3.2 Extraction of L-(+)-glutamic acid in the test portion	9
8.3.3 Determination	9
8.4 Calculation and results	10
8.4.1 Absorbance difference for L-(+)-glutamic acid standard solution	10
8.4.2 Absorbance difference for L-(+)-glutamic acid test solution	10
8.4.3 Formula of linear regression for L-(+)-glutamic acid standard curve	11
8.4.4 L-(+)-glutamic acid concentration of the test solution	11
8.4.5 L-(+)-glutamic acid content of test sample	11
8.5 Precision	12
8.5.1 Interlaboratory test	12
8.5.2 Repeatability	12
8.5.3 Reproducibility	12
8.6 Detection limit	12
9 Test report	12
Annex A (informative) Safety practices	14
Bibliography	15

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 34, *Food products*, Subcommittee SC 6, *Meat, poultry, fish, eggs and their products*.

This third edition cancels and replaces the second edition (ISO 4134:1999), which has been technically revised. The main changes compared with the previous edition are as follows:

- a new test method, the light absorption microplate reader method, has been added;
- the order of the clauses has been rearranged;
- the Scope ([Clause 1](#)) has been revised to specify free L-(+)-glutamic acid in meat and meat products;
- the Normative references ([Clause 2](#)) have been updated;
- the Terms and definitions ([Clause 3](#)) have been modified by adding the term “free L-(+)-glutamic acid”;
- in [Clause 4](#), the description of “extraction of L-(+)-glutamic acid of test portion” has been modified and the detection wavelength has been changed from “492 nm” to “490 nm”;
- in [7.1](#), the identification of enzyme activity units for diaphorase and glutamate dehydrogenase has been supplemented; the concentration of KOH, NAD has been modified; the NAD and diaphorase have been mixed into a solution; and the buffer, NAD and enzymes have been labelled with R1, R2, and R3;
- the apparatus list ([7.2](#)) has been updated;
- in [7.3](#), the procedure of the test method of spectrophotometer has been modified by halving the sample mass and solution volume;
- in [7.3.4](#), the method of judging the absorbance of the reaction end point has been modified and, as a result, the previous Annex B “Example of plotting and extrapolation of absorbance values” has been deleted;

- in 8.4, the formula and symbol description of spectrophotometer has been modified;
- the previous Annex C “Derivation of equation for calculation of L-(+)-glutamic acid content” has been deleted;
- the Bibliography has been updated.

Any feedback or questions on this document should be directed to the user’s national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

ISO 4134:2021

<https://standards.itih.ai/catalog/standards/iso/fa1946fc-a311-4798-b899-68cfd69da41f/iso-4134-2021>

Meat and meat products — Determination of L-(+)-glutamic acid content — Reference method

1 Scope

This document specifies the spectrophotometer method and the light absorption microplate reader method for the determination of the free L-(+)-glutamic acid content of meat and meat products.

This document is applicable to meat and meat products, including livestock and poultry products.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 648, *Laboratory glassware — Single-volume pipettes*

ISO 1042, *Laboratory glassware — One-mark volumetric flasks*

ISO 1442, *Meat and meat products — Determination of moisture content (Reference method)*

ISO 3696, *Water for analytical laboratory use — Specification and test methods*

ISO 8655-2, *Piston-operated volumetric apparatus — Part 2: piston pipettes*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>


3.1


free L-(+)-glutamic acid

L-(+)-glutamic acid and glutamate existing in meat and meat products in the form of free state

4 Principle

The free L-(+)-glutamic acid present in a test portion is extracted with perchloric acid solution. The extract is centrifuged, decanted and filtered, and diluted to appropriate concentration with water, and the pH is adjusted to 10. Nicotinamide adenine dinucleotide (NAD) is reduced by the L-(+)-glutamic acid in the presence of glutamate dehydrogenase, see [Formula \(1\)](#). The resultant reduced nicotinamide adenine dinucleotide (NADH) reacts with idonitrotetrazolium chloride in the presence of diaphorase, see [Formula \(2\)](#). The resulting formazane is measured at a wavelength of 490 nm and the free L-(+)-glutamic acid content of the test sample is calculated.





5 Sampling

Sampling is not part of the method specified in this document. A recommended sampling method is given in CAC/GL 50-2004.

It is important that the sample received by the laboratory is truly representative and has not been damaged or changed during transport or storage.

Start from a representative sample of at least 200 g. Store the sample at a temperature of 4 °C or frozen at –18 °C if not immediately analysed, so that deterioration and change in composition are prevented.

6 Preparation of test sample

Homogenize the laboratory sample with the appropriate equipment (see 7.2.1). Note that the temperature of the sample should not exceed 25 °C. If a mincer is used, process the sample at least twice with the equipment.

Fill a suitable airtight container with the prepared sample. Seal the container and store it at a temperature of 4 °C or frozen at –18 °C if not immediately analysed, so that deterioration and change in composition are prevented. Analyse the sample as soon as practicable, but always within 24 h after homogenization.

7 Test method of spectrophotometer

7.1 Reagents

Only reagents of recognized analytical grade and only water of at least grade 2 purity as defined in ISO 3696 shall be used. Except for the solutions of inorganic compounds (7.1.1 and 7.1.2), store all solutions in stoppered brown glass bottles which have been scrupulously cleaned and steamed or sterilized.

7.1.1 Dilute perchloric acid, $c = 1,0 \text{ mol/l}$.

WARNING — Contact with oxidizable or combustible materials or with dehydrating or reducing agents can result in fire or explosion. Persons using this acid should be thoroughly familiar with its hazards. See the safety practices listed in Annex A.

Add 8,6 ml of the perchloric acid (70 g/ 100 g, $\rho_{20} = 1,67 \text{ g/ml}$) to the bulk of water, diluting to 100 ml.

7.1.2 Potassium hydroxide solution, $c = 4 \text{ mol/l}$, 2 mol/l , $0,5 \text{ mol/l}$ and $0,02 \text{ mol/l}$.

Dissolve 22,4 g of potassium hydroxide in water. Dilute the solution to 100 ml, $c = 4 \text{ mol/l}$, and mix evenly after cooling.

Dissolve 11,2 g of potassium hydroxide in water. Dilute the solution to 100 ml, $c = 2 \text{ mol/l}$, and mix evenly after cooling.

Transfer 2,5 ml of 2 mol/l potassium hydroxide solution to 10 ml volumetric flask, dilute to the mark with water and mix, $c = 0,5 \text{ mol/l}$.

Transfer 0,1 ml of 2 mol/l potassium hydroxide solution to 10 ml volumetric flask, dilute to the mark with water and mix, $c = 0,02 \text{ mol/l}$.

7.1.3 Solution R1, triethanolamine phosphate buffer solution, pH = 8,6.

Dissolve 1,86 g of triethanolamine hydrochloride in approximately 25 ml of water, adjust the pH to 8,6 with 2 mol/l potassium hydroxide solution (7.1.2), detecting with a pH-meter. Add 0,68 g of octylphenol decaethyleneglycol ether (e.g. Triton X-100). Dilute to 100 ml with water and mix (solution A).

Dissolve 0,86 g of dipotassium hydrogen phosphate (K_2HPO_4) and 7 mg of potassium dihydrogen phosphate (KH_2PO_4) in water. Dilute to 100 ml with water and mix evenly (solution B).

Mix 20 ml of solution A with 5 ml of solution B.

The solution is stable for two months when stored at a temperature of between 0 °C and 6 °C.

7.1.4 Solution R2, the mixed solution of NAD and diaphorase (lipoamide dehydrogenase EC¹ 1.8.1.4), $\rho_{NAD} = 11$ mg/ml, diaphorase, approximately 4 IU/ml.

Weigh 110 mg of NAD, and approximately 8 mg (approximately 40 IU) of diaphorase into a stoppered flask. Add 10,0 ml water and mix evenly.

The solution is stable for one week when stored in the dark at a temperature of between 0 °C and 6 °C.

7.1.5 Solution R3, iodonitrotetrazolium chloride (INT) solution, 2-(4-iodophenyl)-3-(4-nitrophenyl)-5-phenyltetrazolium chloride, $\rho = 0,6$ mg/ml.

Weigh 6 mg of INT into a small, stoppered brown flask. Add 10 ml of water and mix evenly.

The solution is stable for four weeks when stored in the dark at a temperature of between 0 °C and 6 °C.

7.1.6 Solution R123, the mixed solution of solution R1, solution R2 and solution R3.

Pipette 6 ml of solution R1, 2 ml of solution R2 and 2 ml of solution R3 into a stoppered brown glass bottle, and mix evenly before the test.

The mixed solution is stable for 1 h in stoppered brown glass bottles at room temperature.

7.1.7 Glutamate dehydrogenase (GLDH) solution (EC¹ 1.4.1.3), approximately 900 IU/ml.

Weigh 10 mg (approximately 900 IU) of lyophilized glutamate dehydrogenase (GLDH) into a small stoppered flask. Add 1 ml water and mix.

Insulated from ammonium sulfate, ethylene-dinitrilotetraacetic acid (EDTA) and glutaminase, this solution is stable for 12 months when stored at a temperature between 0 °C and 6 °C.

7.1.8 L-(+)-glutamic acid standard stock solution, $\rho = 1\,000$ mg/l.

Weigh, to the nearest 0,000 1 g, approximately 50,0 mg of L-(+)-glutamic acid ($C_5H_9O_4N$). Dissolve it in approximately 25 ml of water.

Adjust the pH to a value range from 5 to 6 with a few drops of 2 mol/l potassium hydroxide solution (7.1.2). Then adjust the pH to 7,0 slowly with 0,02 mol/l potassium hydroxide solution (7.1.2). Dilute to 50 ml with water and mix evenly.

The solution is stable for six months when stored at a temperature between 0 °C and 6 °C.

1) The EC number refers to the Enzyme Classification number as given in: The International Union of Biochemistry, Enzymenomenclature, Elsevier, Amsterdam, 1965.

7.1.9 L-(+)-glutamic acid standard solution, $\rho = 100$ mg/l.

Pipette accurately 5,0 ml of L-(+)-glutamic acid standard stock solution (7.1.8) into a 50 ml volumetric flask (7.2.8), dilute to the mark with water and mix evenly.

The solution is for the current use.

7.1.10 L-(+)-glutamic acid series standard solution, $\rho = 5$ mg/l, 10 mg/l, 15 mg/l, 20 mg/l, 30 mg/l and 40 mg/l.

Pipette accurately 0,50 ml, 1,00 ml, 1,50 ml, 2,00 ml, 3,00 ml and 4,00 ml of L-(+)-glutamic acid standard solution (7.1.9) into each of six 10 ml volumetric flasks (7.2.8) separately, dilute to the mark with water and mix evenly.

The solution is for the current use.

7.2 Apparatus

The usual laboratory equipment and, in particular, the following shall be used.

7.2.1 Mechanical or electrical equipment, capable of homogenizing the laboratory sample.

This includes a high-speed rotational cutter, or a mincer fitted with a plate with apertures not exceeding 4,0 mm in diameter.

7.2.2 Laboratory mixer, a stirrer or an oscillator.

7.2.3 Laboratory centrifuge, with 50 ml or 100 ml centrifuge tubes, operating at a radial acceleration of about 2 000g or an equivalent speed (e.g. 3 500 r/min to 4 000 r/min).

7.2.4 Analytical balance, capable of weighing to the nearest 0,001 g, 0,000 1 g.

7.2.5 Constant temperature drying box.

7.2.6 pH-meter.

7.2.7 Filter papers, with a diameter of about 15 cm, high or moderate speed.

7.2.8 One-mark volumetric flasks, capacities of 10 ml, 50 ml and 100 ml, conforming to ISO 1042, class B standard.

7.2.9 Single-volume pipettes, capacities of 50 ml, 25 ml and 1 ml conforming to ISO 648, class B standard.

7.2.10 Single channel or multi-channel transferring pipettes and tips, of 5 ml, 1 000 μ l, 200 μ l and 100 μ l, conforming to ISO 8655-2.

7.2.11 Small plastic spatula or lid, for mixing the content evenly by stirring with the spatula in the cuvette or by shaking the cuvette covered with the lid.

7.2.12 Photoelectric colorimeter, provided with a filter which has a transmittance maximum at a wavelength of 490 nm, or **spectrometer**.

7.2.13 Cuvettes, of 10 mm optical path length.