
Plastics piping systems — Mechanical fittings for pressure piping systems — Specifications

Systèmes de canalisations en plastiques — Raccords mécaniques pour les canalisations sous pression — Spécifications

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 17885:2021

<https://standards.iteh.ai/catalog/standards/iso/666ae3db-7aaf-4d2e-91d3-66ca3465e0b8/iso-17885-2021>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 17885:2021

<https://standards.iteh.ai/catalog/standards/iso/666ae3db-7aaf-4d2e-91d3-66ca3465e0b8/iso-17885-2021>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	3
3.1 Terms and definitions	3
3.2 Symbols and abbreviated terms	5
3.2.1 Materials	5
3.2.2 Applications	6
4 Manufacturers' declaration for the field of application	6
5 Material	6
5.1 General	6
5.2 Plastic materials	7
5.3 Metals	8
5.4 Elastomers	9
5.5 Lubricants and/or greases	10
6 General characteristics	10
6.1 Appearance	10
6.2 Colour	10
6.3 Weathering protection	10
6.4 Threads	10
6.5 Transition fittings to metal pipes	10
6.6 Combined fittings	11
6.7 Twisting	11
7 Geometrical characteristics	11
8 Physical characteristics	11
8.1 Evaluation of the MRS value of the plastic material	11
8.2 Verification of long-term behaviour of the plastic material	11
8.3 Specific material related characteristics of fitting materials	11
8.4 Application-related characteristics	12
8.4.1 Effect on water quality (W)	12
8.4.2 Resistance to gas constituents (GAS)	12
8.4.3 Chemical resistance of fittings for industrial applications (IS)	13
9 Performance requirements	13
9.1 General	13
9.2 Pressure resistance of the fitting body	13
9.2.1 Preparation of test piece	13
9.2.2 Testing of pressure resistance	14
9.3 Fitting assemblies	14
9.3.1 Preparation of test assemblies	14
9.3.2 Test scheme	14
9.3.3 Requirements	16
10 Marking	25
11 Packaging	25
Annex A (informative) List of standards	26
Annex B (normative) Stiffener requirements	27
Annex C (normative) Test stress of materials and fitting bodies	28
Annex D (normative) Physical characteristics of fitting materials	30

Annex E (normative) Resistance to gas constituents	34
Annex F (normative) Test stresses	35
Annex G (normative) Cyclic test procedure	37
Bibliography	38

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 17885:2021](https://standards.iteh.ai/catalog/standards/iso/666ae3db-7aaf-4d2e-91d3-66ca3465e0b8/iso-17885-2021)

<https://standards.iteh.ai/catalog/standards/iso/666ae3db-7aaf-4d2e-91d3-66ca3465e0b8/iso-17885-2021>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 138, *Plastics pipes, fittings and valves for the transport of fluids*, Subcommittee SC 4, *Plastics pipes and fittings for the supply of gaseous fuels*.

This second edition cancels and replaces the first edition (ISO 17885:2015), which has been technically revised. It also incorporates the Amendment ISO 17885:2015/Amd 1:2016.

The main changes compared to the previous edition are as follows:

- a clarification for the relation between the nominal pressure and the MOP declared by the manufacturer is given;
- the term 'weathering' is used instead of 'ultraviolet radiation', to be in line with PE pipe standards;
- a clarification that the own reprocessible material of glass reinforced materials with a fibre length up to 3 mm may be used;
- the diameter for various pipe materials for the 'Resistance of plastic pipe/pipe or pipe/fitting assemblies to tensile loading at 23 °C has been increased from 63 mm to 250 mm;
- unplasticized polyamide (PA-U) is included in [Table 7](#);
- errors in [Table D.1](#) regarding the viscosity number of unplasticized polyamide (PA-U) are resolved;
- the requirement for the melt mass flow rate for PB in [Table D.1](#) is aligned with ISO 15494;
- the requirement for the depth of dezincification for Cu in [Table D.1](#) is aligned with EN 1254-3, -6 and -8;
- [Formulae \(1\) and \(2\)](#) and [Annex C](#) are corrected;
- the test pressures for unplasticized polyamide (PA-U) in [Table F.1](#) are increased;
- the test procedure in [Annex G](#) is clarified.

This corrected version of ISO 17885:2021 incorporates the following corrections:

- original Formula (1) from ISO 17885:2021 has been deleted and the subsequent formulae have been renumbered accordingly;
- in [Annex C](#), the term "pressure" has been replaced by the term "stress".

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

iTeh Standards (<https://standards.iteh.ai>) Document Preview

ISO 17885:2021

<https://standards.iteh.ai/catalog/standards/iso/666ae3db-7aaf-4d2e-91d3-66ca3465e0b8/iso-17885-2021>

Introduction

This document specifies the requirements for mechanical fittings for joining plastic piping systems for the supply of gaseous fuels, the supply of water for human consumption and other purposes, as well as for industrial application.

It provides a unified set of test methods to check the performance of the fittings, depending on their intended use.

It is the responsibility of the purchaser or specifier to select the appropriate fitting, taking into account their particular requirements and any relevant national guidance or regulations and installation practices or codes.

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[ISO 17885:2021](https://standards.itih.ai/catalog/standards/iso/666ae3db-7aaf-4d2e-91d3-66ca3465e0b8/iso-17885-2021)

<https://standards.itih.ai/catalog/standards/iso/666ae3db-7aaf-4d2e-91d3-66ca3465e0b8/iso-17885-2021>

Plastics piping systems — Mechanical fittings for pressure piping systems — Specifications

1 Scope

This document specifies the requirements and test methods for mechanical fittings intended to join plastic pressure piping systems including transition fittings to metal pipes for the following:

- supply of gaseous fuels (GAS);
- supply of water for human consumption (W), including raw water prior to treatment and for the supply of water for general purposes, as well as underground drainage and sewerage under pressure (P);
- supply of water for irrigation (I);
- industrial applications (IS).

This document is applicable only to mechanical fittings with operating-temperature and pressure limits as indicated in the relevant systems standards.

NOTE A list of International Standards for plastic pipes for which mechanical fittings can be used can be found in [Annex A](#).

Flanges are not covered by this document.

Mechanical fittings for hot and cold water systems inside buildings, as well as for district heating applications, are not covered by this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7-1, *Pipe threads where pressure-tight joints are made on the threads — Part 1: Dimensions, tolerances and designation*

ISO 75-2, *Plastics — Determination of temperature of deflection under load — Part 2: Plastics and ebonite*

ISO 228-1, *Pipe threads where pressure-tight joints are not made on the threads — Part 1: Dimensions, tolerances and designation*

ISO 306, *Plastics — Thermoplastic materials — Determination of Vicat softening temperature (VST)*

ISO 307, *Plastics — Polyamides — Determination of viscosity number*

ISO 472, *Plastics — Vocabulary*

ISO 580:2005, *Plastics piping and ducting systems — Injection-moulded thermoplastics fittings — Methods for visually assessing the effects of heating*

ISO 1043-1, *Plastics — Symbols and abbreviated terms — Part 1: Basic polymers and their special characteristics*

ISO 1133-1, *Plastics — Determination of the melt mass-flow rate (MFR) and melt volume-flow rate (MVR) of thermoplastics — Part 1: Standard method*

ISO 1167-1, *Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 1: General method*

ISO 1167-2, *Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 2: Preparation of pipe test pieces*

ISO 1167-4, *Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 4: Preparation of assemblies*

ISO 2507-1, *Thermoplastics pipes and fittings — Vicat softening temperature — Part 1: General test method*

ISO 2507-2, *Thermoplastics pipes and fittings — Vicat softening temperature — Part 2: Test conditions for unplasticized poly(vinyl chloride) (PVC-U) or chlorinated poly(vinyl chloride) (PVC-C) pipes and fittings and for high impact resistance poly(vinyl chloride) (PVC-HI) pipes*

ISO 3451-4, *Plastics — Determination of ash — Part 4: Polyamides*

ISO 3458, *Plastics piping systems — Mechanical joints between fittings and pressure pipes — Test method for leaktightness under internal pressure*

ISO 3459, *Plastic piping systems — Mechanical joints between fittings and pressure pipes — Test method for leaktightness under negative pressure*

ISO 3501, *Plastics piping systems — Mechanical joints between fittings and pressure pipes — Test method for resistance to pull-out under constant longitudinal force*

ISO 3503, *Plastics piping systems — Mechanical joints between fittings and pressure pipes — Test method for leaktightness under internal pressure of assemblies subjected to bending*

ISO 4633, *Rubber seals — Joint rings for water supply, drainage and sewerage pipelines — Specification for materials*

ISO 6509-1, *Corrosion of metals and alloys — Determination of dezincification resistance of copper alloys with zinc — Part 1: Test method*

ISO 6957, *Copper alloys — Ammonia test for stress corrosion resistance*

ISO 6993-1, *Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels — Part 1: Pipes for a maximum operating pressure of 1 bar (100 kPa)*

ISO 6993-2, *Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels — Part 2: Fittings for a maximum operating pressure of 200 mbar (20 kPa)*

ISO 6993-3, *Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels — Part 3: Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)*

ISO 7686, *Plastics pipes and fittings — Determination of opacity*

ISO 9080, *Plastics piping and ducting systems — Determination of the long-term hydrostatic strength of thermoplastics materials in pipe form by extrapolation*

ISO 10147, *Pipes and fittings made of crosslinked polyethylene (PE-X) — Estimation of the degree of crosslinking by determination of the gel content*

ISO 12162, *Thermoplastics materials for pipes and fittings for pressure applications — Classification, designation and design coefficient*

ISO 13783, *Plastics piping systems — Unplasticized poly(vinyl chloride) (PVC-U) end-load-bearing double-socket joints — Test method for leaktightness and strength while subjected to bending and internal pressure*

ISO 13844, *Plastics piping systems — Elastomeric-sealing-ring-type socket joints for use with plastic pressure pipes — Test method for leaktightness under negative pressure, angular deflection and deformation*

ISO 13845, *Plastics piping systems — Elastomeric-sealing-ring-type socket joints for use with thermoplastic pressure pipes — Test method for leaktightness under internal pressure and with angular deflection*

ISO 13951, *Plastics piping systems — Test method for the resistance of plastic pipe/pipe or pipe/fitting assemblies to tensile loading*

ISO 16010, *Elastomeric seals — Material requirements for seals used in pipes and fittings carrying gaseous fuels and hydrocarbon fluids*

ISO 16486-1:2020, *Plastics piping systems for the supply of gaseous fuels — Unplasticized polyamide (PA-U) piping systems with fusion jointing and mechanical jointing — Part 1: General*

ISO 17778, *Plastics piping systems — Fittings, valves and ancillaries — Determination of gaseous flow rate/pressure drop relationships*

ISO 19899, *Plastics piping systems — Polyolefin pipes and mechanical fitting assemblies — Test method for the resistance to end load (AREL test)*

ISO 23711, *Elastomeric seals — Requirements for materials for pipe joint seals used in water and drainage applications — Thermoplastic elastomers*

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 472, ISO 1043-1, and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1.1 **mechanical fitting**

fitting for assembling plastics pipes with each other or with a metal pipe or fitting, that includes one or more compression zones to provide pressure integrity, leak tightness and resistance to end loads

3.1.2

full-end-load resistance

combination of component and joint design and characteristics such that under any load condition the plastic pipe will fail first

3.1.3

end-load resistance

resistance to end load transmitted via the connecting pipe and generated by internal pressure, pipeline external interference, and thermally induced pipe stresses in any combination

3.1.4

non-end-load resistance

lack of resistance to axial loads without additional external mechanical axial support

3.1.5

lower confidence limit of predicted hydrostatic strength

σ_{LPL}

quantity, with the dimensions of stress, which represents the 97,5 % lower confidence limit of the predicted hydrostatic strength at a temperature θ and time t

Note 1 to entry: It is expressed in megapascals.

Note 2 to entry: Temperature, θ , is expressed in degrees Celsius and time, t , is expressed in years.

[SOURCE: ISO 12162:2009, 3.2]

3.1.6

minimum required strength

MRS

value of σ_{LPL} (3.1.5) at 20 °C and 50 years, rounded down to the next smaller value of the R10 series when σ_{LPL} is below 10 MPa, or to the next lower value of the R20 series when σ_{LPL} is 10 MPa or greater

Note 1 to entry: The R10 series conforms to ISO 3 and the R20 series conforms to ISO 497.

[SOURCE: ISO 4437-1:2014, 3.3.2]

3.1.7

design coefficient

C

coefficient with a value greater than 1, which takes into consideration service conditions, as well as properties of the components of a piping system other than those represented in the lower confidence limit

Note 1 to entry: The minimum value of C , C_{\min} , is defined and given for various thermoplastics pipe systems in ISO 12162 and [Annex C](#).

[SOURCE: ISO 12162:2009, 3.5, modified — The original notes 1 and 2 to entry have been replaced by a new note 1 to entry.]

3.1.8

gaseous fuel

fuel which is in the gaseous state at a temperature of 15 °C and a pressure of 1 bar

Note 1 to entry: 1 bar = 0,1 MPa = 10^5 Pa; 1 MPa = 1 N/mm².

[SOURCE: ISO 4437-1:2014, 3.4.1, modified — Note 1 to entry has been added.]

3.1.9

standard dimension ratio

SDR

numerical designation of a pipe series, which is a convenient round number, approximately equal to the dimension ratio of the nominal outside diameter, d_n , and the nominal wall thickness, e_n

[SOURCE: ISO 4437-1:2014, 3.1.15]

3.1.10

nominal pressure

PN

numerical designation, which is a convenient rounded number for reference purposes

Note 1 to entry: For plastic piping systems conveying water, it corresponds to the maximum continuous operating pressure, expressed in bar, which can be sustained with water at 20 °C, based on the minimum *design coefficient* (3.1.7).

3.1.11

virgin material

material in a form such as granules or powder that has not been subjected to use or processing other than that required for its manufacture and to which no reprocessible or recyclable materials have been added