

Designation: D7640 - 11

StandardSpecification for Engine Coolant Grade Glycerin¹

This standard is issued under the fixed designation D7640; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This specification covers engine coolant grade glycerine (1, 2, 3 Propanetriol, Glycerol).
- 1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.
- 1.3 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

2. Referenced Documents

- 2.1 ASTM Standards:²
- D1122 Test Method for Density or Relative Density of Engine Coolant Concentrates and Engine Coolants By The Hydrometer
- D1119 Test Method for Percent Ash Content of Engine Coolants
- D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)
- D1287 Test Method for pH of Engine Coolants and Antirusts
 D3634 Test Method for Trace Chloride Ion in Engine Coolants
- D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter

- D5827 Test Method for Analysis of Engine Coolant for Chloride and Other Anions by Ion Chromatography
- D5931 Test Method for Density and Relative Density of Engine Coolant Concentrates and Aqueous Engine Coolants by Digital Density Meter
- D6130 Test Method for Determination of Silicon and Other Elements in Engine Coolant by Inductively Coupled Plasma-Atomic Emission Spectroscopy
- D7637 Test Method for Determination of Glycerin Assay by Titration (Sodium Meta Periodate)
- D7638 Test Method for Determination of Fatty Acids and Esters in Glycerin
- D7716 Test Method for Determination of Residual Methanol in Glycerin by Gas Chromatography
- E202 Test Methods for Analysis of Ethylene Glycols and Propylene Glycols
- E300 Practice for Sampling Industrial Chemicals

3. Requirements

3.1 Engine coolant grade glycerin shall conform to the chemical and physical property requirements in Table 1.

4. Sampling

4.1 Sample glycerin in accordance with the appropriate sections of Practice E300 for liquid samples.

5. Packaging and Package Marking

5.1 The packaging, labeling, and transportation of commercial quantities shall conform to applicable federal, state, and local regulations. Conformance is the responsibility of the manufacturer and the shipper.

6. Keywords

6.1 1, 2, 3 Propanetriol; engine coolant; glycerin; glycerin; glycerol; glycol

¹ This specification is under the jurisdiction of ASTM Committee D15 on Engine Coolants and Related Fluids and is the direct responsibility of Subcommittee D15.07 on Specifications.

Current edition approved April 1, 2011. Published June 2011.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.