

---

---

**Plain bearings — Hydrostatic  
plain journal bearings without  
drainage grooves under steady-state  
conditions —**

Part 1:

**Calculation of oil-lubricated plain  
journal bearings without drainage  
grooves**

*Paliers lisses — Paliers lisses radiaux hydrostatiques sans rainure  
d'écoulement fonctionnant en régime stationnaire —*

*Partie 1: Calcul pour la lubrification des paliers lisses radiaux sans  
rainure d'écoulement*

<https://standards.iteh.ai/catalog/standards/iso/44569261-40d1-451a-917a-2f31a37e4751/iso-12168-1-2019>



iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

[ISO 12168-1:2019](https://standards.iteh.ai/catalog/standards/iso/445b92b1-a0df-451a-917a-2f31a37e4751/iso-12168-1-2019)

<https://standards.iteh.ai/catalog/standards/iso/445b92b1-a0df-451a-917a-2f31a37e4751/iso-12168-1-2019>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword .....	iv
Introduction .....	v
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Symbols, terms and units</b> .....	<b>1</b>
<b>5 Bases of calculation and boundary conditions</b> .....	<b>3</b>
<b>6 Method of calculation</b> .....	<b>5</b>
6.1 General .....	5
6.2 Load-carrying capacity .....	5
6.3 Lubricant flow rate and pumping power .....	7
6.4 Frictional power .....	9
6.5 Optimization .....	9
6.6 Temperatures and viscosities .....	11
6.7 Minimum pressure in recesses .....	11
<b>Annex A (informative) Description of the approximation method for the calculation of hydrostatic plain journal bearings</b> .....	<b>13</b>
<b>Annex B (informative) Examples of calculation</b> .....	<b>23</b>
<b>Bibliography</b> .....	<b>31</b>

iTech Standards  
(<https://standards.iteh.ai>)  
Document Preview

<https://standards.iteh.ai>  
ISO 12168-1:2019

<https://standards.iteh.ai/catalog/standards/iso/445b92b1-a0df-451a-917a-2f31a37e4751/iso-12168-1-2019>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 123, *Plain bearings*, Subcommittee SC 8, *Calculation methods for plain bearings and their applications*.

This second edition cancels and replaces the first edition (ISO 12168-1:2001), of which it constitutes a minor revision.

The changes compared to the previous edition are as follows:

- adjustment to ISO/IEC Directives, Part 2:2018;
- correction of typographical errors.

A list of all parts in the ISO 12168 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

The functioning of hydrostatic bearings is characterized by the fact that the supporting pressure of the bearing is generated by external lubrication. The special advantages of hydrostatic bearings are lack of wear, quiet running, wide useable speed range as well as high stiffness and damping capacity. These properties are also the reason for the special importance of hydrostatic bearing units in different fields of application such as machine tools.

The bases of calculation described in this document apply to bearings with different numbers of recesses and different width/diameter ratios for identical recess geometry. In this document, only bearings without oil drainage grooves between the recesses are taken into account. As compared to bearings with oil drainage grooves, this type needs less power with the same stiffness behaviour.

The oil is fed to each bearing recess by means of a common pump with constant pump pressure (system  $p_{en} = \text{constant}$ ) and via preceding linear restrictors (e.g. in the form of capillaries).

The calculation procedures listed in this document enable the user to calculate and assess a given bearing design as well as to design a bearing as a function of some optional parameters. Furthermore, this document contains the design of the required lubrication system including the calculation of the restrictor data.

# iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO 12168-1:2019](https://standards.iteh.ai/catalog/standards/iso/445b92b1-a0df-451a-917a-2f31a37e4751/iso-12168-1-2019)

<https://standards.iteh.ai/catalog/standards/iso/445b92b1-a0df-451a-917a-2f31a37e4751/iso-12168-1-2019>



# Plain bearings — Hydrostatic plain journal bearings without drainage grooves under steady-state conditions —

## Part 1:

# Calculation of oil-lubricated plain journal bearings without drainage grooves

## 1 Scope

This document specifies a calculation method of oil-lubricated plain journal bearings without drainage grooves under steady-state conditions.

It applies to hydrostatic plain journal bearings under steady-state conditions.

In this document, only bearings without oil drainage grooves between the recesses are taken into account.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12168-2:2019, *Plain bearings — Hydrostatic plain journal bearings without drainage grooves under steady-state conditions — Part 2: Characteristic values for the calculation of oil-lubricated plain journal bearings without drainage grooves* [ISO 12168-1:2019](https://standards.iteh.ai/catalog/standards/iso/445b92b1-a0df-451a-917a-2f31a37e4751/iso-12168-1-2019)

<https://standards.iteh.ai/catalog/standards/iso/445b92b1-a0df-451a-917a-2f31a37e4751/iso-12168-1-2019>

## 3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

## 4 Symbols, terms and units

Symbols, terms and units are shown in [Table 1](#).

**Table 1 — Symbols, terms and units**

Symbol	Term	Unit
$a$	Inertia factor	1
$A_{lan}$	Land area	m <sup>2</sup>
$A_{lan}^*$	Relative land area $\left( A_{lan}^* = \frac{A_{lan}}{\pi \times B \times D} \right)$	1
$A_p$	Recess area	m <sup>2</sup>

Table 1 (continued)

Symbol	Term	Unit
$b$	Width perpendicular to the direction of flow	m
$b_{ax}$	Width of axial outlet $\left[ b_{ax} = \frac{\pi \times D}{Z} \right]$	m
$b_c$	Width of circumferential outlet ( $b_c = B - l_{ax}$ )	m
$B$	Bearing width	m
$c$	Stiffness coefficient	N/m
$c_p$	Specific heat capacity of the lubricant ( $p = \text{constant}$ )	J/kg·K
$C_R$	Radial clearance $\left[ C_R = (D_B - D_J) / 2 \right]$	m
$d_{cp}$	Diameter of capillaries	m
$D$	Bearing diameter ( $D_J$ : shaft; $D_B$ : bearing; $D \approx D_J \approx D_B$ )	m
$e$	Eccentricity (shaft displacement)	m
$F$	Load-carrying capacity (load)	N
$F^*$	Characteristic value of load-carrying capacity [ $F^* = F / (B \times D \times p_{en})$ ]	1
$F_{eff}^*$	Characteristic value of effective load-carrying capacity	1
$F_{eff,0}^*$	Characteristic value of effective load-carrying capacity for $N = 0$	1
$h$	Local lubricant film thickness (clearance gap height)	m
$h_{min}$	Minimum lubricant film thickness (minimum clearance gap height)	m
$h_p$	Depth of recess	m
$K_{rot}$	Speed-dependent parameter	1
$l$	Length in the direction of flow	m
$l_{ax}$	Axial land length	m
$l_c$	Circumferential land length	m
$l_{cp}$	Length of capillaries	m
$N$	Rotational frequency (speed)	s <sup>-1</sup>
$p$	Recess pressure, general	Pa
$\bar{p}$	Specific bearing load [ $\bar{p} = F / (B \times D)$ ]	Pa
$p_{en}$	Feed pressure (pump pressure)	Pa
$p_i$	Pressure in recess $i$	Pa
$p_{i,0}$	Pressure in recess $i$ , when $\varepsilon = 0$	Pa
$P^*$	Power ratio ( $P^* = P_f / P_p$ )	1
$P_f$	Frictional power	W
$P_p$	Pumping power	W
$P_{tot}$	Total power ( $P_{tot} = P_p + P_f$ )	W
$P_{tot}^*$	Characteristic value of total power	1
$Q$	Lubricant flow rate (for complete bearing)	m <sup>3</sup> /s
$Q^*$	Lubricant flow rate parameter	1
$R_{cp}$	Flow resistance of capillaries	Pa·s/m <sup>3</sup>
$R_{lan,ax}$	Flow resistance of one axial land $\left( R_{lan,ax} = \frac{12 \times \eta \times l_{ax}}{b_{ax} \times C_R^3} \right)$	Pa·s/m <sup>3</sup>
$R_{lan,c}$	Flow resistance of one circumferential land $\left( R_{lan,c} = \frac{12 \times \eta \times l_c}{b_c \times C_R^3} \right)$	Pa·s/m <sup>3</sup>



Table 1 (continued)

Symbol	Term	Unit
$R_{P,0}$	Flow resistance of one recess, when $\varepsilon = 0$ , ( $R_{P,0} = 0,5R_{lan,ax}$ )	Pa·s/m <sup>3</sup>
$Re$	Reynolds number	1
$So$	Sommerfeld number	1
$T$	Temperature	°C
$\Delta T$	Temperature difference	K
$u$	Flow velocity	m/s
$U$	Circumferential speed	m/s
$\bar{w}$	Average velocity in restrictor	m/s
$Z$	Number of recesses	1
$\alpha$	Position of 1st recess related to recess centre	rad
$\beta$	Attitude angle of shaft	°
$\gamma$	Exponent in viscosity formula	1
$\varepsilon$	Relative eccentricity ( $\varepsilon = e/C_R$ )	1
$\eta$	Dynamic viscosity	Pa·s
$\kappa$	Resistance ratio $\left( \kappa = \frac{R_{lan,ax}}{R_{lan,c}} = \frac{l_{ax} \times b_c}{l_c \times b_{ax}} \right)$	1
$\xi$	Restrictor ratio $\left( \xi = \frac{R_{cp}}{R_{P,0}} \right)$	1
$\pi_f$	Relative frictional pressure $\left( \pi_f = \frac{\eta_B \times \omega}{p_{en} \times \psi^2} \right)$	1
$\rho$	Density	kg/m <sup>3</sup>
$\tau$	Shearing stress	N/m <sup>2</sup>
$\varphi$	Angular coordinate	rad
$\psi$	Relative bearing clearance $\left( \psi = \frac{2 \times C_R}{D} \right)$	1
$\omega$	Angular velocity ( $\omega = 2 \times \pi \times N$ )	s <sup>-1</sup>

## 5 Bases of calculation and boundary conditions

Calculation within the meaning of this document is the mathematical determination of the operational parameters of hydrostatic plain journal bearings as a function of operating conditions, bearing geometry and lubrication data. This means the determination of eccentricities, load-carrying capacity, stiffness, required feed pressure, oil flow rate, frictional and pumping power, and temperature rise. Besides the hydrostatic pressure build-up, the influence of hydrodynamic effects is also approximated.

The Reynolds equation provides the theoretical bases for the calculation of hydrostatic bearings. In most practical cases of application, it is, however, possible to arrive at sufficiently exact results by approximation.

The approximation used in this document is based on two basic formulae for describing the flow via the bearing lands, which can be derived from the Reynolds equation when special boundary conditions are observed. The Hagen-Poiseuille law describes the pressure flow in a parallel clearance gap and the Couette equation the drag flow in the bearing clearance gap caused by shaft rotation. A detailed presentation of the theoretical background of the calculation procedure is included in [Annex A](#).

The following important premises apply to the calculation procedures described in this document:

- a) all lubricant flows in the lubrication clearance gap are laminar;
- b) the lubricant adheres completely to the sliding surfaces;
- c) the lubricant is an incompressible Newtonian fluid;
- d) in the whole lubrication clearance gap, as well as in the preceding restrictors, the lubricant is partially isoviscous;
- e) a lubrication clearance gap completely filled with lubricant is the basis for the frictional behaviour;
- f) fluctuations of pressure in the lubricant film normal to the sliding surfaces do not take place;
- g) half bearing and journal have completely rigid surfaces;
- h) the radii of curvature of the surfaces in relative motion to each other are large in comparison to the lubricant film thickness;
- i) the clearance gap height in the axial direction is constant (axial parallel clearance gap);
- j) the pressure over the recess area is constant;
- k) there is no motion normal to the sliding surfaces.

With the aid of the above-mentioned approximation formulae, all parameters required for the design or calculation of bearings can be determined. The application of the similarity principle results in dimensionless similarity values for load-carrying capacity, stiffness, oil flow rate, friction as well as recess pressures.

The results indicated in this document in the form of tables and diagrams are restricted to operating ranges common in practice for hydrostatic bearings. Thus, the range of the bearing eccentricity (displacement under load) is limited to  $\varepsilon = 0$  to 0,5.

Limitation to this eccentricity range means a considerable simplification of the calculation procedure as the load-carrying capacity is a nearly linear function of the eccentricity. However, the applicability of this procedure is hardly restricted as in practice eccentricities  $\varepsilon > 0,5$  are mostly undesirable for reasons of operational safety. A further assumption for the calculations is the approximated optimum restrictor ratio<sup>[2]</sup>  $\xi = 1$  for the stiffness behaviour.

As for the outside dimensions of the bearing, this document is restricted to the range bearing width/bearing diameter  $B/D = 0,3$  to 1 which is common in practical cases of application. The recess depth is larger than the clearance gap height by the factor 10 to 100. When calculating the friction losses, the friction loss over the recess in relation to the friction over the bearing lands can generally be neglected on account of the above premises. However, this does not apply when the bearing shall be optimized with regard to its total power losses.

To take into account the load direction of a bearing, difference is made between the two extreme cases, the load in the direction of the recess centre and the load in the direction of the land centre.

Apart from the aforementioned boundary conditions, some other requirements are to be mentioned for the design of hydrostatic bearings in order to ensure their functioning under all operating conditions. In general, a bearing shall be designed in such a manner that a clearance gap height of at least 50 % to 60 % of the initial clearance gap height is assured when the maximum possible load is applied. With this in mind, particular attention shall be paid to misalignments of the shaft in the bearing due to shaft deflection which can result in contact between the shaft and the bearing edge and thus in damage of the bearing. In addition, the parallel clearance gap required for the calculation is no longer present in such a case.

As the shaft contacts the bearing lands when the hydrostatic pressure is switched off, it can be necessary to check the contact zones with regard to rising surface pressures.

It shall be assured that the heat originating in the bearing does not lead to a non-permissible rise in the temperature of the oil.

If necessary, a means of cooling the oil shall be provided. Furthermore, the oil shall be filtered in order to avoid choking of the capillaries and damage to the sliding surfaces.

Low pressure in the relieved recess shall also be avoided, as this leads to air being drawn in from the environment and this would lead to a decrease in stiffness (see 6.7).

## 6 Method of calculation

### 6.1 General

This document covers the calculation as well as the design of hydrostatic plain journal bearings. In this case, calculation is understood to be the verification of the operational parameters of a hydrostatic bearing with known geometrical and lubrication data. In the case of a design calculation, with the given methods of calculation it is possible to determine the missing data for the required bearing geometry, the lubrication data and the operational parameters on the basis of a few initial data (e.g. required load-carrying capacity, stiffness and rotational frequency).

In both cases, the calculations are carried out according to an approximation method based on the Hagen-Poiseuille and the Couette equations, mentioned in Clause 5. The bearing parameters calculated according to this method are given as relative values in the form of tables and diagrams as a function of different parameters. The procedure for the calculation or design of bearings is described in 6.2 to 6.7. This includes the determination of different bearing parameters with the aid of the given calculation formulae or the tables and diagrams. The following calculation items are explained in detail:

- a) the determination of load-carrying capacity with and without consideration of shaft rotation;
- b) the calculation of lubricant flow rate and pumping power;
- c) the determination of frictional power with and without consideration of losses in the bearing recesses;
- d) the procedure for bearing optimization with regard to minimum total power loss.

For all calculations, it shall be checked in addition whether the important premise of laminar flow in the bearing clearance gap, in the bearing recess and in the capillary is met. This is checked by determining the Reynolds numbers. Furthermore, the portion of the inertia factor in the pressure differences shall be kept low at the capillary (see A.3.2.2).

If the boundary conditions defined in Clause 5 are observed, this method of calculation yields results with deviations which can be neglected for the requirements of practice, in comparison with an exact calculation by solving the Reynolds equation.

Examples of calculation are given in Annex B.

### 6.2 Load-carrying capacity

Unless indicated otherwise, it is assumed in the following that capillaries with a linear characteristic are used as restrictors and that the restrictor ratio is  $\xi = 1$ . Furthermore, difference is only made between the two cases "load in direction of recess centre" and "load in direction of land centre". For this reason, it is no longer mentioned in each individual case that the characteristic values are a function of the three parameters "restrictor type", "restrictor ratio" and "load direction relative to the bearing".